Clock Oscillators Surface Mount Type
Clock "K" Series

KYOCERA

CMOS/ 1.8V, 2.5V, 3.3V Compatible/ 2.0×1.6, 2.5×2.0, 3.2×2.5, 5.0×3.2, 7.0×5.0mm



RoHS Compliant

Features

- Frequency Range 1.5 to 80MHz
- CMOS output
- Wide Supply Voltage 1.6 to 3.63V
- Low current consumption
- Option: Low Phase Noise Version

Table 1

Freq. Tol. Code	× 10^{-6}	Operating Temperature Range (°C)	Note
0	± 50	−10 to +70	Standard specifications
S	± 30		With only certain frequencies
U	± 25		
G	± 50	−40 to +85	
6	± 50	−40 to +105	

Packaging Tape & Reel
KC7050K/ KC5032K
: 1000 pcs/ reel
KC3225K/ KC2520K/ KC2016K
: 2000 pcs/ reel

How to Order

KC2520K 25.0000 C 1 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

① Type 2.0×1.6mm: KC2016K
2.5×2.0mm: KC2520K
3.2×2.5mm: KC3225K
5.0×3.2mm: KC5032K
7.0×5.0mm: KC7050K
② Output Frequency (25.0000: 25MHz)
③ Output Type (C: CMOS)
④ Supply Voltage
1 : 1.8V/ 2.5V/ 3.3V Multi Voltage
(Version E : Standard)
2 : 2.5V (Version N : Low Phase Noise)
3 : 3.3V (Version N : Low Phase Noise)
⑤ Frequency Tolerance (See Table 1)
⑥ Symmetry/ INH Function
E : 45/ 55%, Stand-by
N : 45/ 55%, Stand-by, Low Phase Noise
⑦ Customer Special Model Suffix
(STD Specification is "00")

Dimensions

(Unit: mm)

KC2016K



KC2520K

KC3225K



KC5032K



KC7050K



Recommended Land Pattern

(Unit: mm)

KC2016K



KC2520K



KC3225K



KC5032K



KC7050K



CMOS/ 1.8V, 2.5V, 3.3V Compatible/ 2.0×1.6, 2.5×2.0, 3.2×2.5, 5.0×3.2, 7.0×5.0mm

Specifications

Item	Symbol	Conditions		Version E (Standard) Min.	Version E (Standard) Max.	Version N (Low Phase Noise) Min.	Version N (Low Phase Noise) Max.	Units
Output Frequency Range[Note1]	fo			1.5	80	1.5	80	MHz
Frequency Tolerance	f_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: −10 to +70°C/ −40 to +85°C/ −40 to +105°C	−50	+50	−50	+50	×10⁻⁶
			Op. Temp.: −10 to +70°C	−30	+30	−30	+30	
			Op. Temp.: −10 to +70°C	−25	+25	−25	+25	
Frequency Aging	f_age	@25°C First year		−3	+3	−3	+3	×10⁻⁶/ y
Storage Temperature Range	T_stg			−55	+125	−55	+125	°C
Operating Temperature Range	T_use			−10	+70	−10	+70	°C
				−40	+85	−40	+85	
				−40	+105	−40	+105	
Max. Supply Voltage	—			−0.3	+4.0	−0.3	+4.0	V
Supply Voltage	Vcc	Code ④ : 1		+1.60	+3.63	—	—	V
		Code ④ : 2		—	—	+2.25	+2.75	
		Code ④ : 3		—	—	+2.97	+3.63	
Current Consumption (Maximum Loaded/ 1.5≤F0<24MHz)	Icc	E : 1.6≤Vcc≤2.25V		—	2.5	—	—	mA
		E : 2.25<Vcc≤2.8V/ N : 2.25≤Vcc≤2.75V		—	3.0	—	4	
		E : 2.8<Vcc≤3.63V/ N : 2.97≤Vcc≤3.63V		—	3.5	—	6	
Current Consumption (Maximum Loaded/ 24≤F0≤40MHz)		E : 1.6≤Vcc≤2.25V		—	3.5	—	—	
		E : 2.25<Vcc≤2.8V/ N : 2.25≤Vcc≤2.75V		—	4.5	—	5	
		E : 2.8<Vcc≤3.63V/ N : 2.97≤Vcc≤3.63V		—	5.0	—	7	
Current Consumption (Maximum Loaded/ 40<F0≤62.5MHz)		E : 1.6≤Vcc≤2.25V		—	5.0	—	—	
		E : 2.25<Vcc≤2.8V/ N : 2.25≤Vcc≤2.75V		—	5.5	—	8	
		E : 2.8<Vcc≤3.63V/ N : 2.97≤Vcc≤3.63V		—	6.0	—	11	
Current Consumption (Maximum Loaded/ 62.5<F0≤80MHz)		E : 1.6≤Vcc≤2.25V		—	6.0	—	—	
		E : 2.25<Vcc≤2.8V/ N : 2.25≤Vcc≤2.75V		—	6.5	—	14	
		E : 2.8<Vcc≤3.63V/ N : 2.97≤Vcc≤3.63V		—	8.0	—	18	
Stand-by Current	I_std			—	5	—	5	µA
Symmetry	SYM	@50% Vcc		45	55	45	55	%
Rise/ Fall Time (10% to 90% Output Level)	tr/ tf	E : 1.6≤Vcc≤2.25V		—	6	—	—	ns
		E : 2.25<Vcc≤2.8V/ N : 2.25≤Vcc≤2.75V		—	5	—	6	
		E : 2.8<Vcc≤3.63V/ N : 2.97≤Vcc≤3.63V		—	4.5	—	5	
Low Level Output Voltage	VOL	IOL=4mA		—	10% Vcc	—	10% Vcc	V
High Level Output Voltage	VOH	IOH=−4mA		90% Vcc	—	90% Vcc	—	V
Output Load	L_CMOS			15[Note2]		15[Note2]		pF
Low Level Input Voltage	VIL			—	30% Vcc	—	30% Vcc	V
High Level Input Voltage	VIH			70% Vcc	—	70% Vcc	—	V
Disable Time	t_dis			—	200	—	150	ns
Enable Time	t_ena			—	5	—	5	ms
Start-up Time	t_str	@Minimum operating voltage to be 0 sec.		—	3	—	5	ms
1 Sigma Jitter	JSigma	Measured with Wavecrest SIA−3000		—	5	—	4	ps
Peak to Peak Jitter	JPK-PK			—	50	—	40	ps
Phase Jitter	JPhase	BW : 12kHz to 20MHz		—	1.0	—	0.5	ps
Phase Noise	—	@25MHz	@10Hz offset	−89		−92		dBc/ Hz
			@100Hz offset	−119		−126		
			@1kHz offset	−143		−151		
			@10kHz offset	−157		−160		
			@100kHz offset	−160		−167		
			@1MHz offset	−162		−170		
			@10MHz offset	−162		−170		

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.
Note2: Please contact us for Output Load 30pF.

Pad Connections	
#1	Enable/ Disable
#2	Case GND
#3	Output
#4	Vcc

INH Function	
Pad1	Pad3 (Output)
Open	Active
"H" Level	Active
"L" Level	High Z (No-Oscillation)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

AVX:

KC7050K32.0000C1GE00 KC3225K24.5760C1GE00 KC7050K24.5760C1GE00 KC7050K20.0000C1GE00
KC3225K32.0000C1GE00 KC3225K50.0000C1GE00 KC3225K27.0000C1GE00 KC7050K27.0000C1GE00
KC7050K48.0000C1GE00 KC7050K33.3333C1GE00 KC7050K24.0000C1GE00 KC3225K20.0000C1GE00
KC3225K24.0000C1GE00 KC7050K50.0000C1GE00 KC3225K25.0000C1GE00 KC3225K40.0000C1GE00
KC3225K48.0000C1GE00 KC7050K25.0000C1GE00 KC7050K40.0000C1GE00 KC3225K33.3333C1GE00
KC2520K60.0000C1GE00 KC3225K28.6364C1GE00 KC2520K25.0000C1GE00 KC3225K66.6667C1GE00
KC2520K32.0000C1GE00 KC2016K22.5792C10E00 KC5032K40.0000C10E00 KC7050K16.0000C10E00
KC7050K10.0000C10E00 KC2016K10.0000C10E00 KC7050K32.7680C1GE00 KC2520K66.6667C1GE00
KC2520K1.84320C1GE00 KC2016K33.0000C10E00 KC2520K24.5760C10E00 KC5032K50.0000C1GE00
KC5032K16.0000C10E00 KC2520K13.5600C1GE00 KC7050K3.68640C1GE00 KC5032K50.0000C10E00
KC5032K80.0000C10E00 KC7050K14.3182C10E00 KC2016K14.3182C10E00 KC5032K24.5760C10E00
KC2520K2.04800C1GE00 KC5032K4.00000C10E00 KC2016K24.0000C1GE00 KC2016K32.0000C10E00
KC5032K32.0000C10E00 KC7050K11.2896C10E00 KC5032K32.7680C1GE00 KC5032K13.5600C1GE00
KC3225K7.37280C10E00 KC7050K33.3333C10E00 KC5032K48.0000C10E00 KC2520K48.0000C1GE00
KC7050K14.7456C10E00 KC7050K25.0000C10E00 KC2016K40.0000C10E00 KC2016K20.0000C10E00
KC7050K13.5600C1GE00 KC2016K33.3333C1GE00 KC2520K12.2880C1GE00 KC2016K18.4320C1GE00
KC3225K11.2896C1GE00 KC2016K12.0000C1GE00 KC7050K32.0000C10E00 KC3225K12.0000C1GE00
KC2016K12.2880C10E00 KC7050K4.00000C1GE00 KC7050K16.3840C10E00 KC2016K27.0000C10E00
KC5032K10.0000C10E00 KC5032K14.3182C1GE00 KC3225K7.37280C1GE00 KC7050K28.6364C10E00
KC2016K40.0000C1GE00 KC5032K18.4320C1GE00 KC3225K75.0000C10E00 KC2016K3.68640C1GE00
KC5032K12.2880C1GE00 KC2016K13.5600C1GE00 KC2016K28.6364C1GE00 KC2016K16.3840C1GE00
KC2016K12.0000C10E00 KC2520K33.3333C10E00 KC5032K14.3182C10E00 KC5032K22.5792C10E00
KC2520K7.37280C10E00 KC3225K8.00000C10E00 KC3225K14.7456C10E00 KC2520K14.3182C10E00
KC2016K11.2896C10E00 KC5032K60.0000C10E00 KC7050K33.0000C10E00 KC7050K66.6667C1GE00
KC2016K14.7456C1GE00 KC5032K28.6364C10E00 KC3225K14.3182C10E00 KC3225K12.0000C10E00