

MHz RANGE CRYSTAL UNIT

FA-20H

 Nominal frequency range 12 MHz to 54 MHz External dimensions 2.5× 2.0×0.55 mm Overtone order **Fundamental**

Mobile phone, Bluetooth, W-LAN Applications

ISM band radio, Clock for MPU





Product Number Q24FA20H0xxxx18





Specifications (characteristics)

| Item | Symbol | Specifications | | Occiditions / Demonitor |
|--|--------|---|------------------------|--|
| | | For RF Reference | For Clock | Conditions / Remarks |
| Nominal frequency range | f_nom | 12.000 MHz to 54.000 MHz | | Fundamental Please contact us about available frequencies. |
| Storage temperature range | T stg | -40 °C to +125 °C | | Storage as single product. |
| Operating temperature range | T_use | -40 °C to +85 °C (+105 °C) | | Please contact us about +85 C < T_use |
| Level of drive | DL | 100 μW Max. | 200 μW Max. | Recommended: 1 µW to 100 µW |
| Frequency tolerance | f_tol | ±10 × 10 ⁻⁶ | ±30 × 10 ⁻⁶ | +25 C Please contact us for inquiries. |
| Frequency versus temperature characteristics | f_tem | $\pm 10\times 10^{\text{-}6}$ | ±30 × 10 ⁻⁶ | -20 C to +75 C Please contact us for inquiries. |
| Load capacitance | C | 6 pF to ∞ | | Please specify. |
| Motional resistance (ESR) | R1 | As per table below | | -20 C to +75 C |
| Frequency aging | f_age | $\pm 1 	imes 10^{-6}$ to $\pm 3 	imes 10^{-6}$ / year Max. *1 | | +25 C, First year |

^{*1} Please contact us for available frequency tolerances as they are dependent upon the nominal frequency.


Motional resistance (ESR)

| | _ | |
|---|---------------------|--|
| Frequency | Motional resistance | |
| 12.0 MHz ≤ f_nom < 16.0 MHz | 150 Ω Max. | |
| $16.0 \text{ MHz} \leq f_{nom} \leq 25.0 \text{ MHz}$ | 80 Ω Max. | |
| 25.0 MHz < f nom ≤ 30.0 MHz | 60 Ω Max. | |
| 30.0 MHz < f nom ≤ 35.0 MHz | 50 Ω Max. | |
| 35 0 MHz < f nom < 54 0 MHz | 40 O Max | |

Product name (Standard form) FA-20H 24.000000MHz 12.0 +10.0-10.0 ① 3 4

③Load capacitance(pF) ④Frequency tolerance(× 10⁻⁶, +25 C) ②Frequency In addition to the above mentioned specification item, please specify frequency temperature characteristics and operating temperature range in case of inquiry.

External dimensions (Unit:mm) 2.5 ± 0.1 Marking Internal connection #2 and #4 are connected to the cover. (Please connect to ground)



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Epson:

FA-20H 16.0000MF12Z-AC3 FA-20H 24.0000MF15Y-W3 FA-20H 24.0000MF20X-K3 FA-20H 25.0000MD30V-C0 FA-20H 25.0000MD30Y-C FA-20H 25.0000MD30Y-C3 FA-20H 25.0000MF20X-K0 FA-20H 25.0000MF20X-K3 FA-20H 12.0000MB30Z-W FA-20H 16.0000MF12V-AJ3 FA-20H 16.0000MF12Z-AC0 FA-20H 24.0000MA14R-K FA-20H 24.0000MB50U-G FA-20H 24.0000MF15Y-W FA-20H 25.0000MD30V-C FA-20H 25.0000MD30Y-C5 FA-20H 25.0000MD30Z-C FA-20H 26.0000MF10Z-AC3 FA-20H 26.0000MF12V-W FA-20H 26.5626MA20X-K0 FA-20H 27.1200MA10V-C3 FA-20H 30.0000MF20X-W0 FA-20H 38.4000MF10Z-AS3 FA-20H 40.0000MF15Z-AC3 FA-20H 26.0000ML81Z-AC3 FA-20H 20.0000ML81Z-AC3 FA-20H 32.0000MF12Y-W3 FA-20H 40.0000MF10Z-K3 FA-20H 32.0000MF20X-K3 FA-20HS 19.2000MF12Y-AG3 FA-20H16.0000MF20X-B FA-20H16.0000MF20X-B0 FA-20H 12.0000MD30Z-K FA-20H 12.0000MF30X-K5 FA-20H 16.0000MF10Z-AC3 FA-20H 16.0000MF10Z-K FA-20H 26.0000MF10Z-AC FA-20H 32.0000MF10Z-AJ3 FA-20H 27.0000MF20X-K3 FA-20H 30.0000MF10V-K FA-20H 32.0000MF10Z-AJ5 FA-20H 32.0000MF10Z-W FA-20H 28.63636MD50X-C FA-20H 32.0000MF10Z-K FA-20H 32.0000MF20X-K0 FA-20H 16.0000MF10Z-AC0 FA-20H 24.0000MD30X-C0 FA-20H 25.0000MF10V-W FA-20H 28.63636MF50Y-C FA-20H 32.0000MF10P-W5 FA-20H 32.0000MF20X-K5 FA-20H 40.0000MF15Z-AC FA-20H 12.0000MD30Z-K3 FA-20H 16.0000MF30X-K0 FA-20H 40.0000MF20X-K FA-20H 16.0000MF10Z-K0 FA-20H 16.0000MF20X-AJ0 FA-20H 25.0000MD30X-B FA-20H 26.0000MF20X-K0 FA-20H 27.0000MF19X-W5 FA-20H 16.0000MF10Z-AJ FA-20H 16.0000MF10Z-AJ3 FA-20H 16.0000MF20X-B FA-20H 26.0000MF20X-K3 FA-20H 28.63636MA20X-AB0 FA-20H 38.4000MF10Z-K5 FA-20H 32.0000MF10Z-W5 FA-20H 32.0000MF12Y-W FA-20H 32.0000MF12Y-W5 FA-20H 40.0000MF10Z-AJ FA-20H 40.0000MF10Z-K FA-20H 12.00M-A0AANNUA5RG3 FA-20H 16.0000MF12Z-AC5 FA-20H 16.3840MA22X-C FA-20H 24.0000MF15Y-W0 FA-20H 24.0000MF20X-K FA-20H 24.0000MF20X-K0 FA-20H 26.0000MF13P-GG5 FA-20H 16.0000MF12Z-AC FA-20H 16.0000MF12Z-AC7 FA-20H 25.0000MF10Z-C FA-20H 26.0000MF10Z-AJ5 FA-20H 27.0000MF10V-AC3 FA-20H 32.0000MF13Y-W FA-20H 26.0000MF20X-K FA-20H 27.0000MF20X-K FA-20H 12.0000MD30V-K5 FA-20H 27.0000MF10V-AC FA-20H 32.0000MF20X-K FA-20H 12.0000MD30V-K FA-20H 40.0000MF20X-AC3 FA-20H 48.0000MB30V-AG FA-20H 16.0000MF10Z-AC FA-20H 16.0000MF20X-AJ3 FA-20H 25.0000MD30V-W FA-20H 25.0000MF20X-K FA-20H 19.2000MF12Y-AG3 FA-20H 25.0000MD30Y-C0 FA-20H 26.0000MF10V-K FA-20H 26.0000ML81Z-AC0