Juice Extractor



Category: **Food Processing & Kitchen** Type: **Full SOP** Priority: **High** 1 labs

Covers these lab items: Fruit juice extractor

What it is used for

To extract juice from suitable fruits or vegetables using a juice extractor. To produce juice efficiently while maintaining food hygiene and preventing contact with moving cutting or pressing parts.

Main parts

- Motor and machine housing
- Feed chute and pusher
- Cutting or grating assembly
- Strainer or filter basket
- Juice outlet and collection container
- Pulp container, lid, and safety interlock

Before you start

1. Read the manual and confirm that the extractor is suitable for the intended produce.
2. Inspect the power cord, motor housing, lid, pusher, filter, and cutting parts for damage.
3. Wash the produce and remove stones, hard pits, or unsuitable parts according to the product requirements.
4. Clean and sanitize food-contact components using an approved procedure.
5. Assemble the filter, lid, containers, and safety locks correctly.
6. Place the machine on a stable, dry surface and ensure the juice and pulp containers are correctly positioned.

How to use

1. Ensure the switch is off before assembling or loading the extractor.
2. Fit the filter or cutting assembly and lock the lid securely.
3. Place a clean collection container under the juice outlet and the pulp container in its position.
4. Connect the power supply according to the manual.
5. Switch on the extractor and allow it to reach normal operating speed.
6. Feed produce gradually through the chute using the supplied pusher only.
7. Do not force oversized pieces into the feed opening or insert fingers or utensils into the chute.
8. Monitor juice flow, pulp collection, and motor sound during operation.
9. Switch off the machine if the filter becomes blocked, vibration increases, or the motor overheats.
10. Wait for all moving parts to stop before opening the lid or removing the filter.
11. Disconnect power before clearing blockages or dismantling parts for cleaning.

2. Transfer the juice to a clean container and refrigerate or serve it according to food-safety requirements.
3. Clean and sanitize all food-contact components promptly after use.

⚠ Safety

- Never bypass the lid lock or safety interlock.
- Keep hands, hair, jewellery, and loose clothing away from the feed chute and moving parts.
- Use only the supplied pusher to guide produce into the machine.
- Do not operate with a cracked filter, damaged cord, loose blade assembly, or missing lid.
- Switch off and unplug the extractor before clearing a blockage or touching internal parts.
- Keep the motor base dry and never immerse it in water.

Care & storage

- Remove pulp and rinse food-contact parts promptly after use.
- Clean the filter carefully with a suitable brush and inspect its mesh for damage.
- Wipe the motor housing with a damp cloth without immersing it.
- Inspect seals, locks, blades, and the power cord regularly.
- Store clean, dry components in a protected location.

Common mistakes to avoid

- Operating the extractor without securing the lid and interlock.
- Pushing produce into the chute with fingers or unsuitable tools.
- Overloading the feed chute and causing blockage or motor strain.
- Opening the machine before the cutting assembly stops.
- Leaving pulp and juice residue on components after use.

Disclaimer: This SOP is prepared from general information available on the internet. For detailed instructions, refer to the manufacturer's original manual / file.