Mould Board Plough



Category: **Agriculture & Gardening** Type: **Full SOP** Priority: **High** 1 labs

Covers these lab items: MB Plough

What it is used for

A mould board plough cuts, lifts and turns soil during primary tillage. It helps bury weeds and crop residues while preparing the field for further cultivation.

Main parts

- Identify the mould board that turns the lifted soil slice.
- Locate the share that cuts soil horizontally near the ground.
- Identify the plough standard, frog and supporting frame.
- Locate the hitching points connecting the plough to the tractor.
- Identify the landside that helps resist sideways soil pressure.
- Locate the depth and width adjustment points, where provided.
- Identify the transport lock and safety components, if fitted.

Before you start

1. Inspect the plough frame, share, mould board and fasteners for damage.
2. Check hitching points and tractor compatibility before attachment.
3. Park the tractor on firm, level ground and apply the parking brake.
4. Lower the implement safely and stop the engine before hitching adjustments.
5. Keep bystanders away and use the correct lifting points during attachment.
6. Check the field for stones, buried objects, people and other hazards.
7. Confirm that transport locks and hydraulic connections are in safe condition.

How to use

1. Position the tractor and plough on firm, level ground for attachment.
2. Attach the plough using the designated hitching points and secure all pins.
3. Connect hydraulic components only as specified for the implement.
4. Adjust plough alignment, working depth and width according to field conditions.
5. Raise the plough fully before moving to the field.
6. Remove transport locks only when safely positioned for field operation.
7. Lower the plough gradually at the field entry point.
8. Drive at a suitable low working speed while monitoring soil turning.
9. Raise the plough before turning at headlands or crossing obstacles.
10. Park on stable ground, lower the implement and stop the tractor before inspection.

⚠ Safety

- Keep clear of the space between the tractor and plough during hitching.
- Never work beneath a raised plough without approved mechanical support.
- Stop the engine and lower the implement before clearing obstructions.
- Keep people away from the operating and turning area.
- Use suitable footwear and gloves when handling sharp shares or edges.
- Secure the implement properly before road transport and follow local transport rules.

Care & storage

- Remove soil and crop residue after the implement is safely lowered.
- Inspect shares, mould boards, pins and fasteners for wear or damage.
- Tighten loose fasteners and replace worn parts as instructed.
- Store the plough in a dry, stable location with cutting edges protected.

Common mistakes to avoid

- Attempting to attach the plough on unstable or sloping ground.
- Working with loose hitch pins or damaged structural parts.
- Turning sharply with the plough buried in the soil.
- Leaving the implement raised or unsupported during inspection and maintenance.

Disclaimer: This SOP is prepared from general information available on the internet. For detailed instructions, refer to the manufacturer's original manual / file.

Prepared by - Subodh Kumar