Thread Sucking Machine



Category: **Sewing, Textile & Handicraft** Type: **Full SOP** Priority: **High** 1 labs

Covers these lab items: Thread Sucking Machine

What it is used for

A thread sucking machine uses suction to collect loose thread ends, lint, and textile waste from garments or sewing work areas. Proper operation keeps the work area clean and helps improve finishing quality.

Main parts

- Machine body and suction motor
- Suction hose or nozzle
- Thread and lint collection container
- Air filter or dust filter
- Power switch and electrical cable
- Foot switch or suction control if fitted

Before you start

1. Read the operating instructions and confirm the machine is suitable for the intended textile work.
2. Inspect the power cable, plug, hose, nozzle, and collection container for damage.
3. Check that the filter is installed correctly and is not blocked.
4. Empty the collection container if it is near capacity.
5. Ensure the work area is dry and the machine is placed securely.
6. Connect the machine to the approved power supply and check that controls are accessible.

How to use

1. Switch on the machine using the designated power control.
2. Adjust the suction setting if the model provides adjustable airflow.
3. Position the nozzle near loose thread ends or lint without touching delicate fabric unnecessarily.
4. Move the nozzle slowly over the required area to collect loose threads and textile waste.
5. Keep fingers, fabric edges, and accessories away from the suction opening.
6. Check the workpiece regularly to confirm that loose threads have been removed without damaging seams.
7. Switch off the machine before emptying the collection container or checking a blockage.
8. Remove collected waste and dispose of it according to workshop procedures.
9. Clean the filter and nozzle as specified by the manufacturer.
10. Switch off, unplug, and store the machine safely after use.

⚠ Safety

- Keep hands, hair, jewellery, and loose clothing away from the suction opening.
- Do not suck liquids, hot material, or sharp objects unless the machine is specifically designed for them.
- Never operate the machine with a damaged cable, plug, or exposed electrical part.
- Disconnect the power supply before cleaning, clearing blockages, or servicing the machine.
- Do not remove filters or open the collection chamber while the machine is running.
- Keep the machine away from water and maintain a dry work area.

Care & storage

- Empty the collection container regularly to maintain suction performance.
- Clean the nozzle and filter according to the manufacturer's instructions.
- Inspect hoses, seals, switches, and cables for wear or damage.
- Store the machine in a clean, dry place with the hose protected from kinks.

Common mistakes to avoid

- Using the machine with a blocked filter reduces suction and can overheat the motor.
- Pressing the nozzle hard against fabric may damage delicate material or seams.
- Allowing the collection container to overfill can block airflow.
- Cleaning or clearing a blockage while connected to power can cause injury.

Disclaimer: This SOP is prepared from general information available on the internet. For detailed instructions, refer to the manufacturer's original manual / file.