Gas Leak Detector



Category: **Safety & PPE** Type: **Short SOP** Priority: **High** 1 labs

Covers these lab items: Gas leakage detector

What it is used for

A gas leak detector identifies or signals the presence of specified combustible or hazardous gases. Use a detector suitable for the target gas and follow its operating and alarm procedures.

How to use

1. Inspect the detector, sensor inlet, display, battery, and accessories for damage.
2. Confirm that the detector is suitable for the gas being checked and within its calibration period.
3. Perform the prescribed bump test or function check before use.
4. Switch on the detector in a safe area and allow its startup checks to finish.
5. Check the display and alarm status before approaching the suspected leak area.
6. Survey the area using the manufacturer's specified method while avoiding direct exposure.
7. If an alarm activates, leave the area and follow the site emergency procedure.
8. Arrange authorised testing, calibration, or servicing if the detector fails its checks.

⚠ Safety

- Never use a gas detector as a reason to enter a suspected hazardous atmosphere without authorisation and protection.
- Do not ignore alarms or rely on smell to identify gas safety.
- Keep away from ignition sources when a flammable gas leak is suspected.
- Only trained personnel should perform calibration and sensor maintenance.

Care & storage

- Keep the detector clean and store it within the specified temperature and humidity limits.
- Charge or replace batteries and complete scheduled function checks and calibration.

Disclaimer: This SOP is prepared from general information available on the internet. For detailed instructions, refer to the manufacturer's original manual / file.