Caulking Tool



Category: **Construction & Masonry** Type: **Short SOP** Priority: **Medium** 4 labs

Covers these lab items: Caulking tools

What it is used for

To apply sealant neatly into joints and gaps using a caulking tool. To achieve a consistent seal while keeping the work surface clean.

Main parts

- Caulking gun or applicator
- Sealant cartridge or tube
- Trigger and plunger
- Nozzle
- Release mechanism

Before you start

1. Select sealant suitable for the surface and application.
2. Check the tool, cartridge, and nozzle for damage.
3. Clean and dry the joint as required.
4. Wear suitable gloves and eye protection.

How to use

1. Load the sealant cartridge according to the tool instructions.
2. Cut the nozzle to the required opening size.
3. Position the nozzle at the joint.
4. Press the trigger steadily while moving along the joint.
5. Maintain an even bead of sealant.
6. Smooth the bead using an approved tool if required.
7. Release pressure before removing the nozzle.
8. Clean the tool according to the sealant instructions.

⚠ Safety

- Follow the sealant label and safety instructions.
- Avoid skin and eye contact with sealant.
- Use ventilation when required.
- Release plunger pressure before removing the cartridge.

Care & storage

- Remove uncured residue using the recommended cleaner.
- Keep the plunger and trigger mechanism clean.
- Store the tool in a dry place.

Common mistakes to avoid

- Using incompatible sealant.
- Applying an uneven bead.
- Leaving the joint dirty or wet when preparation is required.
- Removing a pressurized cartridge carelessly.

Disclaimer: This SOP is prepared from general information available on the internet. For detailed instructions, refer to the manufacturer's original manual / file.

Prepared by - Subodh Kumar