Boaster



Category: **Construction & Masonry** Type: **Short SOP** Priority: **Medium** 3 labs

Covers these lab items: Boaster

What it is used for

To dress, shape, or remove excess material from masonry surfaces using a boaster, where this tool type is specified for the task. To work with controlled blows and maintain a stable tool position.

Main parts

- Striking head or working end
- Body or shaft
- Handle or grip, if fitted
- Cutting or dressing edge, depending on design

Before you start

1. Confirm the tool type and its intended masonry application.
2. Inspect the working end, body, and handle for cracks or looseness.
3. Wear safety glasses, suitable gloves, and protective footwear.
4. Secure the masonry workpiece and clear the surrounding area.

How to use

1. Mark the area to be dressed or shaped.
2. Hold the tool securely using its intended grip.
3. Position the working end at the marked location.
4. Apply controlled force appropriate to the material and tool design.
5. Work gradually and check the surface after each series of blows.
6. Remove loose fragments and inspect the finished area.
7. Clean and store the tool after use.

⚠ Safety

- Wear eye protection against flying masonry fragments.
- Keep hands and feet clear of the impact area.
- Do not use a tool with a loose handle or damaged working end.
- Keep other people outside the striking zone.

Care & storage

- Brush away masonry dust and debris after use.
- Inspect the tool for cracks, mushrooming, or other damage.

- Keep metal parts dry to reduce corrosion.
- Store in a secure tool rack.

Common mistakes to avoid

- Using the tool for an unsuitable task.
- Striking too hard and breaking the masonry.
- Working with a loose or damaged tool.
- Ignoring flying fragments and nearby people.

Disclaimer: This SOP is prepared from general information available on the internet. For detailed instructions, refer to the manufacturer's original manual / file.