Brick Hammer



Category: **Hand Tools - Striking & Digging** Type: **Short SOP** Priority: **Medium** 3 labs

Covers these lab items: Brick hammer

What it is used for

To split, trim, or shape bricks and masonry using a brick hammer. To produce controlled breaks while reducing the risk of flying fragments and tool damage.

Main parts

- Striking face
- Chisel or cutting edge
- Hammer head
- Handle
- Grip

Before you start

1. Inspect the head and handle for cracks, looseness, or damage.
2. Choose a hammer suitable for the masonry task.
3. Mark the intended cut or break line.
4. Place the brick on a stable, supportive surface.
5. Wear safety glasses, gloves, and suitable protective footwear.

How to use

1. Position the brick securely on the work surface.
2. Hold the hammer firmly at the end of its handle for control.
3. Use the chisel edge to score the intended line if appropriate.
4. Strike with controlled blows along the marked line.
5. Increase force gradually rather than using one excessive blow.
6. Check the break and remove loose fragments safely.
7. Clean the hammer and work area after use.

⚠ Safety

- Wear eye protection against flying chips.
- Keep hands and feet clear of the striking area.
- Do not use a hammer with a loose head or split handle.
- Keep bystanders outside the work zone.

Care & storage

- Remove dust and masonry fragments after use.
- Inspect the head and handle regularly.
- Keep the tool dry and store it securely.
- Replace damaged handles or tools before further use.

Common mistakes to avoid

- Striking an unsupported brick.
- Using excessive force and causing uncontrolled breakage.
- Holding the brick too close to the impact point.
- Ignoring cracks or looseness in the hammer.

Disclaimer: This SOP is prepared from general information available on the internet. For detailed instructions, refer to the manufacturer's original manual / file.

Prepared by - Subodh Kumar