Flaring Tool



Category: **Plumbing & Pipe Fitting** Type: **Short SOP** Priority: **Medium** 1 labs

Covers these lab items: Flaring tool

What it is used for

A flaring tool forms a flared end on compatible tubing to create a secure connection with the correct fitting. Use the tool and flare type specified for the tubing material and application.

How to use

1. Identify the tubing material, diameter, wall thickness, and required flare type.
2. Inspect the flaring tool, clamp, cone, and tubing for damage.
3. Cut the tubing squarely and deburr the end according to the service procedure.
4. Fit the correct flare nut onto the tubing before forming the flare.
5. Position the tubing at the specified projection in the tool clamp.
6. Operate the flaring tool evenly to form the required flare without cracks or distortion.
7. Inspect the flare and assemble it with the compatible fitting to the specified torque.

⚠ Safety

- Wear eye protection and gloves suitable for handling cut tubing.
- Secure the tool and keep fingers clear of the forming mechanism.
- Do not use cracked tubing, damaged tools, or incompatible fittings.
- For refrigerant, gas, or high-pressure systems, follow the applicable service standards and leak-test procedure.

Care & storage

- Remove metal debris, clean the tool, and lightly protect moving parts as recommended.

Disclaimer: This SOP is prepared from general information available on the internet. For detailed instructions, refer to the manufacturer's original manual / file.