

Global

1. IKEv2 Settings:
 - a. Enable/Disable
 - b. Timer in Hours

Add Tunnel

Any IP Address should never be in /32 form. It must be a single IP

If /32 is required in the backend, just hardcode it in the backend

No /32 on frontend

Encapsulation

```
Port:      # encapsulation_port No Range Check
Src Mac:   # encapsulation_src_mac
Dst Mac:   # encapsulation_dst_mac
Src IP:    # encapsulation_src_ip
Dst IP:    # encapsulation_dst_ip
```

Tunnel

```
Tunnel Name: # Single/Unique Word
Port:        # tunnel_port No Range Check
Src Mac:     # tunnel_src_mac
Dst Mac:     # tunnel_dst_mac
Src IP:      # tunnel_src_ip
Dst IP:      # tunnel_dst_ip
```

```
SrcID:
DstID:
Pre-Shared Key:
Comment
Enable/Disable
```

Example

```
#####

#SP Rules
#1
sp ipv4 out esp protect 102 pri 1 dst 10.10.10.2/32 sport 0:65535 dport 0:65535
sp ipv4 in esp protect 101 pri 1 dst 10.10.10.1/32 sport 0:65535 dport 0:65535
```

#SA Rules

#1

```
sa out 102 cipher_algo aes-128-cbc cipher_key a0:a0:a0:a0:a0:a0:a0:a0:a0:a0:\
a0:a0:a0:a0:a0 auth_algo sha1-hmac auth_key a0:a0:a0:a0:a0:a0:a0:a0:a0:a0:\
a0:a0:a0:a0:a0:a0:a0:a0 mode ipv4-tunnel src 1.1.1.1 dst 1.1.1.2
```

```
sa in 101 cipher_algo aes-128-cbc cipher_key a0:a0:a0:a0:a0:a0:a0:a0:a0:a0:\
a0:a0:a0:a0:a0 auth_algo sha1-hmac auth_key a0:a0:a0:a0:a0:a0:a0:a0:a0:a0:\
a0:a0:a0:a0:a0:a0:a0:a0 mode ipv4-tunnel src 1.1.1.2 dst 1.1.1.1
```

#Routing Rules

#1

```
rt ipv4 dst 10.10.10.1/32 port 0
rt ipv4 dst 1.1.1.2/32 port 4
```

#Neighbour Rules

#1

```
neigh port 0 aa:bb:cc:00:00:00
```

#####

Co-Relation

spi_number = Formula

10.10.10.1 = encapsulation_src_ip

10.10.10.2 = encapsulation_dst_ip

1.1.1.1 = tunnel_src_ip

1.1.1.2 = tunnel_dst_ip

aa:bb:cc:00:00:00 = encapsulation_src_mac

rt ipv4 dst encapsulation_src_ip/32 port encapsulation_port

rt ipv4 dst tunnel_dst_ip/32 port tunnel_port

neigh port encapsulation_port encapsulation_src_mac