

# COMP(2041|9044) 23T2 — Python Regular Expressions

---

<https://www.cse.unsw.edu.au/~cs2041/23T2/>

# Regular Expression History Revisited

- You've seen two versions of Ken Thompson's regex language:
  - POSIX **Basic Regular Expressions**
    - limited syntax, e.g no `|`
    - used by **grep** & **sed**
    - needed when computers were every slow to make regex matching faster
  - POSIX **Extended Regular Expressions** - superset of Basic Regular Expressions
    - used by **grep -E** & **sed -E**
- Henry Spencer produced the first open source regex library
  - used many place e.g. postgresql, tcl
  - extended (added features & syntax) to Ken's regex language.
- Perl (Larry Wall) copied Henry's library & extended much further
  - available outside Perl via **Perl Compatible Regular Expressions** library
  - used by **grep -P**
- Python standard **re** package also copied Henry's library
  - added most of the features in Perl/PCRE
  - many commonly used features are common to both
- we will cover some (not all) useful extra regex features found in both Python & Perl/PCRE
- <https://regex101.com/> lets you specify which regex language

```
re.search(regex, string, flags)
```

- search for a *regex* match within *string*
- return object with information about match or **None** if match fails
- optional parameter modifies matching, e.g. make matching case-insensitive with: `flags=re.I`

```
re.match(regex, string, flags)
```

- only match at start of string
- same as `re.search` stating with `^`

```
re.fullmatch(regex, string, flags)
```

- only match the full string
- same as `re.search` stating with `^` and ending with `$`

```
re.sub(regex, replacement, string, count, flags)
```

- return *string* with anywhere *regex* matches, substituted by *replacement*
- optional parameter *count*, if non-zero, sets maximum number of substitutions

```
re.findall(regex, string, flags)
```

- return all non-overlapping matches of pattern in string
- if pattern contains `()` return part matched by `()`
- if pattern contains multiple `()` return tuple

```
re.split(regex, string, maxsplit, flags)
```

- Split *string* everywhere *regex* matches
- optional parameter *maxsplit*, if non-zero, set maximum number of splits

---

<code>\d</code>	matches any <i>digit</i> , for ASCII: <code>[0-9]</code>
<code>\D</code>	matches any non- <i>digit</i> , for ASCII: <code>[^0-9]</code>
<code>\w</code>	matches any <i>word</i> char, for ASCII: <code>[a-zA-Z_0-9]</code>
<code>\W</code>	matches any non- <i>word</i> char, for ASCII: <code>[^a-zA-Z_0-9]</code>
<code>\s</code>	matches any <i>whitespace</i> , for ASCII: <code>[ \t\n\r\f]</code>
<code>\S</code>	matches any non- <i>whitespace</i> , for ASCII: <code>[^ \t\n\r\f]</code>
<code>\b</code>	matches at a word boundary
<code>\B</code>	matches except at a word boundary
<code>\A</code>	matches at the start of the string, same as <code>^</code>
<code>\Z</code>	matches at the end of the string, same as <code>\$</code>

---

- convenient and make your regex more likely to be portable to non-English locales
- `\b` and `\B` are like `^` and `$` - they don't match characters, they anchor the match

## raw strings

- Python raw-string is prefixed with an r (for raw)
  - can prefix with r strings quoted with ' " ''' """
- backslashes have no special meaning in raw-string except before quotes
  - backslashes escape quotes but also stay in the string
- regexes often contain backslashes - using raw-strings makes them more readable

```
>>> print('Hello\nAndrew')
Hello
Andrew
>>> print(r'Hello\nAndrew')
Hello\nAndrew
>>> r'Hello\nAndrew' == 'Hello\\nAndrew'
True
>>> len('\n')
1
>>> len(r'\n')
2
```

## Match objects

- `re.search`, `re.match`, `re.fullmatch` return a match object if a match succeeds, `None` if it fails
  - hence their return can to control `if` or `while`

```
print("Destroy the file system? ")
answer = input()
if re.match(r'yes|ok|affirmative', answer, flags=re.I):
    subprocess.run("rm -r /", Shell=True)
```

- the match object can provide useful information:

```
>>> m = re.search(r'[aiou].*[aeiou]', 'pillow')
>>> m
<re.Match object; span=(1, 5), match='illo'>
>>> m.group(0)
'illo'
>>> m.span()
(1, 5)
>>>
```

## Capturing Parts of a Regex Match

- brackets are used for grouping (like arithmetic) in extended regular expressions
- in Python (& PCRE) brackets also capture the part of the string matched
- **group(*n*)** returns part of the string matched by the *n*th-pair of brackets

```
>>> m = re.search('(\w+)\s+(\w+)', 'Hello Andrew')
>>> m.groups()
('Hello', 'Andrew')
>>> m.group(1)
'Hello'
>>> m.group(2)
'Andrew'
```

- **\number** can be used to refer to group *number* in an **re.sub** replacement string

```
>>> re.sub(r'(\d+) and (\d+)', r'\2 or \1', "The answer is 42 and 43?")
'The answer is 43 or 42?'
```



- **\number** can be used further on in a regex - often called a back-reference
  - e.g. `r'^(\d+) (\1)$'` match the same integer twice

```
>>> re.search(r'^(\d+) (\d+)$', '42 43')
<re.Match object; span=(0, 5), match='42 43'>
>>> re.search(r'^(\d+) (\1)$', '42 43')
None
>>> re.search(r'^(\d+) (\1)$', '42 42')
<re.Match object; span=(0, 5), match='42 42'>
```

- back-references allow matching impossible with classical regular expressions
- python supports up to 99 back-references, `\1`, `\2`, `\3`, ..., `\99`
  - `\01` or `\100` is interpreted as an octal number

- `(?:...)` is a non-capturing group
  - it has the same grouping behaviour as `(...)`
  - it doesn't capture the part of the string matched by the group

```
>>> m = re.search(r'.*(?:[aeiou]).*([aeiou]).*', 'abcde')
>>> m
<re.Match object; span=(0, 5), match='abcde'>
>>> m.group(1)
'e'
```

# Greedy versus non-Greedy Pattern Matching

- The default semantics for pattern matching is **greedy**:
  - starts match the first place it can succeed
  - make the match as long as possible
- The **?** operator changes pattern matching to **non-greedy**:
  - starts match the first place it can succeed
  - make the match as short as possible

```
>>> s = "abbbc"
>>> re.sub(r'ab+', 'X', s)
'Xc'
>>> re.sub(r'ab+?', 'X', s)
'Xbbbc'
```

# Why Implementing a Regex Matching isn't Easy

- regex matching starts match the first place it can succeed
- but a regex can partly match many places

```
>>> re.sub(r'ab+c', 'X', "abbabbbbbbbabbbc")  
'abbabbbbbbbX'
```

- and may need to *backtrack*, e.g:

```
>>> re.sub(r'a.*bc', 'X', "abbabbbbbbbcabbb")  
'Xabbb'
```

- poorly design regex engines can get very slow
  - have been used for denial-of-service attacks
- Python extensions (back-references) make matching **NP-hard**

- `re.findall` returns a list of the matched strings, e.g:

```
>>> re.findall(r'\d+', "-5==10zzz200_")
['5', '10', '200']
```

- if the regex contains `()` only the captured text is returned

```
>>> re.findall(r'(\d)\d*', "-5==10zzz200_")
['5', '1', '2']
```

- if the regex contains multiple `()` a list of tuples is return

```
>>> re.findall(r'(\d)\d*(\d)', "-5==10zzz200_")
[('1', '0'), ('2', '0')]
>>> re.findall(r'([^\,]*), (\S+)', "Hopper, Grace Brewster Murray")
[('Hopper', 'Grace')]
>>> re.findall(r'([A-Z])([aeiou])', "Hopper, Grace Brewster Murray")
[('H', 'o'), ('M', 'u')]
```

- `re.split` splits a string where a regex match

```
>>> re.split(r'\d+', "-5==10zzz200_")  
['-', '==', 'zzz', '_']
```

- like `cut` in Shell scripts - but more powerful
- for example, you can't do this with `cut`

```
>>> re.split(r'\s*,\s*', "abc,de, ghi ,jk , mn")  
['abc', 'de', 'ghi', 'jk', 'mn']
```

see also the string `join` function

```
>>> a = re.split(r'\s*,\s*', "abc,de, ghi ,jk , mn")  
>>> a  
['abc', 'de', 'ghi', 'jk', 'mn']  
>>> ':'.join(a)  
'abc:de:ghi:jk:mn'
```

## Example - printing the last number

```
# Print the last number (real or integer) on every line
# Note: regexp to match number:  -?\d+\.\?\d*
# Note: use of assignment operator :=
import re, sys
for line in sys.stdin:
    if m := re.search(r'(-?\d+\.\?\d*)\D*$', line):
        print(m.group(1))
```

source code for print\_last\_number.py

## Example - finding numbers #0

```
# Find the positive integers among input text
# print their sum and mean
# Note regexp to split on non-digits
# Note check to handle empty string from split
# Only positive integers handled
import re, sys
input_as_string = sys.stdin.read()
numbers = re.split(r"\D+", input_as_string)
total = 0
n = 0
for number in numbers:
    if number:
        total += int(number)
        n += 1
if numbers:
    print(f"{n} numbers, total {total}, mean {total / n:.1f}")
```



## Example - finding numbers #1

```
# Find the positive integers among input text
# print their sum and mean
# Note regexp to match number -?\d+\.\?\d*
# match postive & integers & floating-point numbers
import re, sys
input_as_string = sys.stdin.read()
numbers = re.findall(r"-?\d+\.\?\d*", input_as_string)
n = len(numbers)
total = sum(float(number) for number in numbers)
if numbers:
    print(f"{n} numbers, total {total}, mean {total / n:.1f}")
```

source code for find\_numbers.1.py

## Example - Changing Filenames with Regex

```
# written by andrewt@unsw.edu.au for COMP(2041|9044)
#
# Change the names of the specified files
# by substituting occurrences of regex with replacement
# (simple version of the perl utility rename)
import os
import re
import sys

if len(sys.argv) < 3:
    print(f"Usage: {sys.argv[0]} <regex> <replacement> [files]", file=sys.stderr)
    sys.exit(1)

regex = sys.argv[1]
replacement = sys.argv[2]

for old_pathname in sys.argv[3:]:
    new_pathname = re.sub(regex, replacement, old_pathname, count=1)
    if new_pathname == old_pathname:
        continue
    if os.path.exists(new_pathname):
        print(f"{sys.argv[0]}: '{new_pathname}' exists", file=sys.stderr)
        continue
    try:
        os.rename(old_pathname, new_pathname)
    except OSError as e:
        print(f"{sys.argv[0]}: '{new_pathname}' {e}", file=sys.stderr)
```

source code for `rename_regex.py`

# Example - Changing Filenames with Regex & Eval

```
# written by andrew@unsw.edu.au for COMP(2041|9044)
#
# Change the names of the specified files
# by substituting occurrences of regex with replacement
# (simple version of the perl utility rename)
#
# also demonstrating argument processing and use of eval
# because eval can allow arbitrary code execution,
# it should not be used where security is important
import argparse
import os
import re
import sys

parser = argparse.ArgumentParser()
# add required arguments
parser.add_argument('regex', type=str, help='match against filenames')
parser.add_argument('replacement', type=str, help='replace matches with this')
parser.add_argument('filenames', nargs='+', help='filenames to be changed')
# add some optional boolean arguments
parser.add_argument(
    "-d", "--dryrun", action='store_true', help='show changes but don't make them'
)
parser.add_argument(
    "-v", "--verbose", action='store_true', help='print more information'
)
parser.add_argument(
    "-e",
    "--eval",
    action='store_true',
    help='evaluate replacement as python expression, match available as _'
)
# optional integer argument which defaults to 1
parser.add_argument(
    "-n",
    "--replace_n_matches",
    type=int,
    default=1,
    help='replace n matches (0 for all matches)',
)

args = parser.parse_args()
def eval_replacement(match):
    """if --eval given, evaluate replacement string as Python
    with the variable _ set to the matching part of the filename
    """
    if not args.eval:
        return args.replacement
    _ = match.group(0)
    return str(eval(args.replacement))

for old_pathname in args.filenames:
    try:
        new_pathname = re.sub(
            args.regex, eval_replacement, old_pathname, count=args.replace_n_matches
        )
    except OSError as e:
        print(
            f"[{sys.argv[0]}]: '{old_pathname}': '{args.replacement}': {e}",
            file=sys.stderr,
        )
        continue
    if new_pathname == old_pathname:
        if args.verbose:
            print("no change:", old_pathname)
        continue
    if os.path.exists(new_pathname):
        print(f"[{sys.argv[0]}]: '{new_pathname}' exists", file=sys.stderr)
        continue
    if args.dryrun:
        print(old_pathname, "would be renamed to", new_pathname)
        continue
    if args.verbose:
        print("renaming", old_pathname, "to", new_pathname)
    try:
        os.rename(old_pathname, new_pathname)
    except OSError as e:
        print(f"[{sys.argv[0]}]: '{new_pathname}' {e}", file=sys.stderr)
```

inspired by renutils, rln, perl

## Example - When Harry Met Hermione #0

```
# For each file given as argument replace occurrences of Hermione
# allowing for some misspellings with Harry and vice-versa.
# Relies on Zaphod not occurring in the text.

import re, sys, os

for filename in sys.argv[1:]:
    tmp_filename = filename + ".new"
    if os.path.exists(tmp_filename):
        print(f"{sys.argv[0]}: {tmp_filename} already exists\n", file=sys.stderr)
        sys.exit(1)
    with open(filename) as f:
        with open(tmp_filename, "w") as g:
            for line in f:
                changed_line = re.sub(r"Herm[io]+ne", "Zaphod", line)
                changed_line = changed_line.replace("Harry", "Hermione")
                changed_line = changed_line.replace("Zaphod", "Harry")
                g.write(changed_line)
    os.rename(tmp_filename, filename)
```

source code for change\_names.0.py

## Example - When Harry Met Hermione #1

```
# For each file given as argument replace occurrences of Hermione
# allowing for some misspellings with Harry and vice-versa.
# Relies on Zaphod not occurring in the text.
import re, sys, os, shutil, tempfile
for filename in sys.argv[1:]:
    with tempfile.NamedTemporaryFile(mode='w', delete=False) as tmp:
        with open(filename) as f:
            for line in f:
                changed_line = re.sub(r"Herm[io]+ne", "Zaphod", line)
                changed_line = changed_line.replace("Harry", "Hermione")
                changed_line = changed_line.replace("Zaphod", "Harry")
                tmp.write(changed_line)
    shutil.move(tmp.name, filename)
```

source code for change\_names.1.py

## Example - When Harry Met Hermione #2

```
# For each file given as argument replace occurrences of Hermione
# allowing for some misspellings with Harry and vice-versa.
# Relies on Zaphod not occurring in the text.
# modified text is stored in a list then file over-written
import re, sys, os
for filename in sys.argv[1:]:
    changed_lines = []
    with open(filename) as f:
        for line in f:
            changed_line = re.sub(r"Herm[io]+ne", "Zaphod", line)
            changed_line = changed_line.replace("Harry", "Hermione")
            changed_line = changed_line.replace("Zaphod", "Harry")
            changed_lines.append(changed_line)
    with open(filename, "w") as g:
        g.write("".join(changed_lines))
```

source code for change\_names.2.py

## Example - When Harry Met Hermione #3

```
# For each file given as argument replace occurrences of Hermione
# allowing for some misspellings with Harry and vice-versa.
# Relies on Zaphod not occurring in the text.
# modified text is stored in a single string then file over-written
import re, sys, os
for filename in sys.argv[1:]:
    changed_lines = []
    with open(filename) as f:
        text = f.read()
    changed_text = re.sub(r"Herm[io]+ne", "Zaphod", text)
    changed_text = changed_text.replace("Harry", "Hermione")
    changed_text = changed_text.replace("Zaphod", "Harry")
    with open(filename, "w") as g:
        g.write("\n".join(changed_text))
```

source code for change\_names.3.py