Wheeled Mobile Robot Autonomy Under Degradation: A Survey of Methods and Evaluation

***Abstract*—Wheeled mobile robots face changing sensing, terrain, map, communication, and computational conditions and errors of learned inference, which violate the assumptions of individual navigation algorithms. Reliable navigation requires estimation, planning, and control to account for these changes jointly, since errors and delays in one component affect decisions elsewhere. This survey compares 245 publications from January 2021 to November 2026 on localization and mapping, traversability and motion control, semantic navigation, multi-robot coordination, and fault management. It codes each work by the degradation sources it addresses, the assumptions they violate, and the evidence linking its response to navigation outcomes. Selective sensing and fusion, adaptive motion models, map revision, and constrained action selection are complementary responses whose effectiveness depends on valid state estimates, fresh information, and feasible actions. Evaluation practice is compared by measurement level, degradation test conditions, and the events underlying risk or diagnostic claims. In this purposively selected sample, 80 of the 244 technical publications (33%) report a task outcome under a named degradation condition in the same experiment, from 1 of 67 localization studies to 36 of 56 planning studies. Four interfaces proposed for joint evaluation rank from 1 to 12 among 32 coded function couplings: localization-triggered recovery, semantic reasoning with fallback under resource limits, terrain decisions under pose uncertainty, and shared-state acceptance after reconnection. Evaluating them requires linking degradation onset, detection, and executed response to safety and task performance under matched conditions. Further challenges concern transfer across platforms, computational resources, sustained operation, and assurance under changing information quality.**

***Index Terms*—Wheeled mobile robots, robust navigation, localization, motion planning, multi-robot systems, fault tolerance, performance evaluation.**

I. Introduction

AUTONOMOUS wheeled robots transport goods, inspect facilities, explore unfamiliar sites, and assist people indoors and outdoors. To navigate, a robot must estimate its pose from imperfect measurements, represent obstacles and traversable space, plan a route that its chassis can execute, and track that route as new observations arrive, while a team member must also reconcile its own observations with information received from teammates. Reliable operation therefore depends both on the individual algorithms and on the information that passes between estimation, mapping, planning, and control.

Degradation occurs when operating conditions depart from the assumptions of these algorithms. Ground-robot datasets document combinations of darkness, lift transitions, abrupt braking, and uneven terrain [1], [2]. Beyond these sensing conditions, long-term deployments depend on charging, network availability, and operator assistance [3]. Addressing these conditions requires methods that relate the quality of the available information to the actions that a robot can still execute safely.

Geometric, learned, and language-based methods address these requirements in combination. Representative simultaneous localization and mapping (SLAM) systems [4], [5] and the dynamic-window [6] and timed-elastic-band [7] planners that recur as comparators [8], [9] illustrate how these components assume different inputs and fail in different ways. Existing surveys examine individual aspects of the problem. They cover SLAM in extreme subterranean environments [10], global LiDAR localization [11], millimeter-wave radar in robotics [12], automated-vehicle perception under adverse weather [13], terrain traversability [14] and its risk assessment [15], safe learning in robotics [16], learned navigation policies [17], social navigation [18], vision-and-language navigation [19], collaborative SLAM [20], and foundation models in robotics [21]. Each centers on one function, sensor, task setting, or method family, although the foundation-model survey spans perception, decision-making, and control. The review of learned navigation policies also serves as the context review of the coded corpus. These surveys were found through targeted searches for each navigation function and through suggestions of an internal review of an earlier draft, not through a systematic search. Table I compares the scopes that their abstracts state.

Automated driving has established a vocabulary for operation under degradation. SAE J3016 defines levels of driving automation through the roles of the user and the system in the dynamic driving task and its fallback [22]. ISO 21448 concerns the safety of the intended functionality, namely hazards that arise from insufficiencies of the specification or of sensing and processing performance rather than from faults, for series-production road vehicles [23]. Runtime monitors and fallback maneuvers make these notions operational, as in a check of the operational design domain that flags laser scans unsuitable for matching before localization runs [24] and in a minimum risk maneuver that brings an automated vehicle to a minimal risk condition after an unanswered takeover request or a severe system failure [25]. A stated operating domain, a monitored validity condition, and a fallback such as stopping in place transfer directly to wheeled robots. The road-vehicle setting does not cover unstructured terrain, robot teams, or semantic task interpretation. On a slope or in a crowd, stopping in place may itself leave a wheeled robot at risk.

This survey organizes the literature around three questions: which navigation assumption a degradation affects, how a method changes the information or action available to the robot, and what evidence connects that change to navigation performance. A codebook applies the first and third questions to every corpus work. Fig. 1 crosses the nine coded degradation sources, grouped by the six assumptions they violate, with the five navigation functions of Sections IV–VIII. The main

TABLE I
RELATED SURVEYS CHARACTERIZED FROM THEIR ABSTRACTS. "NOT STATED" MEANS THAT THE ABSTRACT DOES NOT NAME THE TOPIC, WHICH DOES NOT EXCLUDE COVERAGE IN THE BODY OF THE SURVEY.

Survey	Platform scope	Degradation coverage	Recovery or faults	Evaluation practice
Ebadi et al. (2024) [10]	Ground and aerial robots	Obscurants, tight computation	Not stated	Six SubT teams, datasets
Yin et al. (2024) [11]	Single and multiple robots	Not stated	Not stated	Not stated
Harlow et al. (2024) [12]	Robots using radar	Fog, dust, smoke	Not stated	Datasets, calibration
Zhang et al. (2023) [13]	Automated road vehicles	Weather effects on sensors	Not stated	Datasets, simulators, chambers
Sevastopoulos and Konstantopoulos (2022) [14]	Mobile robots	Slope, roughness, surface	Not stated	Not stated
Benrabah et al. (2024) [15]	Ground vehicles, robots	Traversability risk	Not stated	Risk metric consistency
Brunke et al. (2022) [16]	Robots, learned control	Uncertain dynamics	Not stated	Physics-based benchmarks
Zhu and Zhang (2021) [17]	Mobile robots	Not stated	Not stated	Not stated
Mavrogiannis et al. (2023) [18]	Robots in public crowds	Not stated	Not stated	Evaluation methods
Gu et al. (2022) [19]	Embodied language agents	Not stated	Not stated	Evaluation metrics
Lajoie et al. (2022) [20]	Multi-robot systems	Communication, resources	Not stated	Not stated
Firoozi et al. (2025) [21]	Perception to control	Not stated	Not stated	Not stated
This survey (2026)	Wheeled robots, transfer cases	Nine coded sources	Monitoring, recovery	Coded evidence, sensitivity

contributions of this survey are summarized as follows. First, it compares responses to degradation across five navigation functions and their sensing, model, action, and drivetrain requirements, distinguishing component improvements from executed recovery. Second, it codes the degradation sources and evaluation evidence of the 244 technical publications and finds that, in this purposively selected sample, 33% report a task outcome under a named degradation condition in the same experiment, from 1% of localization and mapping studies to 64% of planning and control studies. A language-model second coding of 40 sampled works checks these codes. Third, it proposes four interfaces between existing methods for joint evaluation, locates them in a ranking of the coded function couplings, and outlines a matched comparison for each.

The remaining sections cover wheeled motion and the navigation stack (Section II), selection and coding (Section III), the technical synthesis (Sections IV–VIII), evaluation practice (Section IX), open challenges (Section X), and conclusions (Section XI).

II. BACKGROUND

A. Wheeled Platforms and Motion Constraints

A wheeled mobile robot moves through driven or steered rolling contacts whose footprint, arrangement, and contact conditions constrain the paths it can execute. Differential-drive, skid-steer, Ackermann, and omnidirectional platforms differ in how they turn and whether they can move sideways [26]. For a planar reference point with position (x, y) and heading ψ, a common idealization is

$$\dot{x} = v\cos\psi, \qquad \dot{y} = v\sin\psi, \qquad \dot{\psi} = \omega, \tag{1}$$

where v is longitudinal speed and ω is angular speed. Under pure rolling, a differential-drive robot with wheel radius r, track width b, and right and left wheel angular speeds ω_R and ω_L satisfies

$$v = \frac{r}{2}(\omega_R + \omega_L), \qquad \omega = \frac{r}{b}(\omega_R - \omega_L). \tag{2}$$

TABLE II
DRIVETRAIN TYPE, THE KINEMATIC ASSUMPTION THAT DEGRADATION VIOLATES, AND THE RECOVERY MOTIONS THAT REMAIN AVAILABLE.

Drive	Degradation effect	Recovery motions
Differential, (1)–(2)	Slip and wheel lift break the encoder model. Covariance can grow along unexplained motion [27]	Turning in place, reversing. Sideways moves need rotation [28]
Skid steer, (2)	Slip varies with speed, maneuver, and surface [29]. A fixed model misses side slip at speed [30]	Turning in place at the cost of odometry. Reversing
Ackermann, (3)	Turning radius and input bounds limit corrections [31]	No turning in place. Reorientation needs space or reversing
Omni-directional	Lateral motion from the wheel arrangement [26]. No drive-specific effect reported on Mecanum bases [32], [33]	Sidestepping and turning in place

Citations mark the corpus works coded with a drivetrain-dependent effect. A legged-wheeled robot also recovers by stepping and support changes that conventional wheels cannot perform [34].

An ideal bicycle approximation for Ackermann steering instead gives

$$\omega = \frac{v}{L}\tan\delta, \tag{3}$$

where L is the wheelbase and δ is the steering angle. Table II lists how slip, steering limits, and wheel arrangement violate (1)–(3) for each drivetrain and which recovery motions remain available. On uneven ground, suspension, pitch, roll, clearance, traction, and payload further affect feasibility. A planar collision-free path may therefore be physically unsuitable even when localization is accurate.

B. The Navigation Stack and Its Degradation

Fig. 2 shows the principal functions of a navigation system, the points at which degradation enters, and the interfaces examined in Section X. Cameras, color and depth (RGB-D) cameras, LiDAR, radar, inertial measurement units (IMUs), wheel encoders, global navigation satellite system (GNSS) receivers,

Violated assumption	Degradation source	Sec. IV Localization	Sec. V Planning	Sec. VI Semantic	Sec. VII Multi-robot	Sec. VIII Faults	Response families
A1. Measurements are informative and correctly associated	Perceptual degradation	38/34/9 W18 R3 N17	3/1/1 W3	2/2/0 W2	4/3/0 W2 G1 N1	6/5/0 W4 R1 N1	IV-A selective updates IV-B complementary sensing IV-E relocalization VIII-B integrity monitors
	Sensor fault and false association	6/5/3 W2 R1 G1 N2	1/0/0 W1	1/1/1 W1	8/6/3 W5 N3	10/10/6 W7 R3	
A2. Wheels roll on supporting ground with known contact	Terrain and wheel-ground contact	17/13/4 W13 R1 N3	20/20/2 W17 R1 G2	4/3/0 W4	3/2/0 W2 G1	5/5/1 W4 N1	IV-C contact priors V-A terrain risk V-E tracking, delay
A3. The mapped scene is static or persistent	Moving agents	16/13/0 W6 R2 N8	23/21/7 W21 G1 N1	8/8/1 W7 G1	–	8/7/0 W6 N2	IV-D persistent maps V-C prediction V-D risk constraints VI-A semantic memory
	Map and scene change	16/16/3 W7 R2 N7	2/2/1 W2	7/6/4 W7	1/1/0 W1	4/0/0 W4	
A4. Learned and semantic inference is valid	Learned and semantic inference error	4/3/1 W1 R2 N1	14/12/1 W13 G1	7/5/0 W7	–	9/8/0 W8 N1	VI-B learned actions VI-C candidate selection VI-D decision timing VIII-B integrity monitors
A5. Shared information is timely and consistent	Communication loss, delay and bandwidth	2/1/0 W1 R1	3/2/2 W3	–	30/18/11 W20 G3 N7	2/1/1 W2	V-E tracking, delay VII-B distributed estimation VII-C rendezvous, repair
A6. Actuation, computation and energy remain available	Actuator fault and saturation	–	5/3/3 W5	1/1/1 W1	5/3/1 W5	8/8/4 W7 R1	VIII-A tolerant control VIII-C executed recovery VIII-D resource management
	Computation and energy limits	4/2/2 W2 N2	4/0/0 W4	9/0/0 W7 G2	6/1/1 W5 N1	7/3/3 W4 R1 N2	

Strongest setting with a named condition: none; replay, simulation, model, or resource; hardware or recorded data; physical closed loop

Fig. 1. Degradation-source by function evidence matrix of the 244 technical publications. Rows group nine degradation sources by the navigation assumption they violate. The right column lists the response families that address each assumption, by subsection. In each cell, $a/n/m$ counts the works of the section that address the source, name it as an evaluated condition (D1 or D2), and inject or vary it against a comparator (D1). The second line splits the a works into target wheeled robots (W), road vehicles (R), other ground robots (G), and non-ground, handheld, mixed, or unspecified carriers (N). Shading marks the strongest evidence setting among the n works. A work appears in every source row it addresses but only in the column of its principal section. Counts describe the purposively selected sample.

and ultra-wideband (UWB) ranging supply measurements with calibration parameters and timestamps. The estimator infers robot state from these measurements and motion inputs, the mapping algorithm estimates spatial structure, the planner selects a route or trajectory, and the controller converts that reference into actuator commands. A supervisor can interrupt execution when measurements, models, or resources no longer support the current action. Deployed systems such as the Nav2 stack of the robot operating system (ROS) [35], [36] realize these functions through interacting maps, planners, controllers, and recovery behaviors, as in planner fallback [37] or behavior-tree supervision [34].

An estimator can be described through the posterior [38]

$$p(\mathbf{x}_t, \mathcal{M} \mid \mathbf{z}_{1:t}, \mathbf{u}_{1:t}), \tag{4}$$

where $\mathbf{x}_t$ is the robot state, $\mathcal{M}$ is the map, and $\mathbf{z}_{1:t}$ and $\mathbf{u}_{1:t}$ denote observation and motion-input sequences available through time t. Localization estimates state relative to a given reference, whereas SLAM estimates state and map jointly, commonly through visual–inertial odometry (VIO) or LiDAR–inertial odometry (LIO). Loop closures constrain revisited places, although an incorrect association can introduce correlated errors into many states. Downstream decisions may therefore require the covariance, association confidence, and age of an estimate as well as its mean.

In local planning, the dynamic window approach (DWA) searches admissible velocity commands [6], timed-elastic-band (TEB) optimization adjusts a sequence of poses and timing variables [7], and model predictive control (MPC) repeatedly solves a finite-horizon control problem. A controller using a control barrier function (CBF) constrains inputs to keep the state within an admissible set under stated assumptions [39]–[41]. For a control-affine model $\dot{\mathbf{x}} = f(\mathbf{x}) + g(\mathbf{x})\mathbf{u}$, a common condition is

$$\nabla h(\mathbf{x})^{\mathsf{T}} \big[f(\mathbf{x}) + g(\mathbf{x})\mathbf{u} \big] + \alpha(h(\mathbf{x})) \geq 0, \tag{5}$$

where f denotes the drift dynamics, g maps the control input $\mathbf{u}$ to the state derivative, $h(\mathbf{x}) \geq 0$ defines the admissible set, and α is a suitable increasing function with $\alpha(0) = 0$.

Here, *degradation* denotes an operating change that reduces the quality or validity of the information, models, resources, or physical capabilities required for navigation. Fig. 2 distinguishes five groups of degradation sources, which can occur together within one navigation episode. The codebook of Section III splits them into nine sources, each violating one of the six navigation assumptions listed in Fig. 1. The figure links each assumption to its sources and to the response families of Sections IV–VIII and counts the coded works and the strongest evidence for every source and function.

C. Accuracy, Task Performance, and Integrity

Absolute trajectory error (ATE) measures differences between estimated and reference poses after a declared alignment, whereas relative pose error (RPE) measures motion error over a declared interval. Both are commonly summarized by the root mean square error (RMSE), whose value depends on alignment freedoms, scale treatment, synchronization, aggregation, and the dependence of the reference on the evaluated sensors. Task measures include goal success, collisions, interventions, completion time, coverage, and energy, while success weighted by path length (SPL) combines goal success with




Fig. 2. Navigation functions, degradation entry points, and open interfaces. Each function box names the section that reviews it. Dashed boxes mark the five groups of degradation sources. Teammates and task interpretation supply information to the motion stack rather than bypassing vehicle constraints. The circled numerals locate the four interfaces of Section X.

path efficiency. Neither task success nor low ATE identifies the source of a failure or the ability to recover after an alarm.

Integrity concerns the risk of an unacceptable estimation error without an adequate warning [42]. A useful conceptual statement is

$$\Pr(E_t > A_t \ \wedge \ \text{no timely alert at } t)\,, \tag{6}$$

where E_t is an error magnitude and A_t is an application-specific alert limit. A protection level is an error bound associated with a specified integrity model, whereas a covariance alone is not a calibrated protection level. Particle-filter and SLAM integrity analyses account for fault hypotheses and association errors when relating alarm conditions to hazardous error [43], [44]. For navigation, the warning must also reach a response policy early enough for the motion and stopping constraints of the robot.

D. Datasets, Simulators, and Transfer

Table III relates representative datasets and simulators to the kinds of evidence they can support.

III. Scope, Literature Selection, and Coding

This survey covers localization and mapping, traversability and motion control, semantic navigation, multi-robot coordination, and fault management for wheeled mobile robots operating under degraded sensing, terrain, maps, communication, or computation. It includes journal articles and main-conference papers published from 2021 to 2026 that propose, evaluate, or benchmark a mechanism relevant to these functions, counting a preprint and its published version once. Studies on road vehicles, other ground robots, or non-ground and handheld carriers are included when the inputs of their mechanism exist on a wheeled robot, its assumptions do not rest on the other embodiment, and the evaluation isolates the mechanism. Their platform group is marked in Table VI and in the supplementary implementation tables.

An initial search of 17 journals over 102 journal–year combinations yielded 58,583 merged records, of which 43,086 had complete metadata. Title and abstract screening assisted by a language model under preset topic allocations stopped after 45 acceptances and left 43,041 records unassessed. Its order and rejection history are unavailable. Six purposive stages then added works (Table IV) under theme quotas, for the four integration questions of Section X, and through IEEE-only and citation-based coverage that included RSS and CoRL proceedings. The 220 archived screening decisions of later candidate searches name Codex as reviewer and host and state a title-and-abstract relevance policy. Part of them also record the read scope and eligibility gates on DOI identity, venue, year, publication type, and main-conference status. No screening record names the language model or its version. IEEE publications form 72% of the corpus, against 64% outside the two IEEE-only stages, which contributed 56 works (Table S1 in the supplementary material). After screening-based selection ended on November 3, 2026, a final stage on November 4 added 16 works from 2021–2024 that an internal review of an earlier draft had named as missing, each with a formal publication record. Even with them, 173 of the 245 works (71%) date from 2025–2026, a skew to which the stage limited to recent IEEE papers contributes. Every included work was read and coded, by full reading for 23 works and by targeted or extract-based reading for the others. The corpus is therefore a purposive sample whose stage quotas and publisher restrictions shape the counts of Section IX, and it supports technical comparisons rather than estimates of topic prevalence. Foundational methods and definitions from before 2021, such as dynamic-window planning, timed elastic bands, barrier-function control, and GNSS integrity, are cited as background references outside the coded corpus.

TABLE III
REPRESENTATIVE EVALUATION RESOURCES, THEIR INTENDED USES, AND RELEVANT LIMITATIONS.

Resource	Evaluation use	Relevant limitation
M2DGR [1]	Ground-robot localization across everyday sensing and motion difficulties	Estimation errors must be connected separately to task outcomes
M2UD [2]	Uneven-terrain localization/mapping and runtime-aware comparison	References mix RTK and offline SLAM, external checks cover selected routes, and mapping includes handheld capture
GEODE [45]	Degeneracy comparisons across sensor conditions	Sensor-specific coverage and severity affect comparisons, and replay does not test action-dependent recovery
SubT-MRS [46]	SLAM accuracy and robustness under visual, geometric, and mixed degradation, including alternating sensor loss	Sequences mix aerial, legged, and wheeled carriers, and robustness is scored offline from velocity error
HK-MEMS [47]	Multi-sensor localization and reference comparisons	Missing reference intervals and failed trajectories require explicit coverage reporting
RELLIS-3D [48]	Off-road semantic segmentation with labeled LiDAR scans and images	One site and one vehicle, with object classes rather than traversability labels
TartanDrive [49]	Learning off-road vehicle dynamics from multimodal driving interactions	Recorded on a joystick-driven all-terrain vehicle, without closed-loop use of the learned models
HM3D [50]	Simulated embodied navigation in reconstructed building interiors	Agents receive exact position and heading in static scenes without object semantics
Robot/network simulation [51]	Designed reception and control conditions with repeated trials	A network-in-the-loop simulation is distinct from a distributed physical deployment

TABLE IV
SELECTION STAGES OF THE 245 PUBLICATIONS. EACH ROW ADDS PUBLICATIONS TO THE EARLIER STAGES. IEEE COUNTS THE WORKS PUBLISHED BY IEEE.

Selection	Basis	Works	IEEE
Initial sample	Capped journal selection, 2021–2026	45	38
Complementary publications	Four technical studies and one context review	5	3
Thematic sample	Ten works under each of six themes	60	42
Integration questions	Four questions on combined navigation functions	15	8
Targeted IEEE coverage	Motion priors, recovery, shared-state diagnosis, and reproducibility	20	20
Further targeted coverage	Map validity, terrain risk, multimodal navigation, collaboration, and adaptation	48	21
Recent IEEE coverage	Six 2025–2026 IEEE journal or ICRA papers per theme	36	36
Coverage additions	2021–2024 works named in an internal review of an earlier draft	16	9
Total		**245**	**177**

Every corpus work is coded with a published codebook (Section S6 of the supplementary material). The coding unit is the publication. A combined attribute such as a task outcome under a named degradation condition counts only when both parts come from the same experiment. Degradation evidence falls into three classes: a condition injected or varied against a comparator (D1), a condition deliberately selected for its difficulty without manipulation (D2), and an incidental condition that the study reports (D3). Here, a named degradation condition means D1 or D2. Each work also receives its addressed sources, response family, platform group, and drivetrain, every value with a source location. A separate language-model session on a different model coded 40 stratified random works without access to the primary codes. Before adjudication, Cohen's kappa over the thirteen double-coded attributes has a median of 0.81 and ranges from -0.04 to 1.00 (Section S7 of the supplementary material). This statistic measures agreement between two language-model coding passes on shared evidence and is not human inter-rater reliability. Reported metrics are interpreted within the platform and protocol of each study, without pooling effect sizes across heterogeneous datasets or trial units.

IV. LOCALIZATION AND MAPPING

Localization and mapping responses to degradation differ in the information they retain and in their assumptions about geometry, contact, and correlations between estimates (Table S3 in the supplementary material).

A. Localizability and Selective Measurement Updates

Under geometric degeneracy, LODESTAR keeps the information that remains in the weak directions by selecting historical Schmidt–Kalman anchors from the condition of the LiDAR measurement Jacobian and choosing points by their contribution along those directions [52]. With a common FAST-LIO2 backbone, absolute pose error (APE) on the Long Corridor recording of the SubT-MRS dataset [46] falls from 3.113 to 1.386 m, while average desktop computation rises from 21.04 to 28.69 ms. The improvement is not uniform, since the APE on the Short exp recording is 0.429 m against 0.412 m for the baseline. Other methods characterize or condition degeneracy explicitly, through screw-theoretic classification of translational, helical, and spherical degeneracy [53], normal-histogram feature selection along weak tunnel directions in DR-ICP [54], a DBSCAN-based detector that adapts to condition-number history and compensates with

IMU motion after a startup phase [55], and DCReg, which preconditions the weak subspaces without changing the least-squares objective [56]. Such conditioning exploits weak but nonzero information, although it neither restores an absent constraint nor rescues an initialization outside the convergence basin.

B. Complementary Sensing

Complementary sensors differ mainly in when the second modality enters the estimate. Mixed degradation remains difficult, since no sensor-fusion entry met the success criteria in the SubT-MRS challenge, whose sequences come from aerial, legged, and wheeled robots [46]. Its LiDAR entries averaged 1.61 m ATE on mixed-degradation sequences against 0.836 m on geometric ones. Switch-SLAM adds visual constraints only when normalized Hessian eigenvalues indicate LiDAR degeneracy and falls back to inertial propagation when both modalities fail [57]. Degradation-resilient LiDAR–radar–inertial odometry fuses continuously, keeping LiDAR constraints along observable directions and using radar velocity as independent motion information in obscurant tests on a flying robot [58]. An equivariant LiDAR–radar–inertial filter estimates inertial biases and rejects radar outliers, with observability resting on an exact map [59]. Radar-centric estimators must also cope with sparse, noisy returns. A continuous-trajectory radar–inertial estimator propagates pose uncertainty to each point timestamp and down-weights uninformative points [60], whereas Super4DR learns radar odometry by self-supervision and completes the radar map with Gaussian primitives partly guided by image depth [61]. Teammates provide another source, as RaLI-Multi corrects LiDAR–inertial drift along the detected degenerate direction with inter-vehicle UWB ranges, provided that at least one horizontal direction remains well constrained [62]. When no modality remains informative, MM-LINS hibernates the unreliable map, reinitializes, and registers the maps once they overlap again [63].

C. Motion Priors, Contact, and Adaptation

Ground geometry enters estimation as a reweighting of ground and non-ground corrections in AESF-LIO, which adds no independent observation [64], as a planar prior in SE2-LIO, which parameterizes pose on $SE(2)$ [65], or as an explicit ground-normal factor in a sparse-channel LiDAR system whose ground detector misses gradual slope changes [66]. All three designs rely on near-planar ground.

Wheel and inertial measurements bridge failures of external sensing while contact and excitation remain adequate. Wheel-aided VIO propagates inertial–wheel motion during visual failure [67], while PL-VIWO adds motion-consistency rejection and point-assisted line triangulation with its calibration held fixed [68]. Ground models extend this propagation beyond flat floors. A quadratic motion-manifold estimator integrates wheel measurements on a local ground model that extremely uneven farmland violates [69], whereas WING learns IMU-bias and wheel-error corrections for skidding and vertical bouncing on a continuous B-spline ground manifold, yielding interoceptive-only odometry [70].

Contact uncertainty can also be estimated explicitly, as when a tire-model observer fuses wheel-level velocities by covariance intersection and excludes inconsistent wheels [29]. Time-of-flight (ToF)–wheel odometry inflates process covariance only along the remainder that differential-drive motion cannot explain [27]. DURAL switches between LiDAR–inertial–UWB estimation inside a surveyed anchor region and wheel-aided estimation outside it [71]. Learned kinematic factors [30] and the hierarchical modality reweighting of Super Odometry [72] train motion priors while perception is reliable and freeze them when supervision degrades.

Lug-generated wheel traces reveal slip on suitable soil [73], whereas commanded collisions with known-map geometry constrain pose in a filter, tested on hardware with manually commanded contacts [74]. GNSS-aided IMU–odometer calibration estimates wheel scale and extrinsics but leaves vertical translation unobservable under planar motion [75]. Such calibration parameters should not absorb transient contact failure. IL-LIO learns point-to-voxel residuals and uncertainty for nonplanar geometry [76], although learned residual variance is not an independently calibrated integrity bound.

D. Dynamic Geometry and Persistent Maps

Dynamic-scene estimators either exclude moving observations or estimate them. Exclusion keeps the static map clean but can remove much of the geometry in crowds, as in semantic rejection of person features in hospital RGB-D SLAM [77] and in GPU-free asynchronous mask propagation in NGD-SLAM, whose reported tracking time excludes concurrent detection [78]. DynoSAM instead estimates rigid-object motion in world-centric factor graphs through full-batch optimization without loop closure [79]. PG-SLAM and JPG-SLAM retain dynamic appearance through Gaussian representations, although neither runs in real time with loop closure [80], [81]. Improved rendering does not by itself establish a better obstacle map.

Across sessions, persistence enters as a survival prior on semantic clusters in ProbPer-LiLo [82] and as local and cross-session ephemerality weights for registration in ELite [83]. A lifelong LiDAR mapper instead stores positive and negative map differences, from which earlier versions can be reconstructed [84]. Chamelion learns change detection from synthesized structural changes and separates disappearance from occlusion before updating construction-site and office maps, performing best when registration error and voxel size resemble its training data [85]. For automotive radar, multi-session loop verification and a temporal occupancy grid retain persistent points for later localization under a planar-trajectory assumption [86]. NVMS-SLAM keeps normal-bearing surfaces apart to avoid merging opposite faces of thin walls and refines alignment offline [87], while NeuSE updates object maps after layout changes within the categories on which it was trained [88].

E. Prior-Map and Cross-Modal Localization

Localization against a compact or structural prior reduces the online representation but becomes sensitive to changes

in the mapped environment. ERPoT matches sparse scans to polygon maps after ground removal [89], Area Graph localization matches filtered scans to walls and doors after WiFi and barometric initialization [90], and building information model (BIM) localization estimates as-designed discrepancies before weighting structural constraints [91]. Orchard trunk maps suppress seasonal foliage at the price of making global recovery depend on adequate trunk support [92]. An uncertainty-aware outdoor localizer weights normal distributions transform (NDT) matching by estimated covariance and gates GNSS, a rule that can reject accurate fixes after extended LiDAR loss [93].

Relocalization obtains pose hypotheses from appearance, through cross-attention image retrieval on pushed-robot recordings [94] or distilled LiDAR–camera place recognition [95], or from structure, through object-level scene graphs that tolerate staged object moves [96], rendered point-cloud, mesh, or neural-radiance maps [97], and density maps for loop closure that can inherit front-end degeneracy [98]. Retrieval provides a candidate rather than a verified pose.

Cross-modal matching relaxes the requirement that map and query share a sensor. CMRNext casts camera-to-LiDAR matching as optical flow followed by perspective-n-point estimation and transfers across camera setups, although it is trained on driving data, does not yet run in real time, and receives an initial pose for every frame [99]. OMCL scores Monte Carlo hypotheses with open-vocabulary features raycast from a three-dimensional map and can initialize from a language description, provided that odometry is map-scaled and the map features still match the scene, since the map is not updated online [100]. LiDAR Teach, Radar Repeat localizes forward-looking 4D radar against LiDAR keyframes from a teaching pass, with registration errors driving label-free fine-tuning [101]. Its route repetition on a four-wheel differential-drive platform covers smoke, moving traffic, and structural change over months, with obstacle avoidance left to other sensors.

F. Cooperative Estimates, Uncertain Maps, and Evaluation Resources

Cooperative estimators add constraints while introducing correlations. CoVOR-SLAM corrects monocular scale with inter-agent ranges in a similarity-pose graph [102], while a Lie-group estimator tracks the cross-covariances among wheel, inertial, and marker estimates over near-straight indoor motion [103]. For uncertainty in the map itself, semantic neural processes predict elevation with an uncertainty that still requires calibration [104], whereas E2-BKI propagates evidential semantic uncertainty through geometry-aligned kernels [105]. A multi-fidelity Gaussian process (GP) explorer on an aquatic robot weights field samples by localization uncertainty [106].

Robot-mounted lighting in LUCID improves visual appearance without necessarily improving odometry [107]. AirSLAM combines learned point and line features with map reuse and reaches 40 Hz on an embedded GPU under illumination change, although it reduces to a point-feature system where structural lines are absent [108].

G. Synthesis

The evidence for these responses stops at the estimate, since only 1 of the 67 studies reviewed in this section reports a task outcome (Table VI). Most of them also evaluate on carriers other than a target wheeled robot.

V. Traversability, Motion Planning, and Control

Under degradation, the feasibility of planned motion depends on terrain support, obstacle motion, state uncertainty, actuator limits, and the age of control information (Table S4 in the supplementary material).

A. Terrain Support and Traversability Costs

Learned costs describe where the robot can go. CADNet predicts heading-dependent accessible range from LiDAR history for a TEB planner on a SCOUT robot [109], whereas GA-Nav projects attention-based terrain segmentation into a cost map combined with elevation [110]. A risk-aware learner labels traversed footprints and weak obstacles before predicting unvisited cells, with predictions evaluated only on manually driven recordings [111]. Such learners depend on off-road data such as the TartanDrive dynamics recordings [49] and the RELLIS-3D campus scans, on which SalsaNext segmentation reaches 40.20% mean intersection over union against 59.5% on an urban benchmark [48]. Physical models describe whether the ground can carry the robot. PE-RRT* infers hidden support planes in vegetation with multivariate Gaussian processes and tracks the route with nonlinear MPC [112], while a multilevel planner checks settling, support polygon, and body collision for a tracked robot, with its wheeled variant tested only in simulation [113]. An anisotropic explorer penalizes motion by slope and travel direction with a quasi-static Euler Cost that omits slip and suspension transients [114]. A footprint label, a support plane, a stability margin, and a cross-slope penalty are not interchangeable estimates of traversal risk.

Recent planners condition terrain risk on approach direction and uncertainty and embed it in optimization. SPARTA predicts angle-conditioned risk distributions as reusable Fourier functions from a fully observed prior point cloud [115]. A visual-foundation-model approach learns cost, speed, and novelty maps from expert driving for model predictive path integral (MPPI) control, with field trials in which operator corrections expose residual failures that offline trajectory agreement conceals [116]. STEP combines risks such as collision, step, tip-over, and slip on a 2.5D elevation map into a conditional value at risk (CVaR) map for path search and MPC, with localization error entering through the elevation-map variance [117]. Its onboard runs on a Husky and a Spot quadruped report explored extent without failure rates. EVORA plans with MPPI against the CVaR of learned traction distributions and penalizes out-of-distribution terrain, succeeding in all five indoor trials at its best risk level on an RC car whose pose comes from motion capture [118]. A terrain-adaptive ϵ-constraint MPC minimizes path length while bounding a pose-stability cost adjusted online from terrain descriptors, with a sparse GP correcting its car-like dynamics [119]. Its success falls from 94% in simulation

to 80% outdoors on a Scout Mini, although it still exceeds the 67% of MPPI and 73% of GAKD in the same outdoor comparison. TRAIL learns an implicit field of terrain attributes from RGB and LiDAR and optimizes path geometry and speed along its gradients [120].

B. Exploration with Information and Geometry

Exploration chooses where to improve the map while preserving the ability to localize, as FIT-SLAM 2 does by attaching frontiers to SLAM keyframes, adapting a traversability roadmap after pose changes, and rejecting edges with low expected landmark information [121]. With a common controller and simulator pose, completion takes 880 s versus 1118 s for FAEL in Cave but 1809 s versus 1706 s in Corridor. Fisher-information evaluation also raises mean planning time from 20.8 to 63.0 ms. Other planners score uncertainty directly. Confidence-rich exploration combines particle-trajectory entropy with occupancy confidence and executes the loop on hardware [122], whereas an uncertainty-frontier planner scores coverage with signed relative entropy under known orientation [123]. A further group changes the representation of unexplored space, including safety levels for unknown regions in LRAE [124], octree category distributions for semantic exploration [125], and overlapping free polytopes in FRTree, which checks that each region can contain the robot geometry and was tested on a quadruped rather than under wheeled curvature limits [126]. A SLAM-aware planner inserts informative loop closures over a supplied topo-metric graph [127]. Potential-field MPC integrates frontier and unknown-space costs on a six-wheel skid-steer robot, although without systematic baselines [128].

C. Learning, Prediction, and Interaction

Learning enters planning at different points. NAMR-RRT learns where a risk-aware tree samples [129], whereas prescient navigation passes multimodal pedestrian hypotheses to nonlinear MPC, which may exhaust its time budget [9]. A learned relaxation of optimal reciprocal collision avoidance (ORCA) predicts escape direction and avoidance responsibility [130]. SCOPE predicts future occupancy-grid distributions from robot motion, tracked objects, and a local static map and inserts their mean and uncertainty into the costmaps of existing planners, with distillation enabling embedded inference [131]. However, its navigation comparisons are mainly simulated, while its constant-velocity robot model fails during abrupt rotation. Homotopy-driven MPC optimizes distinct trajectory classes in parallel from externally tracked poses [132], a form of candidate diversity that reduces local inconsistency without compensating for a missed pedestrian or an incorrect interaction model.

Learned local policies encode observation history implicitly. Visual proximal policy optimization (PPO) adds a motion-perceptibility auxiliary task [133], depth-based recurrent PPO is compared with DWA and TEB in simulation [8], and a LiDAR actor–critic controller uses spatiotemporal attention under adaptive Monte Carlo localization (AMCL) on a prebuilt map [134]. HEIGHT separates pedestrians from static obstacles in a heterogeneous spatio-temporal graph and transfers from a low-fidelity simulator to four everyday environments, although its deployed obstacle input assumes a map and reliable localization [135]. A rough-terrain sim-to-real policy trained with terrain scaling and pose noise still fails under vibration and inaccurate reconstructed geometry [136]. Lifelong navigation, in turn, learns only where an initial DWA policy supplies useful experience [137]. As the learned-navigation review notes [17], the training data and observation representation determine which disturbances such controllers can accommodate.

D. Safety Filters and Explicit Risk Conditions

A LiDAR-based CBF safety filter fits a GP to current obstacle edges and uses its mean and gradient in a quadratic program, with an invariance argument that excludes the GP variance [41]. Other barrier designs add structure to the motion or address the conditions under which the barrier must hold, through circulation with hold logic [138], CBF-corrected movement primitives [139], high-order filtering of iterative linear quadratic regulator (LQR) commands under input bounds [40], disturbance estimation on a tracked robot [140], and high-order barrier penalties learned alongside soft actor–critic [141]. Their evidence ranges from external pose and offboard computation to numerical studies.

Other controllers constrain an explicit risk event, through noisy barrier samples in a distributionally robust CBF [142], selectable CVaR levels in crowds [143], or a risk-aware zone expanded under input saturation, whose score is not a calibrated probability [144]. Safe Horizon MPC samples obstacle trajectories, applies a plan only after slack and support checks, and otherwise decelerates [145]. In 100 Gaussian eight-pedestrian simulations with a joint-risk specification of 0.05, its mean traversal takes 16.0 s (standard deviation 1.9 s) versus 18.4 s (2.4 s) for chance-constrained MPC, with maximum estimated plan collision probabilities of 0.0092 and 0.0019. Calibration offers a third route. Perceive With Confidence calibrates obstacle inflation over sampled environments for a planner with an inevitable-collision-set constraint on a legged robot [146], whereas conformal crowd navigation limits cumulative intrusion into calibrated pedestrian regions on a Mecanum robot [33]. MonoMPC learns the distribution of minimum clearance for candidate controls from monocular depth, without temporal memory, and minimizes a distribution-based risk [147]. In Jackal trials on the same estimated depth, its collision rate is 6.6% against 25% for a navigation stack at a similar mean speed and 48.3% for a faster setting.

E. Tracking, Mission Costs, and Network Support

A GP-MPC controller learns residual dynamics offline from field data and uses only the GP mean [148], while predictive learning refines repetitive Mecanum trajectories under external UWB pose [32]. Communication loss calls for a different response. Delay-aware MPC predicts current states from delayed packets and buffers future controls [149], whereas vehicle–cloud MPC runs onboard and remote optimizers in parallel and stops on timeout [150]. Mission-dependent costs add

another reason to change a route, as in infrastructure-based hazard inference added to a cost map [151] and in payload- or sensing-aware MPPI on a compressed scouting map [152].

Several controllers offer guarantees or savings under restricted models, including prescribed-time spatiotemporal tubes [153] and memory-event-triggered MPC, which reduces repeated solves for a no-slip Ackermann model in hardware-in-the-loop tests [154]. Curvature-constrained vector fields co-design motion and saturation on an Ackermann vehicle with motion capture [31], while universal constrained tracking filters references that exceed prescribed state bounds [155].

F. Synthesis

Support and stability models describe physical failure modes such as sinkage, tipping, or slip, which learned terrain costs capture only through appearance and traversal experience, whereas predictive constraints with a stated risk event make admissibility around moving obstacles testable under their state, dynamics, and update assumptions. Unlike the estimation studies of Section IV, these studies have the largest share among the five functions of task outcomes reported under a named degradation condition in the same experiment (Table VI).

VI. Semantic and Language-Guided Navigation

The output of a semantic navigation system, whether a room, an object instance, frontier scores, a path, a cost layer, or an action sequence, determines how a reasoning error propagates into planning and control (Table S5 in the supplementary material).

A. Semantic Memory and Scene Structure

Persistent semantic maps support relational queries but must be updated when objects move. HOV-SG organizes a mapped building into floors, rooms, and objects for hierarchical retrieval [156], while DualMap searches stable anchors globally before checking objects locally [157]. ConceptGraphs builds an open-vocabulary 3D object graph from 2D foundation models, whose node captions a language model reads to select targets [158]. On a Jackal, the language model redirects search to a plausible container when the target has moved, in demonstrations without success rates. OpenIN updates the existence confidence of a carrier–object pair when an expected object is not observed [159]. Such updates must distinguish removal from occlusion or poor depth. osmAG-LLM instead assumes from the outset that objects move, keeping a lightweight text-based area graph for context, asking a language model for likely locations, and confirming targets by online detection [160]. In 30 building trials it succeeds end to end in 21 and reaches a correct position in 27, with detection errors causing most failures.

Goal-conditioned maps store less reusable structure, as VLFM projects image–language similarity into a frontier value map until a detector supplies the goal [161]. VLN-Game builds an object-centric three-dimensional map and uses a game-theoretic vision-language model (VLM) to disambiguate attribute-rich descriptions [162] in Habitat-Matterport 3D (HM3D) scenes, whose own point-goal benchmark gives simulated agents exact position and heading [50]. SysNav reserves VLM calls for room-level decisions and leaves viewpoint selection and waypoint execution to geometric modules [163]. Multimodal spatial language maps add image and audio features to an offline map, although a remembered sound marks where it was heard rather than its source [164]. Temporal scene-object graphs report corner trapping from missing depth and episodes that end with the target out of view among their physical failures [165].

B. Geographic Grounding, Priors, and Learned Actions

Outdoor instructions often refer to places beyond the sensor horizon. OPEN associates visual semantics with OpenStreetMap and replans locally when road geometry differs from the map [166]. G-DRAGON constrains generated identifiers to existing map entities before composing a behavior tree [167], whereas CAUSALNAV retrieves destinations from an object–building–cluster graph and combines global routing with constrained local control [168]. HAM-Nav associates live landmarks with an imperfect hand-drawn map and predicts omitted ones before A*/TEB execution [169], whereas Mobility VLA retrieves a goal frame from a demonstration tour and routes over an offline graph without exploring [170].

Navigation foundation models reuse pretrained components or pooled robot data. LM-Nav parses an instruction into landmarks with GPT-3, grounds them with CLIP in a graph built by manually driving a Jackal, and finds a successful walk for 85% of 20 instructions over more than 6 km with one disengagement [171]. GNM trains one image-goal policy on data pooled from six robots and controls four robots zero-shot, including a quadrotor, still reaching goals when its angular velocity is clipped or its camera is displaced [172]. ViNT scales the data to over 100 h from eight platforms and drives an unseen Go 1 quadruped at a higher inference cost than feedforward convolutional policies [173], whereas NoMaD unifies goal-free exploration and image-goal navigation in one diffusion policy on a LoCoBot with 15 times fewer parameters than the strongest exploration baseline [174]. Learned policies map language and images directly to motion, as in LeLaN, which trains a last-mile policy from labeled robot and action-free video [175]. In 150 trials with 28 initially visible objects, its success within 0.2 m is 0.89 versus 0.67 for OWL-v2 with ZoeDepth, while in a separate ablation collision training raises arrival with obstacles from 0.13 to 0.60 in 15 trials but lowers success without obstacles from 0.89 to 0.77. Uni-NaVid compresses multiscale video history before predicting discrete primitives whose vocabulary bounds the available actions [176], whereas LGX prompts a language model for exploration directions and falls back to random exploration after an invalid response [177].

C. Candidate Selection and Behavioral Constraints

VL-TGS generates LiDAR-based trajectories, projects them into an image for GPT-4V ranking, and follows the choice with DWA while later decisions are pending [178]. However,

its ranking cannot recover a route that the generator never proposes. Sem-NaVAE applies the same generate-and-select structure without a map, scoring conditional variational autoencoder (VAE) proposals with lightweight open-vocabulary segmentation and reporting 90% success on 120–240 m campus and park routes with few repetitions per route [179]. VAMOS adds an embodiment filter, in which a per-robot affordance model trained in simulation re-ranks the image-space paths proposed by a VLM planner [180]. With the planner unchanged, the affordance model of a wheeled robot raises its success on a ramp-or-stairs task from 6 to 9 of 10 runs.

Social and behavioral constraints separate preference from collision geometry at different levels of the stack. Cue-triggered judgments become social costs for DWA in VLM-Social-Nav [181], while NORM-Nav writes instruction-parsed semantic, directional, and speed layers into standard costmaps [182]. VLM-informed path selection ranks clustered detours before an ORCA controller computes velocities [183], whereas GSON supplies group labels to a mid-level planner above a barrier-constrained predictive controller [184]. OLiVia-Nav distills large-model social reasoning into lightweight encoders that are updated online, with evaluation against expert trajectories and personal-space violation rather than collision rates [185]. Safe-VLN masks predicted waypoints with simulated occupancy and selects a new waypoint after a collision occurs [186]. SocialNav-SUB shows that strong VLMs still trail human consensus and position-based rules on social scene questions [187], while VLM-GroNav revises terrain costs and waypoints from visual and proprioceptive exemplars [188]. A grouping or grounding error can thus alter the route even when the local controller avoids detected people, whereas an occluded pedestrian can invalidate the controller itself.

D. Memory, Timing, and Embodied Execution

Semantic decisions remain valid for different durations. TARIC triangulates intermittent goal cues into a particle memory that keeps an executable goal direction during cue-free travel, although the memory drifts over long cue-free stretches [189]. Other systems align the timing of reasoning with the scene, as SysNav queries at room transitions, GSON uses updated keyframes, and the social path selector associates asynchronous responses with current candidates [163], [183], [184]. VAMOS plans at 1 Hz on a laptop GPU [180], a rate that a fast local controller can bridge only while it retains a valid action. Embodiment then determines how a semantic choice becomes motion. VLFM uses different low-level controllers in simulation and on Spot [161], Uni-NaVid runs remote inference on a quadruped [176], and LeLaN executes on a wheeled base [175]. Table II lists the recovery motions that each wheeled drive allows.

E. Synthesis

Candidate selection confines semantic errors more directly than cost layers, which keep geometry in charge of the final motion but can still misdirect the route, whereas direct policies depend on their history and action vocabulary. Semantic correctness and collision avoidance therefore require separate evaluation. As in Section V, most studies report task outcomes, while fewer than half report one under a named degradation condition in the same experiment (Table VI).

VII. Multi-Robot Coordination

Since robot teams exchange frontiers, maps, observations, poses, or position histories, communication degradation turns local operation and shared-state consistency into separate objectives (Table S6 in the supplementary material).

A. Task Allocation and Spatial Responsibility

Allocation reduces redundant work through a common state. Centralized planners partition merged maps into dynamic Voronoi cells in CURE [190], assign known targets over a sparse Delaunay graph with priority yielding in DMT-CPP [191], or fix a robust task schedule before the mission under uncertain agent capabilities [192]. Distributed methods reduce negotiation without removing shared state, as CQLite exchanges selected Q-values and frontiers [193], whereas LPFE predicts teammate frontier choices from a common map and last known positions [194] and 4CNet predicts map structure from shared trajectories [195]. Such inference avoids messages only while robots hold compatible inputs.

Region-level allocation makes the shared state coarser, as URGE abstracts the map into subregions with exploration states and allocates them by jointly minimizing path cost and balancing load [196]. Its field runs with three robots use an ad hoc mesh network in a forest, a parking lot, and a tunnel. Terrain-aware partitioning (TAPM-IVP) extends spatial responsibility to uneven ground with communication-radius-constrained regions and traversability-aware subgoals [197]. In ten simulated trials of Scene 1, each robot succeeds in 90% of trials, compared with 40% and 30% for an ablation that removes both partitioning and greedy subgoal selection.

B. Compact Sharing and Distributed Estimation

Compact representations trade bandwidth against what teammates can infer. MR-TopoMap shares topological vertices with place descriptors and keeps occupancy local for avoidance [198]. Cross-rank exchanges position histories and assigns directions at intersections [199], while WiSER-X infers relative positions from radio pings, which require an interpretation when they are missing [200]. Map-sharing systems decide what to transmit and when to fuse it. SlideSLAM buffers exchanged object observations until a loop closure fixes the frame transform [201], whereas Commerge minimizes the scans transmitted for central submap registration without adapting to radio capacity [202]. Feedback-guided hierarchical transmission sends a pose-and-factor skeleton, prioritized geometry, and semantic labels in layers and reallocates bandwidth each round from back-end signals, although its authors note that round-wise guidance can become stale under asynchronous links [203]. PROMO-Orchard gates submap merging with orchard priors and posterior checks [204].

Distributed estimators must also handle delayed and repeated information. iMESA keeps local incremental factor graphs and updates consensus variables through a two-stage exchange that must complete once started [205]. riMESA, by the same authors, removes this blocking requirement with edge-based consensus under the alternating direction method of multipliers (ADMM), robust local outlier rejection, and discarding of failed exchanges [206]. Multi-Proxy combines lightweight descriptors for progressive loop detection with asynchronous ADMM pose-graph optimization and continues under simulated packet loss and latency, where a two-stage Gauss–Seidel baseline fails to converge, provided that front-end odometry stays stable [207]. Parallel graph inference separates current-state from historical-message inference [208]. Inter-robot loop closures also require outlier rejection. Kimera-Multi rejects outlier loop closures with distributed graduated non-convexity (GNC) on recorded Jackal data, with robots kept constantly in communication range [209]. LAMP 2.0 instead queues pose graphs and keyed scans while a robot is out of range and sends them as a batch on reconnection to a base station that filters loop closures by consistency checks or GNC, keeping map errors below 4 m on replayed data from Husky and Spot robots [210]. Swarm-SLAM runs decentralized inference with sparse loop prioritization online on a heterogeneous physical team [211], whereas foundation-model loop closing anchors monocular scale with metric odometry, evaluated by replay on a Jetson [212]. Radio geometry adds constraints with their own assumptions, as in cooperative range-only SLAM [213] and in formation-controlled UWB anchors whose geometry competes with obstacle clearance [214]. A prior-graph extension of single-robot SLAM-aware planning [127] adds informative loop edges to multi-robot coverage paths, although its approximation bound concerns the graph objective rather than physical loop correspondences [215].

C. Rendezvous, Disconnection, and Conditional Repair

Communication can become part of the motion objective. A rendezvous-aware explorer creates backtracking frontiers from decaying trajectory records [216], whereas a communication-constrained controller schedules sub-team meetings that require full-team agreement to update [217]. CoCoPlan treats team-wise communication events as decision variables and co-optimizes them with task assignment through branch-and-bound search [218]. In simulations with up to 100 robots, it reports a 22.4% higher task-completion rate and 58.6% lower communication overhead than the compared protocols. MEF-Explore derives rendezvous from entropy fields and assumes that low-rate position exchange is always available, exploring 21.32% faster with a 16.67% higher success rate than the baseline on three TurtleBot2 robots [219].

During disconnection, robots can continue locally and reconcile later. ROAM continues planning from local maps during observed Wi-Fi cutoffs at the cost of revisits [220]. In the DARPA Subterranean Challenge, Team CSIRO Data61 had every tracked, legged, and aerial robot solve the same multi-agent pose graph from data exchanged by store-and-forward messaging, with agents returning to base when mission-critical data remained unsynchronized [221]. Team Explorer's wheeled robots and drones broadcast a ledger of submaps and fetch missing ones from whichever robot holds them [222], whereas CERBERUS merged odometry and sensor data from ANYmal quadrupeds and aerial scouts at a base station while they were in range, with robots backtracking to connectivity or returning after a time budget [223]. These systems report scored competition runs rather than repeated trials. Correlation-aware collaboration, evaluated on recorded road-vehicle data, exchanges states, covariances, and cross-covariances of common landmarks before Kullback–Leibler averaging and Schmidt–Kalman updates [224]. Failure-aware target tracking fuses target estimates by covariance intersection after reconnection and lets a permanently isolated aerial tracker signal a hazard [225]. The communication-aware CBF controller relaxes conflicting constraints and drops unreliable links, with recovery evaluated under partial connectivity [51]. Planned synchronization makes observation an action, scheduling check-ins in which a TurtleBot pair stops and pans to observe each other [226]. A range-based integrity monitor reconstructs shared localization errors with distributed ADMM [227].

D. Motion Interaction and Persistent Service

Coordination also occurs below the allocation layer. RL-RVO learns a distributed velocity policy from reciprocal velocity-obstacle features with external localization [228], while predefined-time formation control compensates modeled actuator faults over a fixed graph [229]. Compensation-based MPC estimates model discrepancy online for four motion-captured nonholonomic robots and leaves deadlock to future work [230]. Reachability-based platoon control preserves separation under bounded inputs and assumes reliable communication [231], whereas distributed barrier control adds a coordinated deadlock response on physical vehicles [232]. In mEclares, evaluated with quadrotor agents and a ground charging rover, a scheduler reserves return and landing opportunities from energy and timing conditions, with agents falling back to committed paths after disconnection [233].

E. Synthesis

When links fail unpredictably, asynchronous optimization and local planning sustain activity without a meeting schedule. When connectivity can be planned, rendezvous and communication-aware allocation trade travel for timely exchange. Fewer than a quarter of the studies reviewed here report a task outcome under a named degradation condition in the same experiment, 2 of them on physical robots (Table VI).

VIII. Fault Tolerance, Recovery, and Long-Term Deployment

Fault detection, isolation, accommodation, and restoration need not occur together, since a controller may tolerate bias without identifying its source (Table S7 in the supplementary material).

A. Fault Estimation and Tolerant Control

Analytic redundancy provides diagnosis without duplicating every sensor. Kinematics-based detection compares position, angular velocity, and acceleration through transport relations, with faults injected into recorded rover data [234]. A linear parameter-varying (LPV) vehicle diagnoser combines zonotopic set-membership estimation with invariant-set bounds, in which separation from the healthy set establishes detectability and overlap between fault classes prevents unique isolation [235]. Tolerant controllers instead accommodate faults in specified channels, each relying on a different remaining capability. Mixed-gain prescribed-performance control tolerates partial wheel-effectiveness loss [236], whereas virtual-error control tolerates heading and wheel-speed faults but assumes exact position [237]. Adaptive sliding-mode control handles injected actuator faults and saturation on industrial hardware as long as some actuation remains [238], while fixed-time adaptive tracking accommodates dead zones and modeled actuator faults in MATLAB studies [239]. An observer-based event-triggered controller reconstructs modeled faults before issuing updates in hardware-in-the-loop tests of a low-speed, no-slip vehicle [240].

B. Integrity and Failure Monitoring

Monitors differ in the failure event they characterize. Reliable Monte Carlo localization (MCL) estimates a latent localization-success state alongside pose and triggers free-space global relocalization [241]. Integrity analysis for extended Kalman filter (EKF) SLAM accumulates landmark fault risk, although its recorded example crosses the threshold only after localization fails [44]. A prior-line-map protection level predicts estimation error, with operational alerting left for future work [242]. Monitors of learned policies use statistical alarm definitions. Conformal anomaly detection controls the nominal false-alarm rate under exchangeability [243], while Sentinel pairs fast action-consistency monitoring with slower vision-language progress assessment [244]. PAAD predicts anomalies along a planned path on field recordings in which people reposition the robot after failures [245]. RADIUM moves failure prediction before deployment by sampling environment parameters from a distribution conditioned on failure and repairs the policy on the discovered cases, reporting up to five times higher robustness for a repaired vision-in-the-loop policy on a 1/10-scale car [246].

C. From Diagnosis to an Executed Response

The response must match the location of the fault in the stack. In the estimator, fault-tolerant prior-map collaboration excludes faulty observations, inflates faulty-landmark covariance, and specifies reinitialization for odometry faults without evaluating an executed reset [224]. At the planning level, a GP predictor of safe-corridor optimizer failure triggers a stop–reposition–resume sequence [247]. With the same planner in simulation, recovery yields eight successes in ten runs against three in ten in a dense world with 1 m doorways, whereas both variants succeed in all ten runs in a sparse world with 2 m doorways. However, the predictor posterior concerns planner failure rather than collision. At the level of the controller and supervisor, a fault-aware CBF controller optimizes over candidate sensor or actuator fault sets in numerical examples [248], whereas FORTRESS caches slow semantic reasoning for runtime reach-avoid fallback on a quadrotor [249].

Implemented recovery policies differ in what they restore, from localization to task feasibility. A nonlinear MPC (NMPC) visual navigation system stops after tracking loss and attempts relocalization [250], whereas behavior-tree supervision on CENTAURO chooses among contact repositioning, reversing, replanning, and human assistance [34]. Task-level policies change the mission instead, as resilient temporal-logic planning relaxes task windows or removes tasks when local correction fails [251] and predictive swarm fault tolerance withdraws an affected robot to maintenance before complete failure [252]. Local recovery acts on the trajectory or the observations, through hybrid-A* reinitialization of an infeasible local trajectory in RTEB [37], return toward familiar visual states in SCALE [253], and repulsive corrections from estimated depth to a visual policy in CARE [254]. However, neither familiarity nor estimated depth supplies a clearance certificate. Help Me Through learns viewpoint actions from about 50 h of human demonstrations, or 20 h followed by online fine-tuning, to keep monocular SLAM tracking through texture-poor transitions, with a physical test that runs the policy on live images while a person teleoperates path planning [28]. When a robot cannot restore a capability, the team can reassign its task, as in energy-aware allocation under staged capability loss on Robotarium [255] and in R-FAC, whose log-sum-exp value factorization keeps search policies effective when members fail without notification, assuming perfect target detection [256].

D. Resources and Sustained Operation

Resource choices determine whether a response remains available. CODEI selects bodies, sensors, algorithms, and computing units from catalogs by coupling simulated planner queries to characterized perception errors [257]. Joint runtime control of motor speed and processor voltage and frequency on a wheeled rover reduces total energy by up to 36.34% relative to prior methods, with measurements showing that computation can dominate the energy of slow motion [258]. Fleet availability adds charging constraints, as in cyclic scheduling of operating and charging periods under a station budget [259] and in persistent-monitoring routes that minimize team size under revisit-latency and recharging limits with deterministic discharge [260]. A ten-home assistive deployment combines docking rules, cloud orchestration, and remote supervision, with internet problems and localization failures among the causes of interruption [3]. A cloud–edge system offloads mapping and trajectory generation over 5G while keeping MPC tracking and collision avoidance on Jetson-equipped Ackermann robots, falling back to a leader-based local network [261].

Maintenance and learning form a second operational loop. Predictive data acquisition selects new training observations

for teach-repeat-learn navigation from visual matching ambiguity [262]. SELFI stabilizes deployment-time reinforcement learning with a model-based objective and counts interventions during learning [263], while LiReN combines foundation-model adaptation with pseudo-resets, keepout rules, charging, and help escalation [264]. Counterfactual replay selects among adapting policies at the cost of between-trial computation [265].

E. Synthesis

Recovery quality in long-term service is a matter of both restored operation and the interruptions needed to achieve it, which depend on charging, energy, network access, offboard computation, and human assistance. The studies reviewed here contain 9 of the 14 integrity or failure-risk assessments in the sample (Table VI), although their faults are often injected or simulated.

IX. Evaluation Practice

Table V draws Sections IV–VIII together by listing, for each navigation function, the main responses to degradation, the conditions under which they help, and the evidence that the reviewed studies leave open. Since most entries in the last column concern how a result was evaluated rather than whether a mechanism exists, this section compares evaluation practice across the reviewed functions.

Evaluation of autonomy under degradation must relate component outputs to executed behavior. The comparison below follows three axes, namely the level at which performance is measured, the conditions under which degradation is tested, and the event and assumptions behind a risk or diagnostic claim. Fig. 3 connects the three axes through one time-aligned navigation episode with a degraded interval. Table VI counts the coded attributes among the 244 technical publications for each reviewed function.

A. Measurement, Test Conditions, and Claim Interpretation

Component measures include trajectory, mapping, segmentation, prediction, and tracking error together with runtime and classification scores, whereas *task outcomes* concern completion, collision, coverage, traversal time, intervention, and service availability. Lower error can help explain a task result, although the connection must be measured rather than assumed. *Degradation evidence* describes an experimental condition rather than a metric. The coding separates conditions injected or varied against a comparator (D1), such as injected faults, outages, or varied terrain, from difficult sequences, sites, or crowds selected without manipulation (D2) and from incidental conditions that a study reports (D3). Only D1 requires a comparison. A matched nominal control is a stricter variant, used below as a sensitivity definition. For *risk and diagnostic assessment*, the defined event matters, since classifier recall, nominal false-positive control, protection-level coverage, and undetected hazardous error are not interchangeable, as reliable MCL, conformal anomaly detection, and EKF-SLAM integrity illustrate [44], [241], [243].

B. Evidence Across Navigation Functions

The counts in Table VI describe the selected sample rather than the field, and assessment depth varies as disclosed in the supplementary material. Three patterns are nevertheless large enough to qualify the comparisons of Sections IV–VIII. First, evidence for localization and mapping stops at the estimate, since all 67 studies report component measures and 61 name a degradation condition, whereas only 1 reports a task outcome. Planning and semantic studies show the opposite profile, with task outcomes in 44 of 56 and 32 of 36 studies. Second, 80 publications (33%) report a task outcome under a named degradation condition in the same experiment, the combination that ties a degraded condition to executed behavior. The share rises from 1% in localization through 24% in multi-robot coordination, 40% in fault management, and 44% in semantic navigation to 64% in planning and control. Of these publications, 27 rest on a condition injected or varied against a comparator and 38 on a physical robot. Third, the sample contains only 14 publications with integrity or failure-risk assessment, 9 of them in Section VIII, and 89 publications that do not report computation placement.

These shares are statistics of the purposively selected sample that depend on definitions and subsets (Table S10 in the supplementary material). The headline share falls to 5% when the condition must be varied against a nominal level, becomes 34% when the two attributes may come from different experiments, and was 25% under the card-level coding of an earlier draft. It is 30%, 38%, and 30% among full, earlier-extraction, and targeted readings, and 40% among target wheeled robots against 17% among other carriers. The share stays between 31% and 34% when any one selection stage is removed, at 33% in the quota stages against 32% elsewhere, and between 23% and 45% across year bands. In every stage, depth, and quota subset, localization keeps the lowest or a tied lowest share and planning the highest.

C. Execution and Reference Dependence

Recorded measurements preserve sensor artifacts without testing feedback between the estimated state and future observations, whereas closed-loop evaluation lets the evaluated output change the commands and thus the subsequent observations. External pose, offboard processing, teleoperated prior mapping, and staged scenes define the conditions of that feedback, as when slip-aware fusion runs without a controller consuming its estimates [29] and LiDAR-based barrier control runs under external pose and offboard computation [41]. The step to hardware can itself change the result, as the drop in success of terrain-adaptive MPC between simulation and outdoor trials shows [119].

References introduce their own dependence when they share sensors or processing with the evaluated method, as in campus line localization [242], kinematic diagnosis with a substitute position [234], and orchard map merging scored against its own mapping backbone [204]. Reference quality also varies within datasets, through the mix of smoothed RTK, offline multisensor SLAM, and selected laser-tracker checks in M2UD [2], the untimestamped HK-MEMS bus-route

TABLE V
RESPONSES TO DEGRADATION BY NAVIGATION FUNCTION, THE CONDITIONS UNDER WHICH THEY HELP, AND THE MAIN EVIDENCE GAPS IN THE REVIEWED STUDIES.

Function	Main responses	Conditions for benefit	Main evidence gaps
Localization and mapping (Sec. IV)	Selective updates, complementary sensing, motion and contact priors, relocalization, map revision	Surviving geometry in observable directions, independently informative measurements, credible supervision for learned priors, later overlap, valid persistence estimates	Mostly recorded or replayed data. Degeneracy, consistency, and similarity scores differ in meaning. Responses to a revised map rarely executed
Traversability, planning, and control (Sec. V)	Terrain costs and risk fields, information-aware exploration, learned prediction and policies, safety filters and risk constraints, delay-aware tracking	Accurate pose and adequate terrain coverage, available priors and loop opportunities, training coverage, known state and admissible inputs	Estimated risk rather than measured collisions. Few quantified simulation-to-hardware comparisons. Pose uncertainty rarely propagated into terrain decisions, with its effect on outcomes untested
Semantic navigation (Sec. VI)	Semantic scene memory, geographic grounding, learned actions, language-derived cost layers, candidate selection with embodiment filters	Valid map updates, coverage of prior maps or tours, a candidate generator that proposes feasible routes, a local controller that stays valid during pending inference	Incorrect or stale reasoning rarely injected. GPS, cloud, and map-preparation dependencies. Few physical trials per route
Multi-robot coordination (Sec. VII)	Allocation and spatial partition, compact sharing, distributed and asynchronous estimation, rendezvous, conditional map repair	Compatible shared inputs, reachable encounters, stable front-end odometry, tracked correlations	Mostly ideal or modeled communication. Acceptance of stale or biased content after a partition untested on moving teams
Fault tolerance and recovery (Sec. VIII)	Analytic redundancy and tolerant control, integrity and runtime monitoring, executed recovery, resource and service management	A modeled fault channel with remaining actuation, a monitored event that matches the response, trustworthy state for the recovery maneuver	Injected or simulated faults. Restarted or censored trials. Interruptions and human assistance seldom reported




Fig. 3. Joint evaluation of detection and response in one navigation episode. The shaded band marks the degraded interval. The operating condition defines the test, internal signals carry component and diagnostic measures, and the executed response and task outcome carry task measures. Detection delay, response delay, and recovery time follow from the synchronized events. A threshold crossing while the pose error stays below the alert limit counts as a false alarm, and an error above the alert limit without a crossing counts as a missed detection.

reference [47], and scene-dependent reference construction in GEODE [45]. Cooperative range-only SLAM runs offline on joystick-recorded bags [213], whereas hierarchical map transmission reports an estimated risk field from dataset replay rather than measured contacts [203]. Controlled variables must also match the claimed mechanism. Varying terrain geometry tests plane-fitting allocation [197], whereas a test of pose-aware terrain decisions must vary pose uncertainty. Similarly, communication studies rank methods under ideal simulated links in URGE [196] and replay benchmark factors under modeled connectivity in riMESA [206]. Neither setting measures how physical link loss changes the ranking.

D. Guarantees, Rates, and Denominators

A formal safety result applies to a specified event, probability space, horizon, and set of assumptions. A scenario-planning certificate concerns the risk of an accepted plan under a predicted obstacle distribution [145], environment-level perception calibration depends on representative calibration environments and known state [146], and a barrier proof may assume feasible inputs that saturation violates [41].

TABLE VI
CODED EVIDENCE ATTRIBUTES OF THE 244 TECHNICAL PUBLICATIONS, BY THE SECTION THAT REVIEWS EACH PUBLICATION. ATTRIBUTES OVERLAP, AND THE CONTEXT REVIEW IS EXCLUDED.

Attribute	IV	V	VI	VII	VIII	All
Publications	67	56	36	45	40	244
Measurement level						
Component measures	67	32	16	32	23	170 (70%)
Task outcome	1	44	32	25	20	122 (50%)
Physical task outcome	1	24	23	15	9	72 (30%)
Degradation evidence						
Named condition (D1 or D2)	61	46	19	27	34	187 (77%)
Injected or varied, D1	16	15	6	13	11	61 (25%)
Selected only, D2	45	31	13	14	23	126 (52%)
Incidental only, D3	1	1	2	4	2	10 (4%)
Same experiment						
Named condition and task outcome	1	36	16	11	16	80 (33%)
D1 condition and task outcome	0	12	6	5	4	27 (11%)
On a physical robot	1	19	12	2	4	38 (16%)
On a target wheeled robot	1	17	11	1	4	34 (14%)
Assessment and resources						
Integrity or failure risk	3	1	0	1	9	14 (6%)
Computation placement	45	31	18	33	28	155 (64%)
Platform group						
Target wheeled robot	30	50	30	32	30	172 (70%)
Road vehicle (R)	7	1	0	0	4	12 (5%)
Other ground robot (G)	1	4	5	3	0	13 (5%)
Non-ground or none (N)	29	1	1	10	6	47 (19%)

Counts are per publication. A same-experiment row counts a publication only when the condition and the task outcome come from one experiment. Percentages refer to all 244 publications. Table S8 gives column percentages.

Spatiotemporal-tube guarantees likewise assume bounded disturbances and terminal separation without explicit input limits [153]. None of these guarantees is an empirical closed-loop collision frequency, which must be estimated from executed trials.

Empirical rates require a denominator and an independent trial unit. Across ten homes, the assistive-robot study records 1539 service requests, of which 1130 succeeded, 177 failed, and 232 were not performed [3]. Its 86.46% success rate uses the 1307 attempted interventions as denominator and is therefore not the fraction of requests served. Eligibility and censoring change the represented population. Some studies remove scenarios before reporting, as when the CENTAURO study discards infeasible or slowly planned scenarios [34]. Others remove methods or runs after a failure. Cross-modal teach-and-repeat excludes methods that fail on the first route from later routes [101], an outdoor visual-inertial benchmark averages error only over surviving runs [266], and multi-session radar mapping omits failed baselines from its averages [86]. A trial repeated after failed relocalization [250] differs from recovery within the original attempt. Completion after temporal-logic relaxation [251] must likewise name the requirements that were changed. Small hardware samples [160], [179] support feasibility more than precise rates. Safety and completion must also be reported together, since refusing every action reduces collisions while preventing useful work.

E. Timing, Placement, and Comparisons

Timing should cover sensing age, transport, perception, estimation, planning, supervision, command delivery, and actuator response, which processor identity and average module runtime do not establish. Sentinel's fast and slow monitors have different intervention horizons [244], FORTRESS caches slow reasoning before runtime planning [249], and a 1 Hz VLM planner [180] or a change detector at 2.74 Hz on an embedded GPU [85] requires a local controller that stays valid between outputs. DMSA processes data at 1.5–4 times the recording duration and distinguishes unsupported sensor adaptations from failed runs [267]. Memory-event-triggered MPC counts updates on an industrial computer rather than measuring onboard execution [154]. A study of LiDAR–inertial non-reproducibility repeats each experiment 30 times after controlling subscribers and buffering [268], showing that repeated playback characterizes implementation variability rather than variation across missions.

F. Joint Evaluation of Detection and Response

A joint evaluation links degradation onset to an internal trigger, an executed response, and a task outcome within one mission, as Fig. 3 shows. Its specification includes the fault model, onset, duration, severity, recovery criterion, and channels assumed to remain trustworthy. The alarm time is the first detector decision that the supervisor receives, and the action time is the onset of the commanded response. Synchronized logs should retain detector outputs, thresholds, false and missed alarms, detection-to-action delay, and which of observation rejection, map correction, filter reset, or physical maneuver was executed. Comparing the nominal stack, a simple response, and an integrated response under matched conditions isolates the contribution of the response mechanism, while no-fault controls reveal the cost of unnecessary interventions. Outcomes should combine completion, contact, interventions, path and time cost, and resource use with component error and diagnostic calibration, reported with the trial unit, censoring, reference coverage, and uncertainty intervals where estimable.

X. OPEN CHALLENGES

The four interfaces below, numbered as in Fig. 2, connect these functions in ways whose behavior under degradation remains insufficiently characterized. Table VII states the unresolved dependency of each interface and a matched comparison that would test it under the evaluation principles of Section IX. In the coded evidence, every pair of functions with one coupling source forms a candidate, ranked by a preregistered rule on the number of its works without direct joint wheeled evidence, that is, without a named condition and a physical task outcome in one experiment on a target wheeled robot (Section S8 of the supplementary material). Among the 32 candidates with at least three works, Interfaces 1–4 rank 4, 9, 12, and 1. Without the integration-questions stage, which was acquired for them, they rank 4, 7, 9, and 1. The interfaces therefore remain an agenda proposed by this survey rather than the four highest-ranked candidates. Six of the 7 candidates that rank above Interface 3 without being developed concern team communication, shared-state faults, or learned decisions, which Interfaces 4 and 2 absorb. Section X-E names the seventh.

TABLE VII
OPEN INTERFACES BETWEEN NAVIGATION FUNCTIONS, THE DEPENDENCY THAT EACH LEAVES UNRESOLVED, AND A MATCHED COMPARISON THAT WOULD TEST IT. EACH INTERFACE LISTS ITS CODED WORKS AND THOSE WITH DIRECT JOINT WHEELED EVIDENCE.

Interface	Unresolved dependency	Matched comparison	Primary outcomes
1. Localization-triggered recovery (Sec. X-A). 15 works, 1 direct	Which response a localization warning should select when part of the state needed to execute it is unreliable	Fixed estimator and route. Immediate stop, threshold-triggered relocalization, and an action chosen from the remaining trustworthy channels, under controlled pose bias and weak geometry, including trials in which one alarm fires while another channel misleads	Restored localization and task progress, contact and interventions, cost of unnecessary stops under nominal sensing
2. Semantic reasoning with fallback (Sec. X-B). 11 works, 5 direct	How long a semantic decision stays valid, and whether wrong as well as late responses are rejected	Fixed model and controller. Periodic querying, scene-triggered querying, and cached decisions, under delayed responses, changed candidate paths, injected incorrect responses, and varied obstacle-track quality	Completion, contact, and fallback duration against energy and query cost, with assignment age for teams
3. Pose uncertainty in terrain decisions (Sec. X-C). 6 works, 1 direct	How pose uncertainty changes the probability that the wheel footprint rests on traversable support	Fixed terrain map and chassis. A calibrated pose distribution propagated into footprint clearance or speed, against geometry-only planning and fixed inflation, on narrow supports and slopes with an independent reference	Contact and interventions against completion and travel time, with aborted risky attempts counted as outcomes
4. Shared-state acceptance after reconnection (Sec. X-D). 17 works, 0 direct	Which returning information to accept when it may be stale, correlated, or biased	Moving ground team after a controlled partition. Immediate fusion, age-based rejection, and correlation- or residual-aware acceptance against a deterministic merge, with delay and landmark bias varied separately	Fault propagation and shared-state divergence, duplicated coverage, completion, and interventions

A. Localization-Triggered Navigation Recovery

Localization monitoring and executed recovery are both available, although the reviewed systems rarely connect them through the same trigger. Monitors cover pose-error protection levels [242], modality switching [57], landmark repair on road-vehicle data [224], and fault-tolerant tracking of specified channels [240]. Executed responses include stop–reposition–resume after optimizer failure [247], stopping and relocalization after visual tracking loss [250], behavior-tree recovery on CENTAURO [34], view planning against tracking loss [28], and interoceptive wheel–inertial odometry whose drift grows without external correction [70]. Among the 15 coded works of this interface, only the cross-modal teach-and-repeat study gives direct joint wheeled evidence [101], whereas the integrity analyses rest on road-vehicle data [43], [44]. These triggers concern different objects, namely optimizer infeasibility, predicted tracking loss, and hazardous pose error. The open question is how a localization warning should select slowing, stopping, relocalization, or repositioning when part of the state needed to execute that action is itself unreliable. In automated driving, the corresponding response is a minimum risk maneuver toward a minimal risk condition [25], whereas a wheeled robot can often also relocalize or reposition within its drivetrain limits (Table II).

B. Resource-Constrained Semantic Reasoning and Fallback

Wheeled systems already combine semantic trajectory selection with geometric planning [178], [179], group reasoning with constrained local control [184], and embodiment-specific re-ranking [180], while perception calibration on a legged robot [146], runtime monitoring [244], cached reasoning with fallback on a quadrotor [249], and distilled encoders [185] address reliability and response time. Language-derived costmap layers [182] and relocation-aware object search [160] move semantic errors into costs or search order, where geometry can check them. This interface has the most direct wheeled evidence of the four, 5 of its 11 coded works, although none of them names a computation limit or response delay among its conditions. The remaining interface concerns the lifetime of a semantic decision, since an old destination can remain valid while an old pedestrian detour becomes unusable. A delayed team assignment, as in Co-NavGPT with perception and planning on a workstation [269], can likewise remain syntactically valid after the shared map or the allocation has changed. HAM-Nav and Mobility VLA depend on sketch or tour coverage, while VLM-GroNav retains GPS and cloud dependencies [169], [170], [188]. SocialNav-SUB indicates that incorrect reasoning, and not only unavailable or delayed responses, requires explicit testing [187].

C. Pose Uncertainty in Wheeled Terrain Decisions

Recent terrain decisions increasingly combine geometry with localization, map, or contact uncertainty, through localizability-aware traversability [121], terrain-aware Ackermann allocation [197], uncertainty-weighted mapping on an aquatic explorer [106], uncertain elevation and terrain classes [104], [105], novelty and speed distributions [116], and angle-dependent risk [115]. Terrain-adaptive stability bounds [119] and implicit traversability fields [120] shape executed speed and route on small skid-steer robots, whose hardware failures are attributed to wheel slip, wet-ground traction, and sensor occlusion rather than to pose error. STEP comes closest to this question among these planners, since localization error enters its collision risk through the elevation-map variance, although its simulation assumes no localization error and its field runs on a Husky and a Spot quadruped report no failure rates [117]. EVORA instead models traction uncertainty under motion-capture pose indoors [118]. These terrain planners give direct wheeled evidence for terrain risk without coding localization as a function. The coded cells of this interface therefore hold only 6 works. Their single direct wheeled study is an OpenStreetMap-grounded navigator rather than a terrain planner [166]. The open question is how

uncertainty in pose, beyond its share of map variance, alters the probability that a wheel-supported footprint lies on the estimated traversable surface under incomplete observation, and whether propagating it changes executed outcomes.

D. Disconnection, Reconnection, and Corrupted Shared Information

Reconnection mechanisms exist for particular shared quantities, such as target estimates fused after a link returns in failure-aware aerial tracking [225], cooperative pose fusion [102], and correlation-aware landmark repair, a candidate estimator-level mechanism rather than a validated reconnection protocol [224]. Reception-aware control [51], sparse position sharing [199], and rendezvous co-optimized with allocation [218] change connectivity or message requirements. Asynchronous consensus tolerates dropped exchanges and outliers [206], [207], whereas a deterministic regional merge tolerates delay without testing corrupted content [196]. Neither outlier rejection of inter-robot loop closures [209], [210] nor store-and-forward sharing in the Subterranean Challenge teams [221]–[223] isolates the effect of stale or biased batches. Sparse loop exchange, lossy keyframe coding, layered transmission, and planned check-ins reduce traffic [203], [211], [226], [270] without establishing safe acceptance after reconnection. None of the 17 coded works of this interface gives direct joint wheeled evidence, which places it first in the ranking. The open interface is selective acceptance beyond outlier rejection when isolated robots return with stale, correlated, or biased information, since receiving a packet establishes neither frame compatibility nor the validity of its map or pose content. Concrete prerequisites to violate one at a time include stable metric odometry in foundation-model loop fusion [212], continuous range visibility in cooperative initialization [213], orchard-specific overlap priors [204], and stable front-end odometry in asynchronous collaborative LiDAR SLAM [207].

E. Broader Challenges

Interacting degradation sources call for benchmarks with controlled severity and onset and repeated independent missions. Transfer across terrain, supervision, platforms, and simulators [30], [120], [136], [246] calls for tests on withheld conditions. Computation and energy choices [249], [257], [258], [261] require response-time distributions under concurrent loads. Map maintenance, long deployments, and continual learning [3], [79], [82], [85], [101], [185], [263], [264] must be related to revisits, availability, and human escalation, which 10 coded works record outside any function pair. Assurance methods [44], [145]–[147] need online monitors of their own assumptions. Embodiment-specific affordances and failure-aware team policies [180], [256] call for cross-platform tests of clearance, curvature, and traction. Among the couplings ranked above Interface 3, actuator faults accommodated inside one tracking controller [236], [238], [240] still lack tests in which planning or supervision responds to them.

XI. Conclusion

This survey compared methods for wheeled autonomy through the navigation assumptions affected by degradation, the information or actions changed by each response, and the evidence for their effectiveness. Selective updates, independent motion sources, model adaptation, and map revision depend on different operating conditions, namely surviving geometry, credible supervision, valid correspondences, and consistent correlations.

The reviewed results also reveal conditional trade-offs, since more observable exploration routes can cost additional travel and computation, risk-constrained planning trades conservatism against progress, and recovery helps when its predicted failure matches the obstacle to task execution. Semantic ranking remains limited by the available candidates and by the capabilities of the executing chassis, whereas compact or asynchronous communication preserves only the information encoded in the shared representation. These dependencies explain why improved component scores alone do not establish more reliable navigation.

The central requirement for further evaluation is to connect degradation onset, an internal trigger, and an executed response within the same mission, as the four interfaces of Section X illustrate. The coded sample shows how unevenly this connection is made, since 33% of the technical publications in the purposively selected sample report a task outcome under a named degradation condition in the same experiment, from 1% of localization and mapping studies to 64% of planning and control studies. The share is 40% among the 172 publications evaluated on target wheeled robots or their data, while only 38 publications obtain the combination on a physical robot. Comparisons that retain the trial unit, reference dependence, timing, and failure conditions can establish when an integrated response improves both task performance and safety. The heterogeneous, purposively selected evidence supports these mechanism-level conclusions, whereas broader performance rankings require matched protocols and more uniform coverage.

Acknowledgment

Large language model tools assisted the screening of candidate records, as described in Section III and the supplementary material, and the drafting and language editing of this manuscript. An internal review of an earlier draft, which named the works of the final selection stage, was prepared with the same tools. The authors reviewed all such output and take full responsibility for the content.

References

[1] J. Yin, A. Li, T. Li, W. Yu, and D. Zou, "M2DGR: A multi-sensor and multi-scenario SLAM dataset for ground robots," *IEEE Robotics and Automation Letters*, vol. 7, no. 2, pp. 2266–2273, 2022.

[2] Y. Jia, S. Wang, S. Shao, Y. Wang, F. Zhang, and T. Wang, "M2UD: A multi-model, multi-scenario, uneven-terrain dataset for ground robot with localization and mapping evaluation," *The International Journal of Robotics Research*, vol. 45, no. 10, pp. 1457–1477, 2026. [Online]. Available: https://doi.org/10.1177/02783649251401224

[3] M. Luperto *et al.*, "User feedback and remote supervision for assisted living with mobile robots: A field study in long-term autonomy," *Robotics and Autonomous Systems*, vol. 155, p. 104170, 2022. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889022000963

[4] C. Campos, R. Elvira, J. J. G. Rodriguez, J. M. M. Montiel, and J. D. Tardos, "ORB-SLAM3: An accurate open-source library for visual, visual–inertial, and multimap SLAM," *IEEE Transactions on Robotics*, vol. 37, no. 6, pp. 1874–1890, 2021.

[5] W. Xu, Y. Cai, D. He, J. Lin, and F. Zhang, "FAST-LIO2: Fast direct LiDAR-inertial odometry," *IEEE Transactions on Robotics*, vol. 38, no. 4, pp. 2053–2073, 2022.

[6] D. Fox, W. Burgard, and S. Thrun, "The dynamic window approach to collision avoidance," *IEEE Robotics & Automation Magazine*, vol. 4, no. 1, pp. 23–33, 1997.

[7] C. Rosmann, W. Feiten, T. Wosch, F. Hoffmann, and T. Bertram, "Efficient trajectory optimization using a sparse model," in *2013 European Conference on Mobile Robots*, 2013, pp. 138–143.

[8] Y. Tao, M. Li, X. Cao, and P. Lu, "Mobile robot collision avoidance based on deep reinforcement learning with motion constraints," *IEEE Transactions on Intelligent Vehicles*, vol. 10, no. 3, pp. 2163–2173, 2025.

[9] Z. Zhang, H. Hajieghrary, E. Dean, and K. Åkesson, "Prescient collision-free navigation of mobile robots with iterative multimodal motion prediction of dynamic obstacles," *IEEE Robotics and Automation Letters*, vol. 8, no. 9, pp. 5488–5495, 2023.

[10] K. Ebadi *et al.*, "Present and future of SLAM in extreme environments: The DARPA SubT Challenge," *IEEE Transactions on Robotics*, vol. 40, pp. 936–959, 2024.

[11] H. Yin *et al.*, "A survey on global LiDAR localization: Challenges, advances and open problems," *International Journal of Computer Vision*, vol. 132, no. 8, pp. 3139–3171, 2024.

[12] K. Harlow, H. Jang, T. D. Barfoot, A. Kim, and C. Heckman, "A new wave in robotics: Survey on recent MmWave radar applications in robotics," *IEEE Transactions on Robotics*, vol. 40, pp. 4544–4560, 2024.

[13] Y. Zhang, A. Carballo, H. Yang, and K. Takeda, "Perception and sensing for autonomous vehicles under adverse weather conditions: A survey," *ISPRS Journal of Photogrammetry and Remote Sensing*, vol. 196, pp. 146–177, 2023.

[14] C. Sevastopoulos and S. Konstantopoulos, "A survey of traversability estimation for mobile robots," *IEEE Access*, vol. 10, pp. 96 331–96 347, 2022.

[15] M. Benrabah, C. Orou Mousse, E. Randriamiarintsoa, R. Chapuis, and R. Aufrère, "A review on traversability risk assessments for autonomous ground vehicles: Methods and metrics," *Sensors*, vol. 24, no. 6, p. 1909, 2024.

[16] L. Brunke *et al.*, "Safe learning in robotics: From learning-based control to safe reinforcement learning," *Annual Review of Control, Robotics, and Autonomous Systems*, vol. 5, no. 1, pp. 411–444, 2022.

[17] K. Zhu and T. Zhang, "Deep reinforcement learning based mobile robot navigation: A review," *Tsinghua Science and Technology*, vol. 26, no. 5, pp. 674–691, 2021.

[18] C. Mavrogiannis *et al.*, "Core challenges of social robot navigation: A survey," *ACM Transactions on Human-Robot Interaction*, vol. 12, no. 3, pp. 1–39, 2023.

[19] J. Gu, E. Stefani, Q. Wu, J. Thomason, and X. Wang, "Vision-and-language navigation: A survey of tasks, methods, and future directions," in *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2022, pp. 7606–7623.

[20] P.-Y. Lajoie, B. Ramtoula, F. Wu, and G. Beltrame, "Towards collaborative simultaneous localization and mapping: A survey of the current research landscape," *Field Robotics*, vol. 2, pp. 971–1000, 2022.

[21] R. Firoozi *et al.*, "Foundation models in robotics: Applications, challenges, and the future," *The International Journal of Robotics Research*, vol. 44, no. 5, pp. 701–739, 2025.

[22] On-Road Automated Driving (ORAD) Committee, *Taxonomy and Definitions for Terms Related to Driving Automation Systems for On-Road Motor Vehicles*, SAE International Std. J3016_202104, 2021.

[23] *Road vehicles — Safety of the intended functionality*, ISO Std. 21448:2022, 2022. [Online]. Available: https://www.iso.org/standard/77490.html

[24] Z. Alsayed, P. Resende, and B. Bradai, "Operational design domain monitoring at runtime for 2D laser-based localization algorithms," in *2021 20th International Conference on Advanced Robotics (ICAR)*, 2021, pp. 449–454.

[25] H. Atoui and P. Resende, "Minimum risk maneuver fallback strategy for autonomous vehicles: Design and experimental validation," in *2025 IEEE Intelligent Vehicles Symposium (IV)*, 2025, pp. 1979–1984.

[26] G. Campion, G. Bastin, and B. Dandrea-Novel, "Structural properties and classification of kinematic and dynamic models of wheeled mobile robots," *IEEE Transactions on Robotics and Automation*, vol. 12, no. 1, pp. 47–62, 1996.

[27] X. Yang, W. Li, Z. Wei, Z. Li, L. Huang, and B. Wang, "ToF-wheel odometry: Navigating degeneration of localization with limited sensing capabilities," *IEEE Robotics and Automation Letters*, vol. 11, no. 10, pp. 11 410–11 417, 2026.

[28] K. Naveed, W. Hussain, I. Hussain, D. Lee, and M. L. Anjum, "Help me through: Imitation learning based active view planning to avoid SLAM tracking failures," *IEEE Transactions on Robotics*, vol. 41, pp. 4236–4252, 2025.

[29] E. Hashemi, X. He, and K. H. Johansson, "Robust slip-aware fusion for mobile robots state estimation," *IEEE Robotics and Automation Letters*, vol. 7, no. 3, pp. 7896–7903, 2022.

[30] T. Okawara *et al.*, "Tightly-coupled LiDAR-IMU-wheel odometry with an online neural kinematic model learning via factor graph optimization," *Robotics and Autonomous Systems*, vol. 187, p. 104929, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889025000156

[31] Y. Qiao, X. He, A. Zhuo, Z. Sun, W. Bao, and Z. Li, "Curvature-constrained vector field for motion planning of nonholonomic robots," *IEEE Transactions on Robotics*, vol. 42, pp. 455–474, 2026.

[32] W. Wang and D. Meng, "Constrained predictive learning control for omnidirectional wheeled mobile robots via reducing iteration horizon," *IEEE Transactions on Automation Science and Engineering*, vol. 22, pp. 15 513–15 525, 2025.

[33] J. Yao, X. Zhang, Y. Xia, Z. Wang, A. Roy-Chowdhury, and J. Li, "Towards generalizable safety in crowd navigation via conformal uncertainty handling," in *Proceedings of The 9th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, J. Lim, S. Song, and H.-W. Park, Eds., vol. 305. PMLR, 27–30 Sep 2025, pp. 4206–4225. [Online]. Available: https://proceedings.mlr.press/v305/yao25a.html

[34] A. De Luca, L. Muratore, and N. G. Tsagarakis, "Autonomous navigation with online replanning and recovery behaviors for wheeled-legged robots using behavior trees," *IEEE Robotics and Automation Letters*, vol. 8, no. 10, pp. 6803–6810, 2023.

[35] S. Macenski, F. Martin, R. White, and J. G. Clavero, "The marathon 2: A navigation system," in *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2020, pp. 2718–2725.

[36] S. Macenski, T. Moore, D. V. Lu, A. Merzlyakov, and M. Ferguson, "From the desks of ROS maintainers: A survey of modern & capable mobile robotics algorithms in the robot operating system 2," *Robotics and Autonomous Systems*, vol. 168, p. 104493, 2023.

[37] G. Kulathunga *et al.*, "Resilient timed elastic band planner for collision-free navigation in unknown environments," *Journal of Field Robotics*, vol. 42, no. 7, pp. 3902–3917, 2025. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.22602

[38] C. Cadena *et al.*, "Past, present, and future of simultaneous localization and mapping: Toward the robust-perception age," *IEEE Transactions on Robotics*, vol. 32, no. 6, pp. 1309–1332, 2016.

[39] A. D. Ames, X. Xu, J. W. Grizzle, and P. Tabuada, "Control barrier function based quadratic programs for safety critical systems," *IEEE Transactions on Automatic Control*, vol. 62, no. 8, pp. 3861–3876, 2017.

[40] X. Kong, W. Ning, Y. Xia, Z. Sun, and H. Xie, "Adaptive high-order control barrier function-based iterative LQR for real time safety-critical motion planning," *IEEE Robotics and Automation Letters*, vol. 9, no. 7, pp. 6099–6106, 2024.

[41] S. Keyumarsi, M. W. S. Atman, and A. Gusrialdi, "LiDAR-based online control barrier function synthesis for safe navigation in unknown environments," *IEEE Robotics and Automation Letters*, vol. 9, no. 2, pp. 1043–1050, 2024.

[42] N. Zhu, J. Marais, D. Betaille, and M. Berbineau, "GNSS position integrity in urban environments: A review of literature," *IEEE Transactions on Intelligent Transportation Systems*, vol. 19, no. 9, pp. 2762–2778, 2018.

[43] O. A. Hafez, M. Joerger, and M. Spenko, "How safe is particle filtering-based localization for mobile robots? an integrity monitoring approach," *IEEE Transactions on Robotics*, vol. 40, pp. 3372–3387, 2024.

[44] ——, "Quantifying mobile robot localization safety for an EKF-based SLAM estimator: An integrity monitoring approach," *The International Journal of Robotics Research*, vol. 44, no. 6, pp. 972–988, 2025. [Online]. Available: https://doi.org/10.1177/02783649241287797

[45] Z. Chen *et al.*, "Heterogeneous LiDAR dataset for benchmarking robust localization in diverse degenerate scenarios," *The International*

Journal of Robotics Research, vol. 45, no. 1, pp. 6–22, 2026. [Online]. Available: https://doi.org/10.1177/02783649251344967

[46] S. Zhao *et al.*, "SubT-MRS dataset: Pushing SLAM towards all-weather environments," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2024, pp. 22 647–22 657.

[47] J. Ruan and D. Zhang, "HK-MEMS, a multi-sensor data set with MEMS LiDAR on degenerate and dynamic urban scenarios," *Journal of Field Robotics*, vol. 43, no. 3, pp. 2159–2182, 2026. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.70136

[48] P. Jiang, P. Osteen, M. Wigness, and S. Saripalli, "RELLIS-3D dataset: Data, benchmarks and analysis," in *2021 IEEE International Conference on Robotics and Automation (ICRA)*, 2021, pp. 1110–1116.

[49] S. Triest, M. Sivaprakasam, S. J. Wang, W. Wang, A. M. Johnson, and S. Scherer, "TartanDrive: A large-scale dataset for learning off-road dynamics models," in *2022 International Conference on Robotics and Automation (ICRA)*, 2022, pp. 2546–2552.

[50] S. K. Ramakrishnan *et al.*, "Habitat-Matterport 3D dataset (HM3D): 1000 large-scale 3D environments for embodied AI," in *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, J. Vanschoren and S. Yeung, Eds., vol. 1, 2021. [Online]. Available: https://datasets-benchmarks-proceedings.neurips.cc/paper_files/paper/2021/file/34173cb38f07f89ddbebc2ac9128303f-Paper-round2.pdf

[51] T.-S. Nguyen, H.-N. Cao, N. H. Thai, and M. T. Pham, "C-CBF: Communication-aware control barrier functions for resilient multi-robot connectivity," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 5596–5614, 2026.

[52] E. M. Lee, K. C. Marsim, and H. Myung, "LODESTAR: Degeneracy-aware LiDAR-inertial odometry with adaptive Schmidt-Kalman filter and data exploitation," *IEEE Robotics and Automation Letters*, vol. 11, no. 1, pp. 922–929, 2026.

[53] J. Wang, C. Cai, Y. Wang, Y. Li, S. Zhang, and H. Chen, "Screw-based feature constraint model and degeneracy analysis for robotic state estimation: Theory and experiments," *The International Journal of Robotics Research*, vol. 0, no. 0, p. 02783649261463720, 2026. [Online]. Available: https://doi.org/10.1177/02783649261463720

[54] G. Qian *et al.*, "DR-ICP: Robust LiDAR SLAM registration for degenerate tunnels," *Journal of Field Robotics*, oct 2026, early access; published online 12 October 2026. [Online]. Available: https://onlinelibrary.wiley.com/doi/10.1002/rob.70362

[55] Z. Liao *et al.*, "A real-time degeneracy sensing and compensation method for enhanced LiDAR SLAM," *IEEE Transactions on Intelligent Transportation Systems*, vol. 26, no. 3, pp. 4202–4213, 2025.

[56] X. Hu, X. Chen, M. Jia, J. Wu, P. Tan, and S. L. Waslander, "DCReg: Decoupled characterization for efficient degenerate LiDAR registration," *The International Journal of Robotics Research*, vol. 0, no. 0, p. 02783649261465040, 2026. [Online]. Available: https://doi.org/10.1177/02783649261465040

[57] J. Lee *et al.*, "Switch-SLAM: Switching-based LiDAR-inertial-visual SLAM for degenerate environments," *IEEE Robotics and Automation Letters*, vol. 9, no. 8, pp. 7270–7277, 2024.

[58] M. Nissov, N. Khedekar, and K. Alexis, "Degradation resilient LiDAR-radar-inertial odometry," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 8587–8594.

[59] A. Tao, Y. Luo, C. Guo, C. Xia, M. Zhao, and X. Li, "An equivariant filter-based state estimator for tightly-coupled LiDAR–radar–inertial odometry," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 14 926–14 940, 2026.

[60] W. Yang, D. Lee, M. Jung, and A. Kim, "Geometrically-constrained radar-inertial odometry via continuous point-pose uncertainty modeling," *IEEE Robotics and Automation Letters*, vol. 11, no. 5, pp. 6098–6105, 2026.

[61] Z. Li, W. Wang, Q. Shen, Y. Zhao, and Z. Fang, "Super4DR: 4-d radar-centric self-supervised odometry and Gaussian-based map optimization," *IEEE Transactions on Robotics*, vol. 42, pp. 3256–3276, 2026.

[62] Z. Jin and C. Jiang, "Range-aided LiDAR-inertial multi-vehicle localization and mapping in degenerate environments," *IEEE Transactions on Intelligent Vehicles*, vol. 11, no. 1, pp. 1–14, 2026.

[63] Y. Ma *et al.*, "MM-LINS: A multi-map LiDAR-inertial system for over-degenerate environments," *IEEE Transactions on Intelligent Vehicles*, vol. 10, no. 1, pp. 472–482, 2025.

[64] Z. Huang, C. Sun, J. Leng, and B. Wang, "AESF-LIO: Adaptive error-state fusion LiDAR-inertial odometry for ground vehicles in structured environments," *IEEE Robotics and Automation Letters*, vol. 11, no. 6, pp. 7372–7379, 2026.

[65] J. Chen, H. Wang, M. Hu, and P. N. Suganthan, "Versatile LiDAR-inertial odometry with SE(2) constraints for ground vehicles," *IEEE Robotics and Automation Letters*, vol. 8, no. 6, pp. 3486–3493, 2023.

[66] S. Wang, F. Cao, T. Wang, S. Shao, and L. Liu, "Robust ground constrained SLAM for mobile robot with sparse-channel LiDAR," *IEEE Transactions on Intelligent Vehicles*, vol. 10, no. 5, pp. 3291–3302, 2025.

[67] W. Zhou, Y. Pan, J. Liu, T. Wang, and H. Zha, "Visual-inertial-wheel odometry with wheel-aided maximum-a-posteriori initialization for ground robots," *IEEE Robotics and Automation Letters*, vol. 9, no. 5, pp. 4814–4821, 2024.

[68] Z. Zhang, W. Bai, L. Zhao, and P. Ladosz, "PL-VIWO: A lightweight and robust point-line monocular visual inertial wheel odometry," in *2025 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2025, pp. 15 205–15 212.

[69] M. Zhang, X. Zuo, Y. Chen, Y. Liu, and M. Li, "Pose estimation for ground robots: On manifold representation, integration, reparameterization, and optimization," *IEEE Transactions on Robotics*, vol. 37, no. 4, pp. 1081–1099, 2021.

[70] C. Jiang, K. Zhang, S. Yang, S. Shen, C. Xu, and F. Gao, "WING: Wheel-inertial neural odometry with ground manifold constraints," *IEEE Transactions on Intelligent Vehicles*, vol. 10, no. 3, pp. 1510–1525, 2025.

[71] K. Hu, M. Li, Z. Jin, C. Tang, E. Hu, and G. Zhou, "DURAL: Degradation-resistant robust adaptive localization by LiDAR-inertial-UWB-wheel fusion for coal mine robots," *Journal of Field Robotics*, vol. 43, no. 5, pp. 3559–3577, 2026. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.70200

[72] S. Zhao *et al.*, "Resilient odometry via hierarchical adaptation," *Science Robotics*, vol. 10, no. 109, p. eadv1818, 2025. [Online]. Available: https://www.science.org/doi/abs/10.1126/scirobotics.adv1818

[73] N. Li, J. Guo, L. Ding, C. Tian, C. Zhou, and H. Gao, "Estimation of slip ratio and side slip angle of wheeled planetary rovers based on trace imprint," *IEEE Robotics and Automation Letters*, vol. 10, no. 8, pp. 7979–7986, 2025.

[74] J. Li, J. Ji, Q. Wang, H. Yu, Y. Pan, and F. Gao, "Active collision-based navigation for wheeled robots," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 10 932–10 938.

[75] B. Song, X. Xia, P. Yan, Y. Zhong, W. Wen, and L.-T. Hsu, "Online IMU-odometer calibration using GNSS measurements for autonomous ground vehicle localization," *IEEE Transactions on Intelligent Transportation Systems*, vol. 27, no. 10, pp. 12 289–12 302, 2026.

[76] Y. Dong, E. Xu, J. Yang, S. Qiu, J. Wang, and B. Han, "Implicit point-to-voxel LiDAR-IMU SLAM," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 8097–8110, 2026.

[77] B. Fang, G. Mei, X. Yuan, L. Wang, Z. Wang, and J. Wang, "Visual SLAM for robot navigation in healthcare facility," *Pattern Recognition*, vol. 113, p. 107822, 2021. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0031320321000091

[78] Y. Zhang, M. Bujanca, and M. Luján, "NGD-SLAM: Towards real-time dynamic SLAM without GPU," in *2025 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2025, pp. 3467–3473.

[79] J. Morris, Y. Wang, M. Kliniewski, and V. Ila, "DynoSAM: Open-source smoothing and mapping framework for dynamic SLAM," *IEEE Transactions on Robotics*, vol. 42, pp. 1178–1197, 2026.

[80] H. Li, X. Meng, X. Zuo, Z. Liu, H. Wang, and D. Cremers, "PG-SLAM: Photorealistic and geometry-aware RGB-D SLAM in dynamic environments," *IEEE Transactions on Robotics*, vol. 41, pp. 6084–6101, 2025.

[81] K. Huang, W. Yang, P. Zhou, L. Li, and J. Yao, "JPG-SLAM: Joint Point-Gaussian splatting representation for dense dynamic SLAM," in *2025 IEEE International Conference on Robotics and Automation (ICRA)*, 2025, pp. 5018–5024.

[82] W. Ali, Y. Cai, P. Jensfelt, and T.-M. Nguyen, "ProbPer-LiLo: Probabilistic persistency modeling for life-long mapping," *IEEE Robotics and Automation Letters*, vol. 11, no. 3, pp. 2530–2537, 2026.

[83] H. Gil, D. Lee, G. Kim, and A. Kim, "Ephemerality meets lidar-based lifelong mapping," in *2025 IEEE International Conference on Robotics and Automation (ICRA)*, 2025, pp. 3312–3319.

[84] L. Yang, S. M. Prakhya, S. Zhu, and Z. Liu, "Lifelong 3D mapping framework for hand-held & robot-mounted LiDAR mapping systems," *IEEE Robotics and Automation Letters*, vol. 9, no. 11, pp. 9446–9453, 2024.

[85] S. Jang, A. J. Lee, I. M. A. Nahrendra, and H. Myung, "Chamelion: Reliable change detection for long-term LiDAR mapping in transient

environments," *IEEE Robotics and Automation Letters*, vol. 11, no. 4, pp. 4361–4368, 2026.

[86] D. C. Herraez, M. Zeller, D. Wang, J. Behley, M. Heidingsfeld, and C. Stachniss, "Multi-session mapping and long-term localization for autonomous vehicles using radar," *IEEE Robotics and Automation Letters*, vol. 11, no. 3, pp. 2522–2529, 2026.

[87] Y. Ma *et al.*, "NVMS-SLAM: Normal vector-based multi-session LiDAR SLAM in indoor environments," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 8034–8045, 2026.

[88] J. Fu, Y. Du, K. Singh, J. B. Tenenbaum, and J. J. Leonard, "NeuSE: Neural SE(3)-equivariant embedding for long-term object-based simultaneous localization and mapping," *The International Journal of Robotics Research*, vol. 45, no. 1, pp. 159–189, 2026. [Online]. Available: https://doi.org/10.1177/02783649251355966

[89] H. Gao, Q. Qiu, H. Liu, D. Liang, C. Wang, and X. Zhang, "ERPoT: Effective and reliable pose tracking for mobile robots using lightweight polygon maps," *IEEE Transactions on Robotics*, vol. 41, pp. 3799–3819, 2025.

[90] F. Xie and S. Schwertfeger, "Robust lifelong indoor LiDAR localization using the area graph," *IEEE Robotics and Automation Letters*, vol. 9, no. 1, pp. 531–538, 2024.

[91] Y. Zhang *et al.*, "BIM-Loc: BIM-integrated discrepancy-aware LiDAR-based indoor localization," *The International Journal of Robotics Research*, vol. 0, no. 0, p. 02783649261462593, 2026. [Online]. Available: https://doi.org/10.1177/02783649261462593

[92] E. Liu, W. Tang, A. Huang, Z. Zhou, and R. Zhang, "A season-robust long-term localization method using trunk semantic features in dynamic orchard environments," *Journal of Field Robotics*, vol. 43, no. 4, pp. 2725–2746, 2026. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.70159

[93] G. Park and W. Chung, "Uncertainty-aware LiDAR-based localization for outdoor mobile robots," *Journal of Field Robotics*, vol. 41, no. 8, pp. 2790–2804, 2024. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.22392

[94] F.-x. Chen *et al.*, "FusedNet: End-to-end mobile robot relocalization in dynamic large-scale scene," *IEEE Robotics and Automation Letters*, vol. 9, no. 5, pp. 4099–4105, 2024.

[95] Z. Wang *et al.*, "LiteFT-PR: Lightweight and fault-tolerant LiDAR-camera fusion network for robust place recognition via model distillation," *IEEE Robotics and Automation Letters*, vol. 11, no. 4, pp. 4267–4274, 2026.

[96] Y. Xie, Y. Guo, Z. Mi, X. Wang, Y. Yang, and M. S. Obaidat, "Indoor visual re-localization for long-term autonomous robots based on object-level features and semantic relationships," *IEEE Robotics and Automation Letters*, vol. 8, no. 2, pp. 840–847, 2023.

[97] L. Zhang, Y. Tao, J. Lin, F. Zhang, and M. Fallon, "Visual localization in 3D maps: comparing point cloud, mesh, and NeRF representations," *Autonomous Robots*, vol. 50, no. 1, 2026, article 14. [Online]. Available: https://doi.org/10.1007/s10514-025-10232-5

[98] S. Gupta, T. Guadagnino, B. Mersch, N. Trekel, M. V. R. Malladi, and C. Stachniss, "Efficiently closing loops in LiDAR-based SLAM using point cloud density maps," *The International Journal of Robotics Research*, vol. 0, no. 0, p. 02783649261449269, 2026. [Online]. Available: https://doi.org/10.1177/02783649261449269

[99] D. Cattaneo and A. Valada, "CMRNext: Camera to LiDAR matching in the wild for localization and extrinsic calibration," *IEEE Transactions on Robotics*, vol. 41, pp. 1995–2013, 2025.

[100] E. Kruzhkov, R. Memmesheimer, and S. Behnke, "OMCL: Open-vocabulary Monte Carlo localization," *IEEE Robotics and Automation Letters*, vol. 11, no. 3, pp. 2698–2705, 2026.

[101] R. Xiao *et al.*, "LiDAR teach, radar repeat: Robust cross-modal navigation in degenerate and varying environments," *IEEE Transactions on Robotics*, vol. 42, pp. 2500–2520, 2026.

[102] Y.-H. Lee, C. Zhu, T. Wiedemann, E. Staudinger, S. Zhang, and C. Günther, "CoVOR-SLAM: Cooperative SLAM using visual odometry and ranges for multi-robot systems," *IEEE Transactions on Intelligent Transportation Systems*, vol. 26, no. 7, pp. 9358–9369, 2025.

[103] M. Zarei and R. Chhabra, "Fault-tolerant multimodal localization of multirobots on matrix Lie groups," *IEEE Transactions on Robotics*, vol. 42, pp. 2459–2477, 2026.

[104] S. Jung, D. Gwak, B. Boots, and J. Hays, "Uncertainty-aware accurate elevation modeling for off-road navigation via neural processes," in *Proceedings of The 9th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, J. Lim, S. Song, and H.-W. Park, Eds., vol. 305. PMLR, 27–30 Sep 2025, pp. 2802–2822. [Online]. Available: https://proceedings.mlr.press/v305/jung25b.html

[105] J. Kim, M. Jeon, J. Min, K. Kwak, and J. Seo, "E2-BKI: Evidential ellipsoidal Bayesian kernel inference for uncertainty-aware Gaussian semantic mapping," *IEEE Robotics and Automation Letters*, vol. 11, no. 3, pp. 2378–2385, 2026.

[106] D. Coleman, S. D. Bopardikar, V. Srivastava, and X. Tan, "Adaptive exploration under localization uncertainty using multi-fidelity Gaussian processes," *Autonomous Robots*, vol. 50, no. 1, p. 10, Feb 2026. [Online]. Available: https://doi.org/10.1007/s10514-025-10235-2

[107] F. Crocetti, R. Brilli, A. Dionigi, M. L. Fravolini, G. Costante, and P. Valigi, "Comparison of DSO and ORB-SLAM3 in low-light environments with auxiliary lighting and deep learning based image enhancing," *Journal of Field Robotics*, vol. 42, no. 7, pp. 3748–3771, 2025. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.22595

[108] K. Xu, Y. Hao, S. Yuan, C. Wang, and L. Xie, "AirSLAM: An efficient and illumination-robust point-line visual SLAM system," *IEEE Transactions on Robotics*, vol. 41, pp. 1673–1692, 2025.

[109] S. Xie, R. Song, Y. Zhao, X. Huang, Y. Li, and W. Zhang, "Circular accessible depth: A robust traversability representation for UGV navigation," *IEEE Transactions on Robotics*, vol. 39, no. 6, pp. 4875–4891, 2023.

[110] T. Guan, D. Kothandaraman, R. Chandra, A. J. Sathyamoorthy, K. Weerakoon, and D. Manocha, "GA-Nav: Efficient terrain segmentation for robot navigation in unstructured outdoor environments," *IEEE Robotics and Automation Letters*, vol. 7, no. 3, pp. 8138–8145, 2022.

[111] I. Cho and W. Chung, "Learning self-supervised traversability with navigation experiences of mobile robots: A risk-aware self-training approach," *IEEE Robotics and Automation Letters*, vol. 9, no. 5, pp. 4122–4129, 2024.

[112] Z. Jian, Z. Liu, H. Shao, X. Wang, X. Chen, and B. Liang, "Path generation for wheeled robots autonomous navigation on vegetated terrain," *IEEE Robotics and Automation Letters*, vol. 9, no. 2, pp. 1764–1771, 2024.

[113] Y. Li *et al.*, "Real-time multilevel terrain-aware path planning for ground mobile robots in large-scale rough terrains," *IEEE Transactions on Robotics*, vol. 41, pp. 4159–4179, 2025.

[114] Y. Zhao, L. Zhou, C. Zhang, and Y. Li, "Anisotropic terrain-aware autonomous exploration via image-domain perception and sparse routing," *IEEE Robotics and Automation Letters*, vol. 11, no. 10, pp. 11 062–11 069, 2026.

[115] Z. Dong *et al.*, "Learning smooth state-dependent traversability from dense point clouds," in *Proceedings of The 9th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, J. Lim, S. Song, and H.-W. Park, Eds., vol. 305. PMLR, 27–30 Sep 2025, pp. 1654–1671. [Online]. Available: https://proceedings.mlr.press/v305/dong25a.html

[116] S. Triest, M. Sivaprakasam, S. Aich, D. Fan, W. Wang, and S. Scherer, "Velociraptor: Leveraging visual foundation models for label-free, risk-aware off-road navigation," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 4483–4494. [Online]. Available: https://proceedings.mlr.press/v270/triest25a.html

[117] D. D. Fan, K. Otsu, Y. Kubo, A. Dixit, J. Burdick, and A. akbar Agha-mohammadi, "STEP: Stochastic traversability evaluation and planning for risk-aware off-road navigation," in *Proceedings of Robotics: Science and Systems*, Virtual, July 2021.

[118] X. Cai *et al.*, "EVORA: Deep evidential traversability learning for risk-aware off-road autonomy," *IEEE Transactions on Robotics*, vol. 40, pp. 3756–3777, 2024.

[119] O. Jerome, G. Kulathunga, and T. Nascimento, "A terrain-adaptive ϵ-constraint MPC for uneven terrain kinodynamic planning," *IEEE Robotics and Automation Letters*, vol. 11, no. 10, pp. 11 865–11 872, 2026.

[120] Y. Jia, Q. Li, and J. P. How, "Off-road navigation via implicit neural representation of terrain traversability," *IEEE Robotics and Automation Letters*, vol. 11, no. 6, pp. 7126–7133, 2026.

[121] S. Saravanan, A. Bains, C. P.C. Chanel, and D. Vivet, "FIT-SLAM 2: Efficient 3D exploration with Fisher information and traversability-based adaptive roadmap," *Robotics and Autonomous Systems*, vol. 194, p. 105188, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889025002854

[122] Y. Xu, R. Zheng, S. Zhang, M. Liu, and J. Yu, "Uncertainty-aware autonomous robot exploration using confidence-rich localization and mapping," *IEEE Transactions on Automation Science and Engineering*, vol. 22, pp. 1124–1138, 2025.

[123] S. Sansoni, J. Gimenez, G. Castro, S. Tosetti, and F. Capraro, "Optimizing exploration with a new uncertainty framework for active SLAM systems," *Robotics and Autonomous Systems*, vol. 193, p. 105059, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889025001459

[124] Q. Bi, X. Zhang, S. Zhang, R. Wang, L. Li, and J. Yuan, "LRAE: Large-region-aware safe and fast autonomous exploration of ground robots for uneven terrains," *IEEE Robotics and Automation Letters*, vol. 9, no. 12, pp. 11 186–11 193, 2024.

[125] A. Asgharivaskasi and N. Atanasov, "Semantic OcTree mapping and Shannon mutual information computation for robot exploration," *IEEE Transactions on Robotics*, vol. 39, no. 3, pp. 1910–1928, 2023.

[126] Y. Li *et al.*, "FRTree planner: Robot navigation in cluttered and unknown environments with tree of free regions," *IEEE Robotics and Automation Letters*, vol. 10, no. 4, pp. 3811–3818, 2025.

[127] R. Bai, H. Guo, W.-Y. Yau, and L. Xie, "Graph-based SLAM-aware exploration with prior topo-metric information," *IEEE Robotics and Automation Letters*, vol. 9, no. 9, pp. 7597–7604, 2024.

[128] A. Hierholz, V. Reß, N. Hentschel, A. Gienger, N. Haala, and O. Sawodny, "Active visual SLAM using potential fields and model predictive control," *Control Engineering Practice*, vol. 172, p. 106897, 2026. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0967066126001413

[129] Z. Sun, B. Xia, P. Xie, X. Li, and J. Wang, "NAMR-RRT: Neural adaptive motion planning for mobile robots in dynamic environments," *IEEE Transactions on Automation Science and Engineering*, vol. 22, pp. 13 087–13 100, 2025.

[130] Z. Liu, W. Na, C. Yao, C. Liu, and Q. Chen, "Relaxing the limitations of the optimal reciprocal collision avoidance algorithm for mobile robots in crowds," *IEEE Robotics and Automation Letters*, vol. 9, no. 6, pp. 5520–5527, 2024.

[131] Z. Xie and P. Dames, "SCOPE: Stochastic cartographic occupancy prediction engine for uncertainty-aware dynamic navigation," *IEEE Transactions on Robotics*, vol. 41, pp. 4139–4158, 2025.

[132] O. de Groot, L. Ferranti, D. M. Gavrila, and J. Alonso-Mora, "Topology-driven parallel trajectory optimization in dynamic environments," *IEEE Transactions on Robotics*, vol. 41, pp. 110–126, 2025.

[133] T. Soualhi, N. Crombez, A. Lombard, Y. Ruichek, and S. Galland, "Leveraging motion perceptibility and deep reinforcement learning for visual control of nonholonomic mobile robots," *Robotics and Autonomous Systems*, vol. 189, p. 104920, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889025000065

[134] J. de Heuvel, X. Zeng, W. Shi, T. Sethuraman, and M. Bennewitz, "Spatiotemporal attention enhances lidar-based robot navigation in dynamic environments," *IEEE Robotics and Automation Letters*, vol. 9, no. 5, pp. 4202–4209, 2024.

[135] S. Liu *et al.*, "HEIGHT: Heterogeneous interaction graph transformer for robot navigation in crowded and constrained environments," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 1211–1230, 2026.

[136] H. Hu, K. Zhang, A. H. Tan, M. Ruan, C. Agia, and G. Nejat, "A sim-to-real pipeline for deep reinforcement learning for autonomous robot navigation in cluttered rough terrain," *IEEE Robotics and Automation Letters*, vol. 6, no. 4, pp. 6569–6576, 2021.

[137] B. Liu, X. Xiao, and P. Stone, "A lifelong learning approach to mobile robot navigation," *IEEE Robotics and Automation Letters*, vol. 6, no. 2, pp. 1090–1096, 2021.

[138] S. Keyumarsi, M. W. S. Atman, and A. Gusrialdi, "Circulation-embedded control barrier function for safe navigation: A solution to avoid undesired equilibria and dysfunctional circulation," *Robotics and Autonomous Systems*, vol. 194, p. 105132, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889025002295

[139] F. Vesentini, D. Meli, N. Sansonetto, L. D. Persio, and R. Muradore, "Dynamic movement primitives with control barrier functions for constrained trajectory planning," *IEEE Robotics and Automation Letters*, vol. 10, no. 9, pp. 9416–9421, 2025.

[140] E. Daş and J. W. Burdick, "Robust control barrier functions using uncertainty estimation with application to mobile robots," *IEEE Transactions on Automatic Control*, vol. 70, no. 7, pp. 4766–4773, 2025.

[141] X. Kong, Y. Xia, Z. Sun, D.-H. Zhai, Y. Deng, and S. Zhang, "Differential high order control barrier function-based safe reinforcement learning," *IEEE Robotics and Automation Letters*, vol. 10, no. 7, pp. 7524–7531, 2025.

[142] K. Long, Y. Yi, Z. Dai, S. Herbert, J. Cortés, and N. Atanasov, "Sensor-based distributionally robust control for safe robot navigation in dynamic environments," *The International Journal of Robotics Research*, vol. 45, no. 2, pp. 328–351, 2026. [Online]. Available: https://doi.org/10.1177/02783649251352000

[143] X. Wang, T. Kim, B. Hoxha, G. Fainekos, and D. Panagou, "Safe navigation in uncertain crowded environments using risk adaptive CVaR barrier functions," in *2025 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2025, pp. 7669–7676.

[144] Y. Ma *et al.*, "Safety-critical control of nonholonomic vehicle trajectory tracking via risk-aware zone control barrier functions," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 13 469–13 479, 2026.

[145] O. de Groot, L. Ferranti, D. M. Gavrila, and J. Alonso-Mora, "Scenario-based motion planning with bounded probability of collision," *The International Journal of Robotics Research*, vol. 44, no. 9, pp. 1507–1525, 2025. [Online]. Available: https://doi.org/10.1177/02783649251315203

[146] A. Dixit, Z. Mei, M. Booker, M. Storey-Matsutani, A. Z. Ren, and A. Majumdar, "Perceive with confidence: Statistical safety assurances for navigation with learning-based perception," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 2517–2541. [Online]. Available: https://proceedings.mlr.press/v270/dixit25a.html

[147] B. Sharma, P. Jadhav, P. Paul, K. Krishna, and A. K. Singh, "MonoMPC: Monocular vision based navigation with learned collision model and risk-aware model predictive control," *IEEE Robotics and Automation Letters*, vol. 11, no. 2, pp. 1330–1337, 2026.

[148] J. Wang, M. T. H. Fader, and J. A. Marshall, "Learning-based model predictive control for improved mobile robot path following using Gaussian processes and feedback linearization," *Journal of Field Robotics*, vol. 40, no. 5, pp. 1014–1033, 2023. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.22165

[149] J. Cao, S. Khan, W. Liu, Y. Li, and B. Vucetic, "Remote UGV control via practical wireless channels: A model predictive control approach," *IEEE Transactions on Intelligent Vehicles*, pp. 1–13, 2024.

[150] R. Wang *et al.*, "Vehicle-cloud cooperative trajectory planning via switched model predictive control for UGVs in unstructured transportation environment," *IEEE Transactions on Intelligent Transportation Systems*, vol. 27, no. 8, pp. 9517–9528, 2026.

[151] P. Y. Ingle and Y.-G. Kim, "Seeing danger before moving: Learning environment-centric risk for safe robot navigation," in *Proceedings of Robotics: Science and Systems*, Sydney, Australia, July 2026.

[152] P. Sherman and N. Bezzo, "A unified framework for mission-gain-aware proactive planning and control of autonomous mobile robots," *IEEE Robotics and Automation Letters*, vol. 11, no. 10, pp. 12 192–12 199, 2026.

[153] R. Das, S. Upadhyay, and P. Jagtap, "Real-time spatiotemporal tubes for dynamic unsafe sets," *IEEE Robotics and Automation Letters*, vol. 11, no. 2, pp. 2146–2153, 2026.

[154] Z. Hu, R. Ma, S. Zhang, H. Wang, X. Liu, and D. Zhao, "Resilient memory-event-triggered predictive tracking control for unmanned ground vehicle," *IEEE Transactions on Intelligent Vehicles*, vol. 11, no. 4, pp. 500–510, 2026.

[155] D. Mu, C. Hua, J. Chen, Y. Li, L. Zhu, and F. Liu, "Universal low-complexity safe tracking control and its application to time-independent path following of nonholonomic mobile robots," *IEEE Transactions on Automation Science and Engineering*, vol. 22, pp. 18 594–18 604, 2025.

[156] A. Werby, C. Huang, M. Büchner, A. Valada, and W. Burgard, "Hierarchical open-vocabulary 3D scene graphs for language-grounded robot navigation," in *Proceedings of Robotics: Science and Systems*, Delft, Netherlands, July 2024.

[157] J. Jiang, Y. Zhu, Z. Wu, and J. Song, "DualMap: Online open-vocabulary semantic mapping for natural language navigation in dynamic changing scenes," *IEEE Robotics and Automation Letters*, vol. 10, no. 12, pp. 12 612–12 619, 2025.

[158] Q. Gu *et al.*, "ConceptGraphs: Open-vocabulary 3D scene graphs for perception and planning," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 5021–5028.

[159] Y. Tang *et al.*, "OpenIN: Open-vocabulary instance-oriented navigation in dynamic domestic environments," *IEEE Robotics and Automation Letters*, vol. 10, no. 9, pp. 9256–9263, 2025.

[160] F. Xie, S. Schwertfeger, and H. Blum, "osmAG-LLM: Zero-shot open-vocabulary object navigation via semantic maps and large language models reasoning," *IEEE Robotics and Automation Letters*, vol. 11, no. 3, pp. 2426–2433, 2026.

[161] N. Yokoyama, S. Ha, D. Batra, J. Wang, and B. Bucher, "VLFM: Vision-language frontier maps for zero-shot semantic navigation," in

2024 IEEE International Conference on Robotics and Automation (ICRA), 2024, pp. 42–48.

[162] B. Yu, Y. Liu, L. Han, H. Kasaei, T. Li, and M. Cao, "VLN-Game: Vision-language equilibrium search for zero-shot semantic navigation," *IEEE Transactions on Robotics*, vol. 42, pp. 1824–1839, 2026.

[163] H. Zhu *et al.*, "SysNav: Multi-level systematic cooperation enables real-world, cross-embodiment object navigation," *IEEE Robotics and Automation Letters*, vol. 11, no. 9, pp. 10 577–10 584, 2026.

[164] C. Huang, O. Mees, A. Zeng, and W. Burgard, "Multimodal spatial language maps for robot navigation and manipulation," *The International Journal of Robotics Research*, vol. 0, no. 0, p. 02783649251351658, 2025. [Online]. Available: https://doi.org/10.1177/02783649251351658

[165] L. Chen, Z. He, L. Wang, C. Liu, and Q. Chen, "Temporal scene-object graph learning for object navigation," *IEEE Robotics and Automation Letters*, vol. 10, no. 5, pp. 4914–4921, 2025.

[166] J. Wang, D. Huo, Y. Shi, C. Gao, Y. Qiao, and G. Zhou, "OPEN: Lightweight map-based semantic navigation for GPS-free last-mile delivery," *IEEE Transactions on Automation Science and Engineering*, vol. 22, pp. 20 713–20 725, 2025.

[167] D. Wang *et al.*, "G-DRAGON: Geospatial reasoning and dynamic planning for retrieval-augmented outdoor navigation," *IEEE Robotics and Automation Letters*, vol. 11, no. 7, pp. 8768–8775, 2026.

[168] H. Duan *et al.*, "CAUSALNAV: A long-term embodied navigation system for autonomous mobile robots in dynamic outdoor scenarios," *IEEE Robotics and Automation Letters*, vol. 11, no. 3, pp. 3198–3205, 2026.

[169] A. H. Tan, A. Fung, H. Wang, and G. Nejat, "Mobile robot navigation using hand-drawn maps: A vision language model approach," *IEEE Robotics and Automation Letters*, vol. 10, no. 7, pp. 7667–7674, 2025.

[170] Z. Xu *et al.*, "Mobility VLA: Multimodal instruction navigation with long-context VLMs and topological graphs," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 3866–3887. [Online]. Available: https://proceedings.mlr.press/v270/xu25b.html

[171] D. Shah, B. Osiński, B. Ichter, and S. Levine, "LM-Nav: Robotic navigation with large pre-trained models of language, vision, and action," in *Proceedings of The 6th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, K. Liu, D. Kulic, and J. Ichnowski, Eds., vol. 205. PMLR, 14–18 Dec 2023, pp. 492–504. [Online]. Available: https://proceedings.mlr.press/v205/shah23b.html

[172] D. Shah, A. Sridhar, A. Bhorkar, N. Hirose, and S. Levine, "GNM: A general navigation model to drive any robot," in *2023 IEEE International Conference on Robotics and Automation (ICRA)*, 2023, pp. 7226–7233.

[173] D. Shah *et al.*, "ViNT: A foundation model for visual navigation," in *Proceedings of The 7th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, J. Tan, M. Toussaint, and K. Darvish, Eds., vol. 229. PMLR, 06–09 Nov 2023, pp. 711–733. [Online]. Available: https://proceedings.mlr.press/v229/shah23a.html

[174] A. Sridhar, D. Shah, C. Glossop, and S. Levine, "NoMaD: Goal masked diffusion policies for navigation and exploration," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 63–70.

[175] N. Hirose, C. Glossop, A. Sridhar, O. Mees, and S. Levine, "LeLaN: Learning a language-conditioned navigation policy from in-the-wild video," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 666–688. [Online]. Available: https://proceedings.mlr.press/v270/hirose25b.html

[176] J. Zhang *et al.*, "Uni-NaVid: A video-based vision-language-action model for unifying embodied navigation tasks," in *Proceedings of Robotics: Science and Systems*, LosAngeles, CA, USA, June 2025.

[177] V. S. Dorbala, J. F. Mullen, and D. Manocha, "Can an embodied agent find your "cat-shaped mug"? LLM-based zero-shot object navigation," *IEEE Robotics and Automation Letters*, vol. 9, no. 5, pp. 4083–4090, 2024.

[178] D. Song, J. Liang, X. Xiao, and D. Manocha, "VL-TGS: Trajectory generation and selection using vision language models in mapless outdoor environments," *IEEE Robotics and Automation Letters*, vol. 10, no. 6, pp. 5791–5798, 2025.

[179] G. Olguín and J. Ruiz-del Solar, "Sem-NaVAE: Semantically-guided outdoor mapless navigation via generative trajectory priors," *IEEE Robotics and Automation Letters*, vol. 11, no. 8, pp. 9335–9342, 2026.

[180] M. G. Castro *et al.*, "VAMOS: A hierarchical vision-language-action model for capability-modulated and steerable navigation," *IEEE Robotics and Automation Letters*, vol. 11, no. 11, pp. 13 055–13 062, 2026.

[181] D. Song, J. Liang, A. Payandeh, A. H. Raj, X. Xiao, and D. Manocha, "VLM-Social-Nav: Socially aware robot navigation through scoring using vision-language models," *IEEE Robotics and Automation Letters*, vol. 10, no. 1, pp. 508–515, 2025.

[182] D. Huo, J. Wang, C. Gao, Y. Qiao, D. Zhang, and G. Zhou, "NORM-Nav: Zero-shot mobile robot navigation with natural language behavioral constraints," in *2026 IEEE International Conference on Robotics and Automation (ICRA)*, 2026, pp. 1139–1146.

[183] Z. Fang, A. Xiao, D. Hsu, and G. H. Lee, "From obstacles to etiquette: Robot social navigation with VLM-informed path selection," *IEEE Robotics and Automation Letters*, vol. 11, no. 4, pp. 3947–3954, 2026.

[184] S. Luo *et al.*, "GSON: A group-based social navigation framework with large multimodal model," *IEEE Robotics and Automation Letters*, vol. 10, no. 10, pp. 9646–9653, 2025.

[185] S. Narasimhan, A. H. Tan, D. Choi, and G. Nejat, "OLiVia-Nav: An online lifelong vision language approach for mobile robot social navigation," in *2025 IEEE International Conference on Robotics and Automation (ICRA)*, 2025, pp. 9130–9137.

[186] L. Yue, D. Zhou, L. Xie, F. Zhang, Y. Yan, and E. Yin, "Safe-VLN: Collision avoidance for vision-and-language navigation of autonomous robots operating in continuous environments," *IEEE Robotics and Automation Letters*, vol. 9, no. 6, pp. 4918–4925, 2024.

[187] M. J. Munje *et al.*, "SocialNav-SUB: Benchmarking VLMs for scene understanding in social robot navigation," in *Proceedings of The 9th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, J. Lim, S. Song, and H.-W. Park, Eds., vol. 305. PMLR, 27–30 Sep 2025, pp. 1120–1143. [Online]. Available: https://proceedings.mlr.press/v305/munje25a.html

[188] M. Elnoor *et al.*, "VLM-GroNav: Robot navigation using physically grounded vision-language models in outdoor environments," in *2025 IEEE International Conference on Robotics and Automation (ICRA)*, 2025, pp. 2391–2398.

[189] T. Zeng, H. Ye, J. Peng, J. Yu, H. Chen, and H. Zhang, "TARIC: Memory-augmented traversability-aware outdoor VLN under interrupted semantic cues," *IEEE Robotics and Automation Letters*, vol. 11, no. 9, pp. 10 082–10 089, 2026.

[190] Q. Bi *et al.*, "CURE: A hierarchical framework for multi-robot autonomous exploration inspired by centroids of unknown regions," *IEEE Transactions on Automation Science and Engineering*, vol. 21, no. 3, pp. 3773–3786, 2024.

[191] P. Wang, Z. Wang, L. Shi, and M. Q.-H. Meng, "DMT-CPP: A Delaunay-Graph-Based framework for real-time multi-robot online target coverage," *IEEE Robotics and Automation Letters*, vol. 11, no. 7, pp. 8785–8792, 2026.

[192] B. Fu, W. Smith, D. M. Rizzo, M. Castanier, M. Ghaffari, and K. Barton, "Robust task scheduling for heterogeneous robot teams under capability uncertainty," *IEEE Transactions on Robotics*, vol. 39, no. 2, pp. 1087–1105, 2023.

[193] E. Latif and R. Parasuraman, "Communication-efficient multi-robot exploration using coverage-biased distributed Q-learning," *IEEE Robotics and Automation Letters*, vol. 9, no. 3, pp. 2622–2629, 2024.

[194] A. Athukorala, B. P. L. Lau, K. Pongsirijinda, C. Yuen, and U.-X. Tan, "Multi-robot collaborative SLAM (Multi-SLAM) with distributed lightweight predictive frontier exploration (LPFE)," *IEEE Robotics and Automation Letters*, vol. 11, no. 2, pp. 2274–2281, 2026.

[195] A. H. Tan, S. Narasimhan, and G. Nejat, "4CNet: A diffusion approach to map prediction for decentralized multirobot exploration," *IEEE Transactions on Robotics*, vol. 42, pp. 1371–1388, 2026.

[196] Q. Bi, X. Zhang, S. Zhang, Q. Dong, and J. Yuan, "URGE: Efficient decentralized multirobot exploration guided by unknown regions under limited communication," *IEEE Transactions on Robotics*, vol. 42, pp. 3028–3047, 2026.

[197] H. Zhao, K. Xu, N. Xu, X. Li, and J. Jin, "Multi-robot collaborative navigation framework based on 3D Voronoi partitioning in uneven and unstructured environments," *Journal of Field Robotics*, vol. 43, no. 7, pp. 4531–4548, 2026. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.70260

[198] Z. Zhang, J. Yu, J. Tang, Y. Xu, and Y. Wang, "MR-TopoMap: Multi-robot exploration based on topological map in communication restricted environment," *IEEE Robotics and Automation Letters*, vol. 7, no. 4, pp. 10 794–10 801, 2022.

[199] J. Bayer and J. Faigl, "Decentralized multi-robot exploration under low-bandwidth communications," *Autonomous Robots*, vol. 50, no. 1, p. 7, Dec 2025. [Online]. Available: https://doi.org/10.1007/s10514-025-10234-3

[200] N. Jadhav, M. Behari, R. J. Wood, and S. Gil, "WiSER-X: Wireless signal-based decentralized multi-robot exploration without explicit information exchange," *IEEE Robotics and Automation Letters*, vol. 11, no. 9, pp. 10 983–10 990, 2026.
[201] X. Liu *et al.*, "SlideSLAM: Sparse, lightweight, decentralized metric-semantic SLAM for multirobot navigation," *IEEE Transactions on Robotics*, vol. 41, pp. 6529–6548, 2025.
[202] H. Kim *et al.*, "Commerge: Communication-efficient, robust, and fast LiDAR map merging framework for multi-robot coordination in resource-constrained scenarios," *The International Journal of Robotics Research*, vol. 0, no. 0, p. 02783649261464202, 2026. [Online]. Available: https://doi.org/10.1177/02783649261464202
[203] G. Niu, S. Nuerdaolieti, J. Li, Z. Jing, L. Hou, and J. Sun, "Feedback-guided hierarchical transmission for multi-robot mapping under bandwidth constraints," *IEEE Robotics and Automation Letters*, vol. 11, no. 7, pp. 8576–8583, 2026.
[204] Y. Sun *et al.*, "PROMO-Orchard: A robust semantic-enhanced framework for dual-robot simultaneous localization and mapping merging in orchard," *Journal of Field Robotics*, vol. 43, no. 7, pp. 4880–4903, 2026. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.70323
[205] D. McGann and M. Kaess, "iMESA: Incremental distributed optimization for collaborative simultaneous localization and mapping," in *Proceedings of Robotics: Science and Systems*, Delft, Netherlands, July 2024.
[206] ——, "riMESA: Consensus ADMM for real-world collaborative SLAM," *IEEE Transactions on Robotics*, vol. 42, pp. 3550–3569, 2026.
[207] J. Wang, C. Cai, J. Tan, and H. Chen, "Communication-robust asynchronous distributed LiDAR collaborative smoothing and mapping," *IEEE Robotics and Automation Letters*, vol. 11, no. 3, pp. 3700–3707, 2026.
[208] Q. Tang, H. Liu, M. Yu, and Y. Wang, "Parallel graph inference for decentralized and asynchronous multi-robot cooperative localization under limited connectivity," *IEEE Robotics and Automation Letters*, vol. 11, no. 10, pp. 12 120–12 127, 2026.
[209] Y. Tian, Y. Chang, F. Herrera Arias, C. Nieto-Granda, J. P. How, and L. Carlone, "Kimera-Multi: Robust, distributed, dense metric-semantic SLAM for multi-robot systems," *IEEE Transactions on Robotics*, vol. 38, no. 4, pp. 2022–2038, 2022.
[210] Y. Chang *et al.*, "LAMP 2.0: A robust multi-robot SLAM system for operation in challenging large-scale underground environments," *IEEE Robotics and Automation Letters*, vol. 7, no. 4, pp. 9175–9182, 2022.
[211] P.-Y. Lajoie and G. Beltrame, "Swarm-SLAM: Sparse decentralized collaborative simultaneous localization and mapping framework for multi-robot systems," *IEEE Robotics and Automation Letters*, vol. 9, no. 1, pp. 475–482, 2024.
[212] P.-Y. Lajoie, B. Ramtoula, D. De Martini, and G. Beltrame, "3D foundation model-based loop closing for decentralized collaborative SLAM," *IEEE Robotics and Automation Letters*, vol. 10, no. 11, pp. 11 188–11 195, 2025.
[213] L. Bianchi and F. Martinelli, "A cooperative approach to range-only SLAM with undelayed initialization," *Robotics and Autonomous Systems*, vol. 196, p. 105230, 2026. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889025003276
[214] J. Liu and G. Hu, "Extended range of localization services via formation-controlled mobile ultra-wideband anchors," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 265–277, 2026.
[215] R. Bai, S. Yuan, H. Guo, P. Yin, W.-Y. Yau, and L. Xie, "Multi-robot active graph exploration with reduced Pose-SLAM uncertainty via submodular optimization," in *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2024, pp. 10 229–10 236.
[216] M. Luperto, M. Tellaroli, M. Antonazzi, and N. Basilico, "Multi-robot rendezvous in communication-restricted unknown environments via backtracking and semantic frontier-based exploration," *Robotics and Autonomous Systems*, vol. 194, p. 105137, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889025002349
[217] A. R. Da Silva, L. Chaimowicz, T. C. Silva, and M. A. Hsieh, "Communication-constrained multi-robot exploration with intermittent rendezvous," in *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2024, pp. 3490–3497.
[218] X. Zhang, J. Chen, Y. Zhu, B. Luo, and M. Guo, "CoCoPlan: Adaptive coordination and communication for multi-robot systems in dynamic and unknown environments," *IEEE Robotics and Automation Letters*, vol. 11, no. 3, pp. 3270–3277, 2026.
[219] K. Pongsirijinda, Z. Cao, B. P. L. Lau, R. Liu, C. Yuen, and U.-X. Tan, "MEF-Explore: Communication-constrained multi-robot entropy-field-based exploration," *IEEE Transactions on Automation Science and Engineering*, vol. 22, pp. 16 062–16 078, 2025.
[220] A. Asgharivaskasi, F. Girke, and N. Atanasov, "Riemannian optimization for active mapping with robot teams," *IEEE Transactions on Robotics*, vol. 41, pp. 1077–1097, 2025.
[221] N. Hudson *et al.*, "Heterogeneous ground and air platforms, homogeneous sensing: Team CSIRO Data61's approach to the DARPA Subterranean Challenge," *Field Robotics*, vol. 2, pp. 595–636, 2022.
[222] S. Scherer *et al.*, "Resilient and modular subterranean exploration with a team of roving and flying robots," *Field Robotics*, vol. 2, pp. 678–734, 2022.
[223] M. Tranzatto *et al.*, "CERBERUS in the DARPA Subterranean Challenge," *Science Robotics*, vol. 7, no. 66, p. eabp9742, 2022. [Online]. Available: https://www.science.org/doi/abs/10.1126/scirobotics.abp9742
[224] M. Escourrou, J. Al Hage, and P. Bonnifait, "Fault tolerant decentralized collaboration for simultaneous localization and prior map update with stable 2D features," *Robotics and Autonomous Systems*, vol. 200, p. 105402, 2026. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889026000758
[225] P. Li, J. Liu, Y. Wu, and L. Zhou, "Failure-aware multi-robot coordination for resilient and adaptive target tracking," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 4023–4038, 2026.
[226] P. Zhong, F. Rossi, and D. A. Shell, "Planned synchronization for multi-robot systems with active observations," *Autonomous Robots*, vol. 50, no. 1, 2026, article 5; first published online 24 December 2025; assigned to the March 2026 issue. [Online]. Available: https://doi.org/10.1007/s10514-025-10225-4
[227] V. Vijay, K. A. Pant, M. Cho, Y. Guo, J. M. Goppert, and I. Hwang, "Range-based multi-robot integrity monitoring for cyberattacks and faults: An anchor-free approach," *IEEE Robotics and Automation Letters*, vol. 10, no. 3, pp. 2630–2637, 2025.
[228] R. Han *et al.*, "Reinforcement learned distributed multi-robot navigation with reciprocal velocity obstacle shaped rewards," *IEEE Robotics and Automation Letters*, vol. 7, no. 3, pp. 5896–5903, 2022.
[229] S. Yin, C. Chen, and Z. Xiang, "Predefined-time fault-tolerant formation control for large-scale heterogeneous wheeled mobile robot swarms," *IEEE Systems Journal*, vol. 20, no. 3, pp. 771–780, 2026.
[230] Z. Du, H. Zhang, P. Cui, Z. Wang, and H. Yan, "Safe trajectory generation for nonholonomic multi-robot systems: A compensation-based MPC approach," *IEEE Transactions on Automation Science and Engineering*, vol. 22, pp. 21 831–21 842, 2025.
[231] S. Rajkumar, C. Tiriolo, and W. Lucia, "A set-theoretic control strategy for a platoon of constrained differential-drive robots with inter-vehicle collision avoidance," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 4213–4222, 2026.
[232] J.-Y. Yin, G.-H. Yang, H. Wang, and J.-S. Wang, "Distributed safe navigation for multi-robot systems with fixed-time convergence and deadlock resolution," *IEEE Robotics and Automation Letters*, vol. 11, no. 5, pp. 5302–5309, 2026.
[233] K. B. Naveed, D. R. Agrawal, R. Kumar, and D. Panagou, "Adaptive ergodic search with energy-aware scheduling for persistent multi-robot missions," *Autonomous Robots*, vol. 49, no. 4, p. 27, Sep 2025. [Online]. Available: https://doi.org/10.1007/s10514-025-10215-6
[234] S. Verma and D. S. Bernstein, "Real-time kinematics-based sensor-fault detection for autonomous vehicles using single and double transport with adaptive numerical differentiation," *Control Engineering Practice*, vol. 159, p. 106304, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S096706612500067X
[235] S. Zhang, V. Puig, and S. Ifqir, "Robust LPV fault diagnosis using the set-based approach for autonomous ground vehicles," *IEEE Transactions on Intelligent Transportation Systems*, vol. 25, no. 8, pp. 9078–9090, 2024.
[236] J.-X. Zhang, J. Ding, and T. Chai, "Fault-tolerant prescribed performance control of wheeled mobile robots: A mixed-gain adaption approach," *IEEE Transactions on Automatic Control*, vol. 69, no. 8, pp. 5500–5507, 2024.
[237] J.-X. Zhang, J. Zhao, and P. K. Wong, "Fault-tolerant trajectory tracking for unmanned ground vehicles via virtual error-based prescribed performance control," *IEEE Transactions on Automatic Control*, vol. 71, no. 4, pp. 2660–2667, 2026.
[238] H. Wu, S. Wang, H. Li, Y. Xie, S. Zheng, and S. Q. Xie, "Adaptive fault-tolerant control of wheeled mobile robots with multiple actuator faults and saturation," *IEEE Robotics and Automation Letters*, vol. 10, no. 4, pp. 4156–4163, 2025.
[239] W. Ao, H. Yin, S. Sun, P. Liu, and P. Shi, "Fixed-time fault-tolerant trajectory tracking control for a wheeled mobile robot," *IEEE Trans-*

actions on Automation Science and Engineering, vol. 23, pp. 811–819, 2026.

[240] R. Ma, Y. Yu, S. Zhang, and P. Shi, "Event-triggered fault-tolerant tracking control for autonomous ground vehicle via descriptor reduced-order observer," *IEEE Transactions on Intelligent Transportation Systems*, vol. 26, no. 7, pp. 10 308–10 319, 2025.

[241] N. Akai, "Reliable Monte Carlo localization for mobile robots," *Journal of Field Robotics*, vol. 40, no. 3, pp. 595–613, 2023. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.22149

[242] X. Zheng, W. Wen, and L.-T. Hsu, "Safety-quantifiable line feature-based monocular visual localization with 3D prior map," *IEEE Transactions on Intelligent Transportation Systems*, vol. 26, no. 7, pp. 9226–9240, 2025.

[243] A. Saboury and M. K. Uyguroglu, "Uncertainty-aware real-time visual anomaly detection with conformal prediction in dynamic indoor environments," *IEEE Robotics and Automation Letters*, vol. 10, no. 5, pp. 4468–4475, 2025.

[244] C. Agia *et al.*, "Unpacking failure modes of generative policies: Runtime monitoring of consistency and progress," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 689–723. [Online]. Available: https://proceedings.mlr.press/v270/agia25a.html

[245] T. Ji, A. N. Sivakumar, G. Chowdhary, and K. Driggs-Campbell, "Proactive anomaly detection for robot navigation with multi-sensor fusion," *IEEE Robotics and Automation Letters*, vol. 7, no. 2, pp. 4975–4982, 2022.

[246] C. Dawson, A. Parashar, and C. Fan, "RADIUM: Predicting and repairing end-to-end robot failures using gradient-accelerated sampling," *IEEE Transactions on Robotics*, vol. 41, pp. 2268–2284, 2025.

[247] N. Mohammad, J. Higgins, and N. Bezzo, "A GP-based robust motion planning framework for agile autonomous robot navigation and recovery in unknown environments," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 2418–2424.

[248] H. Zhang, Z. Li, and A. Clark, "Safe control for nonlinear systems under faults and attacks via control barrier functions," *IEEE Transactions on Automatic Control*, vol. 70, no. 11, pp. 7334–7349, 2025.

[249] M. Ganai, R. Sinha, C. Agia, D. Morton, L. D. Lillo, and M. Pavone, "Real-time out-of-distribution failure prevention via multi-modal reasoning," in *Proceedings of The 9th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, J. Lim, S. Song, and H.-W. Park, Eds., vol. 305. PMLR, 27–30 Sep 2025, pp. 283–308. [Online]. Available: https://proceedings.mlr.press/v305/ganai25a.html

[250] M. H. Shahna, P. Mustalahti, and J. Mattila, "NMPC-augmented visual navigation and safe learning control for large-scale mobile robots," *IEEE Robotics and Automation Letters*, vol. 11, no. 4, pp. 5182–5189, 2026.

[251] A. T. Buyukkocak and D. Aksaray, "Resilient online planning for mobile robots with minimal relaxation of signal temporal logic specifications," *IEEE Robotics and Automation Letters*, vol. 10, no. 6, pp. 5935–5942, 2025.

[252] J. O'Keeffe, "Anticipating degradation: A predictive approach to fault tolerance in robot swarms," *IEEE Robotics and Automation Letters*, vol. 10, no. 9, pp. 8954–8961, 2025.

[253] C. Chen, Y. Liu, Y. Zhuang, S. Mao, K. Xue, and S. Zhou, "SCALE: Self-correcting visual navigation for mobile robots via anti-novelty estimation," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 16 360–16 366.

[254] J. Kim, J. Sim, W. Kim, K. P. Sycara, and C. Nam, "CARE: Enhancing safety of visual navigation through collision avoidance via repulsive estimation," in *Proceedings of The 9th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, J. Lim, S. Song, and H.-W. Park, Eds., vol. 305. PMLR, 27–30 Sep 2025, pp. 3704–3719. [Online]. Available: https://proceedings.mlr.press/v305/kim25c.html

[255] G. Notomista *et al.*, "A resilient and energy-aware task allocation framework for heterogeneous multirobot systems," *IEEE Transactions on Robotics*, vol. 38, no. 1, pp. 159–179, 2022.

[256] H. Guo, Q. Kang, W.-Y. Yau, C.-M. Chew, and D. Rus, "R-FAC: Resilient value function factorization for multirobot efficient search with individual failure probabilities," *IEEE Transactions on Robotics*, vol. 41, pp. 3385–3401, 2025.

[257] D. Milojevic, G. Zardini, M. Elser, A. Censi, and E. Frazzoli, "CODEI: Resource-efficient task-driven co-design of perception and decision making for mobile robots applied to autonomous vehicles," *IEEE Transactions on Robotics*, vol. 41, pp. 2727–2748, 2025.

[258] S. Shahsavari, H. Haghbayan, A. Miele, E. Immonen, and J. Plosila, "A coordinated approach to control mechanical and computing resources in mobile robots," *IEEE Transactions on Robotics*, vol. 41, pp. 347–363, 2025.

[259] N. Kumar, J. J. Lee, S. Rathinam, S. Darbha, P. B. Sujit, and R. Raman, "The persistent robot charging problem for long-duration autonomy," *IEEE Robotics and Automation Letters*, vol. 10, no. 3, pp. 2191–2198, 2025.

[260] A. B. Asghar, S. Sundaram, and S. L. Smith, "Multirobot persistent monitoring: Minimizing latency and number of robots with recharging constraints," *IEEE Transactions on Robotics*, vol. 41, pp. 236–252, 2025.

[261] C. Wang *et al.*, "Design and implementation of cloud–edge collaborative mapping and control system for mobile robots," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 11 096–11 116, 2026.

[262] T. Rouček, Z. Rozsypálek, J. Blaha, J. Ulrich, and T. Krajník, "Predictive data acquisition for lifelong visual teach, repeat and learn," *IEEE Robotics and Automation Letters*, vol. 9, no. 11, pp. 10 042–10 049, 2024.

[263] N. Hirose, D. Shah, K. Stachowicz, A. Sridhar, and S. Levine, "SELFI: Autonomous self-improvement with RL for vision-based navigation around people," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 97–116. [Online]. Available: https://proceedings.mlr.press/v270/hirose25a.html

[264] K. Stachowicz, L. Ignatova, and S. Levine, "Lifelong autonomous improvement of navigation foundation models in the wild," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 1035–1047. [Online]. Available: https://proceedings.mlr.press/v270/stachowicz25a.html

[265] A. Paudel, X. Xiao, and G. J. Stein, "Multi-strategy deployment-time learning and adaptation for navigation under uncertainty," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 3908–3923. [Online]. Available: https://proceedings.mlr.press/v270/paudel25a.html

[266] F. Schmidt, C. Blessing, M. Enzweiler, and A. Valada, "Visual-inertial SLAM for unstructured outdoor environments: Benchmarking the benefits and computational costs of loop closing," *Journal of Field Robotics*, vol. 42, no. 7, pp. 3726–3747, 2025. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.22581

[267] D. Skuddis and N. Haala, "DMSA - dense multi scan adjustment for LiDAR inertial odometry and global optimization," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 12 027–12 033.

[268] H. Huang, M. Zhang, J. Hu, and X. Guan, "Unveiling non-reproducibility in LiDAR-inertial odometry," *IEEE Robotics and Automation Letters*, vol. 11, no. 1, pp. 994–1001, 2026.

[269] B. Yu, Q. Yuan, K. Li, H. Kasaei, and M. Cao, "Co-NavGPT: Multi-robot cooperative visual semantic navigation using vision language models," *IEEE Robotics and Automation Letters*, vol. 11, no. 2, pp. 2122–2129, 2026.

[270] W. Zhang, L. Cheng, J. Wei, X. Xu, Z. Zhang, and B. Xin, "Bandwidth-efficient collaborative SLAM: Mutual information for data selection and finite-state entropy for lossless compression," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 5401–5412, 2026.