# Supplementary Material: Literature Selection and Comparative Evidence

This supplement accompanies *Wheeled Mobile Robot Autonomy Under Degradation: A Survey of Methods and Evaluation*. It provides the selection and assessment details summarized in Section III, selected numerical comparisons discussed in the technical synthesis, and the tables of representative implementations referenced in Sections IV–VIII. Counts describe the selected literature and do not estimate research-topic prevalence across the field.

## S1. Search Coverage and Selection

The initial search emphasized 2021–2026 publications across 17 journals and 102 journal–year combinations. It yielded 58,583 merged records, of which 43,086 had sufficient metadata for title/abstract screening. Language-model-assisted screening used preset topic allocations and stopped after 45 acceptances, leaving 43,041 metadata-complete records unassessed. Selection emphasized mechanisms relevant to compact wheeled platforms. The screening order and complete rejection history are unavailable. These missing records and the stopping rule limit the representativeness of the sample.

Additional coverage comprised 5 complementary publications, a 60-work thematic sample, 15 studies selected for the four integration questions developed in the survey, 20 IEEE publications concerning motion priors, recovery, shared-state diagnosis, and reproducibility, a further 48 targeted works, and 36 recent IEEE publications. The 48-work stage covers degeneracy and map validity, constrained motion and terrain risk, multimodal navigation, communication-aware collaboration, and recovery or online learning. The final stage selected six 2025–2026 IEEE journal or ICRA papers for each of the six themes after an exact-DOI check against the library. Table S1 summarizes these additions. The thematic sample contained 45 journal articles and 15 conference papers, with ten works under each of six themes: perception/localization, mapping/exploration, planning/control, multi-robot coordination, semantic navigation, and reliability/deployment. Searches combined technical, scenario, and mechanism terms with citation follow-up. Selection was completed by November 3, 2026, leaving coverage of the 2026 calendar year incomplete.

TABLE S1
Selection stages. Each row contains additional publications.

| Selection | Basis | Works |
|---|---|---|
| Initial sample | Capped journal selection, 2021–2026 | 45 |
| Complementary publications | Four technical studies and one context review | 5 |
| Thematic sample | Ten works under each of six themes | 60 |
| Integration questions | Four questions on combined navigation functions | 15 |
| Targeted IEEE coverage | Motion priors, recovery, shared-state diagnosis, and reproducibility | 20 |
| Further targeted coverage | Map validity, terrain risk, multimodal navigation, collaboration, and adaptation | 48 |
| Recent IEEE coverage | Six 2025–2026 IEEE journal or ICRA papers per theme | 36 |
| **Total** | | **229** |

### A. Journal and Conference Sources

The journal searches covered Automatica, Autonomous Robots, Control Engineering Practice, IEEE Robotics and Automation Letters, IEEE Transactions on Automatic Control, IEEE Transactions on Automation Science and Engineering, IEEE Transactions on Cybernetics, IEEE Transactions on Image Processing, IEEE Transactions on Intelligent Transportation Systems, IEEE Transactions on Intelligent Vehicles, IEEE Transactions on Robotics, Information Fusion, Journal of Field Robotics, Pattern Recognition, Robotics and Autonomous Systems, Science Robotics, and The International Journal of Robotics Research. The 2025–2026 searches covered 34 journal–year combinations. Completion of a search provider's enumeration does not establish omission-free retrieval of the publisher's catalog.

Formal CoRL volumes for 2024 and 2025 and RSS indexes for 2024–2026 were consulted. ICRA/IROS papers were assessed individually, without exhaustive enumeration of their proceedings. Complete enumeration of a formal CoRL 2026 volume was not established. Overlapping results from different search sources are not independent screening denominators.

## S2. Eligibility and Publication Scope

Eligible publications include journal articles and main-conference papers concerning wheeled mobile robots or autonomy methods relevant to the navigation problems examined in the survey. Preprints and established conference-to-journal extensions are counted as one work, identified by title, authors, DOI or proceedings identifier, venue, and year. Publication-year statistics use formal volume years, whereas bibliography entries retain publishers' citation years, which can instead refer to online publication.

The selected literature contains 195 journal articles and 34 conference papers: 228 technical studies and one context review on learned navigation [8]. All corpus works are from 2021–2026, and two older examples remain only in the internal library. The 5 additional references are representative estimators and complementary reviews published from 2021 to 2025. Earlier foundational sources, including the original dynamic-window, timed-elastic-band, and barrier-function papers, are retained in the internal library and are not cited.

TABLE S2
SELECTED RESULTS AND WITHIN-STUDY COMPARISONS. TABLE AND FIGURE NUMBERS IN THE FIRST COLUMN REFER TO THE CITED PAPERS. EACH ROW RETAINS ITS OWN METRIC AND PROTOCOL.

| Study / source | Protocol and measure | Reported result | Interpretation |
|---|---|---|---|
| LODESTAR [1] Tables III and V | SubT-MRS Long Corridor replay: absolute pose error (APE). Desktop computation averaged across benchmark recordings. | APE 1.386 m versus 3.113 m for FAST-LIO2; benchmark-average computation 28.69 versus 21.04 ms. | Selective anchoring and point selection improve this sequence at additional computation cost; no LiDAR-blackout or closed-loop test. |
| FIT-SLAM 2 [2] Tables 2 and 4 | Exploration with simulator poses and common control; completion time, plus Fisher-information timing analysis. | Cave: 880 versus 1118 s for FAEL; Corridor: 1809 versus 1706 s. Planning: 20.8 ms without and 63.0 ms with Fisher information. | The ordering changes with the scene. Planner benchmarks and the SLAM/localizability ablation answer different questions. |
| Safe Horizon MPC [3] Table 2 | 100 Gaussian eight-pedestrian simulations; common solver/cost and matched joint-risk specification 0.05; duration mean (SD). | 16.0 (1.9) s versus 18.4 (2.4) s for CC-MPC. Maximum estimated plan collision probabilities: 0.0092 versus 0.0019. | Faster traversal accompanies less conservative plan risk under a known motion distribution; these are not empirical mission collision rates. |
| LeLaN [4] Tables 2 and 3 | Visible-target navigation: 150 trials, 28 objects, success within 0.2 m; separate 15-trial obstacle ablation. | Goal success 0.89 versus 0.67 for OWL-v2 + ZoeDepth. With obstacles: arrival 0.60 with versus 0.13 without collision training. | Target arrival and obstacle handling are separate evaluations; visible-target success does not establish open-world search or a collision-risk bound. |
| TAPM-IVP [5] Table 2 | Scene 1 simulation; two robots, ten independent trials per method, common local planner/tracker. | Success 90% for each robot versus 40% and 30% in the two-robot ablation without partitioning and greedy subgoal selection. | The ablation supports the combined design, not either module alone. Rates are per robot; hardware demonstrations use two Ackermann vehicles. |
| GP-based recovery [6] Fig. 6 and Section V | Ten simulated runs per goal/world; same planner with and without recovery. Counts read from the plotted rates. | Dense 1 m doorways, goal 0: 8/10 versus 3/10 successes. Sparse 2 m doorways, goal 0: 10/10 for both. | Recovery benefit depends on the failure setting. The physical demonstrations do not provide a comparable success-rate estimate. |
| Home deployment [7] Table 3 | Ten-home field deployment; three assistive-service types, including requested but unperformed interventions. | 1130 successful, 177 failed, and 232 unperformed interventions out of 1539 requests. Reported success: 86.46% of 1307 attempts. | The success denominator excludes unperformed requests; availability and assistance conditions remain relevant to service-level interpretation. |

The selected literature includes 68 works involving road vehicles, other embodiments, handheld or mixed configurations, or no specified physical platform. These works inform mechanism comparisons, with platform differences considered when assessing transfer. The remaining 161 works also vary in drivetrain, sensing, and computational resources.

For the technical synthesis, publications are grouped by their principal contribution to localization/mapping, traversability/planning/control, semantic navigation, multi-robot coordination, or fault management. A publication may also inform other areas, although it appears only once in Fig. S1. These five functional groups differ from the six themes used to allocate the thematic sample.





Fig. S1. Selected publications by year and principal navigation function. Each publication appears once. The distribution reflects purposive sampling and topic quotas.

## S3. ASSESSMENT AND COMPARISON

Comparison attributes include the technical mechanism, platform, sensing, computation, experimental setting, baselines, measured outputs, and limitations. For 23 publications, assessment covered the full paper and numerical tables, whereas for 206 it was limited to selected method, evaluation, and conclusion passages or existing extracts. Of these 206 publications, 87 assessments were based on earlier extractions and 119 on targeted readings. These assessment levels do not provide uniform whole-paper verification across the selected literature.

The 48 and 36 works of the last two stages received targeted readings with page-located excerpts matched to both the transcription and PDF text. Their evidence cards retain mechanism and protocol conditions. Numbers that the survey reports from these works were rechecked in the PDF text, without rendered-table audits. Three citation records are explicitly derived, including an early-access year correction. One further work has a documented official-title/PDF-title variant. These provenance exceptions remain visible separately from reading depth.

Experimental settings distinguish hardware control, online estimation, recorded robot data, dataset replay, simulation, and numerical studies. Dataset and review publications are identified separately. Tables S3–S7 summarize mechanisms and

inputs alongside experimental settings, evaluated quantities, and computation location. Interpretation accounts for external pose, remote computation, low speed, and staged scenes where applicable. Complete-pipeline timing and placement require information beyond processor identity.

Quantitative comparisons retain the reported metrics, baselines, and evaluation conditions. Effect sizes are not pooled across heterogeneous datasets, platforms, or trial units. The evaluation table of the survey counts attributes over the 228 technical publications, excluding the context review. It groups overlapping attributes by measurement level, test conditions, and risk or diagnostic assessment. A study may report component and task measures during a degradation test. Purposive selection, uneven assessment depth, and heterogeneous protocols limit the generality of comparative conclusions.

## S4. Selected Results and Within-Study Comparisons

Table S2 retains the measures and experimental units of seven selected examples. Numerical results were checked against the cited tables or plots. Each comparison concerns the stated scene, baseline, and information available to the method. The rows therefore do not form a cross-study ranking. The examples include changes in performance ordering, added computation, combined-module ablations, and success denominators to clarify the scope of the conclusions drawn in the survey.

## S5. Representative Implementations by Navigation Function

Tables S3–S7 list representative implementations for the five functional sections of the survey. Each row reports the mechanism and its inputs, the experimental setting with the evaluated quantities, and the platform with the computation placement stated by the authors. The rows were chosen to cover the response families discussed in each section, and they are not a ranking or a complete list of the selected works.

## References


[1] E. M. Lee, K. C. Marsim, and H. Myung, "LODESTAR: Degeneracy-aware LiDAR-inertial odometry with adaptive Schmidt-Kalman filter and data exploitation," *IEEE Robotics and Automation Letters*, vol. 11, no. 1, pp. 922–929, 2026.

[2] S. Saravanan, A. Bains, C. P.C. Chanel, and D. Vivet, "FIT-SLAM 2: Efficient 3D exploration with Fisher information and traversability-based adaptive roadmap," *Robotics and Autonomous Systems*, vol. 194, p. 105188, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889025002854

[3] O. de Groot, L. Ferranti, D. M. Gavrila, and J. Alonso-Mora, "Scenario-based motion planning with bounded probability of collision," *The International Journal of Robotics Research*, vol. 44, no. 9, pp. 1507–1525, 2025. [Online]. Available: https://doi.org/10.1177/02783649251315203

[4] N. Hirose, C. Glossop, A. Sridhar, O. Mees, and S. Levine, "LeLaN: Learning a language-conditioned navigation policy from in-the-wild video," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 666–688. [Online]. Available: https://proceedings.mlr.press/v270/hirose25b.html

[5] H. Zhao, K. Xu, N. Xu, X. Li, and J. Jin, "Multi-robot collaborative navigation framework based on 3D Voronoi partitioning in uneven and unstructured environments," *Journal of Field Robotics*, vol. 43, no. 7, pp. 4531–4548, 2026. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.70260

[6] N. Mohammad, J. Higgins, and N. Bezzo, "A GP-based robust motion planning framework for agile autonomous robot navigation and recovery in unknown environments," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 2418–2424.

[7] M. Luperto *et al.*, "User feedback and remote supervision for assisted living with mobile robots: A field study in long-term autonomy," *Robotics and Autonomous Systems*, vol. 155, p. 104170, 2022. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889022000963

[8] K. Zhu and T. Zhang, "Deep reinforcement learning based mobile robot navigation: A review," *Tsinghua Science and Technology*, vol. 26, no. 5, pp. 674–691, 2021.

[9] G. Park and W. Chung, "Uncertainty-aware LiDAR-based localization for outdoor mobile robots," *Journal of Field Robotics*, vol. 41, no. 8, pp. 2790–2804, 2024. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.22392

[10] X. Yang, W. Li, Z. Wei, Z. Li, L. Huang, and B. Wang, "ToF-wheel odometry: Navigating degeneration of localization with limited sensing capabilities," *IEEE Robotics and Automation Letters*, vol. 11, no. 10, pp. 11 410–11 417, 2026.

[11] K. Hu, M. Li, Z. Jin, C. Tang, E. Hu, and G. Zhou, "DURAL: Degradation-resistant robust adaptive localization by LiDAR-inertial-UWB-wheel fusion for coal mine robots," *Journal of Field Robotics*, vol. 43, no. 5, pp. 3559–3577, 2026. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.70200

[12] Y. Ma *et al.*, "MM-LINS: A multi-map LiDAR-inertial system for over-degenerate environments," *IEEE Transactions on Intelligent Vehicles*, vol. 10, no. 1, pp. 472–482, 2025.

[13] J. Chen, H. Wang, M. Hu, and P. N. Suganthan, "Versatile LiDAR-inertial odometry with SE(2) constraints for ground vehicles," *IEEE Robotics and Automation Letters*, vol. 8, no. 6, pp. 3486–3493, 2023.

[14] W. Ali, Y. Cai, P. Jensfelt, and T.-M. Nguyen, "ProbPer-LiLo: Probabilistic persistency modeling for life-long mapping," *IEEE Robotics and Automation Letters*, vol. 11, no. 3, pp. 2530–2537, 2026.

[15] D. Skuddis and N. Haala, "DMSA - dense multi scan adjustment for LiDAR inertial odometry and global optimization," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 12 027–12 033.

[16] J. Lee *et al.*, "Switch-SLAM: Switching-based LiDAR-inertial-visual SLAM for degenerate environments," *IEEE Robotics and Automation Letters*, vol. 9, no. 8, pp. 7270–7277, 2024.

[17] Y. Jia, S. Wang, S. Shao, Y. Wang, F. Zhang, and T. Wang, "M2UD: A multi-model, multi-scenario, uneven-terrain dataset for ground robot with localization and mapping evaluation," *The International Journal of Robotics Research*, vol. 45, no. 10, pp. 1457–1477, 2026. [Online]. Available: https://doi.org/10.1177/02783649251401224

[18] G. Qian *et al.*, "DR-ICP: Robust LiDAR SLAM registration for degenerate tunnels," *Journal of Field Robotics*, oct 2026, early access; published online 12 October 2026. [Online]. Available: https://onlinelibrary.wiley.com/doi/10.1002/rob.70362

[19] X. Hu, X. Chen, M. Jia, J. Wu, P. Tan, and S. L. Waslander, "DCReg: Decoupled characterization for efficient degenerate LiDAR registration," *The International Journal of Robotics Research*, vol. 0, no. 0, p. 02783649261465040, 2026. [Online]. Available: https://doi.org/10.1177/02783649261465040

[20] S. Jung, D. Gwak, B. Boots, and J. Hays, "Uncertainty-aware accurate elevation modeling for off-road navigation via neural processes," in *Proceedings of The 9th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, J. Lim, S. Song, and H.-W. Park, Eds., vol. 305. PMLR, 27–30 Sep 2025, pp. 2802–2822. [Online]. Available: https://proceedings.mlr.press/v305/jung25b.html

[21] Q. Bi, X. Zhang, S. Zhang, R. Wang, L. Li, and J. Yuan, "LRAE: Large-region-aware safe and fast autonomous exploration of ground robots for uneven terrains," *IEEE Robotics and Automation Letters*, vol. 9, no. 12, pp. 11 186–11 193, 2024.

[22] S. Xie, R. Song, Y. Zhao, X. Huang, Y. Li, and W. Zhang, "Circular accessible depth: A robust traversability representation for UGV navigation," *IEEE Transactions on Robotics*, vol. 39, no. 6, pp. 4875–4891, 2023.

[23] T. Guan, D. Kothandaraman, R. Chandra, A. J. Sathyamoorthy, K. Weerakoon, and D. Manocha, "GA-Nav: Efficient terrain segmentation for robot navigation in unstructured outdoor environments," *IEEE Robotics and Automation Letters*, vol. 7, no. 3, pp. 8138–8145, 2022.

[24] Y. Zhao, L. Zhou, C. Zhang, and Y. Li, "Anisotropic terrain-aware autonomous exploration via image-domain perception and sparse routing," *IEEE Robotics and Automation Letters*, vol. 11, no. 10, pp. 11 062–11 069, 2026.

TABLE S3
LOCALIZATION AND MAPPING: REPRESENTATIVE MECHANISMS, SENSING, AND EVALUATION SETTINGS.

| Work | Mechanism and inputs | Evaluation setting<br>*Evaluated quantities* | Platform<br>*Computation* |
|---|---|---|---|
| **Uncertainty-aware localization** [9] | Uncertainty-weighted prior-map matching with LIO and gated GNSS.<br>*Inputs:* 3D LiDAR, IMU, GNSS | Acquired data<br>*Pose error and covariance estimates* | wheeled (drive unspecified)<br>*Unspecified* |
| **LODESTAR** [1]† | Selective historical anchoring and point selection under degeneracy.<br>*Inputs:* 3D LiDAR, IMU | Replay<br>*Absolute pose error and runtime* | mixed<br>*Desktop evaluation* |
| **ToF-Wheel** [10] | Directional process-covariance inflation from geometric corrections.<br>*Inputs:* time-of-flight camera and wheels; LiDAR replaces depth in replay | Acquired data, Replay<br>*Trajectory error across covariance variants* | differential drive<br>*Onboard* |
| **DURAL** [11] | Region- and degeneracy-dependent sensor fusion.<br>*Inputs:* LiDAR, IMU, UWB, wheel encoders | Acquired data, Sim.<br>*Localization error across fusion modes* | wheeled (drive unspecified)<br>*Unspecified* |
| **MM-LINS** [12]† | Map hibernation, reinitialization, and pose-graph registration.<br>*Inputs:* LiDAR/IMU from handheld and vehicle rigs | Acquired data, Replay<br>*Trajectory error and map registration* | road vehicle<br>*Unspecified* |
| **SE2-LIO** [13] | Near-planar pose with stochastic out-of-plane perturbations.<br>*Inputs:* 3D LiDAR, IMU | Online estimate, Acquired data<br>*Pose error; slope-model boundary* | wheeled (drive unspecified)<br>*Onboard* |
| **ProbPer-LiLo** [14]† | Semantic-cluster persistence estimation and map filtering.<br>*Inputs:* 3D LiDAR, semantic labels | Acquired data, Replay<br>*Registration and map persistence* | mixed<br>*Unspecified* |
| **DMSA** [15]† | Joint grid-distribution fitting over multiple scans.<br>*Inputs:* 3D LiDAR, IMU | Acquired data, Replay<br>*Pose error, runtime, sensor compatibility* | mixed<br>*Desktop evaluation* |
| **Switch-SLAM** [16]† | Degeneracy-triggered introduction of visual constraints.<br>*Inputs:* LiDAR, camera, IMU | Replay, Sim.<br>*Trajectory error under modality failure* | mixed<br>*Desktop evaluation* |
| **M2UD** [17] | Uneven-terrain localization and mapping benchmark.<br>*Inputs:* LiDAR, RGB-D, IMU, GNSS; mixed reference systems | Dataset, Acquired data<br>*Localization/mapping error and runtime* | wheeled (drive unspecified)<br>*Unspecified* |
| **DR-ICP** [18]† | Directional feature selection and weighting.<br>*Inputs:* LiDAR; capture IMU not integrated | Acquired data, Replay, Sim.<br>*Tunnel pose error; pure-LiDAR scope* | mixed<br>*Desktop evaluation* |
| **Decoupled registration** [19]† | Subspace decoupling and directional preconditioning.<br>*Inputs:* LiDAR registration constraints | Acquired data, Replay, Numerical<br>*Registration; missing-information boundary* | mixed<br>*Desktop evaluation* |
| **Semantic neural processes** [20]† | Semantic neural-process elevation and uncertainty.<br>*Inputs:* LiDAR, image semantics, poses | Acquired data<br>*Elevation error and uncertainty; calibration needed* | road vehicle<br>*Desktop evaluation* |

† Road-vehicle, non-wheeled, handheld, or mixed-platform evaluations.


[25] R. Wang *et al.*, "Vehicle-cloud cooperative trajectory planning via switched model predictive control for UGVs in unstructured transportation environment," *IEEE Transactions on Intelligent Transportation Systems*, vol. 27, no. 8, pp. 9517–9528, 2026.

[26] S. Keyumarsi, M. W. S. Atman, and A. Gusrialdi, "Circulation-embedded control barrier function for safe navigation: A solution to avoid undesired equilibria and dysfunctional circulation," *Robotics and Autonomous Systems*, vol. 194, p. 105132, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889025002295

[27] R. Das, S. Upadhyay, and P. Jagtap, "Real-time spatiotemporal tubes for dynamic unsafe sets," *IEEE Robotics and Automation Letters*, vol. 11, no. 2, pp. 2146–2153, 2026.

[28] A. Dixit, Z. Mei, M. Booker, M. Storey-Matsutani, A. Z. Ren, and A. Majumdar, "Perceive with confidence: Statistical safety assurances for navigation with learning-based perception," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 2517–2541. [Online]. Available: https://proceedings.mlr.press/v270/dixit25a.html

[29] O. de Groot, L. Ferranti, D. M. Gavrila, and J. Alonso-Mora, "Topology-driven parallel trajectory optimization in dynamic environments," *IEEE Transactions on Robotics*, vol. 41, pp. 110–126, 2025.

[30] S. Triest, M. Sivaprakasam, S. Aich, D. Fan, W. Wang, and S. Scherer, "Velociraptor: Leveraging visual foundation models for label-free, risk-aware off-road navigation," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 4483–4494. [Online]. Available: https://proceedings.mlr.press/v270/triest25a.html

[31] Z. Dong *et al.*, "Learning smooth state-dependent traversability from dense point clouds," in *Proceedings of The 9th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, J. Lim, S. Song, and H.-W. Park, Eds., vol. 305. PMLR, 27–30 Sep 2025, pp. 1654–1671. [Online]. Available: https://proceedings.mlr.press/v305/

TABLE S4
TRAVERSABILITY, PLANNING, AND CONTROL: REPRESENTATIVE MECHANISMS, SENSING, AND EVALUATION SETTINGS.

| **Work** | **Mechanism and inputs** | **Evaluation setting**<br>*Evaluated quantities* | **Platform**<br>*Computation* |
|---|---|---|---|
| **LRAE** [21] | Unknown-region safety classification and route optimization.<br>*Inputs:* 3D LiDAR | Hardware, Sim.<br>*Exploration time and travel cost* | skid steer<br>*Unspecified* |
| **CADNet** [22] | Heading-dependent accessible-range prediction for TEB planning.<br>*Inputs:* LiDAR history | Hardware, Replay, Sim.<br>*Traversability prediction and navigation* | wheeled (drive unspecified)<br>*Onboard* |
| **GA-Nav** [23] | Semantic terrain segmentation combined with elevation costs.<br>*Inputs:* RGB images, 3D LiDAR | Hardware, Replay<br>*Terrain segmentation and navigation success* | wheeled (drive unspecified)<br>*Onboard* |
| **Anisotropic exploration** [24] | Direction-dependent quasi-static terrain costs.<br>*Inputs:* LiDAR terrain map, FAST-LIO pose | Hardware, Sim.<br>*Exploration, travel cost, body roll* | differential drive<br>*Onboard* |
| **FIT-SLAM2** [2] | Keyframe-linked frontiers and information-aware adaptive roadmaps.<br>*Inputs:* RGB-D/LiDAR (simulation); stereo depth (hardware) | Hardware, Sim.<br>*Exploration time, pose error, and runtime* | skid steer<br>*Unspecified* |
| **Vehicle–cloud MPC** [25] | Switching between onboard linear and cloud nonlinear MPC.<br>*Inputs:* externally measured poses | Hardware, Sim., Theory<br>*Tracking and collision outcomes* | Ackermann<br>*Mixed placement* |
| **CECBF** [26] | CBF constraints with circulation and hold logic.<br>*Inputs:* 2D LiDAR, external robot pose | Hardware<br>*Obstacle avoidance and escape from equilibria* | differential drive<br>*Local offboard* |
| **Safe Horizon MPC** [3] | Scenario constraints on joint collision risk with deceleration fallback.<br>*Inputs:* robot/pedestrian poses and velocity estimates | Hardware, Sim.<br>*Task duration and planned collision risk* | skid steer<br>*Unspecified* |
| **Spatiotemporal-Tubes** [27] | Adaptive spherical tubes for prescribed-time reach-avoid.<br>*Inputs:* robot state, online unsafe-set geometry | Hardware, Sim., Numerical<br>*Reach-avoid and prescribed-time behavior* | omnidirectional<br>*Unspecified* |
| **Perceive With Confidence** [28]† | Environment-level calibration of obstacle inflation for constrained planning.<br>*Inputs:* RGB-D point clouds, VIO | Hardware, Sim.<br>*Collision-free outcomes and calibration* | legged<br>*Onboard* |
| **Homotopy MPC** [29] | Parallel optimization of homotopy alternatives.<br>*Inputs:* externally tracked robot/pedestrian states | Hardware, Sim.<br>*Dynamic avoidance; external pose* | wheeled (drive unspecified)<br>*Unspecified* |
| **Visual-geometric MPPI** [30] | Expert-trained cost, speed, and novelty maps for MPPI.<br>*Inputs:* RGB features, LiDAR geometry | Hardware, Acquired data<br>*Interventions, speed, and terrain response* | wheeled (drive unspecified)<br>*Unspecified* |
| **SPARTA** [31] | Angle-conditioned risk queried during planning.<br>*Inputs:* prepared point cloud, LiDAR/IMU pose | Hardware, Sim.<br>*Simulated tire risk; virtual risky hardware branch* | skid steer<br>*Onboard* |

† Road-vehicle, non-wheeled, handheld, or mixed-platform evaluations.

dong25a.html
[32] D. Song, J. Liang, A. Payandeh, A. H. Raj, X. Xiao, and D. Manocha, "VLM-Social-Nav: Socially aware robot navigation through scoring using vision-language models," *IEEE Robotics and Automation Letters*, vol. 10, no. 1, pp. 508–515, 2025.
[33] B. Yu, Q. Yuan, K. Li, H. Kasaei, and M. Cao, "Co-NavGPT: Multirobot cooperative visual semantic navigation using vision language models," *IEEE Robotics and Automation Letters*, vol. 11, no. 2, pp. 2122–2129, 2026.
[34] Y. Tang *et al.*, "OpenIN: Open-vocabulary instance-oriented navigation in dynamic domestic environments," *IEEE Robotics and Automation Letters*, vol. 10, no. 9, pp. 9256–9263, 2025.
[35] N. Yokoyama, S. Ha, D. Batra, J. Wang, and B. Bucher, "VLFM: Vision-language frontier maps for zero-shot semantic navigation," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 42–48.
[36] A. Werby, C. Huang, M. Büchner, A. Valada, and W. Burgard, "Hierarchical open-vocabulary 3D scene graphs for language-grounded robot navigation," in *Proceedings of Robotics: Science and Systems*, Delft, Netherlands, July 2024.
[37] J. Zhang *et al.*, "Uni-NaVid: A video-based vision-language-action model for unifying embodied navigation tasks," in *Proceedings of Robotics: Science and Systems*, LosAngeles, CA, USA, June 2025.
[38] D. Song, J. Liang, X. Xiao, and D. Manocha, "VL-TGS: Trajectory generation and selection using vision language models in mapless outdoor environments," *IEEE Robotics and Automation Letters*, vol. 10, no. 6, pp. 5791–5798, 2025.
[39] S. Luo *et al.*, "GSON: A group-based social navigation framework with large multimodal model," *IEEE Robotics and Automation Letters*, vol. 10, no. 10, pp. 9646–9653, 2025.
[40] C. Huang, O. Mees, A. Zeng, and W. Burgard, "Multimodal spatial language maps for robot navigation and manipulation," *The International Journal of Robotics Research*, vol. 0, no. 0, p. 02783649251351658, 2025. [Online]. Available: https://doi.org/10.1177/02783649251351658
[41] M. Elnoor *et al.*, "VLM-GroNav: Robot navigation using physically grounded vision-language models in outdoor environments," in *2025 IEEE International Conference on Robotics and Automation (ICRA)*, 2025, pp. 2391–2398.
[42] M. J. Munje *et al.*, "SocialNav-SUB: Benchmarking VLMs for scene understanding in social robot navigation," in *Proceedings of The 9th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, J. Lim, S. Song, and H.-W. Park, Eds., vol. 305. PMLR, 27–30 Sep 2025, pp. 1120–1143. [Online]. Available: https://proceedings.mlr.press/v305/munje25a.html

TABLE S5
SEMANTIC AND LANGUAGE-GUIDED NAVIGATION: REPRESENTATIVE MECHANISMS, SENSING, AND EVALUATION SETTINGS.

| **Work** | **Mechanism and inputs** | **Evaluation setting**<br>*Evaluated quantities* | **Platform**<br>*Computation* |
|---|---|---|---|
| **VLM-Social-Nav** [32] | Cue-triggered VLM judgments used as social DWA costs.<br>*Inputs:* RGB images, LiDAR | Hardware<br>*Task success, collisions, and social behavior* | differential drive<br>*Mixed placement* |
| **Co-NavGPT** [33]† | VLM frontier allocation with geometric goal execution.<br>*Inputs:* RGB-D, shared map, robot states | Hardware, Sim.<br>*HM3D search; separate hardware demos* | legged<br>*Onboard pose; offboard perception/planning* |
| **OpenIN** [34] | Carrier–object memory with visibility-dependent updates.<br>*Inputs:* RGB-D, language/image queries, SLAM pose | Hardware, Sim.<br>*Success across sequential object queries* | wheeled (drive unspecified)<br>*Unspecified* |
| **VLFM** [35]† | Image–language similarity projected into a frontier value map.<br>*Inputs:* RGB-D, odometry | Hardware, Sim.<br>*Goal success and path efficiency* | legged<br>*Unspecified* |
| **HOV-SG** [36]† | Hierarchical retrieval over floor, room, and object graphs.<br>*Inputs:* RGB-D, LiDAR-derived poses | Hardware, Sim., Replay<br>*Object retrieval and navigation success* | legged<br>*Unspecified* |
| **Uni-NaVid** [37]† | Multiscale video memory and discrete action prediction.<br>*Inputs:* monocular RGB video, instruction | Hardware, Sim.<br>*Goal success and path efficiency* | legged<br>*Local offboard* |
| **LeLaN** [4] | Receding-horizon language-conditioned velocity prediction.<br>*Inputs:* RGB image, text instruction | Hardware, Replay<br>*Target arrival and action-generation time* | differential drive<br>*Onboard* |
| **VL-TGS** [38] | VLM selection among generated trajectories with local DWA control.<br>*Inputs:* LiDAR, RGB, velocity, GPS | Hardware, Acquired data<br>*Outdoor traversal and model-response time* | wheeled (drive unspecified)<br>*Mixed placement* |
| **GSON** [39] | Group-aware routing with predictive barrier-constrained control.<br>*Inputs:* 2D LiDAR, RGB images | Hardware, Replay<br>*Social disturbance, travel time, and jerk* | differential drive<br>*Unspecified* |
| **AVLMaps** [40] | Multimodal spatial retrieval and goal APIs.<br>*Inputs:* offline RGB-D/pose/audio map, instructions | Hardware, Sim.<br>*Multimodal goals; prepared-map validity* | wheeled (drive unspecified)<br>*Unspecified* |
| **VLM-GroNav** [41] | Interaction-grounded terrain costs and DWA.<br>*Inputs:* RGB, LiDAR, proprioception, GPS, aerial images | Hardware<br>*Outdoor task outcomes; GPS/cloud dependencies* | skid steer<br>*Mixed placement* |
| **SocialNav-SUB** [42] | Social scene-understanding VQA benchmark.<br>*Inputs:* recorded images, pedestrian annotations | Dataset<br>*Human/rule agreement; no closed-loop control* | wheeled (drive unspecified)<br>*Mixed placement* |

† Road-vehicle, non-wheeled, handheld, or mixed-platform evaluations.


[43] A. Asgharivaskasi, F. Girke, and N. Atanasov, "Riemannian optimization for active mapping with robot teams," *IEEE Transactions on Robotics*, vol. 41, pp. 1077–1097, 2025.

[44] R. Bai, S. Yuan, H. Guo, P. Yin, W.-Y. Yau, and L. Xie, "Multi-robot active graph exploration with reduced Pose-SLAM uncertainty via submodular optimization," in *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2024, pp. 10 229–10 236.

[45] V. Vijay, K. A. Pant, M. Cho, Y. Guo, J. M. Goppert, and I. Hwang, "Range-based multi-robot integrity monitoring for cyberattacks and faults: An anchor-free approach," *IEEE Robotics and Automation Letters*, vol. 10, no. 3, pp. 2630–2637, 2025.

[46] H. Kim *et al.*, "Commerge: Communication-efficient, robust, and fast LiDAR map merging framework for multi-robot coordination in resource-constrained scenarios," *The International Journal of Robotics Research*, vol. 0, no. 0, p. 02783649261464202, 2026. [Online]. Available: https://doi.org/10.1177/02783649261464202

[47] D. McGann and M. Kaess, "iMESA: Incremental distributed optimization for collaborative simultaneous localization and mapping," in *Proceedings of Robotics: Science and Systems*, Delft, Netherlands, July 2024.

[48] M. Escourrou, J. Al Hage, and P. Bonnifait, "Fault tolerant decentralized collaboration for simultaneous localization and prior map update with stable 2D features," *Robotics and Autonomous Systems*, vol. 200, p. 105402, 2026. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0921889026000758

[49] P. Li, J. Liu, Y. Wu, and L. Zhou, "Failure-aware multi-robot coordination for resilient and adaptive target tracking," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 4023–4038, 2026.

[50] J. Bayer and J. Faigl, "Decentralized multi-robot exploration under low-bandwidth communications," *Autonomous Robots*, vol. 50, no. 1, p. 7, Dec 2025. [Online]. Available: https://doi.org/10.1007/s10514-025-10234-3

[51] Y.-H. Lee, C. Zhu, T. Wiedemann, E. Staudinger, S. Zhang, and C. Günther, "CoVOR-SLAM: Cooperative SLAM using visual odometry and ranges for multi-robot systems," *IEEE Transactions on Intelligent Transportation Systems*, vol. 26, no. 7, pp. 9358–9369, 2025.

[52] P.-Y. Lajoie and G. Beltrame, "Swarm-SLAM: Sparse decentralized collaborative simultaneous localization and mapping framework for multi-robot systems," *IEEE Robotics and Automation Letters*, vol. 9, no. 1, pp. 475–482, 2024.

[53] P. Zhong, F. Rossi, and D. A. Shell, "Planned synchronization for multi-robot systems with active observations," *Autonomous Robots*, vol. 50, no. 1, 2026, article 5; first published online 24 December 2025; assigned to the March 2026 issue. [Online]. Available: https://doi.org/10.1007/s10514-025-10225-4

[54] W. Zhang, L. Cheng, J. Wei, X. Xu, Z. Zhang, and B. Xin, "Bandwidth-efficient collaborative SLAM: Mutual information for data selection and finite-state entropy for lossless compression," *IEEE Transactions on Automation Science and Engineering*, vol. 23, pp. 5401–5412, 2026.

[55] M. H. Shahna, P. Mustalahti, and J. Mattila, "NMPC-augmented visual navigation and safe learning control for large-scale mobile robots," *IEEE Robotics and Automation Letters*, vol. 11, no. 4, pp. 5182–5189, 2026.

TABLE S6
MULTI-ROBOT COORDINATION: REPRESENTATIVE MECHANISMS, SENSING, AND EVALUATION SETTINGS.

| Work | Mechanism and inputs | Evaluation setting<br>*Evaluated quantities* | Platform<br>*Computation* |
|---|---|---|---|
| **ROAM** [43] | One-hop consensus for semantic mapping and viewpoint planning.<br>*Inputs:* RGB-D, LiDAR | Hardware, Sim.<br>*Distributed mapping and exploration* | skid steer<br>*Onboard* |
| **Active graph exploration** [44]† | Submodular loop-edge selection after coverage planning.<br>*Inputs:* prior topo-metric graph | Sim.<br>*Simulated coverage and graph objective* | none<br>*Desktop evaluation* |
| **Range integrity** [45]† | Range-consistency localization-error reconstruction.<br>*Inputs:* emulated ranges, reported poses | Online monitor (mixed reality), Sim.<br>*Error reconstruction with emulated ranges* | aerial<br>*Central ground station; emulated ranges* |
| **Commerge** [46] | Descriptor matching and scan selection before submap registration.<br>*Inputs:* 3D LiDAR, LIO poses | Acquired data, Replay<br>*Map-merging error and transmitted data* | wheeled (drive unspecified)<br>*Desktop evaluation* |
| **iMESA** [47]† | Incremental local factor graphs with shared-variable consensus.<br>*Inputs:* odometry and inter-robot factors | Replay, Numerical<br>*Estimation error with limited communication* | mixed<br>*Desktop evaluation* |
| **Collaborative map repair** [48]† | Residual-based fault isolation and correlation-aware map repair.<br>*Inputs:* LiDAR, wheel odometry; GNSS initialization | Acquired data, Sim.<br>*Pose/map error and fault isolation* | road vehicle<br>*Unspecified* |
| **TAPM-IVP** [5] | Terrain-aware 3D Voronoi allocation and subgoal selection.<br>*Inputs:* LiDAR, A-LOAM poses | Hardware, Sim.<br>*Success, travel cost, and path duplication* | Ackermann<br>*Onboard* |
| **Failure-aware tracking** [49]† | Failure-dependent tracking modes and target-state fusion.<br>*Inputs:* target range/bearing and inter-robot messages | Hardware, Sim.<br>*Target-state error during failures* | aerial<br>*Unspecified* |
| **Cross-rank** [50]† | Intersection allocation from shared position histories.<br>*Inputs:* LiDAR localization and low-bandwidth radio | Hardware, Sim.<br>*Exploration under intermittent reception* | legged<br>*Mixed placement* |
| **CoVOR-SLAM** [51] | Similarity-pose-graph fusion for monocular scale correction.<br>*Inputs:* camera, inter-rover UWB ranges | Acquired data, Replay, Sim.<br>*Pose error and monocular scale correction* | wheeled (drive unspecified)<br>*Desktop evaluation* |
| **Swarm-SLAM** [52] | Sparse loop prioritization and decentralized inference.<br>*Inputs:* local odometry, loop observations | Online estimate, Replay<br>*Online collaborative estimation; team exchange* | skid steer<br>*Onboard* |
| **Planned synchronization** [53] | Joint motion and observation scheduling.<br>*Inputs:* relative marker observations, IMU | Hardware, Numerical<br>*Formation and check-in cost; modeled non-idealities* | differential drive<br>*Onboard* |
| **Bandwidth-efficient SLAM** [54] | Lossy keyframe selection and lossless coding.<br>*Inputs:* visual/inertial keyframes | Online estimate, Replay<br>*Bandwidth/accuracy tradeoff; central back end* | wheeled (drive unspecified)<br>*Mixed placement* |

† Road-vehicle, non-wheeled, handheld, or mixed-platform evaluations.


[56] S. Zhang, V. Puig, and S. Ifqir, "Robust LPV fault diagnosis using the set-based approach for autonomous ground vehicles," *IEEE Transactions on Intelligent Transportation Systems*, vol. 25, no. 8, pp. 9078–9090, 2024.

[57] N. Akai, "Reliable Monte Carlo localization for mobile robots," *Journal of Field Robotics*, vol. 40, no. 3, pp. 595–613, 2023. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.22149

[58] S. Verma and D. S. Bernstein, "Real-time kinematics-based sensor-fault detection for autonomous vehicles using single and double transport with adaptive numerical differentiation," *Control Engineering Practice*, vol. 159, p. 106304, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S096706612500067X

[59] A. De Luca, L. Muratore, and N. G. Tsagarakis, "Autonomous navigation with online replanning and recovery behaviors for wheeled-legged robots using behavior trees," *IEEE Robotics and Automation Letters*, vol. 8, no. 10, pp. 6803–6810, 2023.

[60] X. Zheng, W. Wen, and L.-T. Hsu, "Safety-quantifiable line feature-based monocular visual localization with 3D prior map," *IEEE Transactions on Intelligent Transportation Systems*, vol. 26, no. 7, pp. 9226–9240, 2025.

[61] R. Ma, Y. Yu, S. Zhang, and P. Shi, "Event-triggered fault-tolerant tracking control for autonomous ground vehicle via descriptor reduced-order observer," *IEEE Transactions on Intelligent Transportation Systems*, vol. 26, no. 7, pp. 10 308–10 319, 2025.

[62] C. Agia *et al.*, "Unpacking failure modes of generative policies: Runtime monitoring of consistency and progress," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer, and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 689–723. [Online]. Available: https://proceedings.mlr.press/v270/agia25a.html

[63] G. Kulathunga *et al.*, "Resilient timed elastic band planner for collision-free navigation in unknown environments," *Journal of Field Robotics*, vol. 42, no. 7, pp. 3902–3917, 2025. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/rob.22602

[64] C. Chen, Y. Liu, Y. Zhuang, S. Mao, K. Xue, and S. Zhou, "SCALE: Self-correcting visual navigation for mobile robots via anti-novelty estimation," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024, pp. 16 360–16 366.

[65] K. Stachowicz, L. Ignatova, and S. Levine, "Lifelong autonomous improvement of navigation foundation models in the wild," in *Proceedings of The 8th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, P. Agrawal, O. Kroemer,

TABLE S7
RELIABILITY AND RECOVERY: REPRESENTATIVE MECHANISMS, SENSING, AND EVALUATION SETTINGS.

| Work | Mechanism and inputs | Evaluation setting<br>*Evaluated quantities* | Platform<br>*Computation* |
|---|---|---|---|
| **Visual NMPC recovery** [55] | Tracking-loss stop and relocalization; restart after failure.<br>*Inputs:* stereo vision, actuator feedback | Hardware<br>*Tracking; stop/relocalization handling* | skid steer<br>*Unspecified* |
| **Set-based LPV diagnosis** [56]† | Zonotopic detection and fault-class separation.<br>*Inputs:* yaw rate, odometry, sideslip, steering angle | Acquired data<br>*Detectability and isolability under injected faults* | road vehicle<br>*Desktop evaluation* |
| **Reliable MCL** [57] | Joint pose/reliability estimation with global relocalization.<br>*Inputs:* 2D LiDAR, odometry or inertial navigation | Acquired data, Replay, Sim.<br>*Reliability estimates and relocalization* | wheeled (drive unspecified)<br>*Unspecified* |
| **Long-term home deployment** [7] | Long-term service, docking, and remote human supervision.<br>*Inputs:* LiDAR, RGB-D, docking and home sensors | Hardware<br>*Service outcomes and interruptions* | wheeled (drive unspecified)<br>*Mixed placement* |
| **KSFD** [58] | Kinematic residuals for sensor-fault diagnosis.<br>*Inputs:* inertial channels and an inertial-aided position substitute | Acquired data, Numerical<br>*Fault-isolation residual patterns* | Ackermann<br>*Desktop evaluation* |
| **Behavior-tree recovery** [59]† | Behavior-tree supervision and failure-specific recovery.<br>*Inputs:* terrain maps, contacts, planner status | Hardware, Sim.<br>*Recovery on retained scenarios; human-rescue boundary* | mixed<br>*Onboard* |
| **Line-map integrity** [60] | Prior-line-map localization with an error protection level.<br>*Inputs:* monocular images, IMU, prior 3D lines | Acquired data, Replay, Sim.<br>*Pose error and protection-level coverage* | wheeled (drive unspecified)<br>*Desktop evaluation* |
| **Event-triggered tracking** [61] | Observer-based fault estimation and event-triggered tracking.<br>*Inputs:* vehicle-posture outputs in the model | Hardware-in-the-loop, Numerical<br>*Tracking error and update frequency* | Ackermann<br>*Mixed placement* |
| **Sentinel** [62] | Action-consistency and VLM progress monitoring.<br>*Inputs:* external RGB-D and mobile-base motion capture | Online estimate, Sim.<br>*Failure detection and nominal alarms* | omnidirectional<br>*Mixed placement* |
| **RTEB** [63] | Hybrid A* reinitialization and local smoothing.<br>*Inputs:* RTK pose, voxel obstacle map | Hardware, Sim.<br>*Planner recovery; TEB/NMPC comparisons* | wheeled (drive unspecified)<br>*Onboard* |
| **SCALE** [64] | Affordance prediction and anti-novelty recovery.<br>*Inputs:* RGB at deployment; offline robot data | Hardware<br>*Visual recovery and intervention need* | skid steer<br>*Onboard* |
| **LiReN** [65] | Online RL with resets, goals, and charging.<br>*Inputs:* RGB policy; LiDAR/map, bumper for supervision | Hardware<br>*Adaptation with operational resets and infrastructure* | differential drive<br>*Mixed placement* |

† Road-vehicle, non-wheeled, handheld, or mixed-platform evaluations.

and W. Burgard, Eds., vol. 270. PMLR, 06–09 Nov 2025, pp. 1035–1047. [Online]. Available: https://proceedings.mlr.press/v270/stachowicz25a.html