

Delivery Buddy API

Requirements Specification

Proposed By : Tambe Enowtabi Princely

This document lists each REST API endpoint required to support the Delivery Buddy courier app UI, including purpose, authentication requirement, HTTP method, URL, request parameters, and example response shapes.

How authentication works

Call POST /api/v1/auth/signup then POST /api/v1/auth/login to receive an accessToken. For every endpoint marked AUTH REQUIRED below, send that token as a header on the request:

```
Authorization: Bearer <accessToken>
```

Access tokens expire after fifteen minutes by default. Use POST /api/v1/auth/refresh with the refreshToken to obtain a new one without logging in again.

1. Authentication

POST

/api/v1/auth/signup

PUBLIC

Purpose

Register a new courier account.

Request parameters

None

Request body example

```
{
  "email": "tyler@example.com",
  "phone": "+15551234567",
  "password": "P@ssw0rd123"
}
```

Response example

```
{
  "id": "b2f1...uuid",
  "email": "tyler@example.com",
  "createdAt": "2026-07-09T10:00:00Z"
}
```

POST

/api/v1/auth/login

PUBLIC

Purpose

Authenticate a courier and issue access and refresh tokens.

Request parameters

None

Request body example

```
{
  "email": "tyler@example.com",
  "password": "P@ssw0rd123"
}
```

Response example

```
{
  "accessToken": "eyJhbGciOi...",
  "refreshToken": "eyJhbGciOi...",
  "expiresIn": 3600
}
```

POST

/api/v1/auth/logout

PUBLIC

Purpose

Invalidate the current session or refresh token.

Request parameters

None

Response example

```
{
  "message": "Logged out successfully"
}
```

POST

/api/v1/auth/refresh

PUBLIC

Purpose

Exchange a valid refresh token for a new access token.

Request parameters

None

Request body example

```
{
  "refreshToken": "eyJhbGciOi..."
}
```

Response example

```
{
  "accessToken": "eyJhbGciOi...",
  "expiresIn": 3600
}
```

2. Courier profile and onboarding

POST

/api/v1/couriers/profile

AUTH REQUIRED

Purpose

Submit onboarding step two form: work ID, name, team, transportation type, vehicle number.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Request body example

```
{
  "workId": "WK-4587",
  "name": "Tyler Teeler",
  "teamId": "team-uuid",
  "transportationType": "bicycle",
  "vehicleNumber": "RE 345 6"
}
```

Response example

```
{
  "id": "courier-uuid",
  "workId": "WK-4587",
  "name": "Tyler Teeler",
  "transportationType": "bicycle",
  "status": "active"
}
```

GET

/api/v1/couriers/me

AUTH REQUIRED

Purpose

Retrieve the authenticated courier profile, used on the Profile screen.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Response example

```
{
  "id": "courier-uuid",
  "workId": "#4173697",
  "name": "Tyler Teeler",
  "avatarUrl": "https://.../avatar.png",
  "level": 3,
  "currentRate": 25.0,
}
```

```
"transportationType": "bicycle",
"vehicleNumber": "RE 345 6",
"status": "active"
}
```

PATCH`/api/v1/couriers/me`**AUTH REQUIRED****Purpose**

Update editable profile fields.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Request body example

```
{
  "name": "Tyler Teeler",
  "avatarUrl": "https://.../new.png"
}
```

Response example

```
{
  "id": "courier-uuid",
  "name": "Tyler Teeler"
}
```

GET`/api/v1/teams`**AUTH REQUIRED****Purpose**

List teams for the onboarding team selection dropdown.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Response example

```
[
  { "id": "team-uuid-1", "name": "North Zone" },
  { "id": "team-uuid-2", "name": "South Zone" }
]
```

3. Shifts

POST

/api/v1/shifts/start

AUTH REQUIRED

Purpose

Start a new shift for the authenticated courier.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Response example

```
{
  "id": "shift-uuid",
  "status": "active",
  "startTime": "2026-07-09T08:34:00Z"
}
```

POST

/api/v1/shifts/stop

AUTH REQUIRED

Purpose

End the courier current active shift.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Response example

```
{
  "id": "shift-uuid",
  "status": "completed",
  "endTime": "2026-07-09T16:20:00Z",
  "earned": 487.67,
  "tips": 276.78,
  "deliveriesCompleted": 8
}
```

GET

/api/v1/shifts/current

AUTH REQUIRED

Purpose

Get the active shift live stats: today earned, tips, rate, deliveries completed.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Response example

```
{
  "id": "shift-uuid",
  "status": "active",
  "startTime": "2026-07-09T08:34:00Z",
  "earned": 487.67,
  "tips": 276.78,
  "deliveriesCompleted": 8,
  "currentRate": 25.0
}
```

GET

/api/v1/shifts

AUTH REQUIRED

Purpose

List past shifts. Supports last=1 to fetch the most recent completed shift for the "My last shift" card.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

- last (optional, integer): limit to N most recent shifts
- page, limit (optional): pagination

Response example

```
[
  {
    "id": "shift-uuid",
    "startTime": "2026-02-24T10:34:00Z",
    "endTime": "2026-02-24T18:00:00Z",
    "earned": 456.89,
    "tips": 123.65,
    "durationLabel": "5h 5min"
  }
]
```

GET

/api/v1/shifts/:id

AUTH REQUIRED

Purpose

Get details of a specific shift by ID.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

- id (path, required): shift UUID

Response example

```
{
  "id": "shift-uuid",
  "status": "completed",
  "earned": 456.89,
  "tips": 123.65,
  "deliveriesCompleted": 6
}
```

4. Wallet

GET

/api/v1/wallet

AUTH REQUIRED

Purpose

Retrieve wallet balances and rate trend for the Wallet screen header cards.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Response example

```
{
  "balance": 487.67,
  "tipsBalance": 276.78,
  "rateTrendPct": 15.0,
  "level": 3
}
```

GET

/api/v1/wallet/transactions

AUTH REQUIRED

Purpose

List wallet transactions: earnings, tips, withdrawals.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

- page (optional, integer)
- limit (optional, integer)
- type (optional): filter by earning, tip, or withdrawal

Response example

```
[
  {
    "id": "txn-uuid",
    "orderId": "#403-540",
    "type": "earning",
    "amount": 45.05,
    "createdAt": "2026-02-23T12:04:00Z"
  },
  {
    "id": "txn-uuid-2",
    "orderId": null,
    "type": "withdrawal",
    "amount": -670.0,
    "createdAt": "2026-02-22T09:00:00Z"
  }
]
```

POST

/api/v1/wallet/withdraw

AUTH REQUIRED

Purpose

Withdraw available funds from the wallet balance.

Authorization header

Authorization: Bearer <accessToken>

Request parameters

None

Request body example

```
{
  "amount": 670.0
}
```

Response example

```
{
  "transactionId": "txn-uuid",
  "newBalance": 0.0,
  "status": "completed"
}
```

5. Orders

GET

/api/v1/orders

AUTH REQUIRED

Purpose

List orders in the courier queue, for example the "Next in the list" section. Filterable by status.

Authorization header


```
Authorization: Bearer <accessToken>
```

Request parameters

- status (optional): pending, assigned, in_transit, arrived, delivered, or cancelled
- page, limit (optional)

Response example

```
[
  {
    "id": "order-uuid",
    "orderNumber": "#403-540",
    "status": "assigned",
    "destinationAddress": "1742 Madison Ave, app. 34",
    "createdAt": "2026-07-09T10:48:00Z"
  }
]
```

GET /api/v1/orders/current

AUTH REQUIRED

Purpose

Get the order the courier is currently delivering, shown on the Dashboard "Currently delivering" card.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Response example

```
{
  "id": "order-uuid",
  "orderNumber": "#403-540",
  "status": "in_transit",
  "etaMinutes": 7
}
```

GET /api/v1/orders/:id

AUTH REQUIRED

Purpose

Get full order detail: pickup, destination, line items, total, payment, earning, and tip, for the Order Detail screen.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

- id (path, required): order UUID

Response example

```
{
  "id": "order-uuid",
  "orderNumber": "#403-540",
  "status": "delivered",
  "pickup": { "name": "Lussy Plaza", "address": "2003 Township Lane" },
  "destination": {
    "customerName": "Mrs. Jorean",
    "phone": "805-304-3456",
    "address": "1742 Madison Ave, apt. 34"
  },
  "items": [
    {
      "name": "Ham and Cheese Pizza 11 inch",
      "options": "Hawaiian, Double Cheese",
      "price": 12.42
    },
    { "name": "Pepperoni Pepper", "price": 10.0 },
    { "name": "Tuesday Combo", "price": 30.0 }
  ],
  "total": 42.0,
  "paymentMethod": "credit_card",
  "earning": 42.0,
  "tip": 10.0
}
```

PATCH`/api/v1/orders/:id/status`**AUTH REQUIRED****Purpose**

Update order status as the courier progresses, for example arrived, at the door, or delivered.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

- id (path, required): order UUID

Request body example

```
{
  "status": "arrived"
}
```

Response example

```
{
  "id": "order-uuid",
  "status": "arrived",
  "updatedAt": "2026-07-09T14:44:00Z"
}
```

GET`/api/v1/orders/:id/route`**AUTH REQUIRED**

Purpose

Get live routing data for the tracking map screen: ETA, distance remaining, and route path. Redis cached with a twenty second TTL to avoid redundant calls to the third party routing provider.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

- id (path, required): order UUID

Response example

```
{
  "etaMinutes": 7,
  "distanceKm": 1.6,
  "path": [
    { "lat": 37.7749, "lng": -122.4194 },
    { "lat": 37.7755, "lng": -122.4180 }
  ],
  "fetchedException": "2026-07-09T14:44:00Z"
}
```

6. Messages (order chat)

GET

/api/v1/orders/:orderId/messages

AUTH REQUIRED

Purpose

Retrieve the chat thread tied to a specific order.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

- orderId (path, required): order UUID

Response example

```
[
  {
    "id": "msg-uuid",
    "senderType": "customer",
    "content": "Hi, cannot reach a customer. Here for 15 mins already.",
    "createdAt": "2026-07-09T14:15:00Z"
  }
]
```

POST

/api/v1/orders/:orderId/messages

AUTH REQUIRED

Purpose

Send a new chat message on the order thread.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

- orderId (path, required): order UUID

Request body example

```
{
  "content": "OK but what should I do with an order?"
}
```

Response example

```
{
  "id": "msg-uuid",
  "senderType": "courier",
  "content": "OK but what should I do with an order?",
  "createdAt": "2026-07-09T14:16:00Z"
}
```

7. Notifications

GET

/api/v1/notifications

AUTH REQUIRED

Purpose

List notifications for the authenticated courier.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

- isRead (optional, boolean): filter read or unread

Response example

```
[
  {
    "id": "notif-uuid",
    "type": "order",
    "title": "New delivery assigned",
    "isRead": false,
    "createdAt": "2026-07-09T09:00:00Z"
  }
]
```

PATCH

/api/v1/notifications/:id/read

AUTH REQUIRED

Purpose

Mark a notification as read.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

- id (path, required): notification UUID

Response example

```
{
  "id": "notif-uuid",
  "isRead": true
}
```

8. Settings

GET / PATCH /api/v1/settings/fuel-management

AUTH REQUIRED

Purpose

Retrieve or update fuel management preferences.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Request body example

```
{
  "fuelCardEnabled": true
}
```

Response example

```
{
  "fuelCardEnabled": true
}
```

GET / PATCH /api/v1/settings/billing-method

AUTH REQUIRED

Purpose

Retrieve or update billing and payout method.

Authorization header

```
Authorization: Bearer <accessToken>
```

Request parameters

None

Request body example

```
{
  "payoutMethod": "bank_transfer"
}
```

Response example

```
{
  "payoutMethod": "bank_transfer"
}
```

GET / PATCH /api/v1/settings/location

AUTH REQUIRED

Purpose

Retrieve or update location sharing preferences.

Authorization header

Authorization: Bearer <accessToken>

Request parameters

None

Request body example

```
{
  "locationSharingEnabled": true
}
```

Response example

```
{
  "locationSharingEnabled": true
}
```

GET / PATCH /api/v1/settings/notifications

AUTH REQUIRED

Purpose

Retrieve or update notification preferences.

Authorization header

Authorization: Bearer <accessToken>

Request parameters

None

Request body example

```
{
  "pushEnabled": true,
  "emailEnabled": false
}
```

Response example

```
{
  "pushEnabled": true,
  "emailEnabled": false
}
```

GET

/api/v1/support

AUTH REQUIRED

Purpose

Retrieve support contact info and help resources.

Authorization header

Authorization: Bearer <accessToken>

Request parameters

None

Response example

```
{
  "supportEmail": "support@deliverybuddy.com",
  "supportPhone": "+1-800-555-0100"
}
```

9. Utility

GET

/

PUBLIC

Purpose

Root health and status check.

Request parameters

None

Response example

```
{
  "status": "ok",
  "message": "Delivery Buddy API is running",
  "docs": "/docs",
  "api": "/api/v1"
}
```

GET

/api/v1

PUBLIC

Purpose

Versioned API root status check.

Request parameters

None

Response example

```
{
  "status": "ok",
  "message": "Delivery Buddy API is running"
}
```

GET

/api/v1/health

PUBLIC

Purpose

Health check with timestamp, useful for uptime monitoring.

Request parameters

None

Response example

```
{
  "status": "ok",
  "timestamp": "2026-07-12T02:21:57.296Z"
}
```