

1. Fully observable vs Partially Observable:

- If an agent sensor can sense or access the complete state of an environment at each point of time then it is **a fully observable** environment, else it is **partially observable**.
- A fully observable environment is easy as there is no need to maintain the internal state to keep track history of the world.
- An agent with no sensors in all environments then such an environment is called as **unobservable**.

2. Deterministic vs Stochastic:

- If an agent's current state and selected action can completely determine the next state of the environment, then such environment is called a deterministic environment.
- A stochastic environment is random in nature and cannot be determined completely by an agent.
- In a deterministic, fully observable environment, agent does not need to worry about uncertainty.

3. Episodic vs Sequential:

- In an episodic environment, there is a series of one-shot actions, and only the current percept is required for the action.
- However, in Sequential environment, an agent requires memory of past actions to determine the next best actions.

4. Single-agent vs Multi-agent

- If only one agent is involved in an environment, and operating by itself then such an environment is called single agent environment.
- However, if multiple agents are operating in an environment, then such an environment is called a multi-agent environment.
- The agent design problems in the multi-agent environment are different from single agent environment.

5. Static vs Dynamic:

- If the environment can change itself while an agent is deliberating then such environment is called a dynamic environment else it is called a static environment.
- Static environments are easy to deal because an agent does not need to continue looking at the world while deciding for an action.
- However for dynamic environment, agents need to keep looking at the world at each action.
- Taxi driving is an example of a dynamic environment whereas Crossword puzzles are an example of a static environment.

6. Discrete vs Continuous:

- If in an environment there are a finite number of percepts and actions that can be performed within it, then such an environment is called a discrete environment else it is called continuous environment.
- A chess game comes under discrete environment as there is a finite number of moves that can be performed.
- A self-driving car is an example of a continuous environment.

7. Known vs Unknown

- Known and unknown are not actually a feature of an environment, but it is an agent's state of knowledge to perform an action.
- In a known environment, the results for all actions are known to the agent. While in unknown environment, agent needs to learn how it works in order to perform an action.
- It is quite possible that a known environment to be partially observable and an Unknown environment to be fully observable.

8. Accessible vs Inaccessible

- If an agent can obtain complete and accurate information about the state's environment, then such an environment is called an Accessible environment else it is called inaccessible.
- An empty room whose state can be defined by its temperature is an example of an accessible environment.

- Information about an event on earth is an example of Inaccessible environment.