

## MOD500 Decision Analysis with Artificial Intelligence Support

Enrico Riccardi<sup>1</sup>


Department of Energy Resources, University of Stavanger (UiS).<sup>1</sup>

Oct 18, 2024



© 2024, Enrico Riccardi. Released under CC Attribution 4.0 license

## A bias recap from last classes




## Probability distribution

A metric is needed

Amount of uncertainty

Number of Modes: unimodal, bimodal, polymodal




## Metrics

### Triangle inequality

Considering a vectors in an N-dimensional space, to be a **distance** it must satisfy the **triangle inequality**:

$$d_{ij} + d_{im} \geq d_{jm}$$

If also  $d_{jj} = 0$ , if  $d_{ij} - d_{ji} = 0$ , then we call it a *metric*.



## Metris example

Common metrics:

- Counting
- Euclidean

$$d_{ij}^{(E)} = \left[ \sum_{k=1}^N (x_{ik} - x_{jk})^2 \right]^{\frac{1}{2}}$$

Categorical variables do not necessarily satisfy these relations.

## Task assignment

Code a discrete probability distribution in Python

Calculate the Mean and Standard Deviation

How to get an experiment out of this distribution?

## How to relate a distribution to information?

First, the origins:

- Daddy: Claude Shannon (1940)
- His initial work has been done on signal transmission.
- It uses Entropy as key measurement of information uncertainty.

## How Entropy can alter a decisions?

It is an interface between data and decisions.

A question to sum up the idea

Does more data bring value?

It has permitted the advances of several fields:

cryptography, neurobiology, signal processing, linguistics, bioinformatics, statistical physics, black holes, quantum computing, information retrieval, intelligence gathering, plagiarism detection, pattern recognition, anomaly detection, etc

zip files, phones, internet!

## Entropy of an information source

$$H_X = -\sum_i (p_i) \log(p_i)$$

$H_X$  of a discrete random variable  $X$  is a measure of the amount of uncertainty associated with the value of  $X$  when only its distribution is known

What is  $p_i$ ?


It is a numerical descriptions of how likely an event is to occur

Do not mix the concepts!

Assigned probability and computed probability are different

## Shannon's entropy shape

$$H_X = -\sum_i (p_i) \log(p_i)$$



## Task assignment [2]

Code a discrete probability distribution in Python


Calculate the Mean and Standard Deviation

How to get an experiment out of this distribution?

Calculate Shannon's Entropy as a function of the number of experiments

## Comparing information

A distribution can be the sum of multiple distributions



How to compare multiple information sources?

$$D_{KL} = \sum_i (p_i) \log\left(\frac{p_i}{q_i}\right)$$

- It is a divergence, as it is asymmetric
- It is NOT a metric

Compare the initial discrete probability distribution with the approximate ones computed as function of the number of experiments.

Calculate Kullback–Leibler divergence

Find the distribution that minimise K-L divergence