

# Fundamentals of Machine learning for and with engineering applications

Enrico Riccardi<sup>1</sup>

Department of Mathematics and Physics, University of Stavanger (UiS).<sup>1</sup>

Sep 15, 2025



1 Linear Regression

2 Linear Regression

3 Model evaluation

4 Neural Network -NN-

# A linear model

Considering a univariate case, we have:

$$q = f(x)$$

which relates the **independent variable**  $x$  to the **true dependent variable**  $q$ .

**Assuming** a linear model

$$q = \beta_0 + \beta_1 x$$

where  $\beta_i$  are the arbitrary selected coefficients.

# A linear model

Considering a univariate case, we have:

$$q = f(x)$$

which relates the **independent variable**  $x$  to the **true dependent variable**  $q$ .

Assuming a linear model

$$q = \beta_0 + \beta_1 x$$

where  $\beta_i$  are the arbitrary selected coefficients.

# A linear model

Considering a univariate case, we have:

$$q = f(x)$$

which relates the **independent variable**  $x$  to the **true dependent variable**  $q$ .

**Assuming** a linear model

$$q = \beta_0 + \beta_1 x$$

where  $\beta_i$  are the arbitrary selected coefficients.

# Model set-up

For a given  $x$  we do not know the true response  $q$ , only the measurement  $y_i$  for experiment  $i$ .

We have that:

$$y_i = q_i + \epsilon_i$$

NOTE: do not proceed if you do not fully understand this equation.

which is

$$y_i = \beta_0 + \beta_1 x_i + \epsilon_i$$

Discussion point

Does  $\epsilon_i$  matter? And why so?

# Model set-up

For a given  $x$  we do not know the true response  $q$ , only the measurements  $y_i$  for experiment  $i$ .

We have that:

$$y_i = q_i + \epsilon_i$$

NOTE: do not proceed if you do not fully understand this equation.

which is

$$y_i = \beta_0 + \beta_1 x_i + \epsilon_i$$

Discussion point

Does  $\epsilon_i$  matter? And why so?

# Model set-up

For a given  $x$  we do not know the true response  $q$ , only the measurements  $y_i$  for experiment  $i$ .

We have that:

$$y_i = q_i + \epsilon_i$$

NOTE: do not proceed if you do not fully understand this equation.

which is

$$y_i = \beta_0 + \beta_1 x_i + \epsilon_i$$

Discussion point

Does  $\epsilon_i$  matter? And why so?



# Model set-up

For a given  $x$  we do not know the true response  $q$ , only the measurements  $y_i$  for experiment  $i$ .

We have that:

$$y_i = q_i + \epsilon_i$$

NOTE: do not proceed if you do not fully understand this equation.

which is

$$y_i = \beta_0 + \beta_1 x_i + \epsilon_i$$

## Discussion point

Does  $\epsilon_i$  matter? And why so?

# Estimated model paramters


The model parameters  $\beta_0, \beta_1$  are unknown, but they can be **estimated**. To distinguish estimates from true model parameters we call them  $b_0, b_1$ . These estimates are calculated such that the model

$$\hat{y} = b_0 + b_1x$$

fits the  $n$  different experimental observations as well as possible.

# Linear model example

We would like to find the TRUTH (What it is?)



# Python Example

```
import numpy as np
import matplotlib.pyplot as plt

def generate_linear_data(n_random_points, noise=16):
    x = np.random.rand(n_random_points) * 10

    # Make 'perfect' data
    true_slope, true_intercept = 2, 5
    y = true_slope * x + true_intercept

    # Add noise
    y += np.random.randn(n_random_points)*noise

    return x, y, true_slope, true_intercept

# Use the function to generate data
x, y, true_slope, true_intercept = generate_linear_data(
    n_random_points=166,
    noise=3)

# Plot all
plt.plot(x, true_slope*x + true_intercept,
         color='red', label='Truth Line')
plt.scatter(x, y, color='blue', label='Data Points')
plt.show()
```

# Estimation of linear regression parameters

For the 1-dimensional problem, we have

$$\hat{y} = b_0 + b_1x$$

where  $\hat{y}$  is the estimated y-value from the approximate model that has been generated from a set of measurements  $(x_i, y_i)$ . We aim to find the  $b_i$  parameters such that the regression line fits the observed data as well as possible.

This means we want to minimise the residuals

$$e_i = y_i - \hat{y}_i$$

# Estimation of linear regression parameters

For the 1-dimensional problem, we have

$$\hat{y} = b_0 + b_1x$$

where  $\hat{y}$  is the estimated y-value from the approximate model that has been generated from a set of measurements  $(x_i, y_i)$ . We aim to find the  $b_i$  parameters such that the regression line fits the observed data as well as possible.

This means we want to minimise the residuals

$$e_i = y_i - \hat{y}_i$$

# Estimation of linear regression parameters

For the 1-dimensional problem, we have

$$\hat{y} = b_0 + b_1x$$

where  $\hat{y}$  is the estimated y-value from the approximate model that has been generated from a set of measurements  $(x_i, y_i)$ . We aim to find the  $b_i$  parameters such that the regression line fits the observed data as well as possible.

This means we want to minimise the residuals

$$e_i = y_i - \hat{y}_i$$

# Estimation of linear regression parameters

For the 1-dimensional problem, we have

$$\hat{y} = b_0 + b_1x$$

where  $\hat{y}$  is the estimated y-value from the approximate model that has been generated from a set of measurements  $(x_i, y_i)$ . We aim to find the  $b_i$  parameters such that the regression line fits the observed data as well as possible.

This means we want to minimise the residuals

$$e_i = y_i - \hat{y}_i$$



# Estimation of linear regression parameters

- Cannot sum  $e_i$  values since they might be positive and negative and thus cancel
- Could use e.g.  $\sum_{i=1}^n |e_i|$ , but is mathematically more difficult to handle
- Residual “smallness” measured by  $\sum_{i=1}^n e_i^2$ .

Thus, we find the linear regression coefficients by *minimising*

$$R = \sum_{i=1}^n e_i^2 = \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

How

Regression!

# Estimation of linear regression parameters

- Cannot sum  $e_i$  values since they might be positive and negative and thus cancel
- Could use e.g.  $\sum_{i=1}^n |e_i|$ , but is mathematically more difficult to handle
- Residual “smallness” measured by  $\sum_{i=1}^n e_i^2$ .

Thus, we find the linear regression coefficients by *minimising*

$$R = \sum_{i=1}^n e_i^2 = \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

How

Regression!

# Estimation of linear regression parameters

- Cannot sum  $e_i$  values since they might be positive and negative and thus cancel
- Could use e.g.  $\sum_{i=1}^n |e_i|$ , but is mathematically more difficult to handle
- Residual “smallness” measured by  $\sum_{i=1}^n e_i^2$ .

Thus, we find the linear regression coefficients by *minimising*

$$R = \sum_{i=1}^n e_i^2 = \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

How?

Regression!

# Estimation of linear regression parameters

- Cannot sum  $e_i$  values since they might be positive and negative and thus cancel
- Could use e.g.  $\sum_{i=1}^n |e_i|$ , but is mathematically more difficult to handle
- Residual “smallness” measured by  $\sum_{i=1}^n e_i^2$ .

Thus, we find the linear regression coefficients by *minimising*

$$R = \sum_{i=1}^n e_i^2 = \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

How?

Regression!

# Estimation of linear regression parameters

- Cannot sum  $e_i$  values since they might be positive and negative and thus cancel
- Could use e.g.  $\sum_{i=1}^n |e_i|$ , but is mathematically more difficult to handle
- Residual “smallness” measured by  $\sum_{i=1}^n e_i^2$ .

Thus, we find the linear regression coefficients by *minimising*

$$R = \sum_{i=1}^n e_i^2 = \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

How?

Regression!

# Estimation of linear regression parameters

- Cannot sum  $e_i$  values since they might be positive and negative and thus cancel
- Could use e.g.  $\sum_{i=1}^n |e_i|$ , but is mathematically more difficult to handle
- Residual “smallness” measured by  $\sum_{i=1}^n e_i^2$ .

Thus, we find the linear regression coefficients by *minimising*

$$R = \sum_{i=1}^n e_i^2 = \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

How?

Regression!

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

Questions

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

Questions

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?



# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

## Discussion

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

## Discussion

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

## Discussion

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

## Discussion

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

## Discussion

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Regression

To minimize the sum of the square residuals, we can try to solve the following equations:

$$\frac{\partial R}{\partial b_0} = 0$$

$$\frac{\partial R}{\partial b_1} = 0$$

where:

$$R = \sum_{i=1}^n (y_i - \hat{y}_i)^2 =$$

$$\sum_{i=1}^n (y_i - (b_0 + b_1 x_i))^2 = \sum_{i=1}^n u_i^2$$

# Regression

To minimize the sum of the square residuals, we can try to solve the following equations:

$$\frac{\partial R}{\partial b_0} = 0$$

$$\frac{\partial R}{\partial b_1} = 0$$

where:

$$R = \sum_{i=1}^n (y_i - \hat{y}_i)^2 =$$

$$\sum_{i=1}^n (y_i - (b_0 + b_1 x_i))^2 = \sum_{i=1}^n u_i^2$$

# Regression

To minimize the sum of the square residuals, we can try to solve the following equations:

$$\frac{\partial R}{\partial b_0} = 0$$

$$\frac{\partial R}{\partial b_1} = 0$$

where:

$$R = \sum_{i=1}^n (y_i - \hat{y}_i)^2 = \sum_{i=1}^n (y_i - (b_0 + b_1 x_i))^2 = \sum_{i=1}^n u_i^2$$



Skipping the math (but you are more than welcome to try), here are the results:

$$\begin{aligned}b_0 &= \bar{y} - b_1 \bar{x} \\b_1 &= \frac{\sum_{i=1}^n (x_i - \bar{x})(y_i - \bar{y})}{\sum_{i=1}^n (x_i - \bar{x})^2}\end{aligned}$$

Straightforward derivation becomes very cumbersome for multiple variables. Thus, a different approach must be used. Yet, it is important to understand that there is an analytical solution (even if not all the time).

Skipping the math (but you are more than welcome to try), here are the results:

$$\begin{aligned}b_0 &= \bar{y} - b_1 \bar{x} \\b_1 &= \frac{\sum_{i=1}^n (x_i - \bar{x})(y_i - \bar{y})}{\sum_{i=1}^n (x_i - \bar{x})^2}\end{aligned}$$

Straightforward derivation becomes very cumbersome for multiple variables. Thus, a different approach must be used. Yet, it is important to understand that there is an analytical solution (even if not all the time).

Skipping the math (but you are more than welcome to try), here are the results:

$$\begin{aligned}b_0 &= \bar{y} - b_1\bar{x} \\b_1 &= \frac{\sum_{i=1}^n (x_i - \bar{x})(y_i - \bar{y})}{\sum_{i=1}^n (x_i - \bar{x})^2}\end{aligned}$$

Straightforward derivation becomes very cumbersome for multiple variables. Thus, a different approach must be used. Yet, it is important to understand that there is an analytical solution (even if not all the time).

# Linear model(s)

Does a linear model mean only straight lines (or hyperplanes in general)?

That answer to this is *no*, different. In general for a model  $f$  to be defined linear, it has to be linear with respect to the unknown parameters  $\beta_0, \dots, \beta_n$ . The general linear model is

$$q = \beta_0 + \beta_1 f_1(x_1) + \beta_2 f_2(x_2) + \dots + \beta_n f_n(x_n)$$

where  $f_i(x_i)$  may be non-linear functions. It is the **form** of the equation which makes it linear, i.e. that  $f_i(x_i)$  does not depend on the parameters  $\beta_i$ .

# Linear model(s)

Does a linear model mean only straight lines (or hyperplanes in general)?

That answer to this is *no*. different. In general for a model  $f$  to be defined linear, it has to be linear with respect to the unknown parameters  $\beta_0, \dots, \beta_n$ . The general linear model is

$$q = \beta_0 + \beta_1 f_1(x_1) + \beta_2 f_2(x_2) + \dots + \beta_n f_n(x_n)$$

where  $f_i(x_i)$  may be non-linear functions. It is the **form** of the equation which makes it linear, i.e. that  $f_i(x_i)$  does not depend on the parameters  $\beta_i$ .

# Linear model(s)

Does a linear model mean only straight lines (or hyperplanes in general)?

That answer to this is *no*. different. In general for a model  $f$  to be defined linear, it has to be linear with respect to the unknown parameters  $\beta_0, \dots, \beta_n$ . The general linear model is

$$q = \beta_0 + \beta_1 f_1(x_1) + \beta_2 f_2(x_2) + \dots + \beta_n f_n(x_n)$$

where  $f_i(x_i)$  may be non-linear functions. It is the **form** of the equation which makes it linear, i.e. that  $f_i(x_i)$  does not depend on the parameters  $\beta_i$ .

Consider the following model example - is it linear?

$$q = \beta_0 + \beta_1 x_1^2 + \beta_2 x_2^{-1} + \beta_3 \log x_3$$

The answer is yes because by simple substitution it is possible to convert this formula into a linear form.

With  $h_1 = x_1^2$ ,  $h_2 = x_2^{-1}$  and  $h_3 = \log x_3$ , then we can formulate the new model:

$$q = \beta_0 + \beta_1 h_1 + \beta_2 h_2 + \beta_3 h_3$$

which is in the standard linear form.

# Linear model(s)

Consider the following model example - is it linear?

$$q = \beta_0 + \beta_1 x_1^2 + \beta_2 x_2^{-1} + \beta_3 \log x_3$$

The answer is yes because by simple substitution it is possible to convert this formula into a linear form.

With  $h_1 = x_1^2$ ,  $h_2 = x_2^{-1}$  and  $h_3 = \log x_3$ , then we can formulate the new model:

$$q = \beta_0 + \beta_1 h_1 + \beta_2 h_2 + \beta_3 h_3$$

which is in the standard linear form.



# Linear model(s)

Consider the following model example - is it linear?

$$q = \beta_0 + \beta_1 x_1^2 + \beta_2 x_2^{-1} + \beta_3 \log x_3$$

The answer is yes because by simple substitution it is possible to convert this formula into a linear form.

With  $h_1 = x_1^2$ ,  $h_2 = x_2^{-1}$  and  $h_3 = \log x_3$ , then we can formulate the new model:

$$q = \beta_0 + \beta_1 h_1 + \beta_2 h_2 + \beta_3 h_3$$

which is in the standard linear form.

# Linear model(s)

Consider the following model example - is it linear?

$$q = \beta_0 + \beta_1 x_1^2 + \beta_2 x_2^{-1} + \beta_3 \log x_3$$

The answer is yes because by simple substitution it is possible to convert this formula into a linear form.

With  $h_1 = x_1^2$ ,  $h_2 = x_2^{-1}$  and  $h_3 = \log x_3$ , then we can formulate the new model:

$$q = \beta_0 + \beta_1 h_1 + \beta_2 h_2 + \beta_3 h_3$$

which is in the standard linear form.

# Curvilinear models

A special class of linear models which we will investigate later are those which are expressed in terms of *polynomials* (here in only 1D):

$$q = \beta_0 + \beta_1 x + \beta_2 x^2 + \cdots + \beta_m x^m = \sum_{i=0}^n \beta_i x^i$$

For n-D case there are a wide range of interaction terms and combinations, that can still be converted to standard linear form.

Such models are sometimes referred to as **curvilinear** instead of non-linear

# Curvilinear models

A special class of linear models which we will investigate later are those which are expressed in terms of *polynomials* (here in only 1D):

$$q = \beta_0 + \beta_1 x + \beta_2 x^2 + \cdots + \beta_m x^m = \sum_{i=0}^n \beta_i x^i$$

For n-D case there are a wide range of interaction terms and combinations, that can still be converted to standard linear form.

Such models are sometimes referred to as **curvilinear** instead of non-linear

# Curvilinear models

A special class of linear models which we will investigate later are those which are expressed in terms of *polynomials* (here in only 1D):

$$q = \beta_0 + \beta_1 x + \beta_2 x^2 + \cdots + \beta_m x^m = \sum_{i=0}^n \beta_i x^i$$

For n-D case there are a wide range of interaction terms and combinations, that can still be converted to standard linear form.

Such models are sometimes referred to as **curvilinear** instead of non-linear

# Nonlinear models

But there are many other models that cannot be substituted to such a form. For instance:

$$q = \beta_0 + \log(x - \beta_1)$$

No substitution can transform this equation to the linear form.

That is the case for all the model that:

$$q \sim f(x, \beta)$$

Another example is:

$$f(x, \beta) = \frac{x\beta}{x + \beta}$$

# Nonlinear models

But there are many other models that cannot be substituted to such a form. For instance:

$$q = \beta_0 + \log(x - \beta_1)$$

No substitution can transform this equation to the linear form.

That is the case for all the model that:

$$q \sim f(x, \beta)$$

Another example is:

$$f(x, \beta) = \frac{x\beta}{x + \beta}$$

# Nonlinear models

But there are many other models that cannot be substituted to such a form. For instance:

$$q = \beta_0 + \log(x - \beta_1)$$

No substitution can transform this equation to the linear form.

That is the case for all the model that:

$$q \sim f(x, \beta)$$

Another example is:

$$f(x, \beta) = \frac{x\beta}{x + \beta}$$



# Nonlinear models

But there are many other models that cannot be substituted to such a form. For instance:

$$q = \beta_0 + \log(x - \beta_1)$$

No substitution can transform this equation to the linear form.

That is the case for all the model that:

$$q \sim f(x, \beta)$$

Another example is:

$$f(x, \beta) = \frac{x\beta}{x + \beta}$$

# Many variable equation

The general equation would look like:

$$\hat{y} = b_0 + b_1x_1 + b_2x_2 + \cdots + b_nx_n = \sum_{j=0}^m x_{ij} b_j$$

where we will have to solve all the  $n + 1$  equations (called the **normal equations**) of the form:

$$\frac{\partial R}{\partial b_j} = 0 \quad \forall j \in [0, n]$$

Is there a way to solve this simply, huh?

We can use vector and matrix algebra.

# Many variable equation

The general equation would look like:

$$\hat{y} = b_0 + b_1x_1 + b_2x_2 + \cdots + b_nx_n = \sum_{j=0}^m x_{ij} b_j$$

where we will have to solve all the  $n + 1$  equations (called the **normal equations**) of the form:

$$\frac{\partial R}{\partial b_j} = 0 \quad \forall j \in [0, n]$$

Is there a way for us to simplify this?

We can use vector and matrix algebra.

# Many variable equation

The general equation would look like:

$$\hat{y} = b_0 + b_1x_1 + b_2x_2 + \cdots + b_nx_n = \sum_{j=0}^m x_{ij} b_j$$

where we will have to solve all the  $n + 1$  equations (called the **normal equations**) of the form:

$$\frac{\partial R}{\partial b_j} = 0 \quad \forall j \in [0, n]$$

Is there a way for us to simplify this?

We can use vector and matrix algebra.

# Many variable equation

The general equation would look like:

$$\hat{y} = b_0 + b_1x_1 + b_2x_2 + \cdots + b_nx_n = \sum_{j=0}^m x_{ij} b_j$$

where we will have to solve all the  $n + 1$  equations (called the **normal equations**) of the form:

$$\frac{\partial R}{\partial b_j} = 0 \quad \forall j \in [0, n]$$

Is there a way for us to simplify this?

We can use vector and matrix algebra.

# Many variable equation

The general equation would look like:

$$\hat{y} = b_0 + b_1x_1 + b_2x_2 + \cdots + b_nx_n = \sum_{j=0}^m x_{ij} b_j$$

where we will have to solve all the  $n + 1$  equations (called the **normal equations**) of the form:

$$\frac{\partial R}{\partial b_j} = 0 \quad \forall j \in [0, n]$$

Is there a way for us to simplify this?

We can use vector and matrix algebra.

1 Linear Regression

2 Linear Regression

3 Model evaluation

4 Neural Network -NN-

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

Questions

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?



# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

Questions

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

## Discussion

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

## Discussion

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

## Discussion

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

## Discussion

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Let's recaps

Before to continue, let's make sure to have all the main elements clear:

- 1 Splitting the data in dependent and independent variables
- 2 Assumption of a linear model between them
- 3 Recognise the difference between the truth and the estimation
- 4 Aiming to *minimize* the residuals

## Discussion

What happen when the sum of residual is 0 ?

What happens where the data is heavily correlated?

# Regression

To minimize the sum of the square residuals, we can try to solve the following equations:

$$\frac{\partial R}{\partial b_0} = 0$$

$$\frac{\partial R}{\partial b_1} = 0$$

where:

$$R = \sum_{i=1}^n (y_i - \hat{y}_i)^2 =$$

$$\sum_{i=1}^n (y_i - (b_0 + b_1 x_i))^2 = \sum_{i=1}^n u_i^2$$

Skipping the math (but you are more than welcome to try), here are the results:

$$\begin{aligned}b_0 &= \bar{y} - b_1\bar{x} \\ b_1 &= \frac{\sum_{i=1}^n (x_i - \bar{x})(y_i - \bar{y})}{\sum_{i=1}^n (x_i - \bar{x})^2}\end{aligned}$$

Straightforward derivation becomes very cumbersome for multiple variables. Thus, a different approach must be used. Yet, it is important to understand that there is an analytical solution (even if not all the time).



# Many variable equation

The general equation would look like:

$$\hat{y} = b_0 + b_1x_1 + b_2x_2 + \cdots + b_nx_n = \sum_{j=0}^m x_{ij} b_j$$

where we will have to solve all the  $n + 1$  equations (called the **normal equations**) of the form:

$$\frac{\partial R}{\partial b_j} = 0 \quad \forall j \in [0, n]$$

Is there a way for us to simplify this?

We can use vector and matrix algebra.

# Many variable equation

The general equation would look like:

$$\hat{y} = b_0 + b_1x_1 + b_2x_2 + \cdots + b_nx_n = \sum_{j=0}^m x_{ij} b_j$$

where we will have to solve all the  $n + 1$  equations (called the **normal equations**) of the form:

$$\frac{\partial R}{\partial b_j} = 0 \quad \forall j \in [0, n]$$

Is there a way for us to simplify this?

We can use vector and matrix algebra.

# Regression via Matrix operation

Remember that

$$R = \sum_{i=1}^N (y_i - \hat{y}_i)^2$$

then we can define the vector  $\mathbf{e}$ :

$$\mathbf{e} = \mathbf{y} - \hat{\mathbf{y}}$$

thus

$$\mathbf{e}^T = [(y_1 - \hat{y}_1) \ (y_2 - \hat{y}_2) \cdots \ (y_N - \hat{y}_N)]$$

and can then write

$$R = \mathbf{e}^T \mathbf{e}$$

# Regression via Matrix operation

Remember that

$$R = \sum_{i=1}^N (y_i - \hat{y}_i)^2$$

then we can define the vector  $\mathbf{e}$ :

$$\mathbf{e} = \mathbf{y} - \hat{\mathbf{y}}$$

thus

$$\mathbf{e}^T = [(y_1 - \hat{y}_1) \ (y_2 - \hat{y}_2) \cdots \ (y_N - \hat{y}_N)]$$

and can then write

$$R = \mathbf{e}^T \mathbf{e}$$

# Regression via Matrix operation

Remember that

$$R = \sum_{i=1}^N (y_i - \hat{y}_i)^2$$

then we can define the vector  $\mathbf{e}$ :

$$\mathbf{e} = \mathbf{y} - \hat{\mathbf{y}}$$

thus

$$\mathbf{e}^T = [(y_1 - \hat{y}_1) \ (y_2 - \hat{y}_2) \cdots \ (y_N - \hat{y}_N)]$$

and can then write

$$R = \mathbf{e}^T \mathbf{e}$$

# Regression via Matrix operation

Remember that

$$R = \sum_{i=1}^N (y_i - \hat{y}_i)^2$$

then we can define the vector  $\mathbf{e}$ :

$$\mathbf{e} = \mathbf{y} - \hat{\mathbf{y}}$$

thus

$$\mathbf{e}^T = [(y_1 - \hat{y}_1) \ (y_2 - \hat{y}_2) \ \cdots \ (y_N - \hat{y}_N)]$$

and can then write

$$R = \mathbf{e}^T \mathbf{e}$$

From the following equation:

$$\hat{y}_i = b_0 + \sum_{j=1}^m x_{ij} b_j = \sum_{j=0}^m x_{ij} b_j$$

where  $x_{i0} = 1$

we make the matrix equation:

$$\hat{\mathbf{y}} = \mathbf{X} \mathbf{b}$$

where the first column in  $\mathbf{X}$  consists of ones only.

# Residual

$$\begin{aligned} R &= \mathbf{e}^T \mathbf{e} \\ &= (\mathbf{y} - \hat{\mathbf{y}})^T (\mathbf{y} - \hat{\mathbf{y}}) \\ &= (\mathbf{y} - \mathbf{X}\mathbf{b})^T (\mathbf{y} - \mathbf{X}\mathbf{b}) \\ &= (\mathbf{y}^T - \mathbf{b}^T \mathbf{X}^T) (\mathbf{y} - \mathbf{X}\mathbf{b}) \\ &= \mathbf{y}^T \mathbf{y} - \mathbf{y}^T \mathbf{X} \mathbf{b} - \mathbf{b}^T \mathbf{X}^T \mathbf{y} \\ &+ \mathbf{b}^T \mathbf{X}^T \mathbf{X} \mathbf{b} \end{aligned}$$

All the parts of this equation are scalar values. This means e.g. that

$$\mathbf{y}^T \mathbf{X} \mathbf{b} = \mathbf{b}^T \mathbf{X}^T \mathbf{y}$$

This gives

$$R = \mathbf{y}^T \mathbf{y} - 2\mathbf{y}^T \mathbf{X} \mathbf{b} + \mathbf{b}^T \mathbf{X}^T \mathbf{X} \mathbf{b}$$

But how can we now compute  $\frac{\partial R}{\partial b_j}$  more efficiently in matrix form?

**Vector differentiation** ! Let

$$y = \mathbf{a}^T \mathbf{x} = a_1 x_1 + \cdots + a_n x_n$$

If

$$\frac{\partial y}{\partial \mathbf{x}} = \begin{bmatrix} \frac{\partial y}{\partial x_1} \\ \frac{\partial y}{\partial x_2} \\ \vdots \\ \frac{\partial y}{\partial x_n} \end{bmatrix} = \begin{bmatrix} a_1 \\ \vdots \\ a_n \end{bmatrix} = \mathbf{a}$$

and  $y = \mathbf{x}^T \mathbf{a}$ , then:

$$\frac{\partial y}{\partial \mathbf{x}} = \mathbf{a}$$



# General solution

In general, when  $y = \mathbf{x}^T \mathbf{A} \mathbf{x}$ , then

$$\frac{\partial y}{\partial \mathbf{x}} = 2\mathbf{A}\mathbf{x}$$

if  $\mathbf{A}$  is symmetric  
(check *Matrix calculus* for more properties)

We can use this to compute

$$\frac{\partial R}{\partial \mathbf{b}}$$

# General solution

We have from above:

$$\begin{aligned} R &= y^T y - 2y^T Xb \\ &+ b^T X^T Xb \end{aligned}$$

Vector differentiation gives

$$\frac{\partial R}{\partial b} = 0 - 2X^T y + 2X^T Xb = 0$$

Solving this for  $b$  we get:

$$\begin{aligned} X^T Xb &= X^T y \\ (X^T X)^{-1} X^T Xb &= (X^T X)^{-1} X^T y \\ b &= (X^T X)^{-1} X^T y \end{aligned}$$

# Multiple linear regression

Previous equation make the solution of MLR rather obvious!

When we have a matrix of y-variables  $\mathbf{Y}$ :

$$\mathbf{B} = (\mathbf{X}^T \mathbf{X})^{-1} \mathbf{X}^T \mathbf{Y}$$

in the equation:

$$\mathbf{Y} = \mathbf{X}\mathbf{B}.$$

These equations give us the **multiple linear regression** (MLR) solution.

# Multiple linear regression

Previous equation make the solution of MLR rather obvious!

When we have a matrix of y-variables  $\mathbf{Y}$ :

$$\mathbf{B} = (\mathbf{X}^T \mathbf{X})^{-1} \mathbf{X}^T \mathbf{Y}$$

in the equation:

$$\mathbf{Y} = \mathbf{X}\mathbf{B}.$$

These equations give us the **multiple linear regression** (MLR) solution.

1 Linear Regression

2 Linear Regression

3 Model evaluation

4 Neural Network -NN-

# Model evaluation

We can measure the accuracy of a prediction only when we have a 'truth' to compare with.

## Model outcome

The accuracy of a prediction is limited by the available data set (not an universal quantity).

Given a dataset, we split the data in a **train** and a test set.

One has to be extremely careful to not introduce a **bias** in each of them when splitting. (or to introduce a bias properly, when for example, working with time series.

# Model evaluation

We can measure the accuracy of a prediction only when we have a 'truth' to compare with.

## Model outcome

The accuracy of a prediction is limited by the available data set (not an universal quantity).

Given a dataset, we split the data in a **train** and a test set.

One has to be extremely careful to not introduce a **bias** in each of them when splitting. (or to introduce a bias properly, when for example, working with time series.

A train dataset is a subset of the original data. Generally it is circa a 70 % (common practice, not a rule) of the *INSTANCES*.

For each selected instance, all the features are kept, as their labels.

## Random measurements

Some models are able to also consider the sequence of instances; the selection of the **train** dataset has to be randomised.

The opposite consideration shall be done for time series, where each data point is correlated to the previous.



A train dataset is a subset of the original data. Generally it is circa a 70 % (common practice, not a rule) of the *INSTANCES*.

For each selected instance, all the features are kept, as their labels.

## Random measurements

Some models are able to also consider the sequence of instances; the selection of the **train** dataset has to be randomised.

The opposite consideration shall be done for time series, where each data point is correlated to the previous.

# Validation

A validation dataset is a subset of the original data. Generally it is circa a 15 % (common practice, not a rule) of the *INSTANCES*.

It is aimed to provide a **unbiased estimate of the model prediction error**. This information is then used to *tune* the model set up (indirectly). I.e. it is not independent from the test phase.

For each selected instance, all the features are kept, as their labels.

## Random measurements

Some models are able to also consider the sequence of instances; the selection of the **validation** dataset has to be randomised.

The opposite consideration shall be done for time series, where each data point is correlated to the previous.

# Validation

A validation dataset is a subset of the original data. Generally it is circa a 15 % (common practice, not a rule) of the *INSTANCES*.

It is aimed to provide a **unbiased estimate of the model prediction error**. This information is then used to *tune* the model set up (indirectly). I.e. it is not independent from the test phase.

For each selected instance, all the features are kept, as their labels.

## Random measurements

Some models are able to also consider the sequence of instances; the selection of the **validation** dataset has to be randomised.

The opposite consideration shall be done for time series, where each data point is correlated to the previous.

A test dataset is a subset of the original data. Generally it is circa a 70 % (common practice, not a rule) of the *INSTANCES*.

For each selected instance, all the features are kept, as their labels.

## Random measurements

Some models are able to also consider the sequence of instances, the selection of the alerttest dataset has to be randomised.

A test dataset is a subset of the original data. Generally it is circa a 70 % (common practice, not a rule) of the *INSTANCES*.

For each selected instance, all the features are kept, as their labels.

## Random measurements

Some models are able to also consider the sequence of instances, the selection of the alerttest dataset has to be randomised.

## Train-Validation-Test

- 1 Data is split into train, validation and test dataset
- 2 A model is trained on the train dataset
- 3 The model (hyper)parameters are improved on the validation dataset
- 4 The model performances (e.g. accuracy) are tested on the test dataset

## Train-Validation-Test

- 1 Data is split into train, validation and test dataset
- 2 A model is trained on the train dataset
- 3 The model (hyper)parameters are improved on the validation dataset
- 4 The model performances (e.g. accuracy) are tested on the test dataset

# Model evaluation

## Train-Validation-Test

- 1 Data is split into train, validation and test dataset
- 2 A model is trained on the train dataset
- 3 The model (hyper)parameters are improved on the validation dataset
- 4 The model performances (e.g. accuracy) are tested on the test dataset



# Model evaluation

## Train-Validation-Test


- 1 Data is split into train, validation and test dataset
- 2 A model is trained on the train dataset
- 3 The model (hyper)parameters are improved on the validation dataset
- 4 The model performances (e.g. accuracy) are tested on the test dataset

# Model evaluation

## Train-Validation-Test

- 1 Data is split into train, validation and test dataset
- 2 A model is trained on the train dataset
- 3 The model (hyper)parameters are improved on the validation dataset
- 4 The model performances (e.g. accuracy) are tested on the test dataset

# Model evaluation



# Cross validation

## Cross validation-Test

- 1 Data is split into train and test.
- 2 Train dataset is then split into k-folds (different subsets, usually 5 to 10)
- 3 A model is trained on all k subset but one, sequentially
- 4 The model is tested on the remaining k data subset and its output averaged
- 5 The model performances (e.g. accuracy) are tested on the test dataset

## Cross validation-Test

- 1 Data is split into train and test.
- 2 Train dataset is then split into k-folds (different subsets, usually 5 to 10)
- 3 A model is trained on all k subset but one, sequentially
- 4 The model is tested on the remaining k data subset and its output averaged
- 5 The model performances (e.g. accuracy) are tested on the test dataset

# Cross validation

## Cross validation-Test

- 1 Data is split into train and test.
- 2 Train dataset is then split into k-folds (different subsets, usually 5 to 10)
- 3 A model is trained on all k subset but one, sequentially
- 4 The model is tested on the remaining k data subset and its output averaged
- 5 The model performances (e.g. accuracy) are tested on the test dataset

# Cross validation

## Cross validation-Test

- 1 Data is split into train and test.
- 2 Train dataset is then split into k-folds (different subsets, usually 5 to 10)
- 3 A model is trained on all k subset but one, sequentially
- 4 The model is tested on the remaining k data subset and its output averaged
- 5 The model performances (e.g. accuracy) are tested on the test dataset

# Cross validation

## Cross validation-Test

- 1 Data is split into train and test.
- 2 Train dataset is then split into k-folds (different subsets, usually 5 to 10)
- 3 A model is trained on all k subset but one, sequentially
- 4 The model is tested on the remaining k data subset and its output averaged
- 5 The model performances (e.g. accuracy) are tested on the test dataset




# Cross validation

## Cross validation-Test

- ➊ Data is split into train and test.
- ➋ Train dataset is then split into k-folds (different subsets, usually 5 to 10)
- ➌ A model is trained on all k subset but one, sequentially
- ➍ The model is tested on the remaining k data subset and its output averaged
- ➎ The model performances (e.g. accuracy) are tested on the test dataset

# Cross validation



1 Linear Regression

2 Linear Regression

3 Model evaluation

4 Neural Network -NN-

# Neural Network -NN-

One of the most famous models in Machine Learning is **Neural Network**.

The name comes from how the brain functions: a set of connected neurons that are either off or active.

In its essence,

NN is a large set of (linear) regressions executed both in parallel and in series.

Conventional NN are composed by:

- 1 Input layer
- 2 Hidden layers
- 3 Output layers

which, together, can approximately approximate any function in any dimension.

# Neural Network -NN-

One of the most famous models in Machine Learning is **Neural Network**.

The name comes from how the brain functions: a set of connected neurons that are either off or active.

In its essence,

NN is a large set of (linear) regressions executed both in parallel and in series.

Conventional NN are composed by:

- 1 Input layer
- 2 Hidden layers
- 3 Output layers

which, together, can approximately approximate any function in any dimension.

# Neural Network -NN-

One of the most famous models in Machine Learning is **Neural Network**.

The name comes from how the brain functions: a set of connected neurons that are either off or active.

In its essence,

NN is a large set of (linear) regressions executed both in parallel and in series.

Conventional NN are composed by:

- 1 Input layer
- 2 Hidden layers
- 3 Output layers

which, together, can approximately approximate any function in any dimension.

# Neural Network -NN-

One of the most famous models in Machine Learning is **Neural Network**.

The name comes from how the brain functions: a set of connected neurons that are either off or active.

In its essence,

NN is a large set of (linear) regressions executed both in parallel and in series.

Conventional NN are composed by:

- 1 Input layer
- 2 Hidden layers
- 3 Output layers

which, together, can approximately approximate any function in any dimension.

# Neural Network -NN-

One of the most famous models in Machine Learning is **Neural Network**.

The name comes from how the brain functions: a set of connected neurons that are either off or active.

In its essence,

NN is a large set of (linear) regressions executed both in parallel and in series.


Conventional NN are composed by:

- 1 Input layer
- 2 Hidden layers
- 3 Output layers

which, together, can approximately approximate any function in any dimension.




# deep Neural Network



# How do they work?

Each node is called **neuron**




Use many of these, many times, and you have builded a NN!

- It is really just a  $Y = f(X)$ , where  $w_i$  and  $b_i$  are the unknowns to solve for.
- As in linear regression, this becomes mainly a number of numerical recipes.
- As the problem's dimensionality is significant, several strategies have been developed.

# How do they work?

Each node is called **neuron**



Use many of these, many times, and you have builded a NN!

- It is really just a  $Y = f(X)$ , where  $w_i$  and  $b_i$  are the unknowns to solve for.
- As in linear regression, this becomes mainly a number of numerical recipes.
- As the problem's dimensionality is significant, several strategies have been developed.


# How do they work?

- 1 We thus need also an **activation function**.
- 2 The **NN structure**
- 3 Also, we might need to specify the number of **epochs**.

Using NN is essentially running a simulation campaign: a set of numerical experiments

Please say yes

Have you already heard of experimental design?




# How do they work?

- 1 We thus need also an **activation function**.
- 2 The **NN structure**
- 3 Also, we might need to specify the number of **epochs**.

Using NN is essentially running a simulation campaign: a set of numerical experiments

Please say yes

Have you already heard of experimental design?




# Activation function


Each node applies an activation function on the weighted sum of the previous nodes.

Such functions are called activation functions. There are MANY!

The most popular has been the logistic

	$\sigma(x) \doteq \frac{1}{1 + e^{-x}}$	$g(x)(1 - g(x))$
---	---	------------------

Now the most common is ReLU (Rectified linear unit)


	$(x)^+ \doteq \begin{cases} 0 & \text{if } x \leq 0 \\ x & \text{if } x > 0 \end{cases}$ $= \max(0, x) = x \mathbf{1}_{x>0}$	$\begin{cases} 0 & \text{if } x < 0 \\ 1 & \text{if } x > 0 \end{cases}$
---	--	--

# Activation function


Each node applies an activation function on the weighted sum of the previous nodes.

Such functions are called activation functions. There are MANY!

The most popular has been the logistic



Now the most common is ReLU (Rectified linear unit)




# Activation function


Each node applies an activation function on the weighted sum of the previous nodes.

Such functions are called activation functions. There are MANY!

The most popular has been the logistic



Now the most common is ReLU (Rectified linear unit)





## A mostly complete chart of Neural Networks

©2016 Fjodor van Veen - asimovinstitute.org

- Backfed Input Cell
- Input Cell
- Noisy Input Cell
- Hidden Cell
- Probabilistic Hidden Cell
- Spiking Hidden Cell
- Output Cell
- Match Input Output Cell
- Recurrent Cell
- Memory Cell
- Different Memory Cell
- Kernel
- Convolution or Pool

Perceptron (P)



Feed Forward (FF)




Radial Basis Network (RBF)




Deep Feed Forward (DFF)




Recurrent Neural Network (RNN)



Long / Short Term Memory (LSTM)



Gated Recurrent Unit (GRU)




Auto Encoder (AE)



Variational AE (VAE)



Denosing AE (DAE)



Sparse AE (SAE)



## A mostly complete chart of Neural Networks

©2016 Fjodor van Veen - asimovinstitute.org

- Backfed Input Cell
- Input Cell
- Noisy Input Cell
- Hidden Cell
- Probabilistic Hidden Cell
- Spiking Hidden Cell
- Output Cell
- Match Input Output Cell
- Recurrent Cell
- Memory Cell
- Different Memory Cell
- Kernel
- Convolution or Pool

Perceptron (P)



Feed Forward (FF)




Radial Basis Network (RBF)




Deep Feed Forward (DFF)




Recurrent Neural Network (RNN)



Long / Short Term Memory (LSTM)



Gated Recurrent Unit (GRU)




Auto Encoder (AE)



Variational AE (VAE)



Denosing AE (DAE)



Sparse AE (SAE)



# NN Architecture

Markov Chain (MC)



Hopfield Network (HN)




Boltzmann Machine (BM)




Restricted BM (RBM)




Deep Belief Network (DBN)




Deep Convolutional Network (DCN)




Deconvolutional Network (DN)



Deep Convolutional Inverse Graphics Network (DCIGN)




Generative Adversarial Network (GAN)




Liquid State Machine (LSM)



Extreme Learning Machine (ELM)



Echo State Network (ESN)



Deep Residual Network (DRN)



Kohonen Network (KN)



Support Vector Machine (SVM)



Neural Turing Machine (NTM)



# NN Architecture

Neural net suffers from overfitting problems.

Even more parameters

The number of nodes, the architecture, the number of hidden layer etc are NN **hyperparameters**

Unfortunately, at the current status of knowledge, the best architecture can be found only by trial and error.

The best fitting NN usually has a poor validation (generalizability).

NN is a very expensive approach and it should be used only if really needed.

# NN Architecture

Neural net suffers from overfitting problems.

Even more parameters

The number of nodes, the architecture, the number of hidden layer etc are NN **hyperparameters**

Unfortunately, at the current status of knowledge, the best architecture can be found only by trial and error.

The best fitting NN usually has a poor validation (generalizability).

NN is a very expensive approach and it should be used only if really needed.

# NN Architecture

Neural net suffers from overfitting problems.

Even more parameters


The number of nodes, the architecture, the number of hidden layer etc are NN **hyperparameters**

Unfortunately, at the current status of knowledge, the best architecture can be found only by trial and error.

The best fitting NN usually has a poor validation (generalizability).

NN is a very expensive approach and it should be used only if really needed.

## Epoch in Machine Learning



# Epoch

## Pro

- 1 Better performance
- 2 Progress tracking
- 3 Memory efficiency
- 4 Improved stopping criteria
- 5 More effective training

## Cons

- 1 Overfitting risk
- 2 Computational cost
- 3 One more hyperparameter



# Epoch

## Pro

- 1 Better performance
- 2 Progress tracking
- 3 Memory efficiency
- 4 Improved stopping criteria
- 5 More effective training

## Cons

- 1 Overfitting risk
- 2 Computational cost
- 3 One more hyperparameter

# NN types

There are many types of NN:

- ANN (artificial NN), just another name for NN
- DNN (deep) deep neural network
- RNN (recurrent NN) for audio
- CNN (convolutional NN) for images
- Autoencoder (for PCA) to compress to a latent space and decompress data
- Deep autoencoder (for interpretability)
- Physics informed NN (to merge NN to differential equations)
- ... and more ...

tensorflow, pytorch and keras are the most popular and popular libraries for NN.

There are many types of NN:

- ANN (artificial NN), just another name for NN
- DNN (deep) deep neural network
- RNN (recurrent NN) for audio
- CNN (convolutional NN) for images
- Autoencoder (for PCA) to compress to a latent space and decompress data
- Deep autoencoder (for interpretability)
- Physics informed NN (to merge NN to differential equations)
- ... and more ...

tensorflow, pytorch and keras are the most popular and popular libraries for NN.

# NN types

There are many types of NN:

- ANN (artificial NN), just another name for NN
- DNN (deep) deep neural network
- RNN (recurrent NN) for audio
- CNN (convolutional NN) for images
- Autoencoder (for PCA) to compress to a latent space and decompress data
- Deep autoencoder (for interpretability)
- Physics informed NN (to merge NN to differential equations)
- ... and more ...

tensorflow, pytorch and keras are the most popular and popular libraries for NN.

# NN types

There are many types of NN:

- ANN (artificial NN), just another name for NN
- DNN (deep) deep neural network
- RNN (recurrent NN) for audio
- CNN (convolutional NN) for images
- Autoencoder (for PCA) to compress to a latent space and decompress data
- Deep autoencoder (for interpretability)
- Physics informed NN (to merge NN to differential equations)
- ... and more ...

tensorflow, pytorch and keras are the most popular and popular libraries for NN

# NN types

There are many types of NN:

- ANN (artificial NN), just another name for NN
- DNN (deep) deep neural network
- RNN (recurrent NN) for audio
- CNN (convolutional NN) for images
- Autoencoder (for PCA) to compress to a latent space and decompress data
- Deep autoencoder (for interpretability)
- Physics informed NN (to merge NN to differential equations)
- ... and more ...

tensorflow, pytorch and keras are the most popular and popular libraries for NN

# NN types

There are many types of NN:

- ANN (artificial NN), just another name for NN
- DNN (deep) deep neural network
- RNN (recurrent NN) for audio
- CNN (convolutional NN) for images
- Autoencoder (for PCA) to compress to a latent space and decompress data
- Deep autoencoder (for interpretability)
- Physics informed NN (to merge NN to differential equations)
- ... and more ...

tensorflow, pytorch and keras are the most popular and popular libraries for NN.

# NN types

There are many types of NN:

- ANN (artificial NN), just another name for NN
- DNN (deep) deep neural network
- RNN (recurrent NN) for audio
- CNN (convolutional NN) for images
- Autoencoder (for PCA) to compress to a latent space and decompress data
- Deep autoencoder (for interpretability)
- Physics informed NN (to merge NN to differential equations)
- ... and more ...

tensorflow, pytorch and keras are the most popular and popular libraries for NN.



# NN types

There are many types of NN:

- ANN (artificial NN), just another name for NN
- DNN (deep) deep neural network
- RNN (recurrent NN) for audio
- CNN (convolutional NN) for images
- Autoencoder (for PCA) to compress to a latent space and decompress data
- Deep autoencoder (for interpretability)
- Physics informed NN (to merge NN to differential equations)
- ... and more ...

tensorflow, pytorch and keras are the most popular and popular libraries for NN.

# NN types

There are many types of NN:

- ANN (artificial NN), just another name for NN
- DNN (deep) deep neural network
- RNN (recurrent NN) for audio
- CNN (convolutional NN) for images
- Autoencoder (for PCA) to compress to a latent space and decompress data
- Deep autoencoder (for interpretability)
- Physics informed NN (to merge NN to differential equations)
- ... and more ...

tensorflow, pytorch and keras are the most popular and popular libraries for NN.