


Indoor Interactive 32-110inch											
<div></div>											
Specification											
Panel	Size	32"	43"	50"	55"	65"	75"	86"	98"	110"	
	Panel Grade	A+	A+	A+	A+	A+	A+	A+	A+	A+	
	Resolution	3840x2160	3840x2160	3840x2160	3840x2160	3840x2160	3840x2160	3840x2160	3840x2160	3840x2160	
	Contrast Ratio	4000:1	4000:1	4000:1	4000:1	4000:1	4000:1	4000:1	4000:1	4000:1	
	Brightness	350nit	350nit	350nit	350nit	350nit	350nit	350nit	350nit	350nit	
	Reaction Time	8ms	8ms	8ms	8ms	8ms	8ms	8ms	8ms	8ms	
	Frame Tate	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	
	Visual Angle	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	
	Interactivity	IR Touch 40 point	IR Touch 40 point	IR Touch 40 point	IR Touch 40 point	IR Touch 40 point	IR Touch 40 point	IR Touch 40 point	IR Touch 40 point	IR Touch 40 point	
	Life Time	30,000hrs(min.)	30,000hrs(min.)	30,000hrs(min.)	30,000hrs(min.)	30,000hrs(min.)	30,000hrs(min.)	30,000hrs(min.)	30,000hrs(min.)	30,000hrs(min.)	
Power	Voltage	100V~240V,50-60HZ	100V~240V,50-60HZ	100V~240V,50-60HZ	100V~240V,50-60HZ	100V~240V,50-60HZ	100V~240V,50-60HZ	100V~240V,50-60HZ	100V~240V,50-60HZ	100V~240V,50-60HZ	
	Average Power Consumption	118W	139W	145W	188W	208W	228W	258W	278W	318W	
	Maximum Power Consumption	280W	280W	280W	280W	280W	280W	280W	300W	360W	
	Standby Power Consumption	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	
Environment	Working Temperature	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C	
	IP Rating	IP30	IP30	IP30	IP30	IP30	IP30	IP30	IP30	IP30	
	Storage Temperature	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	
	Storage Humidity	10%~90%RH Non-Condensing	10%~90%RH Non-Condensing	10%~90%RH Non-Condensing	10%~90%RH Non-Condensing	10%~90%RH Non-Condensing	10%~90%RH Non-Condensing	10%~90%RH Non-Condensing	10%~90%RH Non-Condensing	10%~90%RH Non-Condensing	
Operating System	Working Humidity	20%~85%RH Non-Condensing									
	Max Working Time(hours/day)	24 hrs	24 hrs	24 hrs	24 hrs	24 hrs	24 hrs	24 hrs	24 hrs	24 hrs	
	OS Android Linux	4gb + 32gb	4gb + 32gb	4gb + 32gb	4gb + 32gb	4gb + 32gb	4gb + 32gb	4gb + 32gb	4gb + 32gb	4gb + 32gb	
Input	HDMI IN	1	1	1	1	1	1	1	1	1	
	DVI IN	1	1	1	1	1	1	1	1	1	
	VGA IN	1	1	1	1	1	1	1	1	1	
	AUDIO IN	1	1	1	1	1	1	1	1	1	
	R/45	1	1	1	1	1	1	1	1	1	
Output	OPS Slot	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
	USB 2.0	2	2	2	2	2	2	2	2	2	
	R/45	1	1	1	1	1	1	1	1	1	
	Speakers	2 x 16w	2 x 16w	2 x 16w	2 x 16w	2 x 16w	2 x 16w	2 x 16w	2 x 16w	2 x 16w	
	AUDIO OUT	1	1	1	1	1	1	1	1	1	
Structure	Display Dimension (mm)	745.4x429.6x58.8	977.7x566.4x58.8	1132.6x653.2x58.8	1250.1x721.4x58.8	1496.7x875.2x88	1722x1000.7x88	1964x1137x91	2221x1275x94.4	2268.7x1342.7x117.5	
	Net Weight (kg)	15	20	30	37	45	60	95	122	140	
	Gross Weight (kg)	20	25	35	45	60	75	120	140	165	
	Packing Dimension(W x H x D)	915 x 575 x 195mm	1165x705x195mm	1335x865x195mm	1335x865x195mm	1680x1110x300mm	1970x1290x300mm	2250x1350x300mm	2430x1530x300mm	2350x1700x300mm	
Language	Shell Material	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	
	Frame Color	Black Powder Coated	Black Powder Coated	Black Powder Coated	Black Powder Coated	Black Powder Coated	Black Powder Coated	Black Powder Coated	Black Powder Coated	Black Powder Coated	
	Vesa Mount with Wall Bracket	Included	Included	Included	Included	Included	Included	Included	Included	Included	