

Outdoor Designer Videoflex® 3500x2000mm



Specification		
Pixel Pitch	2.6mm	3.9mm
Diode	SMD1515	SMD2121
Module Size (mm)	250X62.5	250X62.5
Module Resolution (pixels)	96X24	64X16
Screen Unit Size (mm)	3500x2000	3500x2000
Screen Resolution (pixels)	1346x768	896x512
Color Depth	12~16bit	12~16bit
Pixel Density	884,736	392,704
Refreshing Rate (Hz)	≥3,840	≥3,840
Scan Rate	1/24	1/16
Brightness	2500nit	2500nit
Screen Weight (kg)	105	105
Top Structure weight(kg)	95	95
Viewing Angle (°)	140	140
Input Voltage (V)	DC24V	DC24V
Max Power Consumption	510W/sqm	510W/sqm
Ave Power Consumption	170W/sqm	170W/sqm
Working Temperature	-20°C/+50°C (working)	-20°C/+50°C (working)
	-40°C/+60°C (storage)	-40°C/+60°C (storage)
IP Level	IP66	IP66
Humidity	10%~60% (working)	10%~60% (working)
	10%~90% (storage)	10%~90% (storage)
Lifetime(hrs)	100,000	100,000
Maintemance	Rear	Rear
Spares	5%	5%