

**Indoor Rigid 27inch  
600x337.5mm**



**Specification**

Pixel Pitch	0.93mm	1.25mm	1.56mm	1.875mm
Pixel Density (sqm)	1,137,778	640,000	409,600	284,444
Module Resolution	160x180	120x135	96x108	80x90
Module Size (mm)	150x168.75	150x168.75	150x168.75	150x168.75
Panel Size (mm)	600x337.5x39	600x337.5x39	600x337.5x39	600x337.5x39
Panel Resolution	640x360	480x270	384x216	320x180
Brightness (nit)	600	600	600	600
Color Temperature	6500K	6500K	6500K	6500K
Horizontal Viewing Angle	≥160°	≥160°	≥160°	≥160°
Vertical Viewing Angle	≥140°	≥140°	≥140°	≥140°
Contrast Ratio	10000:1	10000:1	10000:1	10000:1
Bit Rate	14 bit	14 bit	14 bit	14 bit
Scan Rate	1/40	1/45	1/48	1/40
Refresh Rate	7680hz	7680hz	7680hz	7680hz
Lifetime	100,000 h	100,000 h	100,000 h	100,000 h
IP Rating	IP65/IP30	IP65/IP30	IP65/IP30	IP65/IP30
Operating Temperature	-20 °C to 50 °C	-20 °C to 50 °C	-20 °C to 50 °C	-20 °C to 50 °C
Operating Humidity	10 %- 80% RH	10 %- 80% RH	10 %- 80% RH	10 %- 80% RH
Storage Temperature	-20 °C to 60 °C	-20 °C to 60 °C	-20 °C to 60 °C	-20 °C to 60 °C
Operating Voltage	110-240V	110-240V	110-240V	110-240V
Maximum Power				
Consumption (W/sqm)	420 W/sqm	420 W/sqm	420 W/sqm	420 W/sqm
Average Power				
Consumption (W/sqm)	100 W/sqm	100 W/sqm	100 W/sqm	100 W/sqm
Weight (kg)	4.5kg	4.5kg	4.5kg	4.5kg

