

Outdoor Rigid Sign  
4480x640mm



Specification

Pixel Pitch (mm)	2.5mm	4mm
Diode	SMD1921	SMD1921
Pixel Density (sqm)	160,000	62,500
Module Resolution	128x64	80x40
Module Size (mm)	320x160	320x160
Panel Size (mm)	4480x640	4480x640
Panel Resolution	1792x256	1792x256
Brightness (nit)	3500	3500
Horizontal Viewing Angle	≥140°	≥140°
Vertical Viewing Angle	≥120°	≥120°
Color Temperature	6500K	6500K
Contrast Ratio	4000:1	4000:1
Bit Rate	14bit	14bit
Scan Rate	1/16	1/16
Refresh Rate	3840 Hz	3840 Hz
Lifetime	100,000 h	100,000 h
IP Rating	IP65	IP65
Operating Temperature	-20 °C to 60 °C	-20 °C to 60 °C
Operating Humidity	10 %- 90% RH	10 %- 90% RH
Storage Temperature	-20 °C to 60 °C	-20 °C to 60 °C
Operating Voltage	110-240V	110-240V
Maximum Power Consumption (W/sqm)	700 W/sqm	700 W/sqm
Average Power Consumption (W/sqm)	250 W/sqm	250 W/sqm
Weight (kg)	118kg	118kg

