

**Indoor Rigid 27inch  
600x337.5mm**



**Specification**

Pixel Pitch	0.9375mm	1.25mm	1.5625mm	1.875mm	2.34mm
Diode	Mini 4in1	SMD1010	SMD1212	SMD1515	SMD1515
Pixel Density (sqm)	1137777	640000	409600	284444	182044
Module Resolution	320X180	240X135	192X108	160X90	128X72
Module Size (mm)	300X168.75	300X168.75	300X168.75	300X168.75	320X168.75
Panel Size (mm)	600x337.5	600x337.5	600x337.5	600x337.5	600x337.5
Panel Resolution	640x360	480x270	384x216	320x180	256x144
Brightness (nit)	600	600	600	600	600
Color Temperature	2000K—12500K	2000K—12500K	2000K—12500K	2000K—12500K	2000K—12500K
Horizontal Viewing Angle	≥160°	≥160°	≥160°	≥160°	≥160°
Vertical Viewing Angle	≥140°	≥140°	≥140°	≥140°	≥140°
Contrast Ratio	5000:1	5000:1	5000:1	5000:1	5000:1
Bit Rate	14 bit	14 bit	14 bit	14 bit	14 bit
Scan Rate	1/64	1/60	1/54	1/32	1/36
Refresh Rate	3840 Hz	3840 Hz	3840 Hz	3840 Hz	3840 Hz
Lifetime	100,000 h	100,000 h	100,000 h	100,000 h	100,000 h
IP Rating	IP30	IP30	IP30	IP30	IP30
Operating Temperature	-20 °C to 50 °C	-20 °C to 50 °C	-20 °C to 50 °C	-20 °C to 50 °C	-20 °C to 50 °C
Operating Humidity	10 %- 80% RH	10 %- 80% RH	10 %- 80% RH	10 %- 80% RH	10 %- 80% RH
Storage Temperature	-20 °C to 60 °C	-20 °C to 60 °C	-20 °C to 60 °C	-20 °C to 60 °C	-20 °C to 60 °C
Operating Voltage	110-240V	110-240V	110-240V	110-240V	110-240V
Maximum Power					
Consumption (W/sqm)	600 W/sqm	600 W/sqm	600 W/sqm	600 W/sqm	600 W/sqm
Average Power					
Consumption (W/sqm)	260 W/sqm	260 W/sqm	260 W/sqm	260 W/sqm	260 W/sqm
Weight (kg)	3.2kg	3.2kg	3.2kg	3.2kg	3.2kg

