

Outdoor Rigid  
32inch - 98inch 4K



Panel size	32inch	43inch	49inch	55inch	65inch	75inch	86inch	98inch
Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
Orientation	Portrait or Landscape	Portrait or Landscape	Portrait or Landscape	Portrait or Landscape	Portrait or Landscape	Portrait or Landscape	Portrait or Landscape	Portrait or Landscape
Panel Grade	A+	A+	A+	A+	A+	A+	A+	A+
Brightness (nit)	2000nit/3000nit	2000nit/3000nit	2000nit/3000nit	2000nit/3000nit	2000nit/3000nit	2000nit/3000nit	2000nit/3000nit	2000nit/3000nit
Contrast Ratio	5000:1	5000:1	5000:1	5000:1	5000:1	5000:1	5000:1	5000:1
Viewing Angle	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)
Lifetime (hrs)	50,000	50,000	50,000	50,000	50,000	50,000	50,000	50,000
Running time	24/7	24/7	24/7	24/7	24/7	24/7	24/7	24/7
Response time	8ms	8ms	8ms	8ms	8ms	8ms	8ms	8ms
Processor	Android 14 8+128GB	Android 14 8+128GB	Android 14 8+128GB	Android 14 8+128GB	Android 14 8+128GB	Android 14 8+128GB	Android 14 8+128GB	Android 14 8+128GB
Display	4+4mm laminated glass, IK 10 grade, Anti-reflective glass	4+4mm laminated glass, IK 10 grade, Anti-reflective glass	4+4mm laminated glass, IK 10 grade, Anti-reflective glass	4+4mm laminated glass, IK 10 grade, Anti-reflective glass	4+4mm laminated glass, IK 10 grade, Anti-reflective glass	4+4mm laminated glass, IK 10 grade, Anti-reflective glass	4+4mm laminated glass, IK 10 grade, Anti-reflective glass	4+4mm laminated glass, IK 10 grade, Anti-reflective glass
Features	Lightning arrester, air switch, timer Cooling module: Fan + Temperature control board	Lightning arrester, air switch, timer Cooling module: Fan + Temperature control board	Lightning arrester, air switch, timer Cooling module: Fan + Temperature control board	Lightning arrester, air switch, timer Cooling module: Fan + Temperature control board	Lightning arrester, air switch, timer Cooling module: Fan + Temperature control board	Lightning arrester, air switch, timer Cooling module: Fan + Temperature control board	Lightning arrester, air switch, timer Cooling module: Fan + Temperature control board	Lightning arrester, air switch, timer Cooling module: Fan + Temperature control board
IP Rating	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66
Power Supply	Switch mode 110 - 240V UL certificated	Switch mode 110 - 240V UL certificated	Switch mode 110 - 240V UL certificated	Switch mode 110 - 240V UL certificated	Switch mode 110 - 240V UL certificated	Switch mode 110 - 240V UL certificated	Switch mode 110 - 240V UL certificated	Switch mode 110 - 240V UL certificated
Voltage	Rated AC 100-240V Max 90-264V 50/60Hz 280W	Rated AC 100-240V Max 90-264V 50/60Hz 280W	Rated AC 100-240V Max 90-264V 50/60Hz 280W	Rated AC 100-240V Max 90-264V 50/60Hz 280W	Rated AC 100-240V Max 90-264V 50/60Hz 450W	Rated AC 100-240V Max 90-264V 50/60Hz 500W	Rated AC 100-240V Max 90-264V 50/60Hz 550W	Rated AC 100-240V Max 90-264V 50/60Hz 600W
Maximum power consumption (W)	0.5W	0.5W	0.5W	0.5W	0.5W	0.5W	0.5W	0.5W
Standby power consumption (W)	0.5W	0.5W	0.5W	0.5W	0.5W	0.5W	0.5W	0.5W
Working temperature	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C
Storage temperature	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C
Working humidity	10%~90%	10%~90%	10%~90%	10%~90%	10%~90%	10%~90%	10%~90%	10%~90%
Input	RJ45 , HDMI 2.0, USB 2.0, USB 3.0, USB Touch	RJ45 , HDMI 2.0, USB 2.0, USB 3.0, USB Touch	RJ45 , HDMI 2.0, USB 2.0, USB 3.0, USB Touch	RJ45 , HDMI 2.0, USB 2.0, USB 3.0, USB Touch	RJ45 , HDMI 2.0, USB 2.0, USB 3.0, USB Touch	RJ45 , HDMI 2.0, USB 2.0, USB 3.0, USB Touch	RJ45 , HDMI 2.0, USB 2.0, USB 3.0, USB Touch	RJ45 , HDMI 2.0, USB 2.0, USB 3.0, USB Touch
Output	RJ45 , HDMI 2.0, Audio	RJ45 , HDMI 2.0, Audio	RJ45 , HDMI 2.0, Audio	RJ45 , HDMI 2.0, Audio	RJ45 , HDMI 2.0, Audio	RJ45 , HDMI 2.0, Audio	RJ45 , HDMI 2.0, Audio	RJ45 , HDMI 2.0, Audio
OPS (Optional)	Processor Intel i5 16+256GB Gen 11 - supports Windows or Linux	Processor Intel i5 16+256GB Gen 11 - supports Windows or Linux	Processor Intel i5 16+256GB Gen 11 - supports Windows or Linux	Processor Intel i5 16+256GB Gen 11 - supports Windows or Linux	Processor Intel i5 16+256GB Gen 11 - supports Windows or Linux	Processor Intel i5 16+256GB Gen 11 - supports Windows or Linux	Processor Intel i5 16+256GB Gen 11 - supports Windows or Linux	Processor Intel i5 16+256GB Gen 11 - supports Windows or Linux
Case	Powder Coated White or Black/ Polished Chrome mirror finish / Matt finish optional / Chrome	Powder Coated White or Black/ Polished Chrome mirror finish / Matt finish optional / Chrome	Powder Coated White or Black/ Polished Chrome mirror finish / Matt finish optional / Chrome	Powder Coated White or Black/ Polished Chrome mirror finish / Matt finish optional / Chrome	Powder Coated White or Black/ Polished Chrome mirror finish / Matt finish optional / Chrome	Powder Coated White or Black/ Polished Chrome mirror finish / Matt finish optional / Chrome	Powder Coated White or Black/ Polished Chrome mirror finish / Matt finish optional / Chrome	Powder Coated White or Black/ Polished Chrome mirror finish / Matt finish optional / Chrome
Vesa Mount	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Wall Mount	Included	Included	Included	Included	Included	Included	Included	Included
Remote Control	Included	Included	Included	Included	Included	Included	Included	Included
Wifi Antenna	Included	Included	Included	Included	Included	Included	Included	Included
IEC Cable	Included	Included	Included	Included	Included	Included	Included	Included
Gross Weight (kg)	40kg	50kg	60kg	70kg	80kg	95kg	110kg	200kg
Stand (Optional)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes