

Indoor Designer Videoflex 750x1200mm



Specification

Model	IDVFX	IDVFX
Pixel Pitch	1.25mm	1.56mm
Diode	SMD1010	SMD1010
Module Size (mm)	250X62.5	250X62.5
Module Resolution (pixels)	200X50	160X40
Screen Unit Size (mm)	750x1200	750x1200
Screen Resolution (pixels)	600x960	480x768
Color Depth	12~16bit	12~16bit
Pixel Density	576,000	368,640
Refreshing Rate (Hz)	≥3,840	≥3,840
Scan Rate	1/50	1/4
Brightness	>600cd/m ²	>600cd/m ²
Viewing Distance (meter)	≥1.2	≥1.5
Screen Weight (kg/m ²)	15	15
Viewing Angle (°)	140	140
Input Voltage (V)	DC24V	DC24V
Max Power Consumption	510W/sqm	510W/sqm
Ave Power Consumption	170W/sqm	170W/sqm
Working Temperature	-20°C/+50°C (working) -40°C/+60°C (storage)	-20°C/+50°C (working) -40°C/+60°C (storage)
IP Level	IP63/IP21	IP63/IP21
Humidity	10%~60% (working) 10%~90% (storage)	10%~60% (working) 10%~90% (storage)
Lifetime(hrs)	100,000	100,000
Maintenance	front & rear	front & rear