

# Mobile Biometrics - Face Recognition

Adam Bronstein, Chris Brooks, Enrique Marquez

University of Southampton

*arb2g11@soton.ac.uk, cjb1g14@soton.ac.uk, esm1g14@ecs.soton.ac.uk*

Tuesday 12<sup>th</sup> May, 2015

# Contents


- 1 Face Recognition Overview
  - Issues
  - Algorithm
- 2 Face Extraction
  - Viola-Jones
- 3 Feature Extraction
  - Dense vs Interest Points
- 4 Feature Description
  - SIFT vs ORB

- 5 Vector Representation
  - Bag of Visual Words (BoVW)
  - Fisher Vectors
- 6 Mobile Face Recognition
  - Mobile Specific Issues
  - Algorithms
  - Algorithm Comparison
- 7 Demo
  - Add Person
  - Recognise Person

# Issues

- Checking the image contains a face
  - Lighting, scale and rotation invariant
- Using the correct internal representation
  - Need to be able to compare them
  - Small changes should have little effect
- Matching the faces correctly
  - Need to be able to compare them

# Face Recognition Algorithm



# Viola-Jones

- Used to separate the face from the background
- Uses a trained Haar feature cascade classifier
- Detects all the faces in the picture
- Fast and lighting invariant
- Not rotational invariant




Figure: Face Detection with Viola-Jones

# Dense vs Interest Points

- Samples a grid around every pixel as a feature
- More points so it's robust, however this also makes it slow




Figure: Dense Features

- Samples on interest point calculated by Harris corner detector or SIFT detector
- Fast, but might take into account too many irrelevant points




Figure: Interest Points

# SIFT vs ORB


- SIFT has 128 Dimensions while ORB is only 32
- Similar accuracy



Figure: SIFT Features



Figure: ORB Features



# Bag of Visual Words (BoVW)

Training	Matching	Test
set	norm	image

- Dense Sampling
- K-means
- Database Representation
- Test Image Histogram Representation
- Matching (KNN)






Figure: Bag of Visual Words Histogram Matching

# Fisher Vectors

- Takes BoVW one step further



$$\Phi_k^{(1)} = \frac{1}{N\sqrt{w_k}} \sum_p^N \alpha_p(k) \left( \frac{x_p - \mu_k}{\sigma_k} \right)$$
$$\Phi_k^{(2)} = \frac{1}{N\sqrt{2w_k}} \sum_p^N \alpha_p(k) \left( \frac{(x_p - \mu_k)^2}{\sigma_k^2} - 1 \right)$$





Figure: Fisher Vector Process


# Mobile Specific Issues

- Camera resolution
  - Two cameras, one worse than the other
- Phone orientation
  - The phone can be held in many different orientations
  - It can also take the picture at different angles
- Limited computing power
  - The memory is limited
  - Processor can be slow
- Sift patented
  - Made it difficult to implement on opencv for Android


# Face Recognition Algorithm




# First Face Recognition Algorithm



# Second Face Recognition Algorithm



# Third Face Recognition Algorithm



# Algorithm Comparison

Training dataset size	Fisher Vectors	BoVW
20%	91.25%	69.7%
50%	98.50%	77%
80%	100%	86.25%

Table: Compares accuracy of methods as training set size increases using AT&T Faces Dataset

# Add Person




Figure: Main Screen




Figure: Take Picture




Figure: Add Person

# Recognise Person




Figure: Main Screen




Figure: Take Picture




Figure: Recognise Person

# Any questions?

# References

-  F. Perronnin and C. Dance. Fisher kernels on visual vocabularies for image categorizaton. In Proc. CVPR, 2006.
-  Simonyan, K. and Parkhi, O. M. and Vedaldi, A. and Zisserman, A. Fisher Vector Faces in the Wild. British Machine Vision Conference, 2013.
-  E. Rublee, V. Rabaud, K. Konolige, and G. Bradski. ORB: an efficient alternative to SIFT or SURF. In Proc. of the IEEE Intl. Conf. on Computer Vision (ICCV), volume 13, 2011.
-  A. Vedaldi and B. Fulkerson VLFeat: An Open and Portable Library of Computer Vision Algorithms, 2008. Available at: <<http://www.vlfeat.org/>>[Accessed 26th April 2015]
-  G. Bradski The OpenCV Library. Dr. Dobbs Journal of Software Tools, 2000. <<http://www.opencv.org/>>[Accessed 26th April 2015]