ÖDEV-Ensar Öztürk

```c
#include <stdio.h>
#include <stdlib.h>
#include <time.h>

struct node {
    int data;
    struct node* next;
};

int size = 0;

struct node* newNode(int data) {
    struct node* yeni = (struct node*)malloc(sizeof(struct node));
    yeni->data = data;
    yeni->next = NULL;
    return yeni;
}

void basaEkle(struct node** head, int item) {
    struct node* yeni = newNode(item);
    yeni->next = *head;
    *head = yeni;
}

void sonaEkle(struct node** head, int item) {
    struct node* yeni = newNode(item);
    if (*head == NULL) {
        *head = yeni;
        return;
    }
    struct node* temp = *head;
    while (temp->next != NULL) {
        temp = temp->next;
    }
    temp->next = yeni;
}

void arayaEkle(struct node** head, int item) {
    if (*head == NULL || rand() % 2 == 0) {
        basaEkle(head, item);
        return;
    }

    int pos = rand() % size;
    struct node* yeni = newNode(item);
    struct node* temp = *head;
    for (int i = 0; i < pos - 1; i++) {
        temp = temp->next;
    }
    yeni->next = temp->next;
    temp->next = yeni;
}

void rastgeleEkle(struct node** head, int item) {
    int secim = rand() % 3;
```

```c
    if (secim == 0) {
        basaEkle(head, item);
        printf("%d -> Basa eklendi.\n", item);
    }
    else if (secim == 1) {
        arayaEkle(head, item);
        printf("%d -> Araya eklendi.\n", item);
    }
    else {
        sonaEkle(head, item);
        printf("%d -> Sona eklendi.\n", item);
    }

    size++;
    if (size % 5 == 0) {
        printf("5'in kati eleman mevcut! (Toplam: %d)\n", size);
    }
}

void printList(struct node* head) {
    struct node* temp = head;
    while (temp != NULL) {
        printf("%d -> ", temp->data);
        temp = temp->next;
    }
    printf("NULL\n");
}

int main() {
    srand(time(0));
    struct node* head = NULL;

    for (int i = 1; i <= 15; i++) {
        rastgeleEkle(&head, i);
        printList(head);
    }

    return 0;
}
```