



SQL Profiler

Version 8.0

0	SQL Profiler	3
1	Installing the SQL Profiler Plugin	3
2	SQL Profiling and Analysis	13
3	Uninstalling SQL Profiler	24

0 SQL Profiler

Postgres Enterprise Manager (PEM) is designed to assist database administrators, system architects, and performance analysts when administering, monitoring, and tuning PostgreSQL and Advanced Server database servers. PEM has been designed to manage and monitor a single server or multiple servers from a single console, allowing complete control over monitored databases.

The SQL Profiler Plugin works with PEM to allow you to profile a server's workload. The SQL Profiler plugin may be installed on servers with or without a PEM Agent, however traces can only be run in ad-hoc mode on unmanaged servers, and may only be scheduled on managed servers.

This document provides step-by-step instructions to guide you through the installation and use of SQL Profiler.

SQL Profiler is officially supported only on the EDB distributions of PostgreSQL and Advanced Server supported versions . The plugin is distributed via StackBuilder, or as operating system dependent packages in EDB's yum repositories. The plugin is also distributed and installed with the Advanced Server installations.

Throughout this guide, the term **Postgres** refers to either a PostgreSQL or an Advanced Server installation, where either is appropriate.

1 Installing the SQL Profiler Plugin

You must install the plugin on each server on which you wish to use SQL Profiler. For example, if you have a host running PostgreSQL 9.6 and PostgreSQL 10, you must install two versions of the plugin, one for each server.

Follow the installation steps listed below to install the plugin for PostgreSQL before continuing to the **Configuration** section. If you are using Advanced Server, you can skip installation and move ahead to the **Configuration** section.


You can use the graphical installer to install any version of SQL Profiler on the Windows platform. On Linux, use an RPM package to install the SQL Profiler. For detailed information about configuring the EDB repository for your host platform, see the [PEM Linux Installation Guide](#).

Installing SQL Profiler on Windows


To invoke the SQL Profiler graphical installer, assume **Administrator** privileges, navigate into the directory that contains the installer, and double-click the installer icon. The SQL Profiler installer welcomes you to the Setup Wizard.




Click **Next** to continue to the **License Agreement**.




Carefully review the license agreement before highlighting the appropriate radio button and accepting the agreement; click **Next** to continue to the **Installation Directory** dialog.




Specify an alternate location for the installation directory, or accept the default location and click **Next** to continue.



The wizard is now ready to install the SQL Profiler plugin. Click **Next** to continue.



The SQL Profiler plugin installer displays progress bars as it copies files to your system.



When the installation is complete, the SQL Profiler plugin is ready to be configured.

Using an RPM Package to Install SQL Profiler

!!! Note You may be required to add the `sslutils` package to your PostgreSQL database servers before installing SQL Profiler.

If you have already configured the EDB repository on your system, you can use `yum` or `dnf` to install SQL Profiler:

```
yum install postgresql<X>-sqlprofiler
```

or

```
dnf install postgresql<X>-sqlprofiler
```

Where, **<X>** is the version of your Postgres installation.

For detailed information about configuring the EDB repository, please see the [PEM Linux Installation Guide](#).

Installing SQL Profiler on Debian/Ubuntu

!!! Note You may be required to add the **sslutils** package to your PostgreSQL database servers before installing SQL Profiler.

You can use an **apt** command to install SQL Profiler using DEB on Debian 9.x or Ubuntu 18; assume root privileges and enter:

```
apt install postgresql-<X>-sqlprofiler
```

Where, **<X>** is the version of your Postgres installation.

When the installation is complete, the SQL Profiler plugin is ready to be configured.

Configuring SQL Profiler

The SQL Profiler plugin is not automatically enabled when the installation process completes. This allows you to restart the server at a convenient time, and prevents the plugin from being loaded unnecessarily on systems where it is not required on a continual basis.

Use the following steps to enable the plugin:

1. Edit the `postgresql.conf` file on the server you wish to profile, modifying the `shared_preload_libraries` parameter as shown below:

```
shared_preload_libraries = '$libdir/sql-profiler'
```

2. Restart the Postgres server.
3. Using the `Query Tool` or the `psql` command line interface, run the `sql-profiler.sql` script in the database specified as the `Maintenance Database` on the server you wish to profile. If you are using:
 - PostgreSQL, the default maintenance database is `postgres`.
 - Advanced Server, the default maintenance database is `edb`.

To use the PEM Query Tool to run the script, highlight the name of the maintenance database in the `Browser` tree control, and navigate through the `Tools` menu to select `Query tool`. When the Query Tool opens, use the `Open` option on the `Files` menu to open a web browser and navigate to the `sql-profiler.sql` script. By default, the `sql-profiler.sql` script is located in the `contrib` folder, under your Postgres installation.

When the script opens in the `SQL Editor` panel of the Query Tool, highlight the content of the script in the SQL Editor and select the `Execute` option from the `Query` menu (or click the `Execute` icon) to invoke the script and configure SQL Profiler.


You can also use the `psql` command line to invoke the configuration script. The following command uses `psql` to invoke the `sql-profiler.sql` script on an Advanced Server database on a Linux system:

```
$ /usr/edb/as<x>/bin/psql -U postgres postgres <
```

```
/usr/edb/as<x>/share/contrib/sql-profiler.sql
```

where <x> is the version of the Advanced Server.

After configuring SQL Profiler, it is ready to use with all databases that reside on the server.



To access SQL Profiler functionality, highlight the name of the database in the PEM **Browser** tree control; navigate through **Server** option under **Tools** menu to the **SQL Profiler** pull-aside menu. Menu options allow you to manage your SQL traces:

- Select **Create trace...** to define a new trace.
- Select **Open trace...** to open an existing trace.
- Select **Delete trace(s)...** to delete one or more traces.
- Select **View scheduled trace(s)...** to review a list of scheduled traces.

2 SQL Profiling and Analysis

Most RDBMS experts agree that inefficient SQL code is the leading cause of most database performance problems. The challenge for DBAs and developers is to locate the poorly-running SQL code in large and complex systems, and then optimize that code for better performance.

The SQL Profiler component allows a database superuser to locate and optimize poorly-running SQL code. Users of Microsoft SQL Server's Profiler will find PEM's SQL Profiler very similar in operation and capabilities. SQL Profiler is installed with each Advanced Server instance; if you are using PostgreSQL, you must download the SQL Profiler installer, and install the SQL Profiler product into each managed database instance you wish to profile.

For each database monitored by SQL Profiler, you must:

1. Edit the `postgresql.conf` file; you must include the SQL Profiler library in the `shared_preload_libraries` configuration parameter.

For Linux installations, the parameter value should include:

```
$libdir/sql-profiler
```

on Windows, the parameter value should include:

```
$libdir/sql-profiler.dll
```

2. Create the functions used by SQL Profiler in your database. The SQL Profiler installation program places a SQL script (named `sql-profiler.sql`) in the `share/postgresql/contrib` subdirectory of the main PostgreSQL installation directory on Linux systems. On Windows systems, this script is located in the `share` subdirectory. You must invoke this script on the maintenance database specified when registering the server with PEM.
3. Stop and re-start the server for the changes to take effect.

Please note: if you have connected to the PEM server with the PEM client

before configuring SQL Profiler, you must disconnect and reconnect with the server to enable SQL Profiler functionality. For more detailed information about installing and configuring the SQL Profiler plugin, please refer to the [PEM Installation Guides](#).

Creating a New SQL Trace

SQL Profiler captures and displays a specific SQL workload for analysis in a SQL trace. You can start and review captured SQL traces immediately, or save captured traces for review at a later time. You can use SQL Profiler to create and store up to 15 named traces; use menu options to create and manage traces.

Creating a Trace

You can use the **Create trace...** dialog to define a SQL Trace for any database on which SQL Profiler has been installed and configured. installed and configured. To access the dialog, highlight the name of the database in the PEM client tree control; navigate through the Management menu to the SQL Profiler pull-aside menu, and select Create trace....

Create trace...

Trace options | Schedule | Periodic job options

Name: test_trace

User filter: x enterisedb

Database filter: x postgres

Maximum trace file size(MB): 0
Note: 0(Zero) indicates maximum trace file size to be 250 MB

Run now? ☒ Yes

? Cancel Create

Use the fields on the **Trace options** tab to specify details about the new trace:

- Provide a name for the trace in the Name field.
- Click in the **User filter** field to specify the roles whose queries will be included the trace; optionally, check the box next to Select All to include queries from all roles.
- Click in the **Database filter** field to specify which databases to trace; optionally, check the box next to Select All to include queries against all databases.
- Specify a **trace size in the Maximum Trace File Size** field; SQL Profiler will terminate the trace when it reaches approximately the size specified.
- Specify Yes in the **Run Now** field to start the trace when you select the Create button; select No to enable fields on the Schedule tab.

The screenshot shows the 'Create trace...' dialog box with the 'Trace options' tab active. The 'Start time' and 'End time' fields are empty. The 'Repeat?' field is set to 'No'. A note below states: 'This option will allow you to schedule periodic trace job.' At the bottom right are 'Cancel' and 'Create' buttons.

Use the fields on the **Schedule** tab to specify scheduling details for the new trace:

- Use the **Start time** field to specify the starting time for the trace.
- Use the **End time** field to specify the ending time for the trace.
- Specify Yes in the **Repeat?** field to indicate that the trace should be repeated every day at the times specified; select No to enable fields on the Periodic job options tab.

Create trace...

Trace options | Schedule | **Periodic job options**

Days

Week days

Month days

Months

Times

Hours

Minutes

Schedules are specified using a **cron-style** format.

- For each selected time or date element, the schedule will execute.
e.g. To execute at 5 minutes past every hour, simply select '05' in the Minutes list box.
- Values from more than one field may be specified in order to further control the schedule.
e.g. To execute at 12:05 and 14:05 every Monday and Thursday, you would click minute 05, hours 12 and 14, and weekdays Monday and Thursday.
- For additional flexibility, the Month days check list includes an extra Last day option. This matches the last day of the month, whether it happens to be the 28th, 29th, 30th or 31st.

? Cancel Create

Fields on the **Periodic job options** tab specify scheduling details about a recurring trace. Use fields in the Days section to specify the days on which the job will execute:

- Click in the **Week days** field to select the days of the week on which the trace will execute.
- Click in the **Month days** field to select the days of the month on which the trace will execute.
- Click in the **Months** field to select the months in which the trace will execute.

Use fields in the **Times** section to specify a time schedule for the trace execution:

- Click in the **Hours** field to select the hours at which the trace will execute.
- Click in the **Minutes** field to select the hours at which the trace will execute.

When you've completed the **Create trace...** dialog, click **Create** to start the newly defined trace or to schedule the trace for a later time.

SQL Profiler (Trace: test_trace)										
#	Start Time	Duration (ms)	Query	Rows Affected	User	Database	PID	File System Read	File System Write	Page Fault
1	2020-04-24 01:54:57.556323-07	1.273133	SELECT heartbeat_inte...	1	agent1	pem	91666	48	0	6
2	2020-04-24 01:54:57.627954-07	12.234771	/*pga4dash*/ SELECT ...	5	enterprisedb	postgres	33485	0	0	0
3	2020-04-24 01:54:57.647487-07	0.00245	SELECT 1	1	enterprisedb	pem	30543	0	0	0
4	2020-04-24 01:54:57.659666-07	0.004035	SELECT pg_has_role(p...	1	enterprisedb	pem	30543	0	0	0
5	2020-04-24 01:54:57.660344-07	0.00083	SELECT 1	1	enterprisedb	pem	30543	0	0	0
6	2020-04-24 01:54:57.69393-07	0.917116	SET DateStyle=ISO; SE...	1	enterprisedb	postgres	33900	0	0	0
7	2020-04-24 01:54:57.696903-07	0.016561	SELECT db_oid as did, ...	1	enterprisedb	postgres	33900	0	0	0
8	2020-04-24 01:54:57.69824-07	0.027168	SELECT oid as id, rolna...	1	enterprisedb	postgres	33900	0	0	0
9	2020-04-24 01:54:58.633668-07	12.019085	/*pga4dash*/ SELECT ...	5	enterprisedb	postgres	33485	0	0	0
10	2020-04-24 01:54:58.814973-07	0.001999	SELECT 1	1	enterprisedb	pem	30543	0	0	0
11	2020-04-24 01:54:58.826576-07	0.050517	SELECT pg_has_role(p...	23	enterprisedb	pem	30543	0	0	0
12	2020-04-24 01:54:59.622713-07	11.296904	/*pga4dash*/ SELECT ...	5	enterprisedb	postgres	33485	0	0	0
13	2020-04-24 01:55:00.137269-07	0.001639	SELECT 1	1	enterprisedb	postgres	32578	0	0	0
14	2020-04-24 01:55:01.250787-07	11.271025	/*pga4dash*/ SELECT ...	5	enterprisedb	postgres	33485	0	0	0
15	2020-04-24 01:55:02.114481-07	0.627253	WITH agent_info AS (...)	1	agent1	pem	91666	680	0	52
16	2020-04-24 01:55:02.236089-07	12.07968	/*pga4dash*/ SELECT ...	5	enterprisedb	postgres	33485	0	0	0
17	2020-04-24 01:55:02.628516-07	13.478983	SELECT * FROM (SEL...	3	agent1	pem	91666	1568	0	49
18	2020-04-24 01:55:03.232281-07	0.049985	SELECT * FROM pem.j...	1	agent1	pem	91666	0	0	0
19	2020-04-24 01:55:03.235696-07	0.011202	SELECT nextval('pem.j...	1	agent1	pem	91666	0	0	0
20	2020-04-24 01:55:03.239847-07	18.327522	/*pga4dash*/ SELECT ...	5	enterprisedb	postgres	33485	0	0	0
21	2020-04-24 01:55:03.243198-07	0.128994	INSERT INTO pem.jobs...	1	agent1	pem	91666	32	0	1
22	2020-04-24 01:55:03.263871-07	0.03972	SELECT log_directory, l...	1	agent1	pem	91666	0	0	0

SQL Query Metrics

SET DateStyle=ISO; SET client_min_messages=notice; SELECT set_config('bytea_output','escape',false);

Graphical Plan

Text-Based Plan


Graphical Analysis Statistics

Function Scan

If you elect to execute the trace immediately, the trace results will display in the PEM client.

Opening an Existing Trace

To view a previous trace, highlight the name of the profiled database in the PEM client tree control; navigate through the **Management** menu to the SQL Profiler pull-aside menu, and select **Open trace....** You can also use the **SQL Profiler toolbar** menu to open a trace; select the **Open trace...** option. The Open trace... dialog opens.



Highlight an entry in the trace list and click Open to open the selected trace. The selected trace opens in the SQL Profiler tab.

Filtering a Trace

A filter is a named set of (one or more) rules, each of which can hide events from the trace view. When you apply a filter to a trace, the hidden events are not removed from the trace, but are merely excluded from the display.

Click the Filter icon to open the **Trace Filter** dialog and create a rule (or set of rules) that define a filter. Each rule will screen the events within the current trace based on the identity of the role that invoked the event, or the query type invoked during the event.

To open an existing filter, select the **Open** button; to define a new filter, click the **Add (+)** icon to add a row to the table displayed on the General tab and provide rule details:

- Use the **Type** drop-down listbox to specify the trace field that the filter rule will apply to.
- Use the **Condition** drop-down listbox to specify the type of operator that SQL Profiler will apply to the Value when it filters the trace:


- Select **Matches to** to filter events that contain the specified Value.
 - Select **Does not match** to filter events that do not contain the specified Value.
 - Select **Is equal to** to filter events that contain an exact match to the string specified in the Value field.
 - Select **Is not equal** to to filter events that do not contain an exact match to the string specified in the Value field.
 - Select **Starts with** to filter events that begin with the string specified in the Value field.
 - Select **Does not start with** to filter events that do not begin with the string specified in the Value field.
 - Select **Less than** to filter events that have a numeric value less than the number specified in the Value field.
 - Select **Greater than** to filter events that have a numeric value greater than the number specified in the Value field.
 - Select **Less than or equal to** to filter events that have a numeric value less than or equal to the number specified in the Value field.
 - Select **Greater than or equal to** to filter events that have a numeric value greater than or equal to the number specified in the Value field.
- Use the **Value** field to specify the string, number or regular expression that SQL Profiler will search for.

When you've finished defining a rule, click the Add (+) icon to add another rule to the filter. To delete a rule from a filter, highlight the rule and click the Delete icon.

Click the **Save** button to save the filter definition to a file without applying the filter; to apply the filter, click **OK**. Select **Cancel** to exit the dialog and discard any changes to the filter.

Deleting a Trace


To delete a trace, highlight the name of the profiled database in the PEM client tree control; navigate through the **Management** menu to the SQL Profiler pull-aside menu, and select **Delete trace(s)...**. You can also use the SQL Profiler toolbar menu to delete a trace; select the **Delete trace(s)...** option. The **Delete traces** dialog opens.



Click the icon to the left of a trace name to mark one or more traces for deletion and click **Delete**. The PEM client will acknowledge that the selected traces have been deleted.

Viewing Scheduled Traces

To view a list of scheduled traces, highlight the name of the profiled database in the PEM client tree control; navigate through the **Management** menu to the SQL Profiler pull-aside menu, and select **Scheduled traces...**. You can also use the SQL Profiler toolbar menu to the list; select the **Scheduled traces...** option.



The **Scheduled traces...** dialog displays a list of the traces that are awaiting execution. Click the edit button to the left of a trace name to access detailed information about the trace:

- The **Status** field lists the status of the current trace.
- The **Enabled?** switch displays Yes if the trace is enabled; No if it is disabled.
- The **Name** field displays the name of the trace.
- The **Agent** field displays the name of the agent responsible for executing the trace.
- The **Last run** field displays the date and time of the last execution of the trace.
- The **Next run** field displays the date and time of the next scheduled trace.
- The **Created** field displays the date and time that the trace was defined.

Using the Index Advisor

Index Advisor is distributed with Advanced Server 9.0 and above. Index Advisor works with SQL Profiler by examining collected SQL statements

and making indexing recommendations for any underlying tables to improve SQL response time. The Index Advisor works on all DML (INSERT, UPDATE, DELETE) and SELECT statements that are invoked by a superuser.

Diagnostic output from the Index Advisor includes:

- Forecasted performance benefits from any recommended indexes
- The predicted size of any recommended indexes
- DDL statements you can use to create the recommended indexes

Before using Index Advisor, you must:

1. Modify the `postgresql.conf` file on each Advanced Server host, adding the `index_advisor` library to the `shared_preload_libraries` parameter.
2. Install the `Index Advisor contrib` module. To install the module, use the `psql` client or PEM Query Tool to connect to the database, and invoke the following command:

```
\i  
<complete_path>/share/contrib/index_advisor.sql
```

3. Restart the server for your changes to take effect.

Index Advisor can make indexing recommendations based on trace data captured by SQL Profiler. Simply highlight one or more queries in the `SQL Profiler Trace Data` pane, and click the `Index Advisor` toolbar button (or select Index Advisor from the View menu). For detailed usage information about Index Advisor, please see the EDB Postgres Advanced Server Guide.

Please note: Index Advisor cannot analyze statements invoked by a non-superuser. If you attempt to analyze statements invoked by a non-superuser, the server log will include the following error:

```
ERROR: access to library "index_advisor" is not
```

allowed

!!! Note It is recommended that you disable the index advisor while using the pg_dump functionality.

For more information about configuring and using Index Advisor, please see the EDB Postgres Advanced Server Guide, available from EDB at:

<https://www.enterprisedb.com/docs>

3 Uninstalling SQL Profiler

The process of uninstalling SQL Profiler is platform-specific.

Uninstalling SQL Profiler from Windows Hosts

If you are using SQL Profiler on a Windows host, Windows will lock any files that have been executed or loaded into memory. To release any locked files, you must stop the Postgres server before performing an uninstall.

On Windows, you can use the **Services** dialog to control the service. To open the **Services** dialog, navigate through the **Control Panel** to the **System and Security** menu. Select **Administrative Tools**, and then double-click the **Services** icon. When the **Services** dialog opens, highlight the service name in the list, and use the option provided on the dialog to **Stop** the service.

After stopping the Postgres Server:

Delete the existing SQL Profiler query set on each node by invoking the `uninstall-sql-profiler.sql` script.

By default, the script resides in the `share\contrib` directory under your Advanced Server or PostgreSQL installation.

Uninstalling SQL Profiler from CentOS or RHEL Hosts

To uninstall a SQL Profiler installation that resides on a Linux host:

Delete the existing SQL Profiler query set on each node by invoking the `uninstall-sql-profiler.sql` script.

By default, if you are using Advanced Server on a Linux host, the script resides in the `share/contrib` directory under the Advanced Server installation.

If you are using a PostgreSQL installation on a Linux host, the script resides in the `share/contrib` directory under the PostgreSQL installation.