



人工智能技术及应用

Artificial Intelligence and Application

机器学习

≈ 找一个函数的能力 根据数据

- Speech Recognition

$$f\left(\text{[audio waveform]}\right) = \text{"How are you"}$$

- Image Recognition

$$f\left(\text{[cat image]}\right) = \text{"Cat"}$$


- Playing Go

$$f\left(\text{[go board state]}\right) = \text{"5-5"}_{\text{(next move)}}$$

- Dialogue System

$$f\left(\begin{array}{c} \text{"How are you?"} \\ \text{(what the user said)} \end{array}\right) = \begin{array}{c} \text{"I am fine."} \\ \text{(system response)} \end{array}$$

Different types of Functions



机器学习很简单

Step 0: What kind of function do you want to find?

Step 1:
define a set
of function




Step 2:
goodness of
function




Step 3: pick
the best
function

就好像把大象装进冰箱



Learning Map

■ scenario ■ task ■ method




回归

Regression




Regression: Output a scalar

- Stock Market Forecast

$$f(\text{ ) = \text{Dow Jones Industrial Average at tomorrow}$$

- Self-driving Car


$$f(\text{ ) = \text{方向盘角度}$$

- Recommendation

$$f(\text{使用者 A} \quad \text{商品 B}) = \text{购买可能性}$$

Example Application

- Estimating the Combat Power (CP) of a pokemon after evolution



Step 1: Model

$$y = b + w \cdot x_{cp}$$

A set of
function

Model

$f_1, f_2 \dots$

w and b are parameters
(can be any value)

$$f_1: y = 10.0 + 9.0 \cdot x_{cp}$$

$$f_2: y = 9.8 + 9.2 \cdot x_{cp}$$

$$f_3: y = -0.8 - 1.2 \cdot x_{cp}$$

..... infinite

$f($



$x) =$

CP after
evolution

y

Linear model:

$$y = b + \sum w_i x_i$$

$x_i: x_{cp}, x_{hp}, x_w, x_h \dots$

feature

w_i : weight, b: bias

Step 2: Goodness of Function

$$y = b + w \cdot x_{cp}$$

A set of
function

Model

$f_1, f_2 \dots$

Training
Data

function
input:

function
Output (scalar):



Step 2: Goodness of Function

Training Data:
10 pokemons


$$(x^1, \hat{y}^1)$$

$$(x^2, \hat{y}^2)$$

⋮

$$(x^{10}, \hat{y}^{10})$$

This is real data.



Source: <https://www.openintro.org/stat/data/?data=pokemon>

Step 2: Goodness of Function

$$y = b + w \cdot x_{cp}$$

A set of
function

Model

$f_1, f_2 \dots$

Loss function L :

Input: a function, output:
how bad it is

Goodness of
function f

Training
Data

$$L(f) = \frac{1}{N} \sum_{n=1}^N \left(\hat{y}^n - \underline{f(x_{cp}^n)} \right)^2$$

Sum over examples

Estimated y based
on input function

$$L(w, b) = \frac{1}{N} \sum_{n=1}^N \left(\hat{y}^n - (b + w \cdot x_{cp}^n) \right)^2$$

MSE (均方差)

Step 2: Goodness of Function


- Loss Function

$$L(w, b) = \sum_{n=1}^{10} \left(\hat{y}^n - (b + w \cdot x_{cp}^n) \right)^2$$


Each point in the figure is a function

The color represents $L(w, b)$.

(true example)




Step 3: Best Function



Step 3: Gradient Descent

$$w^* = \arg \min_w L(w)$$

- Consider loss function $L(w)$ with one parameter w :



Step 3: Gradient Descent


$$w^* = \arg \min_w L(w)$$

- Consider loss function $L(w)$ with one parameter w :

➤ (Randomly) Pick an initial value w^0

➤ Compute $\frac{dL}{dw} \big|_{w=w^0}$


$$w^1 \leftarrow w^0 - \eta \frac{dL}{dw} \big|_{w=w^0}$$



Step 3: Gradient Descent

$$w^* = \arg \min_w L(w)$$

- Consider loss function $L(w)$ with one parameter w :



Step 3: Gradient Descent

$$\begin{bmatrix} \frac{\partial L}{\partial w} \\ \frac{\partial L}{\partial b} \end{bmatrix} \text{gradient}$$

- How about two parameters? $w^*, b^* = \arg \min_{w, b} L(w, b)$

➤ (Randomly) Pick an initial value w^0, b^0

➤ Compute $\frac{\partial L}{\partial w} \big|_{w=w^0, b=b^0}, \frac{\partial L}{\partial b} \big|_{w=w^0, b=b^0}$


$$w^1 \leftarrow w^0 - \eta \frac{\partial L}{\partial w} \big|_{w=w^0, b=b^0} \quad b^1 \leftarrow b^0 - \eta \frac{\partial L}{\partial b} \big|_{w=w^0, b=b^0}$$

➤ Compute $\frac{\partial L}{\partial w} \big|_{w=w^1, b=b^1}, \frac{\partial L}{\partial b} \big|_{w=w^1, b=b^1}$

$$w^2 \leftarrow w^1 - \eta \frac{\partial L}{\partial w} \big|_{w=w^1, b=b^1} \quad b^2 \leftarrow b^1 - \eta \frac{\partial L}{\partial b} \big|_{w=w^1, b=b^1}$$

Step 3: Gradient Descent

- Formulation of $\partial L / \partial w$ and $\partial L / \partial b$


$$L(w, b) = \sum_{n=1}^{10} \left(\hat{y}^n - (b + \underline{w \cdot x_{cp}^n}) \right)^2$$


$$\frac{\partial L}{\partial w} = ? \sum_{n=1}^{10} 2 \left(\hat{y}^n - (b + w \cdot x_{cp}^n) \right)$$

$$\frac{\partial L}{\partial b} = ?$$

Step 3: Gradient Descent


- Formulation of $\partial L / \partial w$ and $\partial L / \partial b$

$$L(w, b) = \sum_{n=1}^{10} \left(\hat{y}^n - (\underline{b} + w \cdot x_{cp}^n) \right)^2$$


$$\frac{\partial L}{\partial w} = ? \sum_{n=1}^{10} 2 \left(\hat{y}^n - (b + w \cdot x_{cp}^n) \right) (-x_{cp}^n)$$

$$\frac{\partial L}{\partial b} = ? \sum_{n=1}^{10} 2 \left(\hat{y}^n - (b + w \cdot x_{cp}^n) \right)$$

Step 3: Gradient Descent



Step 3: Gradient Descent

- When solving:


$$\theta^* = \arg \min_{\theta} L(\theta) \quad \text{by gradient descent}$$

- Each time we update the parameters, we obtain θ that makes $L(\theta)$ smaller.

$$L(\theta^0) > L(\theta^1) > L(\theta^2) > \dots$$

Is this statement correct?

Step 3: Gradient Descent



How's the results?


$$y = b + w \cdot x_{cp}$$

$$b = -188.4$$

$$w = 2.7$$

Average Error on
Training Data

$$= \frac{1}{10} \sum_{n=1}^{10} e^n = 31.9$$



How's the results?

- Generalization

What we really care about is the error on new data (testing data)

$$y = b + w \cdot x_{cp}$$

$$b = -188.4$$


$$w = 2.7$$

Average Error on
Testing Data

$$= \frac{1}{10} \sum_{n=1}^{10} e^n = 35.0$$

> Average Error on
Training Data (31.9)

Another 10 pokemons as testing data



Selecting another Model

$$y = b + w_1 \cdot x_{cp} + w_2 \cdot (x_{cp})^2$$

Best Function

$$b = -10.3$$



$$w_1 = 1.0, w_2 = 2.7 \times 10^{-3}$$

Average Error = 15.4

Testing:

Average Error = 18.4

Better! Could it be even better?



Selecting another Model

$$y = b + w_1 \cdot x_{cp} + w_2 \cdot (x_{cp})^2 + w_3 \cdot (x_{cp})^3$$

Best Function

$$b = 6.4, w_1 = 0.66$$

$$w_2 = 4.3 \times 10^{-3}$$



$$w_3 = -1.8 \times 10^{-6}$$

Average Error = 15.3

Testing:

Average Error = 18.1

Slightly better.
How about more
complex model?



Selecting another Model

$$y = b + w_1 \cdot x_{cp} + w_2 \cdot (x_{cp})^2 + w_3 \cdot (x_{cp})^3 + w_4 \cdot (x_{cp})^4$$



Best Function

Average Error = 14.9

Testing:

Average Error = 28.8

The results become worse ...



Selecting another Model

$$y = b + w_1 \cdot x_{cp} + w_2 \cdot (x_{cp})^2 + w_3 \cdot (x_{cp})^3 + w_4 \cdot (x_{cp})^4 + w_5 \cdot (x_{cp})^5$$



Best Function

Average Error = 12.8

Testing:

Average Error = 232.1

The results are so bad.



Model Selection

1. $y = b + w \cdot x_{cp}$



2. $y = b + w_1 \cdot x_{cp} + w_2 \cdot (x_{cp})^2$

3. $y = b + w_1 \cdot x_{cp} + w_2 \cdot (x_{cp})^2 + w_3 \cdot (x_{cp})^3$

4. $y = b + w_1 \cdot x_{cp} + w_2 \cdot (x_{cp})^2 + w_3 \cdot (x_{cp})^3 + w_4 \cdot (x_{cp})^4$

5. $y = b + w_1 \cdot x_{cp} + w_2 \cdot (x_{cp})^2 + w_3 \cdot (x_{cp})^3 + w_4 \cdot (x_{cp})^4 + w_5 \cdot (x_{cp})^5$


Training Data



A more complex model yields lower error on training data.

If we can truly find the best function

Model Selection




	Training	Testing
1	31.9	35.0
2	15.4	18.4
3	15.3	18.1
4	14.9	28.2
5	12.8	232.1


A more complex model does not always lead to better performance on testing data.

This is Overfitting.  Select suitable model

Let's collect more data



What are the hidden factors?



Back to step 1: Redesign the Model

$$y = b + \sum w_i x_i$$

Linear model?

x_s = species of x



If $x_s = \text{Pidgey}$:

$$y = b_1 + w_1 \cdot x_{cp}$$

If $x_s = \text{Weedle}$:

$$y = b_2 + w_2 \cdot x_{cp}$$

If $x_s = \text{Caterpie}$:

$$y = b_3 + w_3 \cdot x_{cp}$$

If $x_s = \text{Eevee}$:

$$y = b_4 + w_4 \cdot x_{cp}$$



Back to step 1: Redesign the Model

$$y = b + \sum w_i x_i$$

Linear model?

$$\begin{aligned} y = & b_1 \cdot \boxed{1} \\ & + w_1 \cdot \boxed{1} \quad x_{cp} \\ & + b_2 \cdot \boxed{0} \\ & + w_2 \cdot \boxed{0} \\ & + b_3 \cdot \boxed{0} \\ & + w_3 \cdot \boxed{0} \\ & + b_4 \cdot \boxed{0} \\ & + w_4 \cdot \boxed{0} \end{aligned}$$


$$\delta(x_s = \text{Pidgey})$$

$$\begin{cases} =1 & \text{If } x_s = \text{Pidgey} \\ =0 & \text{otherwise} \end{cases}$$


If $x_s = \text{Pidgey}$

$$y = b_1 + w_1 \cdot x_{cp}$$




Average error
= 3.8



Average error
= 14.3



Are there any other hidden factors?



Back to step 1: Redesign the Model Again



If $x_s = \text{Pidgey}$: $y' = b_1 + w_1 \cdot x_{cp} + w_5 \cdot (x_{cp})^2$

If $x_s = \text{Weedle}$: $y' = b_2 + w_2 \cdot x_{cp} + w_6 \cdot (x_{cp})^2$

If $x_s = \text{Caterpie}$: $y' = b_3 + w_3 \cdot x_{cp} + w_7 \cdot (x_{cp})^2$

If $x_s = \text{Eevee}$: $y' = b_4 + w_4 \cdot x_{cp} + w_8 \cdot (x_{cp})^2$

$$y = y' + w_9 \cdot x_{hp} + w_{10} \cdot (x_{hp})^2$$
$$+ w_{11} \cdot x_h + w_{12} \cdot (x_h)^2 + w_{13} \cdot x_w + w_{14} \cdot (x_w)^2$$



Training Error
= 1.9

Testing Error
= 102.3

Overfitting!

Back to step 2: Regularization

$$y = b + \sum w_i x_i$$

$$L = \sum_n \left(\hat{y}^n - \left(b + \sum w_i x_i \right) \right)^2$$

The functions with smaller w_i are better

$$+ \lambda \sum (w_i)^2$$

➤ Smaller w_i means ... **smoother**


$$y = b + \sum w_i x_i$$

$$y + \sum w_i \Delta x_i = b + \sum w_i (x_i + \Delta x_i)$$

➤ We believe smoother function is more likely to be correct

Do you have to apply regularization on bias?

Regularization



λ	Training	Testing
0	1.9	102.3
1	2.3	68.7
10	3.5	25.7
100	4.1	11.1
1000	5.6	12.8
10000	6.3	18.7
100000	8.5	26.8

How smooth?

Select λ obtaining the best model

- Training error: larger λ , considering the training error less
- We prefer smooth function, but don't be too smooth.

Conclusion

- Pokémon: Original CP and species almost decide the CP after evolution
 - There are probably other hidden factors (输入特征)
- Gradient descent (梯度下降)
 - More theory and tips in the following lectures
- We finally get average error = 11.1 on the testing data
 - How about new data? Larger error? Lower error?
- Next lecture: Where does the error come from? (误差)
 - More theory about overfitting and regularization
 - The concept of validation