



人工智能技术及应用


Artificial Intelligence and Application

Self-attention




Sophisticated Input

- Input is a **vector**




- Input is a **set of vectors**



Vector Set as Input

this is a cat



One-hot Encoding

apple = [1 0 0 0 0]


bag = [0 1 0 0 0]

cat = [0 0 1 0 0]


dog = [0 0 0 1 0]

elephant = [0 0 0 0 1]

Word Embedding



Vector Set as Input



Vector Set as Input

- Graph is also a set of vectors (consider each **node** as a **vector**)



Vector Set as Input


- Graph is also a set of vectors (consider each **node** as a **vector**)

$$H = [1 \ 0 \ 0 \ 0 \ 0 \ \dots]$$

$$C = [0 \ 1 \ 0 \ 0 \ 0 \ \dots]$$

$$O = [0 \ 0 \ 1 \ 0 \ 0 \ \dots]$$

⋮



What is the output?

- Each vector has a label.




Example Applications

I saw a saw
↓ ↓ ↓ ↓
N V DET N

POS tagging

a a b b
↓ ↓ ↓ ↓

Phoneme recognition



What is the output?

- Each vector has a label.





- The whole sequence has a label.



Example Applications


this is good
Sentiment
analysis
↓
positive



What is the output?

- Each vector has a label.

focus of this lecture



- The whole sequence has a label.



- Model decides the number of labels itself.

seq2seq




Sequence Labeling

Is it possible to consider the context?


FC can consider the neighbor


How to consider the whole sequence?

a window covers the whole sequence?




Self-attention






Attention is all you need.

Self-attention



Can be either **input** or a **hidden layer**

Self-attention





Find the relevant vectors in a sequence

Self-attention


Additive

Dot-product

$$\alpha = q \cdot k$$




Self-attention



Self-attention


$$\alpha'_{1,i} = \exp(\alpha_{1,i}) / \sum_j \exp(\alpha_{1,j})$$




Self-attention

Extract information based on attention scores

$$b^1 = \sum_i \alpha'_{1,i} v^i$$




Self-attention



Can be either **input** or a **hidden layer**

Self-attention

$$b^2 = \sum_i \alpha'_{2,i} v^i$$



Self-attention

$$q^i = W^q a^i$$





$$\begin{array}{c} \boxed{q^1} \boxed{q^2} \boxed{q^3} \boxed{q^4} \\ Q \end{array} = \begin{array}{c} \boxed{W^q} \begin{array}{c} \boxed{a^1} \boxed{a^2} \boxed{a^3} \boxed{a^4} \\ I \end{array} \end{array}$$

$$k^i = W^k a^i$$

$$\begin{array}{c} \boxed{k^1} \boxed{k^2} \boxed{k^3} \boxed{k^4} \\ K \end{array} = \begin{array}{c} \boxed{W^k} \begin{array}{c} \boxed{a^1} \boxed{a^2} \boxed{a^3} \boxed{a^4} \\ I \end{array} \end{array}$$


$$v^i = W^v a^i$$

$$\begin{array}{c} \boxed{v^1} \boxed{v^2} \boxed{v^3} \boxed{v^4} \\ V \end{array} = \begin{array}{c} \boxed{W^v} \begin{array}{c} \boxed{a^1} \boxed{a^2} \boxed{a^3} \boxed{a^4} \\ I \end{array} \end{array}$$



Self-attention


$$\begin{aligned}\alpha_{1,1} &= k^1 q^1 & \alpha_{1,2} &= k^2 q^1 \\ \alpha_{1,3} &= k^3 q^1 & \alpha_{1,4} &= k^4 q^1\end{aligned}$$
$$\begin{matrix} \alpha_{1,1} \\ \alpha_{1,2} \\ \alpha_{1,3} \\ \alpha_{1,4} \end{matrix} = \begin{matrix} k^1 \\ k^2 \\ k^3 \\ k^4 \end{matrix} q^1$$



Self-attention

$$\begin{aligned}
 \alpha_{1,1} &= k^1 q^1 & \alpha_{1,2} &= k^2 q^1 \\
 \alpha_{1,3} &= k^3 q^1 & \alpha_{1,4} &= k^4 q^1
 \end{aligned}$$


$$\begin{matrix} \alpha_{1,1} \\ \alpha_{1,2} \\ \alpha_{1,3} \\ \alpha_{1,4} \end{matrix} = \begin{matrix} k^1 \\ k^2 \\ k^3 \\ k^4 \end{matrix} q^1$$



$$\begin{matrix} \alpha'_{1,1} & \alpha'_{2,1} & \alpha'_{3,1} & \alpha'_{4,1} \\ \alpha'_{1,2} & \alpha'_{2,2} & \alpha'_{3,2} & \alpha'_{4,2} \\ \alpha'_{1,3} & \alpha'_{2,3} & \alpha'_{3,3} & \alpha'_{4,3} \\ \alpha'_{1,4} & \alpha'_{2,4} & \alpha'_{3,4} & \alpha'_{4,4} \end{matrix} \xleftarrow{\text{softmax}} \begin{matrix} \alpha_{1,1} & \alpha_{2,1} & \alpha_{3,1} & \alpha_{4,1} \\ \alpha_{1,2} & \alpha_{2,2} & \alpha_{3,2} & \alpha_{4,2} \\ \alpha_{1,3} & \alpha_{2,3} & \alpha_{3,3} & \alpha_{4,3} \\ \alpha_{1,4} & \alpha_{2,4} & \alpha_{3,4} & \alpha_{4,4} \end{matrix} = \begin{matrix} k^1 \\ k^2 \\ k^3 \\ k^4 \end{matrix} \begin{matrix} q^1 & q^2 & q^3 & q^4 \end{matrix}$$

A' softmax A K^T Q



Self-attention



Self-attention

$$\begin{array}{lcl} Q & = & W^q I \\ K & = & W^k I \\ V & = & W^v I \end{array}$$

Parameters
to be learned



=




=



Attention Matrix




=



Multi-head Self-attention Different types of relevance

$$q^{i,1} = W^{q,1} q^i$$

$$q^{i,2} = W^{q,2} q^i$$




Multi-head Self-attention

Different types of relevance


$$q^{i,1} = W^{q,1} q^i$$

$$q^{i,2} = W^{q,2} q^i$$




Multi-head Self-attention Different types of relevance

$$b^i = W^o \begin{bmatrix} b^{i,1} \\ b^{i,2} \end{bmatrix}$$




Positional Encoding

- No position information in self-attention.
- Each position has a unique positional vector e^i
- **hand-crafted**
- **learned from data**



Each column represents a positional vector e^i




<https://arxiv.org/abs/2003.09229>



Table 1. Comparing position representation methods

Methods	Inductive	Data-Driven	Parameter Efficient
Sinusoidal (Vaswani et al., 2017)	✓	✗	✓
Embedding (Devlin et al., 2018)	✗	✓	✗
Relative (Shaw et al., 2018)	✗	✓	✓
This paper	✓	✓	✓


(a) Sinusoidal



(b) Position embedding



(c) FLOATER



(d) RNN

Many applications ...



Transformer

<https://arxiv.org/abs/1706.03762>




BERT

<https://arxiv.org/abs/1810.04805>



Widely used in Natural Language Processing (NLP)!

Self-attention for Speech

Speech is a very long vector sequence.





If input sequence is length L



Truncated Self-attention


Self-attention for Image

An **image** can also be considered as a **vector set**.




Source of image: https://www.researchgate.net/figure/Color-image-representation-and-RGB-matrix_fig15_282798184


Self-Attention GAN



DEtection Transformer (DETR)



Self-attention v.s. CNN





CNN: self-attention that can only attends in a receptive field

- CNN is simplified self-attention.

Self-attention: CNN with learnable receptive field

- Self-attention is the complex version of CNN.

Self-attention v.s. CNN




On the Relationship between Self-Attention and Convolutional Layers

<https://arxiv.org/abs/1911.03584>

Self-attention v.s. CNN

Good for more data


Self-attention



An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale

<https://arxiv.org/pdf/2010.11929.pdf>


Self-attention v.s. RNN



Transformers are RNNs: Fast Autoregressive Transformers with Linear Attention









<https://arxiv.org/abs/2006.16236>

Self-attention for Graph



Consider **edge**: only attention to connected nodes

Attention Matrix


	1	2	3	4	5	6	7	8
1								
2								
3								
4								
5								
6								
7								
8							0	

This is one type of **Graph Neural Network (GNN)**.

To Learn More ...

Long Range Arena: A Benchmark for Efficient Transformers

<https://arxiv.org/abs/2011.04006>



Efficient Transformers: A Survey

<https://arxiv.org/abs/2009.06732>

