




Gumbel Softmax

Machine Learning: Jordan Boyd-Graber
University of Maryland


SLIDES ADAPTED FROM ERIC JANG

Sampling screws up Backprop



- Problem for any single sample
- Can't backprop through sample

Sampling screws up Backprop



- Problem for any single sample
- Can't backprop through sample
- Express sample so gradient avoids randomness
- For example, $z \sim \mathcal{N}(\mu, \sigma)$ as $z = \mu + \sigma \epsilon$, $\epsilon \sim \mathcal{N}(0, 1)$

Gumbel

- Want to do the same thing for discrete distributions
- Instead of ϵ , we'll use Gumbel distribution
 - Sample $u \sim \text{Uniform}(0, 1)$
 - Compute $g = -\log(-\log(u))$
- We then could then draw samples from π_i with $\arg \max_i [g_i + \log \pi_i]$

Gumbel

- Want to do the same thing for discrete distributions
- Instead of ϵ , we'll use Gumbel distribution
 - Sample $u \sim \text{Uniform}(0, 1)$
 - Compute $g = -\log(-\log(u))$
- We then could then draw samples from π_i with $\arg \max_i [g_i + \log \pi_i]$
- But $\arg \max$ isn't differentiable


Backpropagate through Softmax

- “softmax” is a continuous approximation

$$y_i = \frac{\exp\left\{\frac{\log(\pi) + g_i}{\tau}\right\}}{\sum_j \frac{\exp\{\log(\pi_j) + g_j\}}{\tau}} \quad (1)$$


- τ is temperature that controls how close to max it is

Visualization




$$\tau = 3$$

Visualization




$$\tau = 2$$

Visualization



$$\tau = 1$$

Visualization



$$\tau = 0.1$$