




GANs

Machine Learning: Jordan Boyd-Graber
University of Maryland

SLIDES ADAPTED FROM GRAHAM NEUBIG

Generative Models Ain't Perfect



(Lotter et al. 2015)

- Fitting conventional prob models focuses on common input
- Can be “fuzzy”
- Still better for smaller ammounts of data or if true objective is ML

Adversarial Training

- It's time for some game theory

Adversarial Training

- It's time for some game theory
- Create “**discriminator**” that criticizes generated output
 - Is this example real or not
- **Generator** is trained to fool discriminator to say it's real


Adversarial Training

- It's time for some game theory
- Create “**discriminator**” that criticizes generated output
 - Is this example real or not
- **Generator** is trained to fool discriminator to say it's real
- Contrast with encoder / decoder:

Adversarial Training

- It's time for some game theory
- Create “**discriminator**” that criticizes generated output
 - Is this example real or not
- **Generator** is trained to fool discriminator to say it's real
- Contrast with encoder / decoder: no fixed representation

Training GAN



Training Equations

Discriminator

$$\begin{aligned}\ell_D(\theta_D, \theta_G) = \\ -\mathbb{E}_{x \sim P_{\text{data}}} [\log D(x)] \\ -\mathbb{E}_z [\log(1 - D(G(z)))]\end{aligned}$$

- Real data should get high score
- Fake data should get low score

Training Equations

Discriminator

$$\begin{aligned}\ell_D(\theta_D, \theta_G) = & \\ & -\mathbb{E}_{x \sim P_{\text{data}}} [\log D(x)] \\ & -\mathbb{E}_z [\log(1 - D(G(z)))]\end{aligned}$$

- Real data should get high score
- Fake data should get low score

Training Equations

Discriminator

$$\begin{aligned}\ell_D(\theta_D, \theta_G) = & \\ & -\mathbb{E}_{x \sim P_{\text{data}}} [\log D(x)] \\ & - \mathbb{E}_z [\log(1 - D(G(z)))]\end{aligned}$$

- Real data should get high score
- Fake data should get low score

Training Equations

Discriminator

$$\begin{aligned}\ell_D(\theta_D, \theta_G) = & \\ & -\mathbb{E}_{x \sim P_{\text{data}}} [\log D(x)] \\ & -\mathbb{E}_z [\log(1 - D(G(z)))]\end{aligned}$$

- Real data should get high score
- Fake data should get low score

Generator

$$\ell_G(\theta_D, \theta_G) = -\ell_D(\theta_D, \theta_G)$$

- If discriminator is very accurate, sometimes better to focus on non-saturating loss
- Focus on where you can confuse discriminator

$$\mathbb{E}_z [-\log D(G(z))] \quad (1)$$

Problems with Training

- GANs are great, but training very hard
- Mode Collapse: generator maps all z to single x
- Over-confident discriminator

Problems with Training

- GANs are great, but training very hard
- Mode Collapse: generator maps all z to single x (other examples as side information)
- Over-confident discriminator

Problems with Training

- GANs are great, but training very hard
- Mode Collapse: generator maps all z to single x
- Over-confident discriminator (smoothing)

Problems with Discrete Data

