Spectral Methods

Advanced Machine Learning for NLP

Jordan Boyd-Graber

ANCHOR TOPIC MODELS

Slides adapted from Thang Nguyen

What are Spectral Methods

- Bayesian and deep models had explicit generative models
- Is it possible to find useful structure from matrix representations of data directly?
- Spectral methods: often very fast, but hard to engineer
- Like last week, a little out of place
- Today:
  - Anchor Words for Topic Models
  - Tensors

What are Spectral Methods

- Bayesian and deep models had explicit generative models
- Is it possible to find useful structure from matrix representations of data directly?
- Spectral methods: often very fast, but hard to engineer
- Like last week, a little out of place
- Today:
  - Anchor Words for Topic Models
  - Tensors
  - Projects / Presentations
  - FCQ

Anchor Method: Definition

- Words are often shared among many topics

Anchor Method: Definition



- Words are often shared among many topics
- Anchor words: words that unique to a topic

Anchor Method: Big Idea

- Normally, we want to find $p(\text{word}|\textbf{topic})$

$$A_{i,k} = \text{p(word = i}|\text{topic = }\textbf{k})$$

- What we'll do instead is find $p(\textbf{topic}|\text{word})$ (topic coefficient)

$$C_{i,k} = \text{p(topic = }\textbf{k}|\text{word = i)}$$

Anchor Method: Big Idea

- Normally, we want to find $p(\text{word}|\textbf{topic})$

$$A_{i,k} = \text{p(word = i}|\text{topic = }\textbf{k})$$

- What we'll do instead is find $p(\textbf{topic}|\text{word})$ (topic coefficient)

$$C_{i,k} = \text{p(topic = }\textbf{k}|\text{word = i)}$$

- Easy: Bayes rule

Anchor Method: Why go backward?

- Finding $C_{i,k}$ is easy if you know the anchor words (assume we do!)
- $Q_{i,j} = p(word_1 = i, word_2 = j)$ is the cooccurrence probability
- Anchor method is so efficient because it uses conditional word distribution

$$\bar{Q}_{i,j} = p(\text{word}_2 = j | \text{word}_1 = i)$$

Anchor Method: Why go backward?

- Finding $C_{i,k}$ is easy if you know the anchor words (assume we do!)
- $Q_{i,j} = p(word_1 = i, word_2 = j)$ is the cooccurrence probability
- Anchor method is so efficient because it uses conditional word distribution

$$\bar{Q}_{i,j} = p(\text{word}_2 = j | \text{word}_1 = i)$$



The conditional probability distribution $\bar{Q}_{\text{shortshop},*}$ looks a lot like the topic distribution!

What about other words?

$$\bar{Q}_{\text{fly},*}$$

What about other words?



$\bar{Q}_{\text{fly},*}$

What about other words?



What about other words?



What about other words?



$\bar{Q}_{\text{shortstop},*}$ $\bar{Q}_{\text{insecta},*}$ $\bar{Q}_{\text{boeing},*}$ $\bar{Q}_{\text{fly},*}$

$$\bar{Q}_{i,j} = \sum_k C_{i,k} \bar{Q}_{g_k,j}$$

What about other words?



$\bar{Q}_{\text{shortstop},*}$ $\bar{Q}_{\text{insecta},*}$ $\bar{Q}_{\text{boeing},*}$ $\bar{Q}_{\text{fly},*}$

$$\bar{Q}_{i,j} = \sum_k C_{i,k} \bar{Q}_{g_k,j}$$

Topic Recovery



Topic Recovery



Let g_k be the anchor word for topic k

Topic Recovery



Let $C_{i,k}$ = p(topic=k | word=i), $C_{i,k} \geq 0$, $\sum_k C_{i,k} = 1$

Topic Recovery



$$\bar{Q}_{i,j} = \sum_k C_{i,k} \bar{Q}_{g_k,j}$$

A Significant Portion of Text is Labeled







Motivation

- Supervised topic models leverage latent document-level themes to capture nuanced sentiment, create sentiment-specific topics and improve sentiment prediction.
- Examples include Supervised LDA (Blei et al., 2007), Labelled LDA (Ramage et al., 2009), Med LDA (Zhu et al., 2009), etc.
- The downside is sluggish performance.

Motivation

- Supervised topic models leverage latent document-level themes to capture nuanced sentiment, create sentiment-specific topics and improve sentiment prediction.
- Examples include Supervised LDA (Blei et al., 2007), Labelled LDA (Ramage et al., 2009), Med LDA (Zhu et al., 2009), etc.
- The downside is sluggish performance.
- Create a supervised model based on Anchor Words?

Supervised Anchor Words: Idea

$$\bar{Q} \equiv \begin{bmatrix} p(w_1|w_1)\ldots \\ \vdots \\ p(w_j|w_i) \end{bmatrix}$$

$$S \equiv \begin{bmatrix} p(w_1|w_1)\ldots & p(y^{(l)}|w_1) \\ \vdots & \vdots \\ p(w_j|w_i) & p(y^{(l)}|w_i) \end{bmatrix}$$

New column(s) encoding word-sentiment relationship

$$S_{i,\cdot} = \sum_{g_k \in \mathcal{G}} C_{i,k} S_{g_k,\cdot}$$

Supervised Anchor Words: Intuition





- Adding sentiment related dimensions moves words UP or DOWN
- forming sentiment-specific points
- possibility of having different anchor words

Evaluation of Supervised Anchor Words

- **Goal**: Evaluate the new topics generated by the proposed model in a prediction task. We focus on binary classification in sentiment analysis datasets.
- Sentiment datasets.

Corpus	Train	Test	Tokens	Vocab	**+1**
amazon	13,300	3,314	1,031,659	2,662	52.2%
tripadvisor	115,384	28,828	12,752,444	4,867	41.5%
yelp	13,955	3,482	1,142,555	2,585	27.7%

Runtime Analysis

- Total time for training and prediction on amazon dataset.

Prediction Accuracy



Topic Coherence



Anchor Words and Their Topics



Ongoing Work

- Near-instant updates
- Using multiple anchor words can improve coherence (and add interactivities)
- Downside: hard to create new models
- Hard to debug