



# Sequence Models

Machine Learning: Jordan Boyd-Graber University of Maryland

# **GRU** simplifies slightly



### **GRU** simplifies slightly




$$\begin{split} z_t &= \sigma \left( W_z \cdot [h_{t-1}, x_t] \right) \\ r_t &= \sigma \left( W_r \cdot [h_{t-1}, x_t] \right) \\ \tilde{h}_t &= \tanh \left( W \cdot [r_t * h_{t-1}, x_t] \right) \\ h_t &= (1 - z_t) * h_{t-1} + z_t * \tilde{h}_t \end{split}$$


# Slightly fewer parameters

- No Input Gate (NIG)
- No Forget Gate (NFG)
- No Output Gate (NOG)
- No Input Activation Function (NIAF)
- No Output Activation Function (NOAF)
- No Peepholes (NP)
- Coupled Input and Forget Gate (CIFG) : GRU,  $f_t = 1 - i_t$
- Full Gate Recurrence (FGR): Original LSTM paper


- No Input Gate (NIG)
- No Forget Gate (NFG)
- No Output Gate (NOG)
- No Input Activation Function (NIAF)
- No Output Activation Function (NOAF)
- No Peepholes (NP)
- Coupled Input and Forget Gate (CIFG) : GRU,  $f_t = 1 - i_t$
- Full Gate Recurrence (FGR): Original LSTM paper




- No Input Gate (NIG)
- No Forget Gate (NFG)
- No Output Gate (NOG)
- No Input Activation Function (NIAF)
- No Output Activation Function (NOAF)
- No Peepholes (NP)
- Coupled Input and Forget Gate (CIFG) : GRU,  $f_t = 1 - i_t$
- Full Gate Recurrence (FGR): Original LSTM paper




- No Input Gate (NIG)
- No Forget Gate (NFG)
- No Output Gate (NOG)
- No Input Activation Function (NIAF)
- No Output Activation Function (NOAF)
- No Peepholes (NP)
- Coupled Input and Forget Gate (CIFG) : GRU,  $f_t = 1 - i_t$
- Full Gate Recurrence (FGR): Original LSTM paper




- No Input Gate (NIG)
- No Forget Gate (NFG)
- No Output Gate (NOG)
- No Input Activation Function (NIAF)
- No Output Activation Function (NOAF)
- No Peepholes (NP)
- Coupled Input and Forget Gate (CIFG) : GRU,  $f_t = 1 - i_t$
- Full Gate Recurrence (FGR): Original LSTM paper



- No Input Gate (NIG)
- No Forget Gate (NFG)
- No Output Gate (NOG)
- No Input Activation Function (NIAF)
- No Output Activation Function (NOAF)
- No Peepholes (NP)
- Coupled Input and Forget Gate (CIFG) : GRU,  $f_t = 1 - i_t$
- Full Gate Recurrence (FGR): Original LSTM paper



- No Input Gate (NIG)
- No Forget Gate (NFG)
- No Output Gate (NOG)
- No Input Activation Function (NIAF)
- No Output Activation Function (NOAF)
- No Peepholes (NP)
- Coupled Input and Forget Gate (CIFG) : GRU,  $f_t = 1 - i_t$
- Full Gate Recurrence (FGR): Original LSTM paper




- No Input Gate (NIG)
- No Forget Gate (NFG)
- No Output Gate (NOG)
- No Input Activation Function (NIAF)
- No Output Activation Function (NOAF)
- No Peepholes (NP)
- Coupled Input and Forget Gate (CIFG) : GRU,  $f_t = 1 - i_t$
- Full Gate Recurrence (FGR): Original LSTM paper




```
z_t = \sigma (W_t \cdot [h_{t-1}, x_t])
r_t = \sigma \left(W_r \cdot [h_{t-1}, x_t]\right)
\tilde{h}_t = \tanh (W \cdot [r_t * h_{t-1}, x_t])
h_t = (1 - z_t) * h_{t-1} + z_t * \tilde{h}_t
```

- No Input Gate (NIG)
- No Forget Gate (NFG)
- No Output Gate (NOG)
- No Input Activation Function (NIAF)
- No Output Activation Function (NOAF)
- No Peepholes (NP)
- Coupled Input and Forget Gate (CIFG) : GRU,  $f_t = 1 - i_t$
- Full Gate Recurrence (FGR): Original LSTM paper



#### **Bi-directional LSTMs**



Simple extension, often slightly improve performance (but don't always make sense for task)

### **Comparing architechtures**

- GRUs seem competitive
- LSTM seems to be good tradeoff
- Bi-directional often offers slight improvement