

Part I — Developer user manual

1. Prerequisites

Before installing and running Claude Code you need:

- **Git for Windows — required.** Claude Code's shell tooling runs through Git's `bash.exe`, and its version-control features (diffs, commits, branches) use `git` itself. A standard install is found automatically (Claude Code looks in `C:\Program Files\Git\bin\bash.exe` and `C:\Program Files (x86)\Git\bin\bash.exe`). If your Git lives anywhere else — a per-user or portable install — set the `CLAUDE_CODE_GIT_BASH_PATH` environment variable to your `bash.exe` location (see §5.1).
- **Node.js / npm — NOT required.** This deployment distributes the precompiled native `claude.exe`; nothing is installed from npm, and `npm install`-based instructions you may find online do not apply here (updates are locked down and this network does not reach npm anyway).
- **An Okta account** in the authorized group, with MFA enrolled — sign-in is your normal corporate SSO in the browser.
- **The managed login policy on your machine.** IT delivers it automatically by GPO/MDM; there is nothing for you to do. Without it Claude Code has no gateway login option at all — if `/login` shows no "Cloud gateway" screen, contact IT rather than trying to configure it yourself (a developer with local admin can self-serve it — §8).
- **The gateway certificate fingerprint published by IT** — you confirm it once, at first connect.
- **No admin rights** — the install itself is entirely user-scope.

2. Installing

Run `Install-ClaudeCode.ps1` directly from the software share, or download the ZIP from the portal and double-click the `install.cmd` inside it. No elevation prompt appears; the installer does exactly three things, all in your own profile:

- **Binary** → `%USERPROFILE%\local\bin\claude.exe`, verified (SHA-256 against the release manifest + Anthropic Authenticode) on a local staging copy before it is moved into place.
- **User PATH** → `%USERPROFILE%\local\bin` is appended to the `user Path` environment variable (registry-backed, persists; no machine PATH edit).
- **User configuration** → an `env` block merged into `%USERPROFILE%\claude\settings.json` (your own settings file). The merge preserves every existing top-level key and every unrelated `env` key, and refuses to overwrite a file it cannot parse. The keys written:

Key (under <code>env</code>)	Set by	Purpose
<code>DISABLE_UPDATES = 1</code>	<code>-DisableUpdates</code>	Blocks all update paths (background checks and manual <code>claude update</code> / <code>claude install</code>) — keeps users on the distributed build
<code>DISABLE_AUTOUPDATER = 1</code>	<code>-DisableUpdates</code>	Background-check lockdown, defense in depth
<code>OTEL_RESOURCE_ATTRIBUTES</code>	<code>-Team / -CostCenter</code>	Telemetry grouping labels (<code>team=...</code> , <code>cost_center=...</code>); telemetry itself is enabled centrally by the gateway
<code>NODE_EXTRA_CA_CERTS</code>	<code>-ExtraCaCertPath</code>	Enterprise CA trust for the gateway TLS chain (the precompiled binary honors it)

These are ordinary environment variables, honored from the user settings file — **not** policy keys. The installer never writes `%ProgramFiles%\ClaudeCode\managed-settings.json` and never touches `HKx\SOFTWARE\Policies\ClaudeCode`. A SYSTEM-context run is refused outright.

After installing, **open a new terminal** so the updated PATH is picked up.

3. First launch & signing in

Signing in is effectively a one-time step: the session persists and refreshes itself. The login method is locked to the corporate gateway and the URL is pre-filled — you never choose an account type or type a URL.

1. Open a **new** terminal and run `claude`.
2. Two things can happen here, **both normal**:
3. Claude Code opens directly on the **gateway login screen**, or
4. it drops you into the **chat window** with a notice telling you to run `/login`. Type `/login` and the same gateway screen appears.
5. The gateway screen shows the pre-filled gateway URL. Press **Enter** to accept and connect.
6. Claude Code usually does **not** launch your browser by itself. Copy the authentication URL it prints and paste it into your browser, then complete the Okta sign-in (+ MFA).
7. At first connect Claude Code also shows the gateway certificate fingerprint and asks you to confirm it (trust-on-first-use). Compare it against the fingerprint IT published — do not blind-accept it; that prompt is what detects TLS interception in front of the gateway.
8. Back in the terminal, Claude Code tells you to press Enter to continue. About half the time the Enter key does nothing at this point — just **close the command window, open a new one, and run** `claude`: you will be fully signed in.
9. Occasionally Claude Code comes back from a successful sign-in not responding to the keyboard at all. Close it and reopen it — the session is already saved.
10. If you have used Claude in some other form before (claude.ai, a personal API key, an earlier install), you may see a **yellow warning** that a previous model was not found and that you are now using **Opus 4.8**. This is normal — see §5.7.

Signing out (if you ever need to): use `claude auth logout` — never the `/logout` slash command. On this network `/logout` leaves Claude Code unable to start (§5.6 has the recovery).

4. Day-to-day notes

- `/model` lists exactly three models — Opus 4.8 (the default), Sonnet 5, and Sonnet 4.5. That is by design, not an error; nothing else is served here.
- Web tools (WebFetch / WebSearch) and MCP tools are disabled centrally and cannot be re-enabled in your local settings.
- Updates are disabled; you always run the IT-distributed build, so `claude update` doing nothing is intentional. New versions arrive through the normal software distribution channel.
- `/status` shows which configuration sources are active — useful to see what is centrally managed vs. your own `settings.json`.

5. Troubleshooting

5.1 Claude Code can't find Git / bash

Symptoms: a startup error saying Claude Code requires Git for Windows, shell commands failing to run, or *"Claude Code was unable to find CLAUDE_CODE_GIT_BASH_PATH path ..."*.

- If Git for Windows is not installed, install it (no admin needed for the per-user installer).
- If Git is installed somewhere other than the standard `C:\Program Files\Git` location (per-user install, portable Git), point Claude Code at your `bash.exe` with the `CLAUDE_CODE_GIT_BASH_PATH` environment variable:

```
powershell setx CLAUDE_CODE_GIT_BASH_PATH "D:\Tools\Git\bin\bash.exe"
```

then open a **new** terminal. Alternatively, put it in the `env` block of `%USERPROFILE%\claude\settings.json` alongside the installer's keys:

```
json { "env": { "CLAUDE_CODE_GIT_BASH_PATH": "D:\\Tools\\Git\\bin\\bash.exe" } }
```

The value must be the full path to `bash.exe` **itself** (normally `...\\Git\\bin\\bash.exe`), not the Git folder and not `git.exe`.

5.2 No login screen at launch — dropped into the chat window

Sometimes the first launch does not take you to the login screen and instead opens the chat window with a notice to log in. This is normal: run `/login` and continue from §3 step 3.

If `/login` shows **no gateway screen at all** (an account picker with no "Cloud gateway" option), the managed login policy is missing from the machine — contact IT (§8; there is nothing you can set in user scope to fix this).

5.3 The browser never opens during sign-in

Expected most of the time: after you accept the gateway screen, Claude Code typically does not launch the browser itself. Copy the authentication URL from the terminal and paste it into your browser manually.

5.4 "Press Enter to continue" does nothing

After the browser sign-in completes, roughly half the time the terminal's Enter key has no effect on the "press Enter to continue" prompt. Close the command window, open a new one, and run `claude` — you will be fully signed in (the session was already saved).

5.5 Keyboard input not recognized after signing in

Occasionally, after a successful sign-in, Claude Code stops responding to keyboard input entirely. Close Claude Code and reopen it; the session persists, so you will not have to sign in again.

5.6 Startup fails: "Unable to connect to Anthropic services"

Claude Code exits at launch before any login screen appears. This happens when the onboarding flag is unset — on a first-ever run on a clean profile, or after running the `/logout` slash command — because a not-yet-onboarded client tries to reach Anthropic's public endpoints, which this network blocks by design.

Fix (no admin needed): mark onboarding as completed in `%USERPROFILE%\claude.json`:

```
$p = "$env:USERPROFILE\claude.json"
Copy-Item $p "$p.bak"           # this file also holds project history – back it up
$j = Get-Content $p -Raw | ConvertFrom-Json
if ($j.PSObject.Properties.Name -contains 'hasCompletedOnboarding') {
    $j.hasCompletedOnboarding = $true
} else {
    $j | Add-Member -NotePropertyName hasCompletedOnboarding -NotePropertyValue $true
}
$j | ConvertTo-Json -Depth 100 | Set-Content $p -Encoding utf8
```

(If `%USERPROFILE%\claude.json` does not exist yet, create it containing just `{"hasCompletedOnboarding": true}`.)

Then open a **new** terminal, run `claude`, and run `/login`. Because `/logout` also deletes the pinned certificate fingerprint, the fingerprint confirmation from §3 step 5 will come back — re-check it against the IT-published value. To avoid the whole trap, sign out with `claude auth logout`, never `/logout`. The service-desk version of this procedure is [om-runbooks.md](#) runbook 12.

5.7 Yellow warning: a model was not found — now using Opus 4.8

If you previously used Claude in some other form (claude.ai, a personal API key, another workplace's install), your old settings may name a model this gateway does not serve. On login Claude Code warns in yellow that the model was not found and switches you to **Opus 4.8**. This is normal behavior, not an error — Opus 4.8 is the default here, and `/model` shows what you can switch to.

5.8 Bounced to the browser sign-in every hour

If you are pushed through the browser SSO at every session expiry (about hourly) and `/login` then shows the default picker until you restart Claude Code, report it to your admins — it means the Okta app is missing the **Refresh Token** grant type (so the session cannot refresh silently). Admin fix: `okta-request-email.md` and `om-runbooks.md`. It is not a problem with your machine or settings.

This manual is Part I (§1–§5) of `docs/operations/client-config.md`. References to §6–§9 point at Part II — Administrators — in the full document; end users normally don't need it (§8 self-service requires local admin).