

A-level

ENVIRONMENTAL SCIENCE

Paper 1 - Generated practice paper Set 03

Mark scheme

120 marks: Questions 1-10 (95 marks) plus one essay from Question 11 (25 marks).

Marking guidance

- The number in brackets after each marking point is the mark it earns; the note above the points says how many are needed.
- Where a question asks for a fixed number of points (eg *two reasons*), credit only the first points given.
- Alternative correct wording and other relevant, accurate points are credited.
- For levels-of-response questions, first determine the level using the descriptors, then position the mark within the level using the indicative content.
- Calculations: credit correct working (method marks) even if the final answer is wrong; incorrect answers with no working score 0.

Textbook references: every question below cites the printed page numbers in R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018) from which the content is drawn, together with the AQA 7447 specification reference.

Question	Marking guidance	Marks
01.1	<i>1 mark.</i> • The length of time a pollutant remains in the environment before it is broken down / degraded (chemically or biologically) (1)	1
01.2	<i>Any 4 from the points below - 1 mark each, maximum 4.</i> • Light: UV light degrades many pesticides (eg neonicotinoids break down fastest in sunlight) so persistence is shorter in bright conditions (1) • Temperature: higher temperatures increase the rate of chemical breakdown / microbial decomposition (1) • Soil microbes / oxygen: aerobic microbial activity breaks pesticides down so persistence is shorter in well-aerated, biologically active soils (1) • pH / presence of other chemicals may increase or decrease the rate of degradation (1) • Adsorption onto clay / organic matter may protect from degradation and increase persistence (1)	4
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 263-266; AQA spec 3.4.3.2.8.	
02.1	<i>1 mark for the correct answer.</i> • $(120 + 95) - (2 + 45) = 168 \text{ t ha}^{-1}$ (1)	1
02.2	<i>1 mark for each point.</i> • Annual ploughing aerates the soil so aerobic decomposers break down dead organic matter faster, releasing CO₂ (1) • Harvest removes biomass so less dead organic matter is returned; pasture roots and litter constantly add organic matter (1)	2
02.3	<i>Any 2 from the points below - 1 mark each, maximum 2.</i> • Low / zero tillage (1) • Adding manure, compost or mulch (1) • Growing cover crops / leaving crop residues (1) • Converting to long-term grass or tree crops in rotation (1)	2

Question	Marking guidance	Marks
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 148-151; AQA spec 3.2.4.2.	
03.1	<i>1 mark for each point.</i> • Spearman's rank correlation coefficient (1) • Chi-squared test (frequencies / counts in categories) (1) • t-test (two means of measured data) (1) • Spearman's rank correlation coefficient (1)	4
03.2	<i>1 mark.</i> • Chi-squared compares frequencies / counts in categories; it cannot be used for continuously variable measured data (1)	1
03.3	<i>1 mark for each point.</i> • The value (ignoring sign) exceeds the critical value so the correlation is significant at the 5% level (1) • The negative sign shows a negative correlation: one variable decreases as the other increases (1) • There is less than a 5% probability the correlation arose by chance; reject the null hypothesis (but correlation is not proof of causation) (1)	3
03.4	<i>1 mark for each point.</i> • Show the standard deviation / range of the original values around each mean (1) • If the bars of two means overlap greatly the difference is probably not significant; little overlap suggests a significant difference (1)	2
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 422-423; AQA spec 3.7.2.3.	
04.1	<i>1 mark for the correct answer.</i> • $4.2 / 0.7 = 6$ (1)	1
04.2	<i>1 mark for each point.</i> • Long summer days (almost 24 hours of daylight) so the total energy received is high, even though the Sun is low (1) • In winter days are very short / the Sun does not rise, so light levels are extremely low (1)	2
04.3	<i>1 mark for each point.</i> • Reflectors can only focus parallel rays of direct sunlight onto the absorber (1) • Clouds, smoke and dust scatter the light so it cannot be focused and intensified (1)	2
04.4	<i>1 mark.</i> • Very large areas of collectors are needed to harness significant amounts of energy (and the changing angle of incidence reduces it further) (1)	1

Question	Marking guidance	Marks
04.5	Levels of response Level 3 (7-9 marks): Answer is comprehensive, relevant and logically structured. Shows detailed knowledge and understanding of the relevant scientific ideas and applies them accurately to the context. Evaluation/analysis is well supported by evidence and a clear judgement or conclusion is reached. Level 2 (4-6 marks): Answer is mostly relevant and shows some structure. Knowledge and understanding of relevant ideas is sound but application to the context or evaluation may be incomplete or lack detail. A judgement may be made but is not fully supported. Level 1 (1-3 marks): Answer is basic, with limited structure. Some relevant knowledge is shown but there are omissions or errors. Little application to the context and little or no evaluation. 0 marks: No relevant content. Indicative content (credit other relevant, accurate points) • Problems: intermittency (daily and seasonal cycles), unpredictable cloud cover, low energy density, changing angle of incidence, land requirements, water for cleaning in deserts, toxic wastes in manufacture (silicon tetrachloride, cadmium), efficiency loss at high temperature • Photothermal: evacuated tubes reduce conduction / convection losses; thermal stores (water, sand, concrete, molten salt) allow later use; passive solar architecture, brise soleil, light tubes; heat pumps deliver up to four times the energy used • Photovoltaic developments: multijunction cells absorbing more wavelengths, anti-reflective / moth-eye textured surfaces (smooth cells reflect 30%), PV-thermal hybrids cooling the cell, transparent PV in windows, heliostats keeping the optimum angle, self-cleaning nanohydrophobic surfaces • Concentrating solar power with molten-salt storage to 550 °C so steam turbines run when needed - overcomes intermittency • Integration: grid-connected solar farms, rooftop space avoiding land conflicts, batteries, pumped storage, links to energy storage and demand management • Evaluation: strong in sunny deserts / low latitudes, weaker in high latitudes in winter; cost falling; manufacturing impacts; no single technology solves all problems; justified conclusion	9
	Model answer - Level 3 (9 marks)	
	Solar power's problems are intrinsic: it is intermittent with daily and seasonal cycles, cloud makes it unpredictable and scatters light so it cannot be focused, its low energy density demands large collector areas, the angle of incidence keeps changing, cleaning in deserts uses scarce water, manufacturing PV produces toxic wastes such as silicon tetrachloride and cadmium, and PV efficiency falls as cells heat up.	

Question	Marking guidance	Marks
	New technology addresses most of these. Evacuated-tube photothermal panels cut conduction and convection losses, and thermal stores of water, sand, concrete or molten salt hold heat for later; passive solar design, brise soleil and light tubes reduce demand; heat pumps deliver up to four times the energy used to run them. Multijunction PV cells absorb more wavelengths, moth-eye anti-reflective surfaces stop the 30% of light a smooth cell reflects, PV-thermal hybrids cool the cell and use the heat, transparent PV turns windows into generators, heliostats keep panels at the optimum angle and nanohydrophobic surfaces self-clean. Concentrating solar power with molten salt stored at 550 °C runs steam turbines when electricity is wanted, directly overcoming intermittency, and grid-connected farms, rooftops that avoid land conflicts, batteries and pumped storage integrate the output.	
	Even so, no technology changes the fact that winter insolation at high latitudes is tiny, that CSP needs cloudless skies, or that manufacturing has impacts. Solar can dominate supply in sunny, low-latitude regions and contribute strongly elsewhere in summer, but overcoming its problems fully depends on storage and a diverse energy mix rather than on solar technology alone.	
	Weaker answer - Level 1 (2 marks)	
	Solar power has problems because it does not work at night or when it is cloudy, and solar panels are not very efficient. New technologies can help. Better solar panels are more efficient. Solar power can be stored in batteries for use at night. Mirrors can concentrate the sunlight to make it hotter. So new technologies can overcome most of the problems with solar power.	
	What makes the difference	
	• Level 1 identifies two problems and three vague technologies; Level 3 names each technology and explains which problem it solves and how.	
	• Level 3 acknowledges what technology cannot fix (high-latitude winters, cloud for CSP, manufacturing impacts) - the 'extent' in the question.	
	• Numbers (30% reflection, 550 °C, four-fold heat-pump output) show detailed knowledge applied to the argument.	
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 199-203; AQA spec 3.3.4.1.	
05.1	<i>Correct answer only.</i> • B - tiny pores between clay particles allow capillary rise; none in sand (1)	1
05.2	<i>1 mark for each point.</i> • Hygroscopic: held tightly by adhesive forces on particle surfaces; cannot drain and cannot be absorbed by plants (1) • Capillary: held in pores by surface tension; does not drain but can be absorbed by plants (1) • Gravitational: drains freely through large pores; available to plants only briefly as it passes (1)	3
05.3	<i>1 mark.</i> • Small round crumbs leave spaces giving good drainage, aeration and easy root penetration; large flat platy peds pack together reducing all three (1)	1

Question	Marking guidance	Marks
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 158-169; AQA spec 3.2.5.	
06.1	Levels of response Level 3 (7-9 marks): Answer is comprehensive, relevant and logically structured. Shows detailed knowledge and understanding of the relevant scientific ideas and applies them accurately to the context. Evaluation/analysis is well supported by evidence and a clear judgement or conclusion is reached. Level 2 (4-6 marks): Answer is mostly relevant and shows some structure. Knowledge and understanding of relevant ideas is sound but application to the context or evaluation may be incomplete or lack detail. A judgement may be made but is not fully supported. Level 1 (1-3 marks): Answer is basic, with limited structure. Some relevant knowledge is shown but there are omissions or errors. Little application to the context and little or no evaluation. 0 marks: No relevant content. Indicative content (credit other relevant, accurate points) • Fossil fuel technologies: secondary / tertiary recovery raising recovery from 20% to 60%; directional drilling and subsea wells; ROVs; fracking for tight oil and gas; tar sands / oil shales; coal gasification / liquefaction; enhanced gas recovery; methane hydrates; CCS (pre / post combustion, storage) • Limits: still finite (discoveries declining since the 1980s); rising energy and financial cost of unconventional sources; environmental impacts (aquifers, water use, tremors, land take, habitat damage); CO₂ and other pollution; CCS unproven at scale and impractical for vehicles • Nuclear: new uranium extraction (polymer adsorption from seawater, phosphate mining, coal ash); molten salt reactors; plutonium breeder and thorium reactors increasing fuel use many-fold; fusion as a long-term prospect • Limits: cost overruns, decommissioning, waste, public opposition, proliferation, embodied energy of low-grade uranium; fusion not commercial • Sustainability criteria: maintaining supply without unacceptable environmental, economic or social impact; comparison with renewables and energy conservation; energy gap argument • Judgement: technologies can extend supplies and reduce some impacts but cannot make non-renewables sustainable indefinitely; role as transition / base-load alongside renewables	9
	Model answer - Level 3 (8 marks)	
	Technology has repeatedly extended fossil-fuel supplies. Secondary and tertiary recovery raise the proportion of oil recovered from about 20% to 60%; directional drilling, subsea wells and ROVs open deep-water fields; fracking releases tight oil and gas; tar sands and oil shales, coal gasification and liquefaction convert lower-grade resources; and carbon capture and storage could reduce the CO ₂ impact. Nuclear fission can be stretched even further: uranium can be adsorbed from seawater with polymers or recovered from phosphate mining and coal ash, molten-salt reactors run more safely, and plutonium breeder and thorium reactors multiply the energy obtainable from each tonne of fuel, with fusion a long-term prospect.	

Question	Marking guidance	Marks
	None of this makes the resources renewable. Discoveries of conventional oil have declined since the 1980s, unconventional sources cost more energy and money per unit and damage aquifers, use huge volumes of water, cause tremors and take land, and CCS is unproven at scale. Nuclear projects overrun their budgets, decommissioning and long-lived waste remain unsolved, public opposition and proliferation constrain expansion, low-grade uranium has a high embodied energy, and fusion is not commercial.	
	Sustainability means maintaining supply without unacceptable environmental, economic or social impact. New technology can extend supplies for decades and cut some impacts, which matters for closing the energy gap while renewables and conservation scale up, but it cannot make non-renewable resources sustainable indefinitely. Their proper role is as a transition and base-load source alongside renewables, not a permanent solution.	
	Weaker answer - Level 2 (5 marks)	
	New technologies mean fossil fuels can last longer. Fracking gets gas out of shale rock and directional drilling reaches oil under the sea. Carbon capture and storage can stop the carbon dioxide going into the atmosphere. For nuclear power, breeder reactors and thorium reactors can use fuel more efficiently and fusion might work in the future. However fossil fuels are still non-renewable so they will run out eventually, and fracking can pollute groundwater. Nuclear waste is still a problem. So new technologies help but they cannot make fossil fuels and nuclear power fully sustainable.	
	What makes the difference	
	Level 2 reaches a sensible conclusion but supports it thinly; Level 3 gives specific evidence (20% to 60% recovery, declining discoveries, embodied energy of low-grade uranium).	
	Level 3 sets out a criterion for sustainability and judges against it - the hallmark of 'evaluate'.	
	Level 3 places the technologies in context (transition and base load alongside renewables) rather than treating them in isolation.	
06.2	1 mark. • 80-90% (1)	1
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 183-196; AQA spec 3.3.3-3.3.4.1.	
07.1	A correct final answer (with unit where asked) scores full marks. If the answer is wrong, award 1 mark for each correct step of working shown. - No reservoir range = $3.9 - 0.7 = 3.2$ m; with reservoir = $2.7 - 1.7 = 1.0$ m (1) - Reduction = 2.2 m (1)	2
07.2	1 mark for each point. - After heavy rainfall surplus water is stored, reducing peak flows / flooding downstream (1) - During dry periods the dam is opened to release water and maintain river levels (1)	2

Question	Marking guidance	Marks
07.3	1 mark for each point. • Deforestation / urbanisation reduce infiltration and interception (1) • So runoff reaches the river faster after rain and less water is stored to maintain flow in dry periods (1)	2
07.4	Levels of response Level 3 (7-9 marks): Answer is comprehensive, relevant and logically structured. Shows detailed knowledge and understanding of the relevant scientific ideas and applies them accurately to the context. Evaluation/analysis is well supported by evidence and a clear judgement or conclusion is reached. Level 2 (4-6 marks): Answer is mostly relevant and shows some structure. Knowledge and understanding of relevant ideas is sound but application to the context or evaluation may be incomplete or lack detail. A judgement may be made but is not fully supported. Level 1 (1-3 marks): Answer is basic, with limited structure. Some relevant knowledge is shown but there are omissions or errors. Little application to the context and little or no evaluation. 0 marks: No relevant content. Indicative content (credit other relevant, accurate points) • Site factors: topography - narrow exit from a large deep basin so a small dam holds a large volume; impermeable, strong bedrock without faults or seismic activity; large catchment with regular high rainfall and low evaporation; catchment land use with low pollution risk (pesticides, industry) and low soil erosion to avoid sedimentation; forest / vegetation in the flooded area decaying anaerobically releasing methane; access for workers and materials and distance to demand; value of the land lost (urban, conservation, agricultural) - loss-benefit analysis differs between countries • Alternatives for supply: rainwater collection, rivers, estuary barrages, desalination (energy-intensive so only where freshwater is inadequate), unexploited aquifers (N Africa, Kenya), inter-basin transfers (China, Australia, Wales-England), artificial aquifer recharge using surplus wet-season water, river-regulation reservoirs, afforestation to even out flow • Conservation strategies: low-water appliances, dual-flush toilets, xeriscaping, drip irrigation, grey-water re-use, leak repair (about 20% lost in the UK), metering • Treatment / pollution control allowing re-use of contaminated sources: sewage treatment, buffer strips, mine drainage control • Evaluation: reservoirs give large reliable supplies and flood control but flood land, cause habitat loss and methane; conservation is cheap and quick but limited by behaviour; transfers create conflicts between regions; desalination has high energy / carbon cost; combination needed as demand grows • Justified conclusion	9
	Model answer - Level 3 (8 marks)	

Question	Marking guidance	Marks
	A reservoir site is judged first on topography: a narrow exit from a large, deep basin lets a small, cheap dam hold a large volume. The bedrock must be impermeable so water is not lost and strong enough, without faults or seismic activity, to carry the dam. The catchment should be large with regular, high rainfall and low evaporation, and its land uses should not pose a pollution risk from industry or pesticides or cause the soil erosion that would silt the reservoir. Flooding forest or vegetation causes anaerobic decay and methane. Access for workers and materials, distance to the area of demand, and the value of the land lost - urban areas and nature reserves protected, farmland less so - complete a loss-benefit analysis that different countries weigh differently.	
	Supply can also be increased without new reservoirs: rainwater collection in cities, estuary barrages, desalination where freshwater is genuinely inadequate, newly found aquifers in North Africa and Kenya, inter-basin transfers as in China and from Wales to England, artificial recharge of aquifers with wet-season surplus, river-regulation reservoirs and afforestation to even out flow. Demand can be cut by low-water appliances, xeriscaping, drip irrigation, grey-water re-use, metering and repairing the leaks that lose about a fifth of UK supply, and treatment lets contaminated sources be re-used.	
	Reservoirs give large, reliable supplies and flood control but flood land and habitats and release methane; conservation is cheap and quick but limited by behaviour; transfers create conflicts between regions; desalination carries a high energy and carbon cost. As demand grows, the sustainable answer is conservation first, then a combination of sources matched to each region.	
	Weaker answer - Level 2 (4 marks)	
	A reservoir needs a large catchment area with lots of rain, impermeable rock so the water does not drain away, and a narrow valley so the dam is small. It should be near the people who need the water and not flood important land. Other ways to get water include desalination, which is expensive, and collecting rainwater. Water can be conserved by fixing leaks, using water meters and having low-flush toilets. All of these help make water supplies more sustainable.	
	What makes the difference	
	• Level 2 lists correct site factors but without the reasons (why impermeable, why the valley shape matters, why land use in the catchment matters, methane from flooded vegetation).	
	• Level 3 covers far more alternatives (aquifer recharge, river regulation, transfers, afforestation) and evaluates each; Level 2 evaluates only desalination.	
	• Level 3 ends with a prioritised judgement; Level 2 ends with 'all of these help'.	
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 122-127; AQA spec 3.2.2.4-3.2.2.5.	
08.1	<i>Correct answer only.</i> • C (1)	1

Question	Marking guidance	Marks
08.2	<i>1 mark for each point.</i> • Stratospheric ozone is natural and beneficial: absorbs UV, protecting living organisms (1) • Tropospheric ozone is a secondary pollutant (from NO_x photochemistry) that is toxic to plants and humans and is a greenhouse gas (1)	2
08.3	<i>1 mark for each point.</i> • HCFCs are less chemically stable / contain hydrogen so they are broken down in the troposphere (1) • So most do not persist long enough to reach the stratosphere where UV would release their chlorine (1)	2
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 108-112; AQA spec 3.2.1.3.	
09.1	<i>1 mark for each point.</i> • Screens (metal grills) trap floating / suspended non-biodegradable items (paper, plastic) which are landfilled or incinerated (1) • Grit traps: the channel widens so flow slows and stones / road grit sink out because there is not enough kinetic energy to carry them (1)	2
09.2	<i>1 mark for each point.</i> • The effluent stands in large tanks so the faecal / organic solids sink and are removed as sludge (1) • This removes over 95% of the organic matter from the fluid so the risk of deoxygenation of the river is greatly reduced (1)	2
09.3	<i>1 mark for each point.</i> • Aerobic bacteria digest / break down the remaining dissolved and suspended organic matter (1) • Air (or pure oxygen) is mixed in by paddle wheels or air stones so oxygen shortage does not limit the aerobic process (1) • The suspended bacteria collected in the secondary sedimentation tank are the 'activated sludge'; returning them maintains a large bacterial population so digestion is rapid (1)	3
09.4	<i>1 mark for each point.</i> • Effluent from secondary treatment may still contain dissolved inorganic nutrients (phosphates, nitrates) that cause eutrophication, and some bacteria (1) • Needed where the discharge site is ecologically sensitive or used by many people (bathing water, drinking water abstraction) (1) • Phosphate stripping with iron(III) sulfate; micro-strainers (very fine sieves) then UV light or chlorine to kill remaining bacteria (1)	3
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 269-272; AQA spec 3.4.3.2.9.	
10.1	<i>1 mark for the correct answer.</i> • $16.0 - 5.0 = \text{£}11 \text{ million}$ (1)	1
10.2	<i>1 mark for each point.</i> • It is rarely practical to reduce emissions to zero and the impact of low-level emissions may be acceptable, so an acceptable level must be decided (1) • ALARA: emissions should be As Low As Reasonably Achievable (1) • BATNEEC: the Best Available Technology Not Entailing Excessive Cost is chosen to achieve this (1)	3

Question	Marking guidance	Marks
10.3	1 mark for each point. - As industries expand or cities grow the number of pollutant sources increases (1) - So the total emissions / combined concentration rises even if each source is unchanged, and higher standards are needed (1)	2
10.4	Levels of response Level 3 (7-9 marks): Answer is comprehensive, relevant and logically structured. Shows detailed knowledge and understanding of the relevant scientific ideas and applies them accurately to the context. Evaluation/analysis is well supported by evidence and a clear judgement or conclusion is reached. Level 2 (4-6 marks): Answer is mostly relevant and shows some structure. Knowledge and understanding of relevant ideas is sound but application to the context or evaluation may be incomplete or lack detail. A judgement may be made but is not fully supported. Level 1 (1-3 marks): Answer is basic, with limited structure. Some relevant knowledge is shown but there are omissions or errors. Little application to the context and little or no evaluation. 0 marks: No relevant content. Indicative content (credit other relevant, accurate points) - Critical Pathway Analysis: predicting movement of mobile persistent pollutants (state of effluent, wind, currents, geology, pH / oxygen and solubility, bioaccumulation, food sources, half-lives) so monitoring focuses on sites at risk; mainly radioactive discharges; checked by sampling - Critical Group Monitoring: exposure of the most-exposed group monitored before health effects; if their risk is acceptable everyone else is safer; emissions reduced if not - Emission control strategies: location (marine discharges, downwind of cities, not over aquifers) and timing (avoiding temperature inversions, low river flow) - Principles: polluter pays (incentive depends on penalties and enforcement), precautionary principle (assume harm until shown otherwise; ignorance no excuse), ALARA / BATNEEC and the non-linear cost-efficiency relationship - Selection of methods: production prevention (desulfurisation), prevention of release (precipitators, catalytic converters), post-release remediation (oil spill clean-up, phytoremediation), alternative processes (electric vehicles, renewables, pyrethroids) - Evaluation: prevention usually cheaper and more effective than remediation; costs rise steeply near 100%; CPA relies on understanding of pathways; enforcement and international agreement needed for transboundary pollutants; judgement about acceptable risk is political as well as scientific - Justified conclusion	9
	Model answer - Level 3 (8 marks)	

Question	Marking guidance	Marks
	Deciding how much to control pollution starts with predicting where a pollutant will go. Critical Pathway Analysis uses the state of the effluent, wind and currents, geology, the effect of pH and oxygen on solubility, bioaccumulation and local food sources to predict whether a discharge will disperse harmlessly or concentrate somewhere sensitive; it is mainly used for radioactive discharges and means monitoring can focus on the sites at risk rather than sampling everywhere. Critical Group Monitoring then checks the exposure of the people most at risk from their lifestyle before any health effects occur: if their risk is acceptable everyone else's is lower, and if not, emissions are reduced.	
	The choice of control is guided by principles. The polluter pays principle gives a financial incentive to prevent damage, but only if penalties are high and polluters cannot escape responsibility. The precautionary principle assumes a waste is harmful until research shows otherwise, so ignorance is no defence. Because the cost of control rises steeply as emissions approach zero, emissions are set As Low As Reasonably Achievable using the Best Available Technology Not Entailing Excessive Cost. Where emission location and timing can be chosen (marine outfalls, downwind of towns, not over aquifers; avoiding temperature inversions) severity is reduced cheaply.	
	Overall, prevention of production (fuel desulfurisation) or of release (electrostatic precipitators, catalytic converters) is more effective than post-release remediation such as oil-spill clean-up, which never recovers all the pollutant. CPA depends on understanding pathways, and transboundary pollutants need international enforcement, but together these principles give a rational basis for deciding acceptable risk rather than aiming for an unaffordable zero.	
	Weaker answer - Level 1 (3 marks)	
	Pollution can be controlled in lots of ways. Critical Pathway Analysis looks at where pollution goes and Critical Group Monitoring looks at people. The polluter pays principle means the person who pollutes has to pay. The precautionary principle means being careful. Pollution can be prevented, or cleaned up afterwards with things like booms for oil spills. Electric cars are an alternative process. Pollution control can be expensive so ALARA is used. All of these are good ways of controlling pollution.	
	What makes the difference	
	• The Level 3 answer explains <i>how</i> each principle works (why penalties matter, why costs rise near zero emissions); the weak answer only names them.	
	• The Level 3 answer groups the material logically (predict, decide, select) rather than listing everything at the same weight.	
	• 'Evaluate' needs comparison and a judgement: prevention vs remediation, CPA's dependence on understanding pathways, and a conclusion about acceptable risk. The weak answer ends with 'all of these are good'.	
	• Precise examples (desulfurisation, precipitators, catalytic converters, temperature inversions) show applied knowledge; 'things like booms' does not.	

Question	Marking guidance	Marks
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 243-245, 303-304; AQA spec 3.4.3.1, 3.4.3.3.	
11.1	Explain how feedback mechanisms and tipping points influence the rate of global climate change and discuss the implications for the strategies needed to control it. Levels of response Level 5 (21-25 marks): Comprehensive and detailed knowledge and understanding drawn from across the specification, applied accurately to the question. Argument is coherent, well-structured and supported by a wide range of relevant, well-chosen examples and quantitative detail where appropriate. Interconnections between topics are made explicitly and a clear, justified conclusion is reached. Level 4 (16-20 marks): Detailed knowledge and understanding with good application to the question. Argument is logically organised with relevant examples; some links between different areas of the specification are made. Conclusions are drawn but may be less fully justified. Level 3 (11-15 marks): Sound knowledge and understanding, mostly applied to the question. Some structure and relevant examples, but coverage may be uneven or descriptive rather than analytical. Limited linking of topics. Level 2 (6-10 marks): Basic knowledge and understanding with partial relevance. Answer is largely descriptive with few examples and limited structure; some errors or omissions. Level 1 (1-5 marks): Limited, fragmented knowledge with little relevance to the question. Little structure; examples absent or inappropriate. 0 marks: No relevant content. Indicative content (students are not expected to cover all of these; credit other relevant material) • Negative feedback: increased low-level cloud (albedo), increased photosynthesis and sequestration; hydrological cycle evaporation-precipitation • Positive feedback: melting permafrost (methane), reduced albedo of snow / ice / sea ice, methane hydrate release, ocean acidification and coral loss, forest and peat fires, soil decomposition, water vapour, cirrus clouds • Tipping points: self-sustaining processes; why control must precede them; examples • Implications: urgency and precautionary principle; need for deep cuts in greenhouse gases (energy, transport, buildings, agriculture, forestry, CCS) rather than only adaptation; geoengineering risks • Difficulty of prediction because feedbacks interact at different scales; models; international agreements and per capita footprints • Judgement on whether current strategies are adequate Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 103-107, 371-372; AQA spec 3.2.1.2, 3.6.1.	25

Question	Marking guidance	Marks
11.2	Discuss the extent to which energy conservation technologies could reduce the need for new energy supplies in a developed country. Levels of response Level 5 (21-25 marks): Comprehensive and detailed knowledge and understanding drawn from across the specification, applied accurately to the question. Argument is coherent, well-structured and supported by a wide range of relevant, well-chosen examples and quantitative detail where appropriate. Interconnections between topics are made explicitly and a clear, justified conclusion is reached. Level 4 (16-20 marks): Detailed knowledge and understanding with good application to the question. Argument is logically organised with relevant examples; some links between different areas of the specification are made. Conclusions are drawn but may be less fully justified. Level 3 (11-15 marks): Sound knowledge and understanding, mostly applied to the question. Some structure and relevant examples, but coverage may be uneven or descriptive rather than analytical. Limited linking of topics. Level 2 (6-10 marks): Basic knowledge and understanding with partial relevance. Answer is largely descriptive with few examples and limited structure; some errors or omissions. Level 1 (1-5 marks): Limited, fragmented knowledge with little relevance to the question. Little structure; examples absent or inappropriate. 0 marks: No relevant content. Indicative content (students are not expected to cover all of these; credit other relevant material) • Scale of the problem: how energy is used (transport, buildings, industry, water); links between affluence and per capita use • Transport: bulk / integrated transport, ATM, vehicle design (aerodynamics, mass, tyres, KERS, combustion efficiency), low embodied energy, design for end of life, driver behaviour, electric vehicles • Buildings: orientation and passive solar, SA:V, thermal mass, low embodied energy materials, earth sheltering, glazing (low-e, inert gas, vacuum), insulation optimum, heat exchangers, automatic ventilation, occupancy sensors, thermostats, low-energy appliances, behaviour • Industry: heat recovery and exchangers, insulation and high-volume storage, CHP, integrated manufacture, recycling and mass reduction, high-voltage grid, peak shaving, ICT management • Limits: rebound effect, cost and payback, existing building stock, embodied energy of replacements, behaviour • Evaluation with quantitative examples; comparison with the cost of new supply; conclusion that conservation is the cheapest first step but cannot alone meet demand growth Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 170-174, 225-235; AQA spec 3.3.4.2, 3.3.1.	25