

A-level

ENVIRONMENTAL SCIENCE

Paper 1 - Generated practice paper Set 08

Mark scheme

120 marks: Questions 1-10 (95 marks) plus one essay from Question 11 (25 marks).

Marking guidance

- The number in brackets after each marking point is the mark it earns; the note above the points says how many are needed.
- Where a question asks for a fixed number of points (eg *two reasons*), credit only the first points given.
- Alternative correct wording and other relevant, accurate points are credited.
- For levels-of-response questions, first determine the level using the descriptors, then position the mark within the level using the indicative content.
- Calculations: credit correct working (method marks) even if the final answer is wrong; incorrect answers with no working score 0.

Textbook references: every question below cites the printed page numbers in R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018) from which the content is drawn, together with the AQA 7447 specification reference.

Question	Marking guidance	Marks
01.1	<i>1 mark for the correct answer.</i> • $16.0 - 5.0 = \text{£}11 \text{ million}$ (1)	1
01.2	<i>1 mark for each point.</i> • It is rarely practical to reduce emissions to zero and the impact of low-level emissions may be acceptable, so an acceptable level must be decided (1) • ALARA: emissions should be As Low As Reasonably Achievable (1) • BATNEEC: the Best Available Technology Not Entailing Excessive Cost is chosen to achieve this (1)	3
01.3	<i>1 mark for each point.</i> • As industries expand or cities grow the number of pollutant sources increases (1) • So the total emissions / combined concentration rises even if each source is unchanged, and higher standards are needed (1)	2

Question	Marking guidance	Marks
01.4	Levels of response Level 3 (7-9 marks): Answer is comprehensive, relevant and logically structured. Shows detailed knowledge and understanding of the relevant scientific ideas and applies them accurately to the context. Evaluation/analysis is well supported by evidence and a clear judgement or conclusion is reached. Level 2 (4-6 marks): Answer is mostly relevant and shows some structure. Knowledge and understanding of relevant ideas is sound but application to the context or evaluation may be incomplete or lack detail. A judgement may be made but is not fully supported. Level 1 (1-3 marks): Answer is basic, with limited structure. Some relevant knowledge is shown but there are omissions or errors. Little application to the context and little or no evaluation. 0 marks: No relevant content. Indicative content (credit other relevant, accurate points) • Critical Pathway Analysis: predicting movement of mobile persistent pollutants (state of effluent, wind, currents, geology, pH / oxygen and solubility, bioaccumulation, food sources, half-lives) so monitoring focuses on sites at risk; mainly radioactive discharges; checked by sampling • Critical Group Monitoring: exposure of the most-exposed group monitored before health effects; if their risk is acceptable everyone else is safer; emissions reduced if not • Emission control strategies: location (marine discharges, downwind of cities, not over aquifers) and timing (avoiding temperature inversions, low river flow) • Principles: polluter pays (incentive depends on penalties and enforcement), precautionary principle (assume harm until shown otherwise; ignorance no excuse), ALARA / BATNEEC and the non-linear cost-efficiency relationship • Selection of methods: production prevention (desulfurisation), prevention of release (precipitators, catalytic converters), post-release remediation (oil spill clean-up, phytoremediation), alternative processes (electric vehicles, renewables, pyrethroids) • Evaluation: prevention usually cheaper and more effective than remediation; costs rise steeply near 100%; CPA relies on understanding of pathways; enforcement and international agreement needed for transboundary pollutants; judgement about acceptable risk is political as well as scientific • Justified conclusion	9
	Model answer - Level 3 (8 marks)	
	Deciding how much to control pollution starts with predicting where a pollutant will go. Critical Pathway Analysis uses the state of the effluent, wind and currents, geology, the effect of pH and oxygen on solubility, bioaccumulation and local food sources to predict whether a discharge will disperse harmlessly or concentrate somewhere sensitive; it is mainly used for radioactive discharges and means monitoring can focus on the sites at risk rather than sampling everywhere. Critical Group Monitoring then checks the exposure of the people most at risk from their lifestyle before any health effects occur: if their risk is acceptable everyone else's is lower, and if not, emissions are reduced.	

Question	Marking guidance	Marks
	The choice of control is guided by principles. The polluter pays principle gives a financial incentive to prevent damage, but only if penalties are high and polluters cannot escape responsibility. The precautionary principle assumes a waste is harmful until research shows otherwise, so ignorance is no defence. Because the cost of control rises steeply as emissions approach zero, emissions are set As Low As Reasonably Achievable using the Best Available Technology Not Entailing Excessive Cost. Where emission location and timing can be chosen (marine outfalls, downwind of towns, not over aquifers; avoiding temperature inversions) severity is reduced cheaply.	
	Overall, prevention of production (fuel desulfurisation) or of release (electrostatic precipitators, catalytic converters) is more effective than post-release remediation such as oil-spill clean-up, which never recovers all the pollutant. CPA depends on understanding pathways, and transboundary pollutants need international enforcement, but together these principles give a rational basis for deciding acceptable risk rather than aiming for an unaffordable zero.	
	Weaker answer - Level 1 (3 marks)	
	Pollution can be controlled in lots of ways. Critical Pathway Analysis looks at where pollution goes and Critical Group Monitoring looks at people. The polluter pays principle means the person who pollutes has to pay. The precautionary principle means being careful. Pollution can be prevented, or cleaned up afterwards with things like booms for oil spills. Electric cars are an alternative process. Pollution control can be expensive so ALARA is used. All of these are good ways of controlling pollution.	
	What makes the difference	
	The Level 3 answer explains <i>how</i> each principle works (why penalties matter, why costs rise near zero emissions); the weak answer only names them.	
	The Level 3 answer groups the material logically (predict, decide, select) rather than listing everything at the same weight.	
	'Evaluate' needs comparison and a judgement: prevention vs remediation, CPA's dependence on understanding pathways, and a conclusion about acceptable risk. The weak answer ends with 'all of these are good'.	
	Precise examples (desulfurisation, precipitators, catalytic converters, temperature inversions) show applied knowledge; 'things like booms' does not.	
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 243-245, 303-304; AQA spec 3.4.3.1, 3.4.3.3.	
02.1	<i>Correct answer only.</i> C (1)	1
02.2	<i>1 mark for each point.</i> - Stratospheric ozone is natural and beneficial: absorbs UV, protecting living organisms (1) - Tropospheric ozone is a secondary pollutant (from NO_x photochemistry) that is toxic to plants and humans and is a greenhouse gas (1)	2

Question	Marking guidance	Marks
02.3	<i>1 mark for each point.</i> • HCFCs are less chemically stable / contain hydrogen so they are broken down in the troposphere (1) • So most do not persist long enough to reach the stratosphere where UV would release their chlorine (1)	2
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 108-112; AQA spec 3.2.1.3.	
03.1	<i>1 mark for each point.</i> • Terracing: sloping land divided into narrow level fields held by retaining walls along contours; water slows as it crosses each terrace and infiltrates instead of running off (1) • Tied ridging: on nearly flat land a criss-cross of intersecting ridges retains rainwater, increasing infiltration and preventing runoff (1) • Windbreaks: hedgerows / tree rows reduce wind velocity (for up to 30 times their height) so the wind has less kinetic energy to carry particles; protect bare fields after harvest (1) • Mulching: organic matter on the surface protects soil from raindrop impact and wind; decomposes to humus which binds particles; retains moisture (1) • Strip cropping: strips of different crops harvested at different times (at 90° to the wind) so there is always a crop protecting part of the field; slows runoff (1)	5
03.2	<i>1 mark for each point.</i> • No frequent replanting / soil disturbance (ploughing) that breaks up soil structure and exposes particles (1) • Permanent root systems and canopy cover protect the soil all year (1)	2
03.3	<i>Any 3 from the points below - 1 mark each, maximum 3.</i> • Control stocking density so vegetation regrows faster than it is eaten (1) • Restrict access to vulnerable areas such as river banks (fencing) (1) • Move / remove livestock at high-risk times, eg after heavy rain when soil is wet (1) • Rotational grazing to rest pastures (1)	3
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 164-166; AQA spec 3.2.5.3.	
04.1	<i>A correct final answer (with unit where asked) scores full marks. If the answer is wrong, award 1 mark for each correct step of working shown.</i> • $(7.7 - 3.9) / 7.7 \times 100$ (1) • = 49.4% (accept 49%) (1)	2
04.2	<i>1 mark for each point.</i> • Floating sea ice has already displaced its own mass of water; when it melts it contracts and occupies the same volume as the ice below the water line (1) • Melting land ice (glaciers, ice sheets) adds new water to the sea, increasing its volume (1)	2
04.3	<i>1 mark for each point.</i> • Ice and snow have a high albedo and reflect most sunlight; open sea water has a low albedo (1) • As ice area shrinks more sunlight is absorbed by the sea and converted to heat, raising temperatures (1) • This melts more ice: a positive feedback mechanism; thinner ice melts more easily each summer (1)	3

Question	Marking guidance	Marks
04.4	<i>1 mark for each point.</i> - Thermal expansion: warmer sea water expands (slow because of the huge volume and high heat capacity; only surface water warms directly) (1) - Melting of land ice (glaciers, Greenland and Antarctic ice sheets) adds water to the oceans (1)	2
04.5	<i>1 mark.</i> Ice shelves grounded on the seabed hold back / block the forward movement of the glaciers or ice sheet behind them; once removed the land ice flows faster (eg West Antarctica) (1)	1
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 94-96; AQA spec 3.2.1.2.	
05.1	<i>Correct answer only.</i> Aerobic decomposition produces little methane and returns nutrients to the soil (1)	1
05.2	<i>1 mark for each point.</i> - It may contain concentrated heavy metals / toxic residues (1) - It is stored in solid form at high pH / in hazardous-waste landfill so the metals stay insoluble (1)	2
05.3	<i>Any 2 from the points below - 1 mark each, maximum 2.</i> - Impermeable polymer / clay liner to stop leachate escaping (1) - Collection and treatment of leachate (1) - Collection of methane and use as fuel (1) - Daily covering of waste / final capping and restoration (1)	2
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 279-285; AQA spec 3.4.3.2.12.	
06.1	<i>1 mark for each point.</i> - Ozone is very low overnight / early morning, rises from about 08:00, peaks at about 80 units at 14:00 and falls in the evening (1) - Ozone is a secondary pollutant formed by photochemical reactions requiring sunlight (UV), so it peaks in the afternoon after several hours of sunlight (1) - NO₂ (from morning traffic) is broken down by UV to NO and monatomic oxygen; monatomic oxygen reacts with O₂ to form ozone (1) - Ozone lags behind the NO / NO₂ peaks (which are produced by the morning rush-hour traffic) because the reactions take time; falls at night when there is no sunlight (1)	4
06.2	<i>1 mark for each point.</i> - NO is the primary pollutant produced in engines when nitrogen and oxygen react at high temperature / pressure (1) - NO is oxidised in the atmosphere (by oxygen / ozone) to NO₂, a secondary pollutant (1)	2
06.3	<i>1 mark for each point.</i> - PANs (peroxyacetyl nitrates) (1) - Eye irritation / breathing difficulty / asthma / emphysema / increased risk of heart attacks (toxic at much lower concentrations than NO_x) (1)	2
06.4	<i>Any 2 from the points below - 1 mark each, maximum 2.</i> - Heavy vehicle use giving high NO_x and hydrocarbon emissions (1) - Sunny climate providing the UV for photochemical reactions (1) - Valley / basin topography and frequent temperature inversions trapping pollutants (1)	2

Question	Marking guidance	Marks
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 248-249, 253-254; AQA spec 3.4.3.2.3-3.4.3.2.4.	
07.1	<i>1 mark for each point.</i> - Minerals can only be exploited where they were deposited (no choice of location), unlike housing, roads or ports (1) - Land take is larger than the mine void: buildings, access roads, overburden and spoil heaps, buffer zones; open-cast mines take far more land than deep mines (1)	2
07.2	<i>1 mark for each point.</i> - Dust: water sprays on roads / blasting areas make particles heavier and clump so they settle (1) - Noise: baffle mounds / embankments absorb and deflect; blasting at set, predictable daytime hours; quieter machinery (1) - Turbid water: sedimentation lagoons where water stands until solids settle before discharge (1) - Leachate: collect drainage water and pass through crushed limestone to neutralise acid and immobilise toxic metals (1) - Amenity: landscaping and tree planting to screen the mine; restoration plans agreed as a condition of planning permission (1)	5
07.3	<i>1 mark for each point.</i> - Landscaping to reduce gradients, compaction, drainage to prevent waterlogging, adding soil / nutrients and planting vegetation whose roots bind the surface (1) - At Aberfan a waterlogged coal-mine spoil heap became unstable and slid into the village (1) - Killing 144 people, mainly children in the primary school (1)	3
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 139-142; AQA spec 3.2.3.6.	

Question	Marking guidance	Marks
08.1	Levels of response Level 3 (7-9 marks): Answer is comprehensive, relevant and logically structured. Shows detailed knowledge and understanding of the relevant scientific ideas and applies them accurately to the context. Evaluation/analysis is well supported by evidence and a clear judgement or conclusion is reached. Level 2 (4-6 marks): Answer is mostly relevant and shows some structure. Knowledge and understanding of relevant ideas is sound but application to the context or evaluation may be incomplete or lack detail. A judgement may be made but is not fully supported. Level 1 (1-3 marks): Answer is basic, with limited structure. Some relevant knowledge is shown but there are omissions or errors. Little application to the context and little or no evaluation. 0 marks: No relevant content. Indicative content (credit other relevant, accurate points) • Uses / benefits: nuclear electricity (low carbon, high energy density), medicine (X-rays, CT, radiotherapy, tracers, sterilising equipment), industry (thickness gauges, polymer cross-linking, testing turbines, oil exploration), agriculture (food irradiation, sterile male technique, mutation breeding), research tracers, smoke detectors, ship / submarine propulsion • Risks: free radical production, DNA damage, mutation, cancer; acute and chronic, somatic and gonadic effects; contamination vs exposure; activation products; long-lived wastes; accidents (Chernobyl, Fukushima); weapons fallout • Factors affecting risk: type of radiation (alpha, beta, gamma, neutrons - penetration, RBE / weighting factors), half-life, dose (Gy, Sv), route of exposure • Risk:benefit analysis and why it is difficult (latency, alternative causes, poor exposure data, risks and benefits to different people, offsets such as avoided surgery) • Principles: ALARA, BATNEEC; closed sources, remote handling, absorbers / shielding, distance (inverse square law), time, protective clothing, decontamination, potassium iodide • Monitoring: dosimeters, film badges, air and contamination monitors; environmental monitoring via CPA and CGM; waste categories and disposal (vitrification, encapsulation, Drigg) • Evaluation / judgement: benefits generally outweigh risks when controls are applied; public perception vs actual risk (background radon 50% of dose vs <1% from nuclear industry)	9
	Model answer - Level 3 (8 marks)	
	Ionising radiation is used because it does things nothing else can: nuclear fission generates low-carbon electricity from fuel of extraordinary energy density; medicine relies on X-rays and CT scans, radiotherapy, tracers and gamma sterilisation of equipment; industry uses thickness gauges, cross-links polymers, tests turbine blades and explores for oil; and agriculture uses irradiation to preserve food and sterilise insect pests. The risks arise because radiation produces free radicals that damage DNA, causing mutation and cancer, with acute and chronic, somatic and gonadic effects; contamination is worse than exposure because the source stays with the person; and activation products, long-lived wastes, accidents at Chernobyl and Fukushima and weapons fallout add environmental risks.	

Question	Marking guidance	Marks
	Risk depends on the type of radiation - alpha is barely penetrating but has a weighting factor of 20 - on half-life, on dose in grays and sieverts and on the route of exposure. Weighing risks against benefits is difficult because cancers appear years later with many other possible causes, exposure data are poor, the people who benefit are often not those at risk, and benefits such as avoided surgery are hard to quantify.	
	Control follows ALARA and BATNEEC: closed sources, remote handling, shielding, distance under the inverse-square law, limiting time, protective clothing, decontamination and potassium iodide against iodine-131. Workers wear dosimeters and film badges and pass contamination monitors; discharges are managed by Critical Pathway Analysis and Critical Group Monitoring; wastes are vitrified, encapsulated or stored at licensed sites. With these controls the benefits generally outweigh the risks - natural radon supplies about half the average dose and the nuclear industry under one per cent - although public perception of risk remains far higher than the measured risk.	
	Weaker answer - Level 2 (5 marks)	
	Ionising radiation is used in nuclear power stations to make electricity, in hospitals for X-rays and treating cancer, and in industry. The risks are that radiation damages DNA and causes cancer, and accidents like Chernobyl release radiation into the environment. Nuclear waste stays dangerous for a long time. Workers are protected by shielding, keeping their distance and wearing film badges to measure their dose. The public is protected by monitoring around nuclear sites. Overall the benefits are worth the risks if it is controlled properly.	
	What makes the difference	
	• Level 2 covers uses, risks, controls and a judgement, but each briefly; Level 3 adds the factors that determine risk (type, half-life, dose units, route) and why risk-benefit analysis is difficult.	
	• Level 3 names the principles (ALARA, BATNEEC, inverse square law, CPA / CGM) rather than describing practice loosely.	
	• The judgement in Level 3 is supported with evidence (radon vs nuclear industry doses); Level 2's is an opinion.	
08.2	<i>1 mark.</i> • Consumers of the electricity may live in a different country / region from the uranium miners or the communities near waste stores who bear the risks (1)	1
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 295-304; AQA spec 3.4.3.2.14.	
09.1	<i>Correct answer only.</i> • B - rivers are accessible over a large area with few natural contaminants (1)	1
09.2	<i>1 mark for each point.</i> • Potable / public supply: no pathogens, low toxins, good appearance / taste / smell (public health) (1) • Industrial boiler / cooling water: soft water with low calcium so mineral deposits do not block pipes or reduce heat exchange; spray irrigation: low turbidity to avoid blocked pipes and low heavy metals (1)	2

Question	Marking guidance	Marks
09.3	<i>1 mark for each point.</i> • Canals / pipes move water from areas with a surplus to areas with a shortage (eg Wales to England, China's Yangtze transfers) (1) • Disadvantage: high cost / energy for pumping; ecological impacts on the donor river; transfer of pollutants or invasive species; political conflict (1)	2
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 122-128; AQA spec 3.2.2.4-3.2.2.5.	
10.1	<i>1 mark for each point.</i> • t-test (or Mann-Whitney U if not normally distributed) (1) • Comparing two means of counted / measured data from two independent samples (1)	2
10.2	<i>1 mark for each point.</i> • The difference is statistically significant (less than 1% probability that it arose by chance) (1) • The null hypothesis (no difference between fields) is rejected; the organic field has significantly more earthworms (1)	2
10.3	<i>1 mark for each point.</i> • A significant difference does not show a causal relationship (1) • Other variables (soil type, moisture, pH, cultivation history) may differ between the two fields and cause the difference (1)	2

Question	Marking guidance	Marks
10.4	Levels of response Level 3 (7-9 marks): Answer is comprehensive, relevant and logically structured. Shows detailed knowledge and understanding of the relevant scientific ideas and applies them accurately to the context. Evaluation/analysis is well supported by evidence and a clear judgement or conclusion is reached. Level 2 (4-6 marks): Answer is mostly relevant and shows some structure. Knowledge and understanding of relevant ideas is sound but application to the context or evaluation may be incomplete or lack detail. A judgement may be made but is not fully supported. Level 1 (1-3 marks): Answer is basic, with limited structure. Some relevant knowledge is shown but there are omissions or errors. Little application to the context and little or no evaluation. 0 marks: No relevant content. Indicative content (credit other relevant, accurate points) • Scientific methodology: identifying the topic, reviewing existing knowledge, formulating a testable hypothesis and null hypothesis, designing the study, analysing and drawing conclusions, planning further research • Sample location: random (grid coordinates / numbered sites) or systematic (transects, fixed intervals) to avoid bias; interval chosen so variation is detected without excess data • Sample timing: diurnal, seasonal, weather-related and long-term changes; sampling on different occasions; interval matched to rate of change • Sample size and number: larger and more samples for non-homogeneous variables; running mean and standard deviation show when the mean is reliable; preliminary study to decide • Standardisation and control of variables; accuracy, precision, reliability, representativeness; anomalies and repeats; calibration of equipment; appropriate techniques and risk management • Statistical analysis: choosing the test (Spearman, chi-squared, t-test, Mann-Whitney), significance and p-values, error bars, correlation vs causation • Evaluation: trade-offs between cost, time, disturbance and reliability; limitations of sub-sampling; justified conclusion	9
	Model answer - Level 3 (8 marks)	
	A valid investigation begins with a clear, testable hypothesis and a null hypothesis, informed by existing knowledge, so that the data collected can actually accept or reject it. The first design decision is sample location: random sampling (grid coordinates or numbered sites) or systematic sampling along transects avoids the bias that would come from choosing convenient sites, and a preliminary study shows the interval needed to detect variation without collecting unnecessary data.	

Question	Marking guidance	Marks
	Timing matters because many variables change diurnally, seasonally or with weather, so samples on different occasions are needed and the interval must match the rate of change. Sample size and number depend on how variable the population is: a running mean shows when enough samples have been taken and the standard deviation shows the scatter around the mean. Techniques must be standardised so results from different sites, times or researchers are comparable, other variables controlled or monitored, and equipment calibrated so that precise readings are also accurate; anomalies should be repeated rather than ignored.	
	Finally the analysis must be chosen to suit the data - Spearman's rank for correlation, chi-squared for frequencies, a t-test for two means or Mann-Whitney U for medians - so that significance ($p < 0.05$) can be assessed, remembering that a significant correlation does not prove causation. Every decision trades reliability against cost, time and disturbance; sub-samples can only estimate the whole, so the most valid study is the one whose sampling design makes its limitations explicit.	
	Weaker answer - Level 2 (5 marks)	
	When planning fieldwork you need a hypothesis. You should choose sites randomly so it is not biased, for example using random numbers. You need to take enough samples and repeat them so the results are reliable. The method should be the same each time. You should measure accurately with calibrated equipment. Then you do a statistical test such as a t-test to see if the results are significant. If p is less than 0.05 the result is significant. This makes the conclusions valid.	
	What makes the difference	
	• Level 2 is sound but generic: it says 'enough samples' where Level 3 explains how a running mean and standard deviation tell you how many.	
	• Level 3 covers timing and the choice between statistical tests; Level 2 mentions one test only.	
	• The evaluation is missing from Level 2 - there is no discussion of trade-offs or of correlation vs causation, so it cannot reach the top level however accurate it is.	
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 390-393, 420-423; AQA spec 3.7.1, 3.7.2.3.	

Question	Marking guidance	Marks
11.1	Discuss how the properties of solar power and hydroelectric power affect their use, and evaluate how new technologies could increase their contribution to energy supplies. Levels of response Level 5 (21-25 marks): Comprehensive and detailed knowledge and understanding drawn from across the specification, applied accurately to the question. Argument is coherent, well-structured and supported by a wide range of relevant, well-chosen examples and quantitative detail where appropriate. Interconnections between topics are made explicitly and a clear, justified conclusion is reached. Level 4 (16-20 marks): Detailed knowledge and understanding with good application to the question. Argument is logically organised with relevant examples; some links between different areas of the specification are made. Conclusions are drawn but may be less fully justified. Level 3 (11-15 marks): Sound knowledge and understanding, mostly applied to the question. Some structure and relevant examples, but coverage may be uneven or descriptive rather than analytical. Limited linking of topics. Level 2 (6-10 marks): Basic knowledge and understanding with partial relevance. Answer is largely descriptive with few examples and limited structure; some errors or omissions. Level 1 (1-5 marks): Limited, fragmented knowledge with little relevance to the question. Little structure; examples absent or inappropriate. 0 marks: No relevant content. Indicative content (students are not expected to cover all of these; credit other relevant material) • Problematic properties of solar: intermittency, unreliability from cloud, low energy density, changing angle; locational constraints (deserts, latitude) • Harnessing solar: photothermal, thermal stores, passive architecture, heat pumps, PV principles and cell efficiencies, solar farms; environmental impacts of manufacture and land use • New solar technologies: multijunction, anti-reflective surfaces, CSP with molten salt, PV-thermal hybrids, transparent PV, heliostats, self-cleaning • HEP: gravitational potential energy, locational constraints (catchment, rainfall, turbidity, impermeable rock, seismic, topography, land use, distance), impacts on habitats, sediment, methane, communities • Energy storage and matching supply to demand: pumped storage, batteries, grid links; combining resources • Evaluation and justified conclusion on how far these resources can replace fossil fuels Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 196-203, 217-224; AQA spec 3.3.4.1.	25

Question	Marking guidance	Marks
11.2	Discuss how the design of a sampling programme and the choice of statistical analysis affect the validity of conclusions drawn from environmental investigations. Levels of response Level 5 (21-25 marks): Comprehensive and detailed knowledge and understanding drawn from across the specification, applied accurately to the question. Argument is coherent, well-structured and supported by a wide range of relevant, well-chosen examples and quantitative detail where appropriate. Interconnections between topics are made explicitly and a clear, justified conclusion is reached. Level 4 (16-20 marks): Detailed knowledge and understanding with good application to the question. Argument is logically organised with relevant examples; some links between different areas of the specification are made. Conclusions are drawn but may be less fully justified. Level 3 (11-15 marks): Sound knowledge and understanding, mostly applied to the question. Some structure and relevant examples, but coverage may be uneven or descriptive rather than analytical. Limited linking of topics. Level 2 (6-10 marks): Basic knowledge and understanding with partial relevance. Answer is largely descriptive with few examples and limited structure; some errors or omissions. Level 1 (1-5 marks): Limited, fragmented knowledge with little relevance to the question. Little structure; examples absent or inappropriate. 0 marks: No relevant content. Indicative content (students are not expected to cover all of these; credit other relevant material) • Attributes: accuracy, precision, representative samples, reliability, anomalies, validity; hypothesis and null hypothesis; preliminary studies • Sampling design: random vs systematic location and avoiding bias; timing (diurnal, seasonal, long-term, weather); sample size and number and the running mean; standardisation of technique and control of other variables • Techniques for abiotic and biotic factors and their limitations (quadrats, transects, traps, mark-release-recapture assumptions, keys, meters and calibration) • Statistics: variability, standard deviation and error bars, significance and p-values, correlation vs causation; choosing Spearman's rank, chi-squared, t-test, Mann-Whitney U • Application to Paper 1 topics: monitoring pollution (noise, air quality, water), climate proxies, energy surveys, soil analysis • Evaluation of trade-offs (cost, time, disturbance) and justified conclusion Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 390-393, 420-423; AQA spec 3.7.	25