

A-level

ENVIRONMENTAL SCIENCE

Questions by topic: Ionising radiation - Set 1

Mark scheme

AQA spec 3.4.3.2.14; Pollution; textbook pp. 295-304

Marking guidance

- The number in brackets after each marking point is the mark it earns; the note above the points says how many are needed.
- Where a question asks for a fixed number of points (eg *two reasons*), credit only the first points given.
- Alternative correct wording and other relevant, accurate points are credited.
- For levels-of-response questions, first determine the level using the descriptors, then position the mark within the level using the indicative content.
- Calculations: credit correct working (method marks) even if the final answer is wrong; incorrect answers with no working score 0.

Textbook references: every question below cites the printed page numbers in R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018) from which the content is drawn, together with the AQA 7447 specification reference.

Question	Marking guidance	Marks
01.1	<i>1 mark.</i> • The time taken for half of the atoms of a radioactive isotope to decay (activity halves) (1)	1
01.2	<i>A correct final answer (with unit where asked) scores full marks. If the answer is wrong, award 1 mark for each correct step of working shown.</i> • $32 / 8 = 4$ half-lives (1) • $6400 / 2^4 = 400$ Bq (1)	2
01.3	<i>1 mark for each point.</i> • Short half-life isotopes (I-131) release all their radiation quickly: dangerous but only briefly so short-term precautions (potassium iodide tablets, evacuation) are sufficient (1) • Very long half-life isotopes (U-238) emit only small amounts of radiation in any period so the level of danger is low (1) • Decades-long half-lives combine a high rate of radiation release with persistence for most or all of a human lifetime, so short-term protection is inadequate (land contaminated for generations) (1)	3
01.4	<i>1 mark for each point.</i> • Alpha particles have very low penetrating power and are absorbed by clothing / dead skin so external sources cause little exposure (1) • Inside the body the alpha particles are absorbed in a very small mass of tissue so damage is concentrated (high RBE - weighting factor 20) (1) • Long half-life means it continues to emit for the rest of the person's life / cannot be excreted quickly (contamination not just exposure) (1)	3
01.5	<i>1 mark.</i> • A previously stable nucleus that becomes radioactive after absorbing a neutron (eg in reactor structures), later decaying to emit ionising radiation (1)	1

Question	Marking guidance	Marks
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 299-301; AQA spec 3.4.3.2.14.	
02.1	<i>1 mark for each point.</i> • Radiation absorbed by tissue produces free radicals (ions with unpaired electrons), mostly from water, which are highly reactive (1) • Free radicals damage DNA / chromosomes in the nucleus causing mutations (cancer, inherited effects) - rapidly dividing cells (skin, gut, bone marrow) most affected (1) • Damage to other cell parts can stop the cell functioning or kill it; low damage may be repaired by the intact nucleus (1)	3
02.2	<i>1 mark for each point.</i> • Acute: effects appearing quickly after a large dose over a short time (radiation sickness, damage to bone marrow / immune system / gut, haemorrhage, rapid death) (1) • Chronic: effects appearing slowly, in proportion to the dose received over a long period (cancers, cataracts) (1)	2
02.3	<i>1 mark for each point.</i> • Exposure: absorption of ionising radiation from a source the person is close enough to (1) • Contamination: physically carrying radioactive material on or in the body, so exposure continues wherever the person goes; sealed sources can expose but not contaminate (1)	2
02.4	<i>A correct final answer (with unit where asked) scores full marks. If the answer is wrong, award 1 mark for each correct step of working shown.</i> • Sieverts = grays x radiation weighting factor (20 for alpha) (1) • $0.002 \times 20 = 0.04 \text{ Sv}$ (40 mSv) (1)	2
02.5	<i>1 mark.</i> • The activity of a source (number of decays per second) (1)	1
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 301, 303; AQA spec 3.4.3.2.14.	
03.1	<i>1 mark for each point.</i> • Doubling the distance from 1 m to 2 m reduces the dose rate from 400 to 100 (one quarter) (1) • Distance x 10 (1 to 10 m) reduces it by 100 times (400 to 4); dose is proportional to $1/\text{distance}^2$ (1)	2
03.2	<i>1 mark for the correct answer.</i> • $400 / 20^2 = 1 \text{ } \mu\text{Sv h}^{-1}$ (1)	1
03.3	<i>1 mark for each point.</i> • Sealed container prevents contact / contamination so exposure stops when the worker moves away; container may absorb alpha completely; remote handling (1) • Barriers (lead, concrete, thick steel flask walls) absorb radiation before it reaches the worker; thickness depends on radiation type (1) • Dose received is proportional to time near the source so work is organised to minimise time close to it (job rotation) (1) • Dosimeters / film badges record exposure; air monitors detect alpha-emitting particles; contamination monitors on leaving check that no material is carried out (1)	4

Question	Marking guidance	Marks
03.4	<i>1 mark for each point.</i> - Stable iodine saturates the thyroid (1) - So radioactive iodine-131 released is not taken up / concentrated in the thyroid gland (1)	2
03.5	<i>1 mark.</i> Exposure should be As Low As Reasonably Achievable (1)	1
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 302-303; AQA spec 3.4.3.2.14.	
04.1	<i>1 mark for each point.</i> - The underlying granite contains uranium whose decay produces the radioactive gas radon (an alpha emitter) (1) - Radon travels up cracks in the rock and through foundations into buildings (1) - It becomes concentrated inside enclosed / poorly ventilated buildings; control by ventilating foundations / sumps (1)	3
04.2	<i>1 mark for the correct answer.</i> $16 + 1.5 = 17.5\%$ (1)	1
04.3	<i>Any 2 from the points below - 1 mark each, maximum 2.</i> - Where they live (geology / radon, altitude) (1) - Occupation (radiographer, nuclear worker, aircrew, miner) (1) - Medical history (number of X-rays / CT scans) (1) - Lifestyle / diet (eg shellfish near discharges); smoking (1)	2
04.4	<i>Any 4 from the points below - 1 mark each, maximum 4.</i> - X-rays carry a small risk of mutation / cancer but the benefit (diagnosis, avoiding invasive surgery) may outweigh it; risks can be reduced (shielding, dose limits) (1) - Symptoms of chronic low-dose exposure take a long time to develop (1) - The same symptoms (cancers) have other causes so effects are hard to attribute (1) - Accurate data on human exposure / doses is often unavailable (especially after accidents) (1) - People who benefit and people who take the risk may be different (eg uranium miners vs electricity consumers) (1)	4
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 297-299; AQA spec 3.4.3.2.14.	
05.1	<i>2 marks for each point (partial credit for a partly correct point).</i> - High-level: used fuel rods / fission products separated in reprocessing; vitrification in molten glass in sealed stainless steel containers, surrounded by concrete, air-cooled to remove decay heat (Sellafield) (2) - Intermediate: fuel cladding / metal tubes around fuel rods, filters from reprocessing; mixed with cement (encapsulated) in stainless steel drums, stored in concrete vaults (2) - Low-level solid: contaminated clothing, equipment; sealed in plastic bags inside steel drums / containers in a concrete-lined, monitored landfill (Drigg) (2)	6
05.2	<i>1 mark for each point.</i> - Radioactive decay of the concentrated fission products generates heat which could damage containers (1) - Isotopes with long half-lives (plutonium 24 400 years) remain hazardous for thousands of years (1)	2

Question	Marking guidance	Marks
05.3	<i>1 mark for each point.</i> - Liquids: filtered and passed through ion-exchange (sands / resins) to remove radionuclides, then discharged (monitored by CPA / CGM) (1) - Gases: filtered (HEPA / charcoal filters) to remove particles and iodine before release (1)	2
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 303; AQA spec 3.4.3.2.14.	
06.1	Levels of response Level 3 (7-9 marks): Answer is comprehensive, relevant and logically structured. Shows detailed knowledge and understanding of the relevant scientific ideas and applies them accurately to the context. Evaluation/analysis is well supported by evidence and a clear judgement or conclusion is reached. Level 2 (4-6 marks): Answer is mostly relevant and shows some structure. Knowledge and understanding of relevant ideas is sound but application to the context or evaluation may be incomplete or lack detail. A judgement may be made but is not fully supported. Level 1 (1-3 marks): Answer is basic, with limited structure. Some relevant knowledge is shown but there are omissions or errors. Little application to the context and little or no evaluation. 0 marks: No relevant content. Indicative content (credit other relevant, accurate points) - Uses / benefits: nuclear electricity (low carbon, high energy density), medicine (X-rays, CT, radiotherapy, tracers, sterilising equipment), industry (thickness gauges, polymer cross-linking, testing turbines, oil exploration), agriculture (food irradiation, sterile male technique, mutation breeding), research tracers, smoke detectors, ship / submarine propulsion - Risks: free radical production, DNA damage, mutation, cancer; acute and chronic, somatic and gonadic effects; contamination vs exposure; activation products; long-lived wastes; accidents (Chernobyl, Fukushima); weapons fallout - Factors affecting risk: type of radiation (alpha, beta, gamma, neutrons - penetration, RBE / weighting factors), half-life, dose (Gy, Sv), route of exposure - Risk:benefit analysis and why it is difficult (latency, alternative causes, poor exposure data, risks and benefits to different people, offsets such as avoided surgery) - Principles: ALARA, BATNEEC; closed sources, remote handling, absorbers / shielding, distance (inverse square law), time, protective clothing, decontamination, potassium iodide - Monitoring: dosimeters, film badges, air and contamination monitors; environmental monitoring via CPA and CGM; waste categories and disposal (vitrification, encapsulation, Drigg) - Evaluation / judgement: benefits generally outweigh risks when controls are applied; public perception vs actual risk (background radon 50% of dose vs <1% from nuclear industry)	9
	Model answer - Level 3 (8 marks)	

Question	Marking guidance	Marks
	Ionising radiation is used because it does things nothing else can: nuclear fission generates low-carbon electricity from fuel of extraordinary energy density; medicine relies on X-rays and CT scans, radiotherapy, tracers and gamma sterilisation of equipment; industry uses thickness gauges, cross-links polymers, tests turbine blades and explores for oil; and agriculture uses irradiation to preserve food and sterilise insect pests. The risks arise because radiation produces free radicals that damage DNA, causing mutation and cancer, with acute and chronic, somatic and gonadic effects; contamination is worse than exposure because the source stays with the person; and activation products, long-lived wastes, accidents at Chernobyl and Fukushima and weapons fallout add environmental risks.	
	Risk depends on the type of radiation - alpha is barely penetrating but has a weighting factor of 20 - on half-life, on dose in grays and sieverts and on the route of exposure. Weighing risks against benefits is difficult because cancers appear years later with many other possible causes, exposure data are poor, the people who benefit are often not those at risk, and benefits such as avoided surgery are hard to quantify.	
	Control follows ALARA and BATNEEC: closed sources, remote handling, shielding, distance under the inverse-square law, limiting time, protective clothing, decontamination and potassium iodide against iodine-131. Workers wear dosimeters and film badges and pass contamination monitors; discharges are managed by Critical Pathway Analysis and Critical Group Monitoring; wastes are vitrified, encapsulated or stored at licensed sites. With these controls the benefits generally outweigh the risks - natural radon supplies about half the average dose and the nuclear industry under one per cent - although public perception of risk remains far higher than the measured risk.	
	Weaker answer - Level 2 (5 marks)	
	Ionising radiation is used in nuclear power stations to make electricity, in hospitals for X-rays and treating cancer, and in industry. The risks are that radiation damages DNA and causes cancer, and accidents like Chernobyl release radiation into the environment. Nuclear waste stays dangerous for a long time. Workers are protected by shielding, keeping their distance and wearing film badges to measure their dose. The public is protected by monitoring around nuclear sites. Overall the benefits are worth the risks if it is controlled properly.	
	What makes the difference	
	• Level 2 covers uses, risks, controls and a judgement, but each briefly; Level 3 adds the factors that determine risk (type, half-life, dose units, route) and why risk-benefit analysis is difficult.	
	• Level 3 names the principles (ALARA, BATNEEC, inverse square law, CPA / CGM) rather than describing practice loosely.	
	• The judgement in Level 3 is supported with evidence (radon vs nuclear industry doses); Level 2's is an opinion.	
06.2	<i>1 mark.</i> • Consumers of the electricity may live in a different country / region from the uranium miners or the communities near waste stores who bear the risks (1)	1

Question	Marking guidance	Marks
	Source: R. Genn, Environmental Science A level AQA (Insight & Perspective, 2018), pp. 295-304; AQA spec 3.4.3.2.14.	