GPK Integration FAQ

Q: What additional work is required to integrate GPK?

A: Add two game protocol messages: one to send DynCode and one to send GPK heartbeat packets. Implement logging, typically including the game region and server, character ID, character name, level, current location, and the IGPKCSAuth::CheckAuthReply result. The project team and developer can agree on the fields required.
GPK-generated data has variable size; use the corresponding function return value to determine it.

Q: What URL and GameCode should be passed to GPKStart("http://localhost/GPK", "Game")?

A: The project team supplies the URL for GPK automatic updates. The developer may choose the GameCode, typically an abbreviation of the game name.

Q: What server and content are needed for GPKStart automatic updates?

A: Any web server supporting HTTP can serve updates. The update URL must contain the entire GPK directory from Redist\Debug\Client in the GPK SDK package.

Q: What should happen if GPKStart fails?

A: Report the failure and exit the game.

Q: After IGPKCltDynCode::SetDynCode(lpDynCode, nlen), can lpDynCode be freed immediately?

A: GPK copies the data referenced by lpDynCode, so that memory can be freed after the call.

Q: Who frees the memory returned through IGPKCSAuth::GetCSAuthDynCode(const unsigned char **ppCodeRet)?

A: GPK allocates and manages this memory. Do not allocate or free it yourself.

Q: Who frees ppDataRet from IGPKCSAuth::GetAuthData(const unsigned char **ppDataRet, void *Object, fnGPK_SvrCallBack SendToClt=NULL)?

A: GPK allocates and manages this memory. Do not allocate or free it yourself. The second and third parameters provide an interface for GPK to send game packets; the original guidance recommends leaving them NULL.

CONFIDENTIALITY / SECURITY WARNING
This document and SDK are the property of Shanda. They may not be used, reworked, or distributed without Shanda's consent. Persons responsible for reviewing and safeguarding them bear legal responsibility for loss or theft. Shanda's consent is required before transferring the document.