MATLAB tips

Enze Chen

Date: April 15, 2018

Here are some suggested style tips that might help clean up your future MATLAB code and plots (and make it a bit easier for us TAs to grade your work, hehe).

Note: These are only recommendations, and style will **not** be factored into assignment grades.

1 Plots

- Multiple lines: Use the hold on command, which will not only allow multiple plots to be displayed on the same figure, but it will automatically cycle through a pre-defined set of colors (blue, orange, yellow, etc.) for each plot in order (even if you plot different lines all in one plot() command, such as with a matrix).
- Line thickness: Inside each plot() function, add the arguments 'linewidth', 4 to increase the thickness of your lines and improve visibility. Even thicker is fine, but 4 is probably the minimum you'd want.
- Axes readability: After you've finished decorating your plot with labels and titles (you all did a great job with labeling!), add one more line with

```
set(gca, 'fontsize', 20, 'linewidth', 2, 'ticklength', [0.03 0.03]);
```

This will increase the font of the labels to 20, increase the thickness of the lines to 2 (in general I make axes line width half of the plot line width), and increase the length of the axes tick marks. This greatly improves readability, particularly when the figure is made smaller.

For comparison, I've included the code for figures with styling, and inserted figures with and without the extra styling:

```
close all; % handy to put this in front of first figure call
figure; hold on;
x = 0:0.01:1;
plot(x, x, 'linewidth', 4);
plot(x, x.^2, 'linewidth', 4);
plot(x, x.^3, 'linewidth', 4);
% Simpler: same figure would show with plot(x, [x; x.^2; x.^3], 'linewidth', 4);
xlabel('x');
ylabel('f(x)');
legend('x', 'x^2', 'x^3', 'location', 'northwest');
set(gca, 'fontsize', 20, 'linewidth', 2, 'ticklength', [0.03 0.03]);
```




Figure 1: MATLAB figures (a) with style formatting and (b) without.

2 Code

- The first line of your MATLAB script can contain clear variables; clc; to clear the workspace and clear the command window respectively at the start of each run.
- Sections are created with two percent symbols, %%. Since MATLAB saves all workspace variables, you can just run a specific section without having to run the whole script.

 Example: You painstakingly solve a PDE and want to plot the solution, but your code errors
 - example: You painstakingly solve a PDE and want to plot the solution, but your code errors out with bugs in the plotting section. You can section off the plot part and just change the plotting code until everything works without having to solve the PDE each time.
- More to come...?