

the $\mathcal{H}_2$ norm of the error signal $\|e\|_2$ is bounded by the $\mathcal{H}_2$ norm of the disturbance $\|d\|_2$.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.

For the $\mathcal{H}_2$ norm, the error signal e is bounded by the disturbance d in the $\mathcal{H}_2$ norm.