

Compilers

Lab Session 1

Advanced calculator grammar

```
prog:  stat+ EOF ;

stat:  expr NEWLINE      # print
      | ID '=' expr NEWLINE # assign
      | NEWLINE          # blank
      ;

expr:  expr (MUL|DIV) expr # prod
      | expr (ADD|SUB) expr # plus
      | INT               # int
      | ID                # id
      ;

MUL :  '*' ;
DIV :  '/' ;
ADD :  '+' ;
SUB :  '-' ;
ID  :  [a-zA-Z]+ ; // match identifiers
INT :  [0-9]+ ;    // match integers
NEWLINE: '\r'? '\n' ; // return newlines to parser
WS :  [ \t]+ -> skip ; // toss out whitespace
```

Calc.g4

Advanced calculator grammar

```
prog:  stat+ EOF ;
```

```
stat:  expr NEWLINE      # print  
      | ID '=' expr NEWLINE # assign  
      | NEWLINE          # blank  
      ;
```

```
expr:  expr (MUL|DIV) expr # prod  
      | expr (ADD|SUB) expr # plus  
      | INT                # int  
      | ID                 # id  
      ;
```

```
MUL : '*' ;  
DIV : '/' ;  
ADD : '+' ;  
SUB : '-' ;  
ID  : [a-zA-Z]+ ; // match identifiers  
INT : [0-9]+ ;    // match integers  
NEWLINE: '\r'? '\n' ; // return newlines to  
parser  
WS : [ \t]+ -> skip ; // toss out whitespace
```

Calc.g4

main.cpp

```
// create a lexer that consumes the character  
// stream, and produces a token stream  
CalcLexer lexer(&input);  
antlr4::CommonTokenStream tokens(&lexer);  
  
// create a parser that consumes the token  
// stream, and parses it  
CalcParser parser(&tokens);  
  
// call the parser and get the parse tree  
antlr4::tree::ParseTree *tree = parser.prog();  
  
// print the parse tree (debugging purposes)  
std::cout << tree->toStringTree(&parser)  
           << std::endl;
```

Advanced calculator grammar

```
prog: stat+ EOF ;

stat:  expr NEWLINE      # print
      | ID '=' expr NEWLINE # assign
      | NEWLINE          # blank
      ;

expr:  expr (MUL|DIV) expr # prod
      | expr (ADD|SUB) expr # plus
      | INT               # int
      | ID                # id
      ;

MUL : '*' ;
DIV : '/' ;
ADD : '+' ;
SUB : '-' ;
ID  : [a-zA-Z]+ ; // match identifiers
INT : [0-9]+ ;    // match integers
NEWLINE: '\r'? '\n' ; // return newlines to
parser
WS : [ \t]+ -> skip ; // toss out whitespace
```

Calc.g4

```
// create a lexer that consumes the character
// stream, and produces a token stream
CalcLexer lexer(&input);
antlr4::CommonTokenStream tokens(&lexer);

// create a parser that consumes the token
// stream, and parses it
CalcParser parser(&tokens);

// call the parser and get the parse tree
antlr4::tree::ParseTree *tree = parser.prog();

// print the parse tree (debugging purposes)
std::cout << tree->toStringTree(&parser)
           << std::endl;
```

main.cpp

Advanced calculator grammar

```
prog:  stat+ EOF ;

stat:  expr NEWLINE      # print
      | ID '=' expr NEWLINE # assign
      | NEWLINE          # blank
      ;

expr:  expr (MUL|DIV) expr # prod
      | expr (ADD|SUB) expr # plus
      | INT               # int
      | ID                 # id
      ;

MUL : '*' ;
DIV : '/' ;
ADD : '+' ;
SUB : '-' ;
ID  : [a-zA-Z]+ ; // match identifiers
INT : [0-9]+ ;    // match integers
NEWLINE: '\r'? '\n' ; // return newlines to
parser
WS : [ \t]+ -> skip ; // toss out whitespace
```

Calc.g4

Rule labels
(Not comments!)

Advanced calculator grammar

```
prog:  stat+ EOF ;  
  
stat:  expr NEWLINE      # print  
      | ID '=' expr NEWLINE # assign  
      | NEWLINE          # blank  
      ;  
  
expr:  expr (MUL|DIV) expr # prod  
      | expr (ADD|SUB) expr # plus  
      | INT               # int  
      | ID                # id  
      ;  
  
MUL : '*' ;  
DIV : '/' ;  
ADD : '+' ;  
SUB : '-' ;  
ID  : [a-zA-Z]+ ;  
INT : [0-9]+ ;  
NEWLINE: '\r'? '\n' ;  
parser  
WS : [ \t]+ -> skip ;
```

Calc.g4

Rule labels
(Not comments!)

Those are comments

Advanced calculator grammar

```
////////////////////////////////////  
// Sample "calculator" using visitors  
class Calculator : public CalcBaseVisitor {  
public:  
  
    // stat : expr NEWLINE    # print  
    antlrcpp::Any visitPrint(CalcParser::PrintContext *ctx) {  
        int value = std::any_cast<int>(visit(ctx->expr())); // evaluate the 'expr' child  
        std::cout << value << endl; // print resulting value  
        return 0; // return dummy value  
    }  
  
    // expr : INT    # int  
    antlrcpp::Any visitInt(CalcParser::IntContext *ctx) {  
        return std::stoi(ctx->INT()->getText()); // get integer value  
    }  
  
    // expr : expr (MUL|DIV) expr    # prod  
    antlrcpp::Any visitProd(CalcParser::ProdContext *ctx) {  
        int left = std::any_cast<int>(visit(ctx->expr(0))); // get value of left subexpr.  
        int right = std::any_cast<int>(visit(ctx->expr(1))); // get value of right subexpr.  
        if (ctx->MUL()) return left*right; // compute and return result  
        else return left/right;  
    }  
};
```

main.cpp

Advanced calculator grammar

```
//////////////////////////////////////  
// Sample "calculator" using visitors  
class Calculator : public CalcBaseVisitor {  
public:  
  
    // stat : expr NEWLINE    # print  
    antlrcpp::Any visitPrint(CalcParser::PrintContext *ctx) {  
        int value = std::any_cast<int>(visit(ctx->expr())); // evaluate the 'expr' child  
        std::cout << value << endl; // print resulting value  
        return 0; // return dummy value  
    }  
  
    // expr : INT    # int  
    antlrcpp::Any visitInt(CalcParser::IntContext *ctx) {  
        return std::stoi(ctx->INT()->getText()); // get integer value  
    }  
  
    // expr : expr (MUL|DIV) expr    # prod  
    antlrcpp::Any visitProd(CalcParser::ProdContext *ctx) {  
        int left = std::any_cast<int>(visit(ctx->expr(0))); // get value of left subexpr.  
        int right = std::any_cast<int>(visit(ctx->expr(1))); // get value of right subexpr.  
        if (ctx->MUL()) return left*right; // compute and return result  
        else return left/right;  
    }  
};
```

main.cpp

Rule labels
generate
different
visitors for
each subrule

Advanced calculator grammar

```
////////////////////////////////////  
// Sample "calculator" using visitors  
class Calculator : public CalcBaseVisitor {  
public:  
    // "memory" for the calculator; stores current value for each variable  
    std::map<std::string, int> memory;  
  
    // stat : ID '=' expr NEWLINE    # assign  
    antlrcpp::Any visitAssign(CalcParser::AssignContext *ctx) {  
        std::string id = ctx->ID()->getText(); // id is left-hand side of '='  
        int value = std::any_cast<int>(visit(ctx->expr())); // compute value of expr. on right  
        memory[id] = value; // store it in the memory  
        return 0; // return dummy value  
    }  
  
    // expr : ID    # id  
    antlrcpp::Any visitId(CalcParser::IdContext *ctx) {  
        std::string id = ctx->ID()->getText();  
        if (memory.find(id) != memory.end())  
            return memory[id]; // retrieve current variable value  
        else  
            return 0; // ...or zero if it does not exist  
    }  
};
```

main.cpp

Advanced calculator grammar

```
////////////////////////////////////  
// Sample "calculator" using visitors  
class Calculator : public CalcBaseVisitor {  
public:  
    // "memory" for the calculator; stores current value for each variable  
    std::map<std::string, int> memory;  
  
    // stat : ID '=' expr NEWLINE    # assign  
    antlrcpp::Any visitAssign(CalcParser::AssignContext *ctx) {  
        std::string id = ctx->ID()->getText(); // id is left-hand side of '='  
        int value = std::any_cast<int>(visit(ctx->expr())); // compute value of expr. on right  
        memory[id] = value; // store it in the memory  
        return 0; // return dummy value  
    }  
  
    // expr : ID    # id  
    antlrcpp::Any visitId(CalcParser::IdContext *ctx) {  
        std::string id = ctx->ID()->getText();  
        if (memory.find(id) != memory.end())  
            return memory[id]; // retrieve current variable value  
        else  
            return 0; // ...or zero if it does not exist  
    }  
};
```

main.cpp

We need to
store and
retrieve
values for
variables

Advanced calculator grammar

Exercise

- Complete the expression grammar to handle other operators:
 - Unary minus
 - Parenthesis
 - Comparison operators ($>$, $<$, $==$, $!=$, $>=$, $<=$)
 - Boolean operators (and, or, not)
 - Unary/binary Predefined functions (e.g. $\text{abs}(a)$, $\text{pow}(a,b)$)
 - N-ary predefined functions (e.g. $\text{max}(a,b,c,\dots)$, $\text{min}(a,b,c,\dots)$, $\text{sum}(a,b,c,\dots)$)
 - Conditional expression (e.g. $[a>b ? x+1 : y-2]$)
- Extend the Calculator **visitor** to handle the missing operators and compute the result in each case. Use **rule labels**.
- Extend your Calc language with additional statements (IF, WHILE, ...)

Summary

Key concepts learnt in this session

- How to write simple antlr4 grammars
- How to create a main program that calls a Lexer and a Parser to get a parse tree.
- How to traverse the parse tree using *Visitors* that return a result after visiting each node
- How to use rule labels in antlr4 to get cleaner code for our visitors
- How to use attributes (e.g. *memory* map) to store information that persists and is accessible from any node.