

Explaining Time Series Classifiers Through Post-Hoc XAI Methods Capturing Temporal Dependencies

Ephrem T. Mekonnen^{1*}, Luca Longo¹, Pierpaolo Dondio¹

¹ Technological University Dublin, *correspondence: D22125038@mytudublin.ie @ephrem-eth ephrem-eth.github.io

Expected Contributions

- **Rule-Based Explanation:** Mimics black-box models using interpretable surrogates like decision trees.
- **LOMATCE:** Local model-agnostic explanations for time series classifiers without segmentation.
- **L2GX:** Aggregates local explanations to form holistic, global insights.

Motivation

- Deep learning models perform well on time series classification tasks; however, they are often considered as **black boxes** [1].
- Existing XAI methods for **image** and **tabular data** may not be suitable for time series data due to its **temporal nature** [1,2].
- Many time series XAI approaches are **developer-focused** and rely on **latent layer activations**, while users need **higher-level, abstract explanations** [2].
- Feature importance methods like **LIME**[3] applied to time series often segment data into **fixed-size windows**, potentially overlooking critical subsequences [2].

How can model-agnostic XAI methods be designed to provide interpretable, faithful explanations while capturing temporal dependencies in the data for **black-box** time series classifiers?

Research Plan and Methodology




Fig 1: Overview of the proposed research plan.

Global Model-Agnostic Rule-Based XAI Method




Fig 2: The proposed global XAI method for DL time series classification models.

LOMATCE: Local Model-Agnostic Time-series Classification Explanations




Fig 3: Step-by-step illustration of the proposed local XAI approach.

Result and Discussion

Global Model-Agnostic Rule-Based XAI Method




Fig 4: A decision tree graph produced by the proposed method on ECG data.

- The graph provides valuable insights into the impact of specific time steps and corresponding events on the model's predictions.

LOMATCE: Local Model-Agnostic Time-series Classification Explanations

Table 1: Explanation faithfulness, with 95% confidence interval, across various perturbation methods.

Dataset	Zero	Mean	Total_mean	Random
ECG	0.82 ± 0.02	0.70 ± 0.02	0.81 ± 0.01	0.29 ± 0.02
GunPoint	0.72 ± 0.02	0.52 ± 0.03	0.73 ± 0.02	0.32 ± 0.04
Coffee	0.65 ± 0.03	0.57 ± 0.02	0.66 ± 0.03	0.22 ± 0.08




Fig 4: Explanation highlights segment significance, relevance scores, and event types (e.g., increasing, decreasing, maxima, minima).

- Our method highlights each time series segment's significance and relevance scores, detailing event types like increases, decreases, maxima, and minima.
- Perturbation strategies vary across different datasets.

Conclusion and Future works

- Post-hoc XAI methods are being developed to provide local and global explanations for time series classifiers, capturing temporal dependencies and aligning with human interpretation.
- Implement L2GX, extend current methods to multivariate time series, and validate using diverse perturbations across multiple datasets and XAI baselines.

Acknowledgements

The scholarship of TU Dublin is acknowledged for their generous support.

Scan QR codes for papers:



References

- [1] Theissler et al. : Explainable ai for time series classification: A review, taxonomy and research directions. IEEE Access (2022)
- [2] Schlegel et al.: Ts-mule (2021)
- [3] Ribeiro et al.: "Why should i trust you?" (2016)
- [4] Kadous: Learning comprehensible descriptions of TS (1999)