

# Dplyr-like API for tech.ml.dataset

GenerateMe

2020-06-17

## Introduction

tech.ml.dataset is a great and fast library which brings columnar dataset to the Clojure. Chris Nuernberger has been working on this library for last year as a part of bigger **tech.ml** stack.

I've started to test the library and help to fix uncovered bugs. My main goal was to compare functionalities with the other standards from other platforms. I focused on R solutions: dplyr, tidyr and data.table.

During conversions of the examples I've come up how to reorganized existing **tech.ml.dataset** functions into simple to use API. The main goals were:

- Focus on dataset manipulation functionality, leaving other parts of **tech.ml** like pipelines, datatypes, readers, ML, etc.
- Single entry point for common operations - one function dispatching on given arguments.
- **group-by** results with special kind of dataset - a dataset containing subsets created after grouping as a column.
- Most operations recognize regular dataset and grouped dataset and process data accordingly.
- One function form to enable thread-first on dataset.

If you want to know more about **tech.ml.dataset** and **tech.ml.datatype** please refer their documentation:

- Datatype
- Date/time
- Dataset

## SOURCE CODE

Join the discussion on Zulip

Let's require main namespace and define dataset used in most examples:

```
(require '[tablecloth.api :as api])
(def DS (api/dataset { :V1 (take 9 (cycle [1 2]))
                      :V2 (range 1 10)
                      :V3 (take 9 (cycle [0.5 1.0 1.5]))
                      :V4 (take 9 (cycle ["A" "B" "C"]))}))
```

DS

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B

:V1	:V2	:V3	:V4
2	6	1.5	C
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

## Functionality

### Dataset

Dataset is a special type which can be considered as a map of columns implemented around `tech.ml.datatype` library. Each column can be considered as named sequence of typed data. Supported types include integers, floats, string, boolean, date/time, objects etc.

### Dataset creation

Dataset can be created from various of types of Clojure structures and files:

- single values
- sequence of maps
- map of sequences or values
- sequence of columns (taken from other dataset or created manually)
- sequence of pairs
- file types: raw/gzipped csv/tsv, json, xls(x) taken from local file system or URL
- input stream

`api/dataset` accepts:

- data
- options (see documentation of `tech.ml.dataset/->dataset` function for full list):
  - `:dataset-name` - name of the dataset
  - `:num-rows` - number of rows to read from file
  - `:header-row?` - indication if first row in file is a header
  - `:key-fn` - function applied to column names (eg. `keyword`, to convert column names to keywords)
  - `:separator` - column separator
  - `:single-value-column-name` - name of the column when single value is provided

---

Empty dataset.

```
(api/dataset)
```

```
_unnamed [0 0]
```

---

Dataset from single value.

```
(api/dataset 999)
```

```
_unnamed [1 1]:
```

---

```
:$value
```

---

```
999
```

---

---

Set column name for single value. Also set the dataset name.

```
(api/dataset 999 {:single-value-column-name "my-single-value"})  
(api/dataset 999 {:single-value-column-name ""  
                  :dataset-name "Single value"})
```

\_\_unnamed [1 1]:

my-single-value
999

Single value [1 1]:

0
999

---

Sequence of pairs (first = column name, second = value(s)).

```
(api/dataset [[:A 33] [:B 5] [:C :a]])
```

\_\_unnamed [1 3]:

:A	:B	:C
33	5	:a

---

Not sequential values are repeated row-count number of times.

```
(api/dataset [[:A [1 2 3 4 5 6]] [:B "X"] [:C :a]])
```

\_\_unnamed [6 3]:

	:A	:B	:C
1	X	:a	
2	X	:a	
3	X	:a	
4	X	:a	
5	X	:a	
6	X	:a	

---

Dataset created from map (keys = column names, vals = value(s)). Works the same as sequence of pairs.

```
(api/dataset {:A 33})  
(api/dataset {:A [1 2 3]})  
(api/dataset {:A [3 4 5] :B "X"})
```

\_\_unnamed [1 1]:

:A
33

\_\_unnamed [3 1]:

:A
1
2
3

\_\_unnamed [3 2]:

:A	:B
3	X
4	X
5	X

You can put any value inside a column

```
(api/dataset { :A [[3 4 5] [:a :b]] :B "X"})
```

\_\_unnamed [2 2]:

:A	:B
[3 4 5]	X
[:a :b]	X

Sequence of maps

```
(api/dataset [{ :a 1 :b 3} { :b 2 :a 99}])
(api/dataset [{ :a 1 :b [1 2 3]} { :a 2 :b [3 4]}])
```

\_\_unnamed [2 2]:

:a	:b
1	3
99	2

\_\_unnamed [2 2]:

:a	:b
1	[1 2 3]
2	[3 4]

---

Missing values are marked by `nil`

```
(api/dataset [{:a nil :b 1} {:a 3 :b 4} {:a 11}])
```

\_\_unnamed [3 2]:

---

:a	:b
	1
3	4
11	

---

---

Import CSV file

```
(api/dataset "data/family.csv")
```

data/family.csv [5 5]:

family	dob_child1	dob_child2	gender_child1	gender_child2
1	1998-11-26	2000-01-29	1	2
2	1996-06-22		2	
3	2002-07-11	2004-04-05	2	2
4	2004-10-10	2009-08-27	1	1
5	2000-12-05	2005-02-28	2	1

---

Import from URL

```
(defonce ds (api/dataset "https://vega.github.io/vega-lite/examples/data/seattle-weather.csv"))
```

```
ds
```

https://vega.github.io/vega-lite/examples/data/seattle-weather.csv [1461 6]:

date	precipitation	temp_max	temp_min	wind	weather
2012-01-01	0.0	12.8	5.0	4.7	drizzle
2012-01-02	10.9	10.6	2.8	4.5	rain
2012-01-03	0.8	11.7	7.2	2.3	rain
2012-01-04	20.3	12.2	5.6	4.7	rain
2012-01-05	1.3	8.9	2.8	6.1	rain
2012-01-06	2.5	4.4	2.2	2.2	rain
2012-01-07	0.0	7.2	2.8	2.3	rain
2012-01-08	0.0	10.0	2.8	2.0	sun
2012-01-09	4.3	9.4	5.0	3.4	rain
2012-01-10	1.0	6.1	0.6	3.4	rain
2012-01-11	0.0	6.1	-1.1	5.1	sun
2012-01-12	0.0	6.1	-1.7	1.9	sun
2012-01-13	0.0	5.0	-2.8	1.3	sun
2012-01-14	4.1	4.4	0.6	5.3	snow
2012-01-15	5.3	1.1	-3.3	3.2	snow
2012-01-16	2.5	1.7	-2.8	5.0	snow
2012-01-17	8.1	3.3	0.0	5.6	snow

date	precipitation	temp_max	temp_min	wind	weather
2012-01-18	19.8	0.0	-2.8	5.0	snow
2012-01-19	15.2	-1.1	-2.8	1.6	snow
2012-01-20	13.5	7.2	-1.1	2.3	snow
2012-01-21	3.0	8.3	3.3	8.2	rain
2012-01-22	6.1	6.7	2.2	4.8	rain
2012-01-23	0.0	8.3	1.1	3.6	rain
2012-01-24	8.6	10.0	2.2	5.1	rain
2012-01-25	8.1	8.9	4.4	5.4	rain

## Saving

Export dataset to a file or output stream can be done by calling `api/write-csv!`. Function accepts:

- dataset
- file name with one of the extensions: `.csv`, `.tsv`, `.csv.gz` and `.tsv.gz` or output stream
- options:
  - `:separator` - string or separator char.

```
(api/write-csv! ds "output.tsv.gz")
(.exists (clojure.java.io/file "output.csv.gz"))
```

```
nil
false
```

## Dataset related functions

Summary functions about the dataset like number of rows, columns and basic stats.

---

Number of rows

```
(api/row-count ds)
```

```
1461
```

---

Number of columns

```
(api/column-count ds)
```

```
6
```

---

Shape of the dataset, [row count, column count]

```
(api/shape ds)
```

```
[1461 6]
```

---

General info about dataset. There are three variants:

- default - containing information about columns with basic statistics
  - `:basic` - just name, row and column count and information if dataset is a result of `group-by` operation

— :columns - columns' metadata

```
(api/info ds)
(api/info ds :basic)
(api/info ds :columns)
```

<https://vega.github.io/vega-lite/examples/data/seattle-weather.csv>: descriptive-stats [6 10]:

:col-name	:datatype	:n-valid	:n-missing	:min	:mean	:mode	:max	:standard-deviation	:skew
date	:packed-local-date	1461	0	2012-01-01	2013-12-31	2015-12-31			
precipitation	:float32	1461	0	0.000	3.029	55.90	6.68019429	3.50564374	
temp_max	:float32	1461	0	-1.600	16.44	35.60	7.34975813	0.28093000	
temp_min	:float32	1461	0	-7.100	8.235	18.30	5.02300419	-	0.24945853
weather	:string	1461	0			sun			
wind	:float32	1461	0	0.4000	3.241	9.500	1.43782506	0.89166753	

<https://vega.github.io/vega-lite/examples/data/seattle-weather.csv> :basic info [1 4]:

:name	:grouped?	:rows	:columns
<a href="https://vega.github.io/vega-lite/examples/data/seattle-weather.csv">https://vega.github.io/vega-lite/examples/data/seattle-weather.csv</a>	false	1461	6

<https://vega.github.io/vega-lite/examples/data/seattle-weather.csv> :column info [6 4]:

:name	:size	:datatype	:categorical?
date	1461	:packed-local-date	
precipitation	1461	:float32	
temp_max	1461	:float32	
temp_min	1461	:float32	
wind	1461	:float32	
weather	1461	:string	true

Getting a dataset name

```
(api/dataset-name ds)
```

"<https://vega.github.io/vega-lite/examples/data/seattle-weather.csv>"

Setting a dataset name (operation is immutable).

```
(->> "seattle-weather"
  (api/set-dataset-name ds)
  (api/dataset-name))
```

"seattle-weather"

## Columns and rows

Get columns and rows as sequences. `column`, `columns` and `rows` treat grouped dataset as regular one. See [Groups](#) to read more about grouped datasets.

---

Select column.

```
(ds "wind")
(api/column ds "date")
```

```
#tech.ml.dataset.column<float32>[1461]
wind
[4.700, 4.500, 2.300, 4.700, 6.100, 2.200, 2.300, 2.000, 3.400, 3.400, 5.100, 1.900, 1.300, 5.300, 3.200, ...]
#tech.ml.dataset.column<packed-local-date>[1461]
date
[2012-01-01, 2012-01-02, 2012-01-03, 2012-01-04, 2012-01-05, 2012-01-06, 2012-01-07, 2012-01-08, 2012-01-09, ...]
```

---

Columns as sequence

```
(take 2 (api/columns ds))
```

```
(#tech.ml.dataset.column<packed-local-date>[1461]
date
[2012-01-01, 2012-01-02, 2012-01-03, 2012-01-04, 2012-01-05, 2012-01-06, 2012-01-07, 2012-01-08, 2012-01-09, ...]
precipitation
[0.000, 10.90, 0.8000, 20.30, 1.300, 2.500, 0.000, 0.000, 4.300, 1.000, 0.000, 0.000, 0.000, 4.100, 5.300, ...])
```

---

Columns as map

```
(keys (api/columns ds :as-map))
```

```
("date" "precipitation" "temp_max" "temp_min" "wind" "weather")
```

---

Rows as sequence of sequences

```
(take 2 (api/rows ds))
```

```
([#object[java.time.LocalDate 0x2114a764 "2012-01-01"] 0.0 12.8 5.0 4.7 "drizzle"] [#object[java.time.LocalDate 0x2114a764 "2012-01-02"] 10.9 12.8 2.8 4.7 "rain"]])
```

---

Rows as sequence of maps

```
(clojure.pprint/pprint (take 2 (api/rows ds :as-maps)))
```

```
({"date" #object[java.time.LocalDate 0x2665466d "2012-01-01"],
 "precipitation" 0.0,
 "temp_min" 5.0,
 "weather" "drizzle",
 "temp_max" 12.8,
 "wind" 4.7}
 {"date" #object[java.time.LocalDate 0x6166cdd0 "2012-01-02"],
 "precipitation" 10.9,
 "temp_min" 2.8,
 "weather" "rain",
 "temp_max" 12.8,
 "wind" 4.7})
```



```
"temp_max" 10.6,
"wind" 4.5})
```

## Printing

Dataset is printed using `dataset->str` or `print-dataset` functions. Options are the same as in `tech.ml.dataset/dataset-data->str`. Most important is `:print-line-policy` which can be one of the: `:single`, `:repl` or `:markdown`.

```
(api/print-dataset (api/group-by DS :V1) {:print-line-policy :markdown})
```

```
_unnamed [2 3]:
```

```
| :name | :group-id |
|-----:|-----:|-----:|
|      1 |          0 | Group: 1 [5 4]:<br><br>\| :V1 \| :V2 \| :V3 \| :V4 \|<br>\|-----:\|-----:\|-----:\|
|      2 |          1 |                               Group: 2 [4 4]:<br><br>\| :V1 \| :V2 \| :V3 \|
```

```
(api/print-dataset (api/group-by DS :V1) {:print-line-policy :repl})
```

```
_unnamed [2 3]:
```

```
| :name | :group-id | :data |
|-----:|-----:|-----:|
|      1 |          0 | Group: 1 [5 4]:
|      |          |
|      |          | \| :V1 \| :V2 \| :V3 \| :V4 \|
|      |          | \|-----:\|-----:\|-----:\|-----:\|
|      |          | \|      1 \|      1 \| 0.5 \|      A \|
|      |          | \|      1 \|      3 \| 1.5 \|      C \|
|      |          | \|      1 \|      5 \| 1.0 \|      B \|
|      |          | \|      1 \|      7 \| 0.5 \|      A \|
|      |          | \|      1 \|      9 \| 1.5 \|      C \|
|      2 |          1 | Group: 2 [4 4]:
|      |          |
|      |          | \| :V1 \| :V2 \| :V3 \| :V4 \|
|      |          | \|-----:\|-----:\|-----:\|-----:\|
|      |          | \|      2 \|      2 \| 1.0 \|      B \|
|      |          | \|      2 \|      4 \| 0.5 \|      A \|
|      |          | \|      2 \|      6 \| 1.5 \|      C \|
|      |          | \|      2 \|      8 \| 1.0 \|      B \|
```

```
(api/print-dataset (api/group-by DS :V1) {:print-line-policy :single})
```

```
_unnamed [2 3]:
```

```
| :name | :group-id | :data |
|-----:|-----:|-----:|
|      1 |          0 | Group: 1 [5 4]: |
|      2 |          1 | Group: 2 [4 4]: |
```

## Group-by

Grouping by is an operation which splits dataset into subdatasets and pack it into new special type of... dataset. I distinguish two types of dataset: regular dataset and grouped dataset. The latter is the result of

grouping.

Grouped dataset is annotated in by `:grouped?` meta tag and consist following columns:

- `:name` - group name or structure
- `:group-id` - integer assigned to the group
- `:data` - groups as datasets

Almost all functions recognize type of the dataset (grouped or not) and operate accordingly.

You can't apply reshaping or join/concat functions on grouped datasets.

## Grouping

Grouping is done by calling `group-by` function with arguments:

- `ds` - dataset
- `grouping-selector` - what to use for grouping
- options:
  - `:result-type` - what to return:
    - \* `:as-dataset` (default) - return grouped dataset
    - \* `:as-indexes` - return rows ids (row number from original dataset)
    - \* `:as-map` - return map with group names as keys and subdataset as values
    - \* `:as-seq` - return sequens of subdatasets
  - `:select-keys` - list of the columns passed to a grouping selector function

All subdatasets (groups) have set name as the group name, additionally `group-id` is in meta.

Grouping can be done by:

- single column name
- seq of column names
- map of keys (group names) and row indexes
- value returned by function taking row as map (limited to `:select-keys`)

Note: currently dataset inside dataset is printed recursively so it renders poorly from markdown. So I will use `:as-seq` result type to show just group names and groups.

---

List of columns in grouped dataset

```
(-> DS
  (api/group-by :V1)
  (api/column-names))
```

```
(:V1 :V2 :V3 :V4)
```

---

List of columns in grouped dataset treated as regular dataset

```
(-> DS
  (api/group-by :V1)
  (api/as-regular-dataset)
  (api/column-names))
```

```
(:name :group-id :data)
```

---

Content of the grouped dataset

```
(api/columns (api/group-by DS :V1) :as-map)
```

```
{:name #tech.ml.dataset.column<int64>[2]
:name
[1, 2, ], :group-id #tech.ml.dataset.column<int64>[2]
:group-id
[0, 1, ], :data #tech.ml.dataset.column<object>[2]
:data
[Group: 1 [5 4]:

| :V1 | :V2 | :V3 | :V4 |
|----:|----:|----:|----:|
|  1  |  1  | 0.5  |  A  |
|  1  |  3  | 1.5  |  C  |
|  1  |  5  | 1.0  |  B  |
|  1  |  7  | 0.5  |  A  |
|  1  |  9  | 1.5  |  C  |
, Group: 2 [4 4]:

| :V1 | :V2 | :V3 | :V4 |
|----:|----:|----:|----:|
|  2  |  2  | 1.0  |  B  |
|  2  |  4  | 0.5  |  A  |
|  2  |  6  | 1.5  |  C  |
|  2  |  8  | 1.0  |  B  |
, ]}
```

---

Grouped dataset as map

```
(keys (api/group-by DS :V1 {:result-type :as-map}))
```

```
(1 2)
```

```
(vals (api/group-by DS :V1 {:result-type :as-map}))
```

```
(Group: 1 [5 4]:
```

:V1	:V2	:V3	:V4
1	1	0.5	A
1	3	1.5	C
1	5	1.0	B
1	7	0.5	A
1	9	1.5	C

```
Group: 2 [4 4]:
```

:V1	:V2	:V3	:V4
2	2	1.0	B
2	4	0.5	A
2	6	1.5	C
2	8	1.0	B

)

---

Group dataset as map of indexes (row ids)

```
(api/group-by DS :V1 {:result-type :as-indexes})
```

```
{1 [0 2 4 6 8], 2 [1 3 5 7]}
```

---

Grouped datasets are printed as follows by default.

```
(api/group-by DS :V1)
```

\_unnamed [2 3]:

---

:name	:group-id	:data
1	0	Group: 1 [5 4]:
2	1	Group: 2 [4 4]:

---

To get groups as sequence or a map can be done from grouped dataset using `groups->seq` and `groups->map` functions.

Groups as seq can be obtained by just accessing `:data` column.

I will use temporary dataset here.

```
(let [ds (-> {"a" [1 1 2 2]
              "b" ["a" "b" "c" "d"]}
  (api/dataset)
  (api/group-by "a"))]
  (seq (ds :data))) ;; seq is not necessary but Markdown treats `:data` as command here
```

(Group: 1 [2 2]:

---

a	b
1	a
1	b

---

Group: 2 [2 2]:

---

a	b
2	c
2	d

---

)

```
(-> {"a" [1 1 2 2]
     "b" ["a" "b" "c" "d"]}
  (api/dataset)
  (api/group-by "a")
  (api/groups->seq))
```

(Group: 1 [2 2]:

a	b
1	a
1	b

Group: 2 [2 2]:

a	b
2	c
2	d

)

---

Groups as map

```
(-> {"a" [1 1 2 2]
     "b" ["a" "b" "c" "d"]})
(api/dataset)
(api/group-by "a")
(api/groups->map))
```

{1 Group: 1 [2 2]:

a	b
1	a
1	b

, 2 Group: 2 [2 2]:

a	b
2	c
2	d

}

---

Grouping by more than one column. You can see that group names are maps. When ungrouping is done these maps are used to restore column names.

```
(api/group-by DS [:V1 :V3] {:result-type :as-seq}))
```

(Group: {:V3 1.0, :V1 1} [1 4]:

:V1	:V2	:V3	:V4
1	5	1.0	B

Group: {:V3 0.5, :V1 1} [2 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
1	7	0.5	A

Group: {:V3 0.5, :V1 2} [1 4]:

:V1	:V2	:V3	:V4
2	4	0.5	A

Group: {:V3 1.0, :V1 2} [2 4]:

:V1	:V2	:V3	:V4
2	2	1.0	B
2	8	1.0	B

Group: {:V3 1.5, :V1 1} [2 4]:

:V1	:V2	:V3	:V4
1	3	1.5	C
1	9	1.5	C

Group: {:V3 1.5, :V1 2} [1 4]:

:V1	:V2	:V3	:V4
2	6	1.5	C

)

---

Grouping can be done by providing just row indexes. This way you can assign the same row to more than one group.

```
(api/group-by DS {"group-a" [1 2 1 2]
                  "group-b" [5 5 5 1]} {:result-type :as-seq}))
```

(Group: group-a [4 4]:

:V1	:V2	:V3	:V4
2	2	1.0	B
1	3	1.5	C
2	2	1.0	B
1	3	1.5	C

Group: group-b [4 4]:

:V1	:V2	:V3	:V4
2	6	1.5	C
2	6	1.5	C
2	6	1.5	C
2	2	1.0	B

)

You can group by a result of grouping function which gets row as map and should return group name. When map is used as a group name, ungrouping restore original column names.

```
(api/group-by DS (fn [row] (* (:V1 row)
                               (:V3 row))) {:result-type :as-seq}))
```

(Group: 1.0 [2 4]:

:V1	:V2	:V3	:V4
2	4	0.5	A
1	5	1.0	B

Group: 2.0 [2 4]:

:V1	:V2	:V3	:V4
2	2	1.0	B
2	8	1.0	B

Group: 0.5 [2 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
1	7	0.5	A

Group: 3.0 [1 4]:

:V1	:V2	:V3	:V4
2	6	1.5	C

Group: 1.5 [2 4]:

:V1	:V2	:V3	:V4
1	3	1.5	C
1	9	1.5	C

)

---

You can use any predicate on column to split dataset into two groups.

```
(api/group-by DS (comp #(< % 1.0) :V3) {:result-type :as-seq}))
```

(Group: false [6 4]:

:V1	:V2	:V3	:V4
2	2	1.0	B
1	3	1.5	C
1	5	1.0	B
2	6	1.5	C
2	8	1.0	B
1	9	1.5	C

Group: true [3 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	4	0.5	A
1	7	0.5	A

)

---

juxt is also helpful

```
(api/group-by DS (juxt :V1 :V3) {:result-type :as-seq}))
```

(Group: [1 1.0] [1 4]:

:V1	:V2	:V3	:V4
1	5	1.0	B

Group: [1 0.5] [2 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
1	7	0.5	A

Group: [2 1.5] [1 4]:

:V1	:V2	:V3	:V4
2	6	1.5	C



Group: [1 1.5] [2 4]:

:V1	:V2	:V3	:V4
1	3	1.5	C
1	9	1.5	C

Group: [2 0.5] [1 4]:

:V1	:V2	:V3	:V4
2	4	0.5	A

Group: [2 1.0] [2 4]:

:V1	:V2	:V3	:V4
2	2	1.0	B
2	8	1.0	B

)

---

`tech.ml.dataset` provides an option to limit columns which are passed to grouping functions. It's done for performance purposes.

```
(api/group-by DS identity { :result-type :as-seq  
                           :select-keys [:V1] })
```

(Group: {:V1 1} [5 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
1	3	1.5	C
1	5	1.0	B
1	7	0.5	A
1	9	1.5	C

Group: {:V1 2} [4 4]:

:V1	:V2	:V3	:V4
2	2	1.0	B
2	4	0.5	A
2	6	1.5	C
2	8	1.0	B

)

## Ungrouping

Ungrouping simply concatenates all the groups into the dataset. Following options are possible

- `:order?` - order groups according to the group name ascending order. Default: `false`
- `:add-group-as-column` - should group name become a column? If yes column is created with provided name (or `:$group-name` if argument is `true`). Default: `nil`.
- `:add-group-id-as-column` - should group id become a column? If yes column is created with provided name (or `:$group-id` if argument is `true`). Default: `nil`.
- `:dataset-name` - to name resulting dataset. Default: `nil` (`_unnamed`)

If group name is a map, it will be splitted into separate columns. Be sure that groups (subdatasets) doesn't contain the same columns already.

If group name is a vector, it will be splitted into separate columns. If you want to name them, set vector of target column names as `:add-group-as-column` argument.

After ungrouping, order of the rows is kept within the groups but groups are ordered according to the internal storage.

---

Grouping and ungrouping.

```
(-> DS
  (api/group-by :V3)
  (api/ungroup))
```

`_unnamed [9 4]`:

---

:V1	:V2	:V3	:V4
2	2	1.0	B
1	5	1.0	B
2	8	1.0	B
1	1	0.5	A
2	4	0.5	A
1	7	0.5	A
1	3	1.5	C
2	6	1.5	C
1	9	1.5	C

---

Groups sorted by group name and named.

```
(-> DS
  (api/group-by :V3)
  (api/ungroup {:order? true
                 :dataset-name "Ordered by V3"}))
```

Ordered by V3 [9 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
2	4	0.5	A
1	7	0.5	A
2	2	1.0	B
1	5	1.0	B
2	8	1.0	B

---

---

:V1	:V2	:V3	:V4
1	3	1.5	C
2	6	1.5	C
1	9	1.5	C

---

Groups sorted descending by group name and named.

```
(-> DS
  (api/group-by :V3)
  (api/ungroup {:order? :desc
                :dataset-name "Ordered by V3 descending"}))
```

Ordered by V3 descending [9 4]:

---

:V1	:V2	:V3	:V4
1	3	1.5	C
2	6	1.5	C
1	9	1.5	C
2	2	1.0	B
1	5	1.0	B
2	8	1.0	B
1	1	0.5	A
2	4	0.5	A
1	7	0.5	A

---

Let's add group name and id as additional columns

```
(-> DS
  (api/group-by (comp #(< % 4) :V2))
  (api/ungroup {:add-group-as-column true
                :add-group-id-as-column true})))
```

\_\_unnamed [9 6]:

---

:\$group-name	:\$group-id	:V1	:V2	:V3	:V4
false	0	2	4	0.5	A
false	0	1	5	1.0	B
false	0	2	6	1.5	C
false	0	1	7	0.5	A
false	0	2	8	1.0	B
false	0	1	9	1.5	C
true	1	1	1	0.5	A
true	1	2	2	1.0	B
true	1	1	3	1.5	C

---

Let's assign different column names

```
(-> DS
  (api/group-by (comp #(< % 4) :V2))
  (api/ungroup {:add-group-as-column "Is V2 less than 4?"
                :add-group-id-as-column "group id"})))
```

\_\_unnamed [9 6]:

Is V2 less than 4?	group id	:V1	:V2	:V3	:V4
false	0	2	4	0.5	A
false	0	1	5	1.0	B
false	0	2	6	1.5	C
false	0	1	7	0.5	A
false	0	2	8	1.0	B
false	0	1	9	1.5	C
true	1	1	1	0.5	A
true	1	2	2	1.0	B
true	1	1	3	1.5	C

If we group by map, we can automatically create new columns out of group names.

```
(-> DS
  (api/group-by (fn [row] {"V1 and V3 multiplied" (* (:V1 row)
                                                       (:V3 row))
                           "V4 as lowercase" (clojure.string/lower-case (:V4 row))}))
  (api/ungroup {:add-group-as-column true})))
```

\_\_unnamed [9 6]:

V1 and V3 multiplied	V4 as lowercase	:V1	:V2	:V3	:V4
1.000	a	2	4	0.5	A
0.5000	a	1	1	0.5	A
0.5000	a	1	7	0.5	A
1.000	b	1	5	1.0	B
2.000	b	2	2	1.0	B
2.000	b	2	8	1.0	B
3.000	c	2	6	1.5	C
1.500	c	1	3	1.5	C
1.500	c	1	9	1.5	C

We can add group names without separation

```
(-> DS
  (api/group-by (fn [row] {"V1 and V3 multiplied" (* (:V1 row)
                                                       (:V3 row))
                           "V4 as lowercase" (clojure.string/lower-case (:V4 row))}))
  (api/ungroup {:add-group-as-column "just map"
                :separate? false})))
```

\_\_unnamed [9 5]:

just map	:V1	:V2	:V3	:V4
{"V1 and V3 multiplied" 1.0, "V4 as lowercase" "a"}	2	4	0.5	A
{"V1 and V3 multiplied" 0.5, "V4 as lowercase" "a"}	1	1	0.5	A
{"V1 and V3 multiplied" 0.5, "V4 as lowercase" "a"}	1	7	0.5	A
{"V1 and V3 multiplied" 1.0, "V4 as lowercase" "b"}	1	5	1.0	B
{"V1 and V3 multiplied" 2.0, "V4 as lowercase" "b"}	2	2	1.0	B
{"V1 and V3 multiplied" 2.0, "V4 as lowercase" "b"}	2	8	1.0	B
{"V1 and V3 multiplied" 3.0, "V4 as lowercase" "c"}	2	6	1.5	C
{"V1 and V3 multiplied" 1.5, "V4 as lowercase" "c"}	1	3	1.5	C
{"V1 and V3 multiplied" 1.5, "V4 as lowercase" "c"}	1	9	1.5	C

The same applies to group names as sequences

```
(-> DS
  (api/group-by (juxt :V1 :V3))
  (api/ungroup {:add-group-as-column "abc"}))
```

\_\_unnamed [9 6]:

:abc-0	:abc-1	:V1	:V2	:V3	:V4
1	1.000	1	5	1.0	B
1	0.5000	1	1	0.5	A
1	0.5000	1	7	0.5	A
2	1.500	2	6	1.5	C
1	1.500	1	3	1.5	C
1	1.500	1	9	1.5	C
2	0.5000	2	4	0.5	A
2	1.000	2	2	1.0	B
2	1.000	2	8	1.0	B

Let's provide column names

```
(-> DS
  (api/group-by (juxt :V1 :V3))
  (api/ungroup {:add-group-as-column ["v1" "v3"]})))
```

\_\_unnamed [9 6]:

v1	v3	:V1	:V2	:V3	:V4
1	1.000	1	5	1.0	B
1	0.5000	1	1	0.5	A
1	0.5000	1	7	0.5	A
2	1.500	2	6	1.5	C
1	1.500	1	3	1.5	C
1	1.500	1	9	1.5	C
2	0.5000	2	4	0.5	A
2	1.000	2	2	1.0	B
2	1.000	2	8	1.0	B

---

Also we can suppress separation

```
(-> DS
  (api/group-by (juxt :V1 :V3))
  (api/ungroup {:separate? false
                :add-group-as-column true}))
;; => _unnamed [9 5]:
```

\_unnamed [9 5]:

:\$group-name	:V1	:V2	:V3	:V4
[1 1.0]	1	5	1.0	B
[1 0.5]	1	1	0.5	A
[1 0.5]	1	7	0.5	A
[2 1.5]	2	6	1.5	C
[1 1.5]	1	3	1.5	C
[1 1.5]	1	9	1.5	C
[2 0.5]	2	4	0.5	A
[2 1.0]	2	2	1.0	B
[2 1.0]	2	8	1.0	B

## Other functions

To check if dataset is grouped or not just use `grouped?` function.

```
(api/grouped? DS)
```

nil

```
(api/grouped? (api/group-by DS :V1))
```

true

---

If you want to remove grouping annotation (to make all the functions work as with regular dataset) you can use `unmark-group` or `as-regular-dataset` (alias) functions.

It can be important when you want to remove some groups (rows) from grouped dataset using `drop-rows` or something like that.

```
(-> DS
  (api/group-by :V1)
  (api/as-regular-dataset)
  (api/grouped?))
```

nil

---

This is considered internal.

If you want to implement your own mapping function on grouped dataset you can call `process-group-data` and pass function operating on datasets. Result should be a dataset to have ungrouping working.

```
(-> DS
  (api/group-by :V1)
```

```
(api/process-group-data #(str "Shape: " (vector (api/row-count %) (api/column-count %))))
(api/as-regular-dataset))
```

\_\_unnamed [2 3]:

:name	:group-id	:data
1	0	Shape: [5 4]
2	1	Shape: [4 4]

## Columns

Column is a special `tech.ml.dataset` structure based on `tech.ml.datatype` library. For our purposes we can treat columns as typed and named sequence bound to particular dataset.

Type of the data is inferred from a sequence during column creation.

## Names

To select dataset columns or column names `columns-selector` is used. `columns-selector` can be one of the following:

- `:all` keyword - selects all columns
- column name - for single column
- sequence of column names - for collection of columns
- `regex` - to apply pattern on column names or datatype
- filter predicate - to filter column names or datatype
- `type` namespaced keyword for specific datatype or group of datatypes

Column name can be anything.

`column-names` function returns names according to `columns-selector` and optional `meta-field`. `meta-field` is one of the following:

- `:name` (default) - to operate on column names
- `:datatype` - to operate on column types
- `:all` - if you want to process all metadata

Datatype groups are:

- `:type/numerical` - any numerical type
- `:type/float` - floating point number (`:float32` and `:float64`)
- `:type/integer` - any integer
- `:type/datetime` - any datetime type

If qualified keyword starts with `:!type`, complement set is used.

To select all column names you can use `column-names` function.

```
(api/column-names DS)
```

```
(:V1 :V2 :V3 :V4)
```

or

```
(api/column-names DS :all)
```

```
(:V1 :V2 :V3 :V4)
```

In case you want to select column which has name `:all` (or is sequence or map), put it into a vector. Below code returns empty sequence since there is no such column in the dataset.

```
(api/column-names DS [ :all])
```

```
()
```

---

Obviously selecting single name returns it's name if available

```
(api/column-names DS :V1)
(api/column-names DS "no such column")
```

```
(:V1)
()
```

---

Select sequence of column names.

```
(api/column-names DS [ :V1 "V2" :V3 :V4 :V5])
```

```
(:V1 :V3 :V4)
```

---

Select names based on regex, columns ends with 1 or 4

```
(api/column-names DS #"^[14]$")
```

```
(:V1 :V4)
```

---

Select names based on regex operating on type of the column (to check what are the column types, call `(api/info DS :columns)`). Here we want to get integer columns only.

```
(api/column-names DS #"^:int.*" :datatype)
```

```
(:V1 :V2)
```

or

```
(api/column-names DS :type/integer)
```

```
(:V1 :V2)
```

---

And finally we can use predicate to select names. Let's select double precision columns.

```
(api/column-names DS #{:float64} :datatype)
```

```
(:V3)
```

or

```
(api/column-names DS :type/float64 :datatype)
```

```
(:V3)
```

---

If you want to select all columns but given, use `complement` function. Works only on a predicate.



```
(api/column-names DS (complement #{:V1}))
(api/column-names DS (complement #{:float64}) :datatype)
(api/column-names DS :!type/float64)
```

```
(:V2 :V3 :V4)
(:V1 :V2 :V4)
(:V1 :V2 :V4)
```

---

You can select column names based on all column metadata at once by using `:all` metadata selector. Below we want to select column names ending with 1 which have long datatype.

```
(api/column-names DS (fn [meta]
  (and (= :int64 (:datatype meta))
    (clojure.string/ends-with? (:name meta) "1")))) :all)
```

```
(:V1)
```

## Select

`select-columns` creates dataset with columns selected by `columns-selector` as described above. Function works on regular and grouped dataset.

---

Select only float64 columns

```
(api/select-columns DS #(= :float64 %) :datatype)
```

\_\_unnamed [9 1]:

:V3
0.5
1.0
1.5
0.5
1.0
1.5
0.5
1.0
1.5

---

Select all but :V1 columns

```
(api/select-columns DS (complement #{:V1}))
```

\_\_unnamed [9 3]:

:V2	:V3	:V4
1	0.5	A
2	1.0	B
3	1.5	C
4	0.5	A
5	1.0	B

:V2	:V3	:V4
6	1.5	C
7	0.5	A
8	1.0	B
9	1.5	C

---

If we have grouped data set, column selection is applied to every group separately.

```
(-> DS
  (api/group-by :V1)
  (api/select-columns [ :V2 :V3 ])
  (api/groups->map))
```

{1 Group: 1 [5 2]:

:V2	:V3
1	0.5
3	1.5
5	1.0
7	0.5
9	1.5

, 2 Group: 2 [4 2]:

:V2	:V3
2	1.0
4	0.5
6	1.5
8	1.0

}

## Drop

`drop-columns` creates dataset with removed columns.

---

Drop float64 columns

```
(api/drop-columns DS # (= :float64 %) :datatype)
```

\_\_unnamed [9 3]:

:V1	:V2	:V4
1	1	A
2	2	B
1	3	C
2	4	A
1	5	B

:V1	:V2	:V4
2	6	C
1	7	A
2	8	B
1	9	C

---

Drop all columns but :V1 and :V2

```
(api/drop-columns DS (complement #{:V1 :V2}))
```

\_\_unnamed [9 2]:

:V1	:V2
1	1
2	2
1	3
2	4
1	5
2	6
1	7
2	8
1	9

---

If we have grouped data set, column selection is applied to every group separately. Selected columns are dropped.

```
(-> DS
  (api/group-by :V1)
  (api/drop-columns [ :V2 :V3])
  (api/groups->map))
```

{1 Group: 1 [5 2]:

:V1	:V4
1	A
1	C
1	B
1	A
1	C

, 2 Group: 2 [4 2]:

:V1	:V4
2	B
2	A
2	C
2	B

```
}
```

## Rename

If you want to rename columns use `rename-columns` and pass map where keys are old names, values new ones.

You can also pass mapping function with optional columns-selector

```
(api/rename-columns DS {:V1 "v1"  
                        :V2 "v2"  
                        :V3 [1 2 3]  
                        :V4 (Object.)})
```

\_\_unnamed [9 4]:

v1	v2	[1 2 3]	java.lang.Object@707627d2
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B
2	6	1.5	C
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

Map all names with function

```
(api/rename-columns DS (comp str second name))
```

\_\_unnamed [9 4]:

1	2	3	4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B
2	6	1.5	C
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

Map selected names with function

```
(api/rename-columns DS [:V1 :V3] (comp str second name))
```

\_\_unnamed [9 4]:

1	:V2	3	:V4
1	1	0.5	A

1	:V2	3	:V4
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B
2	6	1.5	C
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

Function works on grouped dataset

```
(-> DS
  (api/group-by :V1)
  (api/rename-columns { :V1 "v1"
                        :V2 "v2"
                        :V3 [1 2 3]
                        :V4 (Object.)})
  (api/groups->map))
```

{1 Group: 1 [5 4]:

v1	v2	[1 2 3]	java.lang.Object@5123a3ae
1	1	0.5	A
1	3	1.5	C
1	5	1.0	B
1	7	0.5	A
1	9	1.5	C

, 2 Group: 2 [4 4]:

v1	v2	[1 2 3]	java.lang.Object@5123a3ae
2	2	1.0	B
2	4	0.5	A
2	6	1.5	C
2	8	1.0	B

}

## Add or update

To add (or replace existing) column call **add-or-replace-column** function. Function accepts:

- **ds** - a dataset
- **column-name** - if it's existing column name, column will be replaced
- **column** - can be column (from other dataset), sequence, single value or function. Too big columns are always trimmed. Too small are cycled or extended with missing values (according to **size-strategy** argument)

- **size-strategy** (optional) - when new column is shorter than dataset row count, following strategies are applied:
  - **:cycle** (default) - repeat data
  - **:na** - append missing values
  - **:strict** - throws an exception when sizes mismatch

Function works on grouped dataset.

---

Add single value as column

```
(api/add-or-replace-column DS :V5 "X")
```

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:V5
1	1	0.5	A	X
2	2	1.0	B	X
1	3	1.5	C	X
2	4	0.5	A	X
1	5	1.0	B	X
2	6	1.5	C	X
1	7	0.5	A	X
2	8	1.0	B	X
1	9	1.5	C	X

---

Replace one column (column is trimmed)

```
(api/add-or-replace-column DS :V1 (repeatedly rand))
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
0.2029	1	0.5	A
0.5817	2	1.0	B
0.9218	3	1.5	C
0.4437	4	0.5	A
0.2126	5	1.0	B
0.6264	6	1.5	C
0.4933	7	0.5	A
0.03256	8	1.0	B
0.1262	9	1.5	C

---

Copy column

```
(api/add-or-replace-column DS :V5 (DS :V1))
```

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:V5
1	1	0.5	A	1

:V1	:V2	:V3	:V4	:V5
2	2	1.0	B	2
1	3	1.5	C	1
2	4	0.5	A	2
1	5	1.0	B	1
2	6	1.5	C	2
1	7	0.5	A	1
2	8	1.0	B	2
1	9	1.5	C	1

---

When function is used, argument is whole dataset and the result should be column, sequence or single value  
`(api/add-or-replace-column DS :row-count api/row-count)`

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:row-count
1	1	0.5	A	9
2	2	1.0	B	9
1	3	1.5	C	9
2	4	0.5	A	9
1	5	1.0	B	9
2	6	1.5	C	9
1	7	0.5	A	9
2	8	1.0	B	9
1	9	1.5	C	9

---

Above example run on grouped dataset, applies function on each group separately.

```
(-> DS
  (api/group-by :V1)
  (api/add-or-replace-column :row-count api/row-count)
  (api/ungroup))
```

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:row-count
1	1	0.5	A	5
1	3	1.5	C	5
1	5	1.0	B	5
1	7	0.5	A	5
1	9	1.5	C	5
2	2	1.0	B	4
2	4	0.5	A	4
2	6	1.5	C	4
2	8	1.0	B	4

---

When column which is added is longer than row count in dataset, column is trimmed. When column is

shorter, it's cycled or missing values are appended.

```
(api/add-or-replace-column DS :V5 [:r :b])
```

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:V5
1	1	0.5	A	:r
2	2	1.0	B	:b
1	3	1.5	C	:r
2	4	0.5	A	:b
1	5	1.0	B	:r
2	6	1.5	C	:b
1	7	0.5	A	:r
2	8	1.0	B	:b
1	9	1.5	C	:r

```
(api/add-or-replace-column DS :V5 [:r :b] :na)
```

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:V5
1	1	0.5	A	:r
2	2	1.0	B	:b
1	3	1.5	C	
2	4	0.5	A	
1	5	1.0	B	
2	6	1.5	C	
1	7	0.5	A	
2	8	1.0	B	
1	9	1.5	C	

Exception is thrown when `:strict` strategy is used and column size is not equal row count

```
(try  
  (api/add-or-replace-column DS :V5 [:r :b] :strict)  
  (catch Exception e (str "Exception caught: "(ex-message e))))
```

"Exception caught: Column size (2) should be exactly the same as dataset row count (9)"

---

Tha same applies for grouped dataset

```
(-> DS  
  (api/group-by :V3)  
  (api/add-or-replace-column :V5 [:r :b] :na)  
  (api/ungroup))
```

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:V5
2	2	1.0	B	:r
1	5	1.0	B	:b



:V1	:V2	:V3	:V4	:V5
2	8	1.0	B	
1	1	0.5	A	:r
2	4	0.5	A	:b
1	7	0.5	A	
1	3	1.5	C	:r
2	6	1.5	C	:b
1	9	1.5	C	

Let's use other column to fill groups

```
(-> DS
  (api/group-by :V3)
  (api/add-or-replace-column :V5 (DS :V2))
  (api/ungroup))
```

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:V5
2	2	1.0	B	1
1	5	1.0	B	2
2	8	1.0	B	3
1	1	0.5	A	1
2	4	0.5	A	2
1	7	0.5	A	3
1	3	1.5	C	1
2	6	1.5	C	2
1	9	1.5	C	3

In case you want to add or update several columns you can call `add-or-replace-columns` and provide map where keys are column names, vals are columns.

```
(api/add-or-replace-columns DS {:V1 #(map inc (% :V1))
                                :V5 #(map (comp keyword str) (% :V4))
                                :V6 11})
```

\_\_unnamed [9 6]:

:V1	:V2	:V3	:V4	:V5	:V6
2	1	0.5	A	:A	11
3	2	1.0	B	:B	11
2	3	1.5	C	:C	11
3	4	0.5	A	:A	11
2	5	1.0	B	:B	11
3	6	1.5	C	:C	11
2	7	0.5	A	:A	11
3	8	1.0	B	:B	11
2	9	1.5	C	:C	11

## Update

If you want to modify specific column(s) you can call `update-columns`. Arguments:

- dataset
- one of:
  - `columns-selector` and function (or sequence of functions)
  - map where keys are column names and vals are function

Functions accept column and have to return column or sequence

---

Reverse of columns

```
(api/update-columns DS :all reverse)
```

\_\_unnamed [9 4]:

---

:V1	:V2	:V3	:V4
1	9	1.500	C
2	8	1.000	B
1	7	0.5000	A
2	6	1.500	C
1	5	1.000	B
2	4	0.5000	A
1	3	1.500	C
2	2	1.000	B
1	1	0.5000	A

---

Apply dec/inc on numerical columns

```
(api/update-columns DS :type/numerical [(partial map dec)  
                                         (partial map inc)])
```

\_\_unnamed [9 4]:

---

:V1	:V2	:V3	:V4
0	2	-0.5000	A
1	3	0.000	B
0	4	0.5000	C
1	5	-0.5000	A
0	6	0.000	B
1	7	0.5000	C
0	8	-0.5000	A
1	9	0.000	B
0	10	0.5000	C

---

You can also assing function to a column by packing operations into the map.

```
(api/update-columns DS {:V1 reverse  
                        :V2 (comp shuffle seq)})
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	9	0.5	A
2	2	1.0	B
1	3	1.5	C
2	8	0.5	A
1	5	1.0	B
2	7	1.5	C
1	4	0.5	A
2	1	1.0	B
1	6	1.5	C

## Map

The other way of creating or updating column is to map rows as regular `map` function. The arity of mapping function should be the same as number of selected columns.

Arguments:

- `ds` - dataset
- `column-name` - target column name
- `columns-selector` - columns selected
- `map-fn` - mapping function

Let's add numerical columns together

```
(api/map-columns DS
  :sum-of-numbers
  (api/column-names DS #{:int64 :float64} :datatype)
  (fn [& rows]
    (reduce + rows)))
```

`__unnamed [9 5]`:

:V1	:V2	:V3	:V4	:sum-of-numbers
1	1	0.5	A	2.5
2	2	1.0	B	5.0
1	3	1.5	C	5.5
2	4	0.5	A	6.5
1	5	1.0	B	7.0
2	6	1.5	C	9.5
1	7	0.5	A	8.5
2	8	1.0	B	11.0
1	9	1.5	C	11.5

The same works on grouped dataset

```
(-> DS
  (api/group-by :V4)
  (api/map-columns :sum-of-numbers
    (api/column-names DS #{:int64 :float64} :datatype)
    (fn [& rows]
      (reduce + rows)))
  (api/ungroup))
```

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:sum-of-numbers
1	1	0.5	A	2.5
2	4	0.5	A	6.5
1	7	0.5	A	8.5
2	2	1.0	B	5.0
1	5	1.0	B	7.0
2	8	1.0	B	11.0
1	3	1.5	C	5.5
2	6	1.5	C	9.5
1	9	1.5	C	11.5

## Reorder

To reorder columns use columns selectors to choose what columns go first. The unselected columns are appended to the end.

```
(api/reorder-columns DS :V4 [:V3 :V2] :V1)
```

\_\_unnamed [9 4]:

:V4	:V2	:V3	:V1
A	1	0.5	1
B	2	1.0	2
C	3	1.5	1
A	4	0.5	2
B	5	1.0	1
C	6	1.5	2
A	7	0.5	1
B	8	1.0	2
C	9	1.5	1

This function doesn't let you select meta field, so you have to call `column-names` in such case. Below we want to add integer columns at the end.

```
(api/reorder-columns DS (api/column-names DS (complement #{:int64}) :datatype))
```

\_\_unnamed [9 4]:

:V3	:V4	:V1	:V2
0.5	A	1	1
1.0	B	2	2
1.5	C	1	3
0.5	A	2	4
1.0	B	1	5
1.5	C	2	6
0.5	A	1	7
1.0	B	2	8

:V3	:V4	:V1	:V2
1.5	C	1	9

## Type conversion

To convert column into given datatype can be done using `convert-types` function. Not all the types can be converted automatically also some types require slow parsing (every conversion from string). In case where conversion is not possible you can pass conversion function.

Arguments:

- `ds` - dataset
- Two options:
  - `coltype-map` in case when you want to convert several columns, keys are column names, vals are new types
  - `column-selector` and `new-types` - column name and new datatype (or datatypes as sequence)

`new-types` can be:

- a type like `:int64` or `:string` or sequence of types
- or sequence of pair of datatype and conversion function

After conversion additional information is given on problematic values.

The other conversion is casting column into java array (`->array`) of the type column or provided as argument. Grouped dataset returns sequence of arrays.

Basic conversion

```
(-> DS
  (api/convert-types :V1 :float64)
  (api/info :columns))
```

`_unnamed :column info [4 6]:`

:name	:size	:datatype	:unparsed-indexes	:unparsed-data	:categorical?
:V1	9	:float64	{}	[]	
:V2	9	:int64			
:V3	9	:float64			
:V4	9	:string			true

Using custom converter. Let's treat `:V4` as hexadecimal values. See that this way we can map column to any value.

```
(-> DS
  (api/convert-types :V4 [[:int16 #(Integer/parseInt % 16)]]))
```

`_unnamed [9 4]:`

:V1	:V2	:V3	:V4
1	1	0.5	10
2	2	1.0	11
1	3	1.5	12

:V1	:V2	:V3	:V4
2	4	0.5	10
1	5	1.0	11
2	6	1.5	12
1	7	0.5	10
2	8	1.0	11
1	9	1.5	12

You can process several columns at once

```
(-> DS
  (api/convert-types {:V1 :float64
                     :V2 :object
                     :V3 [[:boolean #(< % 1.0)]
                     :V4 :object]})
  (api/info :columns))
```

\_\_unnamed :column info [4 5]:

:name	:size	:datatype	:unparsed-indexes	:unparsed-data
:V1	9	:float64	{}	[]
:V2	9	:object	{}	[]
:V3	9	:boolean	{}	[]
:V4	9	:object		

Convert one type into another

```
(-> DS
  (api/convert-types :type/numerical :int16)
  (api/info :columns))
```

\_\_unnamed :column info [4 6]:

:name	:size	:datatype	:unparsed-indexes	:unparsed-data	:categorical?
:V1	9	:int16	{}	[]	
:V2	9	:int16	{}	[]	
:V3	9	:int16	{}	[]	
:V4	9	:string			true

Function works on the grouped dataset

```
(-> DS
  (api/group-by :V1)
  (api/convert-types :V1 :float32)
  (api/ungroup)
  (api/info :columns))
```

\_\_unnamed :column info [4 6]:

:name	:size	:datatype	:unparsed-indexes	:unparsed-data	:categorical?
:V1	9	:float32	{}	[]	
:V2	9	:int64			
:V3	9	:float64			
:V4	9	:string			true

Double array conversion.

```
(api/->array DS :V1)
```

```
#object["[J" 0x75a26872 "[J@75a26872"]
```

Function also works on grouped dataset

```
(-> DS
  (api/group-by :V3)
  (api/->array :V2))
```

```
(#object["[J" 0x36120b79 "[J@36120b79"] #object["[J" 0x6b15234a "[J@6b15234a"] #object["[J" 0x6d73e5a7
```

You can also cast the type to the other one (if casting is possible):

```
(api/->array DS :V4 :string)
(api/->array DS :V1 :float32)
```

```
#object["[Ljava.lang.String;" 0x4be890b8 "[Ljava.lang.String;@4be890b8"]
#object["[F" 0x50ec7a4b "[F@50ec7a4b"]
```

## Rows

Rows can be selected or dropped using various selectors:

- row id(s) - row index as number or sequence of numbers (first row has index 0, second 1 and so on)
- sequence of true/false values
- filter by predicate (argument is row as a map)

When predicate is used you may want to limit columns passed to the function (**select-keys** option).

Additionally you may want to precalculate some values which will be visible for predicate as additional columns. It's done internally by calling **add-or-replace-columns** on a dataset. **:pre** is used as a column definitions.

## Select

Select fourth row

```
(api/select-rows DS 4)
```

\_\_unnamed [1 4]:

:V1	:V2	:V3	:V4
1	5	1.0	B

---

Select 3 rows

```
(api/select-rows DS [1 4 5])
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
2	2	1.0	B
1	5	1.0	B
2	6	1.5	C

---

Select rows using sequence of true/false values

```
(api/select-rows DS [true nil nil true])
```

\_\_unnamed [2 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	4	0.5	A

---

Select rows using predicate

```
(api/select-rows DS (comp #(< % 1) :V3))
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	4	0.5	A
1	7	0.5	A

---

The same works on grouped dataset, let's select first row from every group.

```
(-> DS  
  (api/group-by :V1)  
  (api/select-rows 0)  
  (api/ungroup))
```

\_\_unnamed [2 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B

---



If you want to select :V2 values which are lower than or equal mean in grouped dataset you have to precalculate it using :pre.

```
(-> DS
  (api/group-by :V4)
  (api/select-rows (fn [row] (<= (:V2 row) (:mean row)))
    {:pre {:mean #(tech.v2.datatype.functional/mean (% :V2))}})
  (api/ungroup))
```

\_\_unnamed [6 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	4	0.5	A
2	2	1.0	B
1	5	1.0	B
1	3	1.5	C
2	6	1.5	C

## Drop

drop-rows removes rows, and accepts exactly the same parameters as select-rows

---

Drop values lower than or equal :V2 column mean in grouped dataset.

```
(-> DS
  (api/group-by :V4)
  (api/drop-rows (fn [row] (<= (:V2 row) (:mean row)))
    {:pre {:mean #(tech.v2.datatype.functional/mean (% :V2))}})
  (api/ungroup))
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

## Other

There are several function to select first, last, random rows, or display head, tail of the dataset. All functions work on grouped dataset.

All random functions accept :seed as an option if you want to fix returned result.

---

First row

```
(api/first DS)
```

\_\_unnamed [1 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A

---

Last row

(`api/last DS`)

\_\_unnamed [1 4]:

:V1	:V2	:V3	:V4
1	9	1.5	C

---

Random row (single)

(`api/rand-nth DS`)

\_\_unnamed [1 4]:

:V1	:V2	:V3	:V4
1	5	1.0	B

---

Random row (single) with seed

(`api/rand-nth DS { :seed 42 }`)

\_\_unnamed [1 4]:

:V1	:V2	:V3	:V4
2	6	1.5	C

---

Random `n` (default: row count) rows with repetition.

(`api/random DS`)

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
2	6	1.5	C
1	3	1.5	C
2	2	1.0	B
1	9	1.5	C
1	5	1.0	B
1	5	1.0	B
2	8	1.0	B
2	8	1.0	B
2	2	1.0	B

---

Five random rows with repetition

```
(api/random DS 5)
```

\_\_unnamed [5 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
1	3	1.5	C
2	8	1.0	B
2	8	1.0	B
2	4	0.5	A

---

Five random, non-repeating rows

```
(api/random DS 5 {:repeat? false})
```

\_\_unnamed [5 4]:

:V1	:V2	:V3	:V4
2	8	1.0	B
1	7	0.5	A
2	2	1.0	B
2	4	0.5	A
2	6	1.5	C

---

Five random, with seed

```
(api/random DS 5 {:seed 42})
```

\_\_unnamed [5 4]:

:V1	:V2	:V3	:V4
2	6	1.5	C
1	5	1.0	B
1	3	1.5	C
1	1	0.5	A
1	9	1.5	C

---

Shuffle dataset

```
(api/shuffle DS)
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	9	1.5	C

:V1	:V2	:V3	:V4
1	3	1.5	C
2	8	1.0	B
1	1	0.5	A
2	2	1.0	B
2	4	0.5	A
1	7	0.5	A
2	6	1.5	C
1	5	1.0	B

---

Shuffle with seed

```
(api/shuffle DS {:seed 42})
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	5	1.0	B
2	2	1.0	B
2	6	1.5	C
2	4	0.5	A
2	8	1.0	B
1	3	1.5	C
1	7	0.5	A
1	1	0.5	A
1	9	1.5	C

---

First **n** rows (default 5)

```
(api/head DS)
```

\_\_unnamed [5 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B

---

Last **n** rows (default 5)

```
(api/tail DS)
```

\_\_unnamed [5 4]:

:V1	:V2	:V3	:V4
1	5	1.0	B

:V1	:V2	:V3	:V4
2	6	1.5	C
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

**by-rank** calculates rank on column(s). It's base on R `rank()` with addition of **:dense** (default) tie strategy which give consecutive rank numbering.

**:desc?** options (default: **true**) sorts input with descending order, giving top values under 0 value.

**rank** is zero based and is defined at `tablecloth.api.utils` namespace.

```
(api/by-rank DS :V3 zero?) ;; most V3 values
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
1	3	1.5	C
2	6	1.5	C
1	9	1.5	C

```
(api/by-rank DS :V3 zero? {:desc? false}) ;; least V3 values
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	4	0.5	A
1	7	0.5	A

Rank also works on multiple columns

```
(api/by-rank DS [:V1 :V3] zero? {:desc? false})
```

\_\_unnamed [2 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
1	7	0.5	A

Select 5 random rows from each group

```
(-> DS
  (api/group-by :V4)
  (api/random 5)
```

```
(api/ungroup))
```

```
_unnamed [15 4]:
```

:V1	:V2	:V3	:V4
1	7	0.5	A
2	4	0.5	A
1	1	0.5	A
1	7	0.5	A
1	7	0.5	A
2	8	1.0	B
1	5	1.0	B
2	2	1.0	B
2	2	1.0	B
2	2	1.0	B
1	9	1.5	C
1	3	1.5	C
1	9	1.5	C
2	6	1.5	C
2	6	1.5	C

## Aggregate

Aggregating is a function which produces single row out of dataset.

Aggregator is a function or sequence or map of functions which accept dataset as an argument and result single value, sequence of values or map.

Where map is given as an input or result, keys are treated as column names.

Grouped dataset is ungrouped after aggregation. This can be turned off by setting `:ungroup` to false. In case you want to pass additional ungrouping parameters add them to the options.

By default resulting column names are prefixed with `summary` prefix (set it with `:default-column-name-prefix` option).

---

Let's calculate mean of some columns

```
(api/aggregate DS #(reduce + (% :V2)))
```

```
_unnamed [1 1]:
```

:summary
45

---

Let's give resulting column a name.

```
(api/aggregate DS {:sum-of-V2 #(reduce + (% :V2))})
```

```
_unnamed [1 1]:
```

:sum-of-V2
45

Sequential result is spread into separate columns

```
(api/aggregate DS #(take 5(% :V2)))
```

\_unnamed [1 5]:

:summary-0	:summary-1	:summary-2	:summary-3	:summary-4
1	2	3	4	5

You can combine all variants and rename default prefix

```
(api/aggregate DS [#(take 3 (% :V2))
  (fn [ds] {:sum-v1 (reduce + (ds :V1))
            :prod-v3 (reduce * (ds :V3))})] {:default-column-name-prefix "V2-value"}))
```

\_unnamed [1 5]:

:V2-value-0-0	:V2-value-0-1	:V2-value-0-2	:V2-value-1-sum-v1	:V2-value-1-prod-v3
1	2	3	13	0.421875

Processing grouped dataset

```
(-> DS
  (api/group-by [:V4])
  (api/aggregate [#(take 3 (% :V2))
    (fn [ds] {:sum-v1 (reduce + (ds :V1))
              :prod-v3 (reduce * (ds :V3))})] {:default-column-name-prefix "V2-value"}))
```

\_unnamed [3 6]:

:V4	:V2-value-0-0	:V2-value-0-1	:V2-value-0-2	:V2-value-1-sum-v1	:V2-value-1-prod-v3
B	2	5	8	5	1.000
C	3	6	9	4	3.375
A	1	4	7	4	0.125

Result of aggregating is automatically ungrouped, you can skip this step by setting :ungroup option to false.

```
(-> DS
  (api/group-by [:V3])
  (api/aggregate [#(take 3 (% :V2))
    (fn [ds] {:sum-v1 (reduce + (ds :V1))
              :prod-v3 (reduce * (ds :V3))})] {:default-column-name-prefix "V2-value"
        :ungroup? false}))
```

\_\_unnamed [3 3]:

:name	:group-id	:data
{:V3 1.0}	0	__unnamed [1 5]:
{:V3 0.5}	1	__unnamed [1 5]:
{:V3 1.5}	2	__unnamed [1 5]:

## Column

You can perform columnar aggregation also. `aggregate-columns` selects columns and apply aggregating function (or sequence of functions) for each column separately.

```
(api/aggregate-columns DS [:V1 :V2 :V3] #([reduce + %])
```

\_\_unnamed [1 3]:

:V1	:V2	:V3
13	45	9.0

```
(api/aggregate-columns DS [:V1 :V2 :V3] [#([reduce + %])  
                                         #([reduce max %])  
                                         #([reduce * %])])
```

\_\_unnamed [1 3]:

:V1	:V2	:V3
13	9	0.421875

```
(-> DS  
  (api/group-by [:V4])  
  (api/aggregate-columns [:V1 :V2 :V3] #([reduce + %])))
```

\_\_unnamed [3 4]:

:V4	:V1	:V2	:V3
B	5	15	3.0
C	4	18	4.5
A	4	12	1.5

## Order

Ordering can be done by column(s) or any function operating on row. Possible order can be:

- `:asc` for ascending order (default)
- `:desc` for descending order
- custom comparator

`:select-keys` limits row map provided to ordering functions.



---

Order by single column, ascending

```
(api/order-by DS :V1)
```

\_\_unnamed [9 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
1	3	1.5	C
1	5	1.0	B
1	7	0.5	A
1	9	1.5	C
2	6	1.5	C
2	4	0.5	A
2	8	1.0	B
2	2	1.0	B

---

---

Descending order

```
(api/order-by DS :V1 :desc)
```

\_\_unnamed [9 4]:

---

:V1	:V2	:V3	:V4
2	2	1.0	B
2	4	0.5	A
2	6	1.5	C
2	8	1.0	B
1	5	1.0	B
1	3	1.5	C
1	7	0.5	A
1	1	0.5	A
1	9	1.5	C

---

---

Order by two columns

```
(api/order-by DS [:V1 :V2])
```

\_\_unnamed [9 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
1	3	1.5	C
1	5	1.0	B
1	7	0.5	A
1	9	1.5	C
2	2	1.0	B
2	4	0.5	A
2	6	1.5	C

---

:V1	:V2	:V3	:V4
2	8	1.0	B

Use different orders for columns

```
(api/order-by DS [ :V1 :V2] [ :asc :desc])
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	9	1.5	C
1	7	0.5	A
1	5	1.0	B
1	3	1.5	C
1	1	0.5	A
2	8	1.0	B
2	6	1.5	C
2	4	0.5	A
2	2	1.0	B

```
(api/order-by DS [ :V1 :V2] [ :desc :desc])
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
2	8	1.0	B
2	6	1.5	C
2	4	0.5	A
2	2	1.0	B
1	9	1.5	C
1	7	0.5	A
1	5	1.0	B
1	3	1.5	C
1	1	0.5	A

```
(api/order-by DS [ :V1 :V3] [ :desc :asc])
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
2	4	0.5	A
2	2	1.0	B
2	8	1.0	B
2	6	1.5	C
1	1	0.5	A
1	7	0.5	A
1	5	1.0	B
1	3	1.5	C
1	9	1.5	C

---

Custom function can be used to provide ordering key. Here order by :V4 descending, then by product of other columns ascending.

```
(api/order-by DS [[:V4 (fn [row] (* (:V1 row)
                                   (:V2 row)
                                   (:V3 row)))] [:desc :asc] {:select-keys [[:V1 :V2 :V3]]})
```

\_\_unnamed [9 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
1	7	0.5	A
2	4	0.5	A
2	2	1.0	B
1	3	1.5	C
1	5	1.0	B
1	9	1.5	C
2	8	1.0	B
2	6	1.5	C

---



---

Custom comparator also can be used in case objects are not comparable by default. Let's define artificial one: if Euclidean distance is lower than 2, compare along z else along x and y. We use first three columns for that.

```
(defn dist
  [v1 v2]
  (->> v2
    (map - v1)
    (map #(* % %)
    (reduce +)
    (Math/sqrt)))
```

#'user/dist

```
(api/order-by DS [[:V1 :V2 :V3] (fn [[x1 y1 z1 :as v1] [x2 y2 z2 :as v2]]
  (let [d (dist v1 v2)]
    (if (< d 2.0)
      (compare z1 z2)
      (compare [x1 y1] [x2 y2])))))]
```

\_\_unnamed [9 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
1	5	1.0	B
1	7	0.5	A
1	9	1.5	C
2	2	1.0	B
2	4	0.5	A
1	3	1.5	C
2	6	1.5	C
2	8	1.0	B

---

## Unique

Remove rows which contains the same data. By default **unique-by** removes duplicates from whole dataset. You can also pass list of columns or functions (similar as in **group-by**) to remove duplicates limited by them. Default strategy is to keep the first row. More strategies below.

**unique-by** works on groups

---

Remove duplicates from whole dataset

```
(api/unique-by DS)
```

\_\_unnamed [9 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B
2	6	1.5	C
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

---

---

Remove duplicates from each group selected by column.

```
(api/unique-by DS :V1)
```

\_\_unnamed [2 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B

---

---

Pair of columns

```
(api/unique-by DS [:V1 :V3])
```

\_\_unnamed [6 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B
2	6	1.5	C

---

---

Also function can be used, split dataset by modulo 3 on columns :V2

```
(api/unique-by DS (fn [m] (mod (:V2 m) 3)))
```

\_\_unnamed [3 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C

---

---

The same can be achieved with group-by

```
(-> DS
  (api/group-by (fn [m] (mod (:V2 m) 3)))
  (api/first)
  (api/ungroup))
```

\_\_unnamed [3 4]:

---

:V1	:V2	:V3	:V4
1	3	1.5	C
1	1	0.5	A
2	2	1.0	B

---

---

Grouped dataset

```
(-> DS
  (api/group-by :V4)
  (api/unique-by :V1)
  (api/ungroup))
```

\_\_unnamed [6 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
2	4	0.5	A
2	2	1.0	B
1	5	1.0	B
1	3	1.5	C
2	6	1.5	C

---

## Strategies

There are 4 strategies defined:

- **:first** - select first row (default)
- **:last** - select last row
- **:random** - select random row

- any function - apply function to a columns which are subject of uniqueness

---

Last

```
(api/unique-by DS :V1 {:strategy :last})
```

\_\_unnamed [2 4]:

---

:V1	:V2	:V3	:V4
2	8	1.0	B
1	9	1.5	C

---



---

Random

```
(api/unique-by DS :V1 {:strategy :random})
```

\_\_unnamed [2 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
2	6	1.5	C

---



---

Pack columns into vector

```
(api/unique-by DS :V4 {:strategy vec})
```

\_\_unnamed [3 3]:

---

:V1	:V2	:V3
[2 1 2]	[2 5 8]	[1.0 1.0 1.0]
[1 2 1]	[3 6 9]	[1.5 1.5 1.5]
[1 2 1]	[1 4 7]	[0.5 0.5 0.5]

---



---

Sum columns

```
(api/unique-by DS :V4 {:strategy (partial reduce +)})
```

\_\_unnamed [3 3]:

---

:V1	:V2	:V3
5	15	3.0
4	18	4.5
4	12	1.5

---



---

Group by function and apply functions

```
(api/unique-by DS (fn [m] (mod (:V2 m) 3)) {:strategy vec}))
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
[1 2 1]	[3 6 9]	[1.5 1.5 1.5]	["C" "C" "C"]
[1 2 1]	[1 4 7]	[0.5 0.5 0.5]	["A" "A" "A"]
[2 1 2]	[2 5 8]	[1.0 1.0 1.0]	["B" "B" "B"]

Grouped dataset

```
(-> DS
  (api/group-by :V1)
  (api/unique-by (fn [m] (mod (:V2 m) 3)) {:strategy vec}))
  (api/ungroup {:add-group-as-column :from-V1}))
```

\_\_unnamed [6 5]:

:from-V1	:V1	:V2	:V3	:V4
1	[1 1]	[3 9]	[1.5 1.5]	["C" "C"]
1	[1 1]	[1 7]	[0.5 0.5]	["A" "A"]
1	[1]	[5]	[1.0]	["B"]
2	[2]	[6]	[1.5]	["C"]
2	[2]	[4]	[0.5]	["A"]
2	[2 2]	[2 8]	[1.0 1.0]	["B" "B"]

## Missing

When dataset contains missing values you can select or drop rows with missing values or replace them using some strategy.

`column-selector` can be used to limit considered columns

Let's define dataset which contains missing values

```
(def DSm (api/dataset {:V1 (take 9 (cycle [1 2 nil]))
  :V2 (range 1 10)
  :V3 (take 9 (cycle [0.5 1.0 nil 1.5]))
  :V4 (take 9 (cycle ["A" "B" "C"])))}))
```

DSm

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
	3		C
1	4	1.5	A
2	5	0.5	B
	6	1.0	C
1	7		A

:V1	:V2	:V3	:V4
2	8	1.5	B
	9	0.5	C

## Select

Select rows with missing values

```
(api/select-missing DSm)
```

\_\_unnamed [4 4]:

:V1	:V2	:V3	:V4
	3		C
	6	1.0	C
1	7		A
	9	0.5	C

Select rows with missing values in :V1

```
(api/select-missing DSm :V1)
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
	3		C
	6	1.0	C
	9	0.5	C

The same with grouped dataset

```
(-> DSm
  (api/group-by :V4)
  (api/select-missing :V3)
  (api/ungroup))
```

\_\_unnamed [2 4]:

:V1	:V2	:V3	:V4
1	7		A
	3		C

## Drop

Drop rows with missing values

```
(api/drop-missing DSm)
```

\_\_unnamed [5 4]:



:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	4	1.5	A
2	5	0.5	B
2	8	1.5	B

---

Drop rows with missing values in :V1

```
(api/drop-missing DSm :V1)
```

\_\_unnamed [6 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	4	1.5	A
2	5	0.5	B
1	7		A
2	8	1.5	B

---

The same with grouped dataset

```
(-> DSm
  (api/group-by :V4)
  (api/drop-missing :V1)
  (api/ungroup))
```

\_\_unnamed [6 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
1	4	1.5	A
1	7		A
2	2	1.0	B
2	5	0.5	B
2	8	1.5	B

## Replace

Missing values can be replaced using several strategies. **replace-missing** accepts:

- dataset
- column selector
- value
  - single value
  - sequence of values (cycled)
  - function, applied on column(s) with stripped missings
- strategy (optional)

Strategies are:

- `:value` - replace with given value (default)
- `:up` - copy values up
- `:down` - copy values down

Let's define special dataset here:

```
(def DSm2 (api/dataset { :a [nil nil nil 1.0 2 nil 4 nil 11 nil nil]
                        :b [2.0 2 2 nil nil 3 nil 3 4 5 5]}))
```

DSm2

\_\_unnamed [11 2]:

:a	:b
	2.0
	2.0
	2.0
1.0	
2.0	
	3.0
4.0	
	3.0
11.0	4.0
	5.0
	5.0

Replace missing with single value in whole dataset

```
(api/replace-missing DSm2 999)
```

\_\_unnamed [11 2]:

:a	:b
999.0	2.0
999.0	2.0
999.0	2.0
1.0	999.0
2.0	999.0
999.0	3.0
4.0	999.0
999.0	3.0
11.0	4.0
999.0	5.0
999.0	5.0

Replace missing with single value in `:a` column

```
(api/replace-missing DSm2 :a 999)
```

\_\_unnamed [11 2]:

---

:a	:b
999.0	2.0
999.0	2.0
999.0	2.0
1.0	
2.0	
999.0	3.0
4.0	
999.0	3.0
11.0	4.0
999.0	5.0
999.0	5.0

---



---

Replace missing with sequence in :a column

```
(api/replace-missing DSm2 :a [-999 -998 -997])
```

\_\_unnamed [11 2]:

:a	:b
-999.0	2.0
-998.0	2.0
-997.0	2.0
1.0	
2.0	
-999.0	3.0
4.0	
-998.0	3.0
11.0	4.0
-997.0	5.0
-999.0	5.0

---



---

Replace missing with a function (mean)

```
(api/replace-missing DSm2 :a tech.v2.datatype.functional/mean)
```

\_\_unnamed [11 2]:

:a	:b
4.5	2.0
4.5	2.0
4.5	2.0
1.0	
2.0	
4.5	3.0
4.0	
4.5	3.0
11.0	4.0
4.5	5.0
4.5	5.0

---

---

Using `:down` strategy, fills gaps with values from above. You can see that if missings are at the beginning, they are left missing.

```
(api/replace-missing DSm2 [:a :b] nil :down)
```

\_\_unnamed [11 2]:

---

:a	:b
	2.0
	2.0
	2.0
1.0	2.0
2.0	2.0
2.0	3.0
4.0	3.0
4.0	3.0
11.0	4.0
11.0	5.0
11.0	5.0

---

---

To fix above issue you can provide value

```
(api/replace-missing DSm2 [:a :b] 999 :down)
```

\_\_unnamed [11 2]:

---

:a	:b
999.0	2.0
999.0	2.0
999.0	2.0
1.0	2.0
2.0	2.0
2.0	3.0
4.0	3.0
4.0	3.0
11.0	4.0
11.0	5.0
11.0	5.0

---

---

The same applies for `:up` strategy which is opposite direction.

```
(api/replace-missing DSm2 [:a :b] 999 :up)
```

\_\_unnamed [11 2]:

---

:a	:b
1.0	2.0
1.0	2.0
1.0	2.0

---

:a	:b
1.0	3.0
2.0	3.0
4.0	3.0
4.0	3.0
11.0	3.0
11.0	4.0
999.0	5.0
999.0	5.0

We can use a function which is applied after applying `:up` or `:down`

```
(api/replace-missing DSml2 [:a :b] tech.v2.datatype.functional/mean :down)
```

\_\_unnamed [11 2]:

:a	:b
4.5	2.0
4.5	2.0
4.5	2.0
1.0	2.0
2.0	2.0
2.0	3.0
4.0	3.0
4.0	3.0
11.0	4.0
11.0	5.0
11.0	5.0

## Join/Separate Columns

Joining or separating columns are operations which can help to tidy messy dataset.

- `join-columns` joins content of the columns (as string concatenation or other structure) and stores it in new column
- `separate-column` splits content of the columns into set of new columns

## Join

`join-columns` accepts:

- dataset
- column selector (as in `select-columns`)
- options
  - `:separator` (default "-")
  - `:drop-columns?` - whether to drop source columns or not (default `true`)
  - `:result-type`
    - \* `:map` - packs data into map
    - \* `:seq` - packs data into sequence
    - \* `:string` - join strings with separator (default)
    - \* or custom function which gets row as a vector

– `:missing-subst` - substitution for missing value

---

Default usage. Create `:joined` column out of other columns.

```
(api/join-columns DSm :joined [:V1 :V2 :V4])
```

\_\_unnamed [9 2]:

:V3	:joined
0.5	1-1-A
1.0	2-2-B
	3-C
1.5	1-4-A
0.5	2-5-B
1.0	6-C
	1-7-A
1.5	2-8-B
0.5	9-C

---

Without dropping source columns.

```
(api/join-columns DSm :joined [:V1 :V2 :V4] {:drop-columns? false})
```

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:joined
1	1	0.5	A	1-1-A
2	2	1.0	B	2-2-B
	3		C	3-C
1	4	1.5	A	1-4-A
2	5	0.5	B	2-5-B
	6	1.0	C	6-C
1	7		A	1-7-A
2	8	1.5	B	2-8-B
	9	0.5	C	9-C

---

Let's replace missing value with "NA" string.

```
(api/join-columns DSm :joined [:V1 :V2 :V4] {:missing-subst "NA"})
```

\_\_unnamed [9 2]:

:V3	:joined
0.5	1-1-A
1.0	2-2-B
	NA-3-C
1.5	1-4-A
0.5	2-5-B
1.0	NA-6-C
	1-7-A

---

:V3	:joined
1.5	2-8-B
0.5	NA-9-C

---



---

We can use custom separator.

```
(api/join-columns DSm :joined [:V1 :V2 :V4] {:separator "/"
                                              :missing-subst "."})
```

\_\_unnamed [9 2]:

---

:V3	:joined
0.5	1/1/A
1.0	2/2/B
	./3/C
1.5	1/4/A
0.5	2/5/B
1.0	./6/C
	1/7/A
1.5	2/8/B
0.5	./9/C

---



---

Or even sequence of separators.

```
(api/join-columns DSm :joined [:V1 :V2 :V4] {:separator ["-" "/"]
                                              :missing-subst "."})
```

\_\_unnamed [9 2]:

---

:V3	:joined
0.5	1-1/A
1.0	2-2/B
	.-3/C
1.5	1-4/A
0.5	2-5/B
1.0	.-6/C
	1-7/A
1.5	2-8/B
0.5	.-9/C

---



---

The other types of results, map:

```
(api/join-columns DSm :joined [:V1 :V2 :V4] {:result-type :map})
```

\_\_unnamed [9 2]:

---

:V3	:joined
0.5	{:V1 1, :V2 1, :V4 "A"}

---

---

:V3	:joined
1.0	{:V1 2, :V2 2, :V4 "B"} {:V1 nil, :V2 3, :V4 "C"}
1.5	{:V1 1, :V2 4, :V4 "A"}
0.5	{:V1 2, :V2 5, :V4 "B"}
1.0	{:V1 nil, :V2 6, :V4 "C"} {:V1 1, :V2 7, :V4 "A"}
1.5	{:V1 2, :V2 8, :V4 "B"}
0.5	{:V1 nil, :V2 9, :V4 "C"}

---

Sequence

```
(api/join-columns DSm :joined [:V1 :V2 :V4] {:result-type :seq})
```

\_\_unnamed [9 2]:

---

:V3	:joined
0.5	(1 1 "A")
1.0	(2 2 "B") (nil 3 "C")
1.5	(1 4 "A")
0.5	(2 5 "B")
1.0	(nil 6 "C") (1 7 "A")
1.5	(2 8 "B")
0.5	(nil 9 "C")

---

Custom function, calculate hash

```
(api/join-columns DSm :joined [:V1 :V2 :V4] {:result-type hash})
```

\_\_unnamed [9 2]:

---

:V3	:joined
0.5	535226087
1.0	1128801549 -1842240303
1.5	2022347171
0.5	1884312041
1.0	-1555412370 1640237355
1.5	-967279152
0.5	1128367958

---

Grouped dataset

```
(-> DSm
  (api/group-by :V4)
```



```
(api/join-columns :joined [:V1 :V2 :V4])
(api/ungroup))
```

\_\_unnamed [9 2]:

:V3	:joined
0.5	1-1-A
1.5	1-4-A
	1-7-A
1.0	2-2-B
0.5	2-5-B
1.5	2-8-B
	3-C
1.0	6-C
0.5	9-C

## Tidyr examples

source

```
(def df (api/dataset {:x ["a" "a" nil nil]
                      :y ["b" nil "b" nil]}))
```

#'user/df

df

\_\_unnamed [4 2]:

:x	:y
a	b
a	
	b

```
(api/join-columns df "z" [:x :y] {:drop-columns? false
                                   :missing-subst "NA"
                                   :separator "_"})
```

\_\_unnamed [4 3]:

:x	:y	z
a	b	a_b
a		a_NA
	b	NA_b
		NA_NA

```
(api/join-columns df "z" [:x :y] {:drop-columns? false
                                   :separator "_"})
```

\_\_unnamed [4 3]:

:x	:y	z
a	b	a_b
a		a
	b	b

## Separate

Column can be also separated into several other columns using string as separator, regex or custom function.  
Arguments:

- dataset
- source column
- target columns
- separator as:
  - string - it's converted to regular expression and passed to `clojure.string/split` function
  - regex
  - or custom function (default: identity)
- options
  - `:drop-columns?` - whether drop source column or not (default: `true`)
  - `:missing-subst` - values which should be treated as missing, can be set, sequence, value or function (default: `""`)

Custom function (as separator) should return sequence of values for given value.

Separate float into integer and fractional values

```
(api/separate-column DS :V3 [:int-part :frac-part] (fn [~double v]
                                                       [(int (quot v 1.0))
                                                        (mod v 1.0)]))
```

\_\_unnamed [9 5]:

:V1	:V2	:int-part	:frac-part	:V4
1	1	0	0.5	A
2	2	1	0.0	B
1	3	1	0.5	C
2	4	0	0.5	A
1	5	1	0.0	B
2	6	1	0.5	C
1	7	0	0.5	A
2	8	1	0.0	B
1	9	1	0.5	C

Source column can be kept

```
(api/separate-column DS :V3 [:int-part :frac-part] (fn [^double v]
  [(int (quot v 1.0))
   (mod v 1.0)]) {:drop-column? false}))
```

\_\_unnamed [9 6]:

:V1	:V2	:V3	:int-part	:frac-part	:V4
1	1	0.5	0	0.5	A
2	2	1.0	1	0.0	B
1	3	1.5	1	0.5	C
2	4	0.5	0	0.5	A
1	5	1.0	1	0.0	B
2	6	1.5	1	0.5	C
1	7	0.5	0	0.5	A
2	8	1.0	1	0.0	B
1	9	1.5	1	0.5	C

We can treat 0 or 0.0 as missing value

```
(api/separate-column DS :V3 [:int-part :frac-part] (fn [^double v]
  [(int (quot v 1.0))
   (mod v 1.0)]) {:missing-subst [0 0.0]}))
```

\_\_unnamed [9 5]:

:V1	:V2	:int-part	:frac-part	:V4
1	1		0.5	A
2	2	1		B
1	3	1	0.5	C
2	4		0.5	A
1	5	1		B
2	6	1	0.5	C
1	7		0.5	A
2	8	1		B
1	9	1	0.5	C

Works on grouped dataset

```
(-> DS
  (api/group-by :V4)
  (api/separate-column :V3 [:int-part :frac-part] (fn [^double v]
    [(int (quot v 1.0))
     (mod v 1.0)]))
  (api/ungroup))
```

\_\_unnamed [9 5]:

:V1	:V2	:int-part	:frac-part	:V4
1	1	0	0.5	A
2	4	0	0.5	A

:V1	:V2	:int-part	:fract-part	:V4
1	7	0	0.5	A
2	2	1	0.0	B
1	5	1	0.0	B
2	8	1	0.0	B
1	3	1	0.5	C
2	6	1	0.5	C
1	9	1	0.5	C

Join and separate together.

```
(-> DSm
  (api/join-columns :joined [:V1 :V2 :V4] {:result-type :map})
  (api/separate-column :joined [:v1 :v2 :v4] (juxt :V1 :V2 :V4)))
```

\_\_unnamed [9 4]:

:V3	:v1	:v2	:v4
0.5	1	1	A
1.0	2	2	B
		3	C
1.5	1	4	A
0.5	2	5	B
1.0		6	C
	1	7	A
1.5	2	8	B
0.5		9	C

```
(-> DSm
  (api/join-columns :joined [:V1 :V2 :V4] {:result-type :seq})
  (api/separate-column :joined [:v1 :v2 :v4] identity))
```

\_\_unnamed [9 4]:

:V3	:v1	:v2	:v4
0.5	1	1	A
1.0	2	2	B
		3	C
1.5	1	4	A
0.5	2	5	B
1.0		6	C
	1	7	A
1.5	2	8	B
0.5		9	C

## Tidyr examples

separate source extract source

```
(def df-separate (api/dataset {:x [nil "a.b" "a.d" "b.c"]}))
(def df-separate2 (api/dataset {:x ["a" "a b" nil "a b c"]}))
(def df-separate3 (api/dataset {:x ["a?b" nil "a.b" "b:c"]}))
(def df-extract (api/dataset {:x [nil "a-b" "a-d" "b-c" "d-e"]}))
```

```
#'user/df-separate
#'user/df-separate2
#'user/df-separate3
#'user/df-extract
```

```
df-separate
```

```
__unnamed [4 1]:
```

```
____
:x
____
a.b
a.d
b.c
____
```

```
df-separate2
```

```
__unnamed [4 1]:
```

```
____
:x
____
a
a b
a b c
____
```

```
df-separate3
```

```
__unnamed [4 1]:
```

```
____
:x
____
a?b
a.b
b:c
____
```

```
df-extract
```

```
__unnamed [5 1]:
```

```
____
:x
____
a-b
a-d
b-c
d-e
____
```

---

```
(api/separate-column df-separate :x [:A :B] "\\\\.")
```

\_\_unnamed [4 2]:

---

:A	:B
a	b
a	d
b	c

---

You can drop columns after separation by setting `nil` as a name. We need second value here.

```
(api/separate-column df-separate :x [nil :B] "\\\\.")
```

\_\_unnamed [4 1]:

---

:B
b
d
c

---

Extra data is dropped

```
(api/separate-column df-separate2 :x ["a" "b"] " ")
```

\_\_unnamed [4 2]:

---

a	b
a	
a	b
a	b

---

Split with regular expression

```
(api/separate-column df-separate3 :x ["a" "b"] "[?\\\\.:]")
```

\_\_unnamed [4 2]:

---

a	b
a	b
a	b
b	c

---

---

Or just regular expression to extract values

```
(api/separate-column df-separate3 :x ["a" "b"] #"(.).(.)")
```

\_\_unnamed [4 2]:

a	b
a	b
a	b
b	c

---

Extract first value only

```
(api/separate-column df-extract :x ["A"] "-")
```

\_\_unnamed [5 1]:

A
a
a
b
d

---

Split with regex

```
(api/separate-column df-extract :x ["A" "B"] #"(\p{Alnum})-(\p{Alnum})")
```

\_\_unnamed [5 2]:

A	B
a	b
a	d
b	c
d	e

---

Only a,b,c,d strings

```
(api/separate-column df-extract :x ["A" "B"] #"([a-d]+)-([a-d]+)")
```

\_\_unnamed [5 2]:

A	B
a	b

A	B
a	d
b	c

## Fold/Unroll Rows

To pack or unpack the data into single value you can use **fold-by** and **unroll** functions.

**fold-by** groups dataset and packs columns data from each group separately into desired datastructure (like vector or sequence). **unroll** does the opposite.

### Fold-by

Group-by and pack columns into vector

```
(api/fold-by DS [:V3 :V4 :V1])
```

\_\_unnamed [6 4]:

:V4	:V3	:V1	:V2
B	1.000	1	[5]
C	1.500	2	[6]
C	1.500	1	[3 9]
A	0.5000	1	[1 7]
B	1.000	2	[2 8]
A	0.5000	2	[4]

You can pack several columns at once.

```
(api/fold-by DS [:V4])
```

\_\_unnamed [3 4]:

:V4	:V1	:V2	:V3
B	[2 1 2]	[2 5 8]	[1.0 1.0 1.0]
C	[1 2 1]	[3 6 9]	[1.5 1.5 1.5]
A	[1 2 1]	[1 4 7]	[0.5 0.5 0.5]

You can use custom packing function

```
(api/fold-by DS [:V4] seq)
```

\_\_unnamed [3 4]:

:V4	:V1	:V2	:V3
B	clojure.lang.LazySeq@7c02	clojure.lang.LazySeq@7c84	clojure.lang.LazySeq@1f0745f
C	clojure.lang.LazySeq@785f	clojure.lang.LazySeq@8065	clojure.lang.LazySeq@20f8745f
A	clojure.lang.LazySeq@785f	clojure.lang.LazySeq@78a3	clojure.lang.LazySeq@c3e0745f



or

```
(api/fold-by DS [:V4] set)
```

\_\_unnamed [3 4]:

:V4	:V1	:V2	:V3
B	#{1 2}	#{2 5 8}	#{1.0}
C	#{1 2}	#{6 3 9}	#{1.5}
A	#{1 2}	#{7 1 4}	#{0.5}

This works also on grouped dataset

```
(-> DS
  (api/group-by :V1)
  (api/fold-by :V4)
  (api/ungroup))
```

\_\_unnamed [6 4]:

:V4	:V1	:V2	:V3
B	[1]	[5]	[1.0]
C	[1 1]	[3 9]	[1.5 1.5]
A	[1 1]	[1 7]	[0.5 0.5]
B	[2 2]	[2 8]	[1.0 1.0]
C	[2]	[6]	[1.5]
A	[2]	[4]	[0.5]

## Unroll

`unroll` unfolds sequences stored in data, multiplying other ones when necessary. You can unroll more than one column at once (folded data should have the same size!).

Options:

- `:indexes?` if true (or column name), information about index of unrolled sequence is added.
- `:datatypes` list of datatypes which should be applied to restored columns, a map

Unroll one column

```
(api/unroll (api/fold-by DS [:V4]) [:V1])
```

\_\_unnamed [9 4]:

:V4	:V2	:V3	:V1
B	[2 5 8]	[1.0 1.0 1.0]	2
B	[2 5 8]	[1.0 1.0 1.0]	1
B	[2 5 8]	[1.0 1.0 1.0]	2
C	[3 6 9]	[1.5 1.5 1.5]	1
C	[3 6 9]	[1.5 1.5 1.5]	2
C	[3 6 9]	[1.5 1.5 1.5]	1
A	[1 4 7]	[0.5 0.5 0.5]	1

:V4	:V2	:V3	:V1
A	[1 4 7]	[0.5 0.5 0.5]	2
A	[1 4 7]	[0.5 0.5 0.5]	1

---

Unroll all folded columns

```
(api/unroll (api/fold-by DS [:V4]) [:V1 :V2 :V3])
```

\_\_unnamed [9 4]:

:V4	:V1	:V2	:V3
B	2	2	1.000
B	1	5	1.000
B	2	8	1.000
C	1	3	1.500
C	2	6	1.500
C	1	9	1.500
A	1	1	0.5000
A	2	4	0.5000
A	1	7	0.5000

---

Unroll one by one leads to cartesian product

```
(-> DS
  (api/fold-by [:V4 :V1])
  (api/unroll [:V2])
  (api/unroll [:V3]))
```

\_\_unnamed [15 4]:

:V4	:V1	:V2	:V3
C	2	6	1.500
A	1	1	0.5000
A	1	1	0.5000
A	1	7	0.5000
A	1	7	0.5000
B	1	5	1.000
C	1	3	1.500
C	1	3	1.500
C	1	9	1.500
C	1	9	1.500
A	2	4	0.5000
B	2	2	1.000
B	2	2	1.000
B	2	8	1.000
B	2	8	1.000

---

You can add indexes

```
(api/unroll (api/fold-by DS [:V1]) [:V4 :V2 :V3] {:indexes? true}))
```

\_\_unnamed [9 5]:

:V1	:indexes	:V2	:V3	:V4
1	0	1	0.5000	A
1	1	3	1.500	C
1	2	5	1.000	B
1	3	7	0.5000	A
1	4	9	1.500	C
2	0	2	1.000	B
2	1	4	0.5000	A
2	2	6	1.500	C
2	3	8	1.000	B

```
(api/unroll (api/fold-by DS [:V1]) [:V4 :V2 :V3] {:indexes? "vector idx"}))
```

\_\_unnamed [9 5]:

:V1	vector idx	:V2	:V3	:V4
1	0	1	0.5000	A
1	1	3	1.500	C
1	2	5	1.000	B
1	3	7	0.5000	A
1	4	9	1.500	C
2	0	2	1.000	B
2	1	4	0.5000	A
2	2	6	1.500	C
2	3	8	1.000	B

You can also force datatypes

```
(-> DS
  (api/fold-by [:V1])
  (api/unroll [:V4 :V2 :V3] {:datatypes {:V4 :string
                                          :V2 :int16
                                          :V3 :float32}})
  (api/info :columns))
```

\_\_unnamed :column info [4 4]:

:name	:size	:datatype	:categorical?
:V1	9	:object	
:V2	9	:int16	
:V3	9	:float32	
:V4	9	:string	true

This works also on grouped dataset

```
(-> DS
  (api/group-by :V1)
  (api/fold-by [:V1 :V4])
  (api/unroll :V3 {:indexes? true})
  (api/ungroup))
```

\_\_unnamed [9 5]:

	:V4	:V1	:V2	:indexes	:V3
A	1		[1 7]	0	0.5000
A	1		[1 7]	1	0.5000
B	1		[5]	0	1.000
C	1		[3 9]	0	1.500
C	1		[3 9]	1	1.500
C	2		[6]	0	1.500
A	2		[4]	0	0.5000
B	2		[2 8]	0	1.000
B	2		[2 8]	1	1.000

## Reshape

Reshaping data provides two types of operations:

- **pivot->longer** - converting columns to rows
- **pivot->wider** - converting rows to columns

Both functions are inspired on tidyr R package and provide almost the same functionality.

All examples are taken from mentioned above documentation.

Both functions work only on regular dataset.

## Longer

**pivot->longer** converts columns to rows. Column names are treated as data.

Arguments:

- dataset
- columns selector
- options:
  - **:target-columns** - names of the columns created or columns pattern (see below) (default: **:\$column**)
  - **:value-column-name** - name of the column for values (default: **:\$value**)
  - **:splitter** - string, regular expression or function which splits source column names into data
  - **:drop-missing?** - remove rows with missing? (default: **:true**)
  - **:datatypes** - map of target columns data types

**:target-columns** - can be:

- column name - source columns names are put there as a data
- column names as sequence - source columns names after split are put separately into **:target-columns** as data
- pattern - is a sequence of names, where some of the names are **nil**. **nil** is replaced by a name taken from splitter and such column is used for values.

Create rows from all columns but "religion".

```
(def relig-income (api/dataset "data/relig_income.csv"))
```

relig-income

data/relig\_income.csv [18 11]:

religion	<\$10k	\$10-20k	\$20-30k	\$30-40k	\$40-50k	\$50-75k	\$75-100k	\$100-150k	>150k	Don't know/refused
Agnostic	27	34	60	81	76	137	122	109	84	96
Atheist	12	27	37	52	35	70	73	59	74	76
Buddhist	27	21	30	34	33	58	62	39	53	54
Catholic	418	617	732	670	638	1116	949	792	633	1489
Don't know/refused	15	14	15	11	10	35	21	17	18	116
Evangelical Prot	575	869	1064	982	881	1486	949	723	414	1529
Hindu	1	9	7	9	11	34	47	48	54	37
Historically Black Prot	228	244	236	238	197	223	131	81	78	339
Jehovah's Witness	20	27	24	24	21	30	15	11	6	37
Jewish	19	19	25	25	30	95	69	87	151	162
Mainline Prot	289	495	619	655	651	1107	939	753	634	1328
Mormon	29	40	48	51	56	112	85	49	42	69
Muslim	6	7	9	10	9	23	16	8	6	22
Orthodox	13	17	23	32	32	47	38	42	46	73
Other Christian	9	7	11	13	13	14	18	14	12	18
Other Faiths	20	33	40	46	49	63	46	40	41	71
Other World Religions	5	2	3	4	2	7	3	4	4	8
Unaffiliated	217	299	374	365	341	528	407	321	258	597

```
(api/pivot->longer relig-income (complement #{"religion"}))
```

data/relig\_income.csv [180 3]:

religion	:\$column	:\$value
Agnostic	<\$10k	27
Atheist	<\$10k	12
Buddhist	<\$10k	27
Catholic	<\$10k	418
Don't know/refused	<\$10k	15
Evangelical Prot	<\$10k	575
Hindu	<\$10k	1
Historically Black Prot	<\$10k	228
Jehovah's Witness	<\$10k	20
Jewish	<\$10k	19
Mainline Prot	<\$10k	289
Mormon	<\$10k	29

religion	:\$column	:\$value
Muslim	<\$10k	6
Orthodox	<\$10k	13
Other Christian	<\$10k	9
Other Faiths	<\$10k	20
Other World Religions	<\$10k	5
Unaffiliated	<\$10k	217
Agnostic	Don't know/refused	96
Atheist	Don't know/refused	76
Buddhist	Don't know/refused	54
Catholic	Don't know/refused	1489
Don't know/refused	Don't know/refused	116
Evangelical Prot	Don't know/refused	1529
Hindu	Don't know/refused	37

Convert only columns starting with "wk" and pack them into :week column, values go to :rank column

```
(def billboard (-> (api/dataset "data/billboard.csv.gz")
  (api/drop-columns :type/boolean))) ;; drop some boolean columns, tidyr just skips them
```

```
(->> billboard
  (api/column-names)
  (take 13)
  (api/select-columns billboard))
```

data/billboard.csv.gz [317 13]:

artist	track	date.entered	wk1	wk2	wk3	wk4	wk5	wk6	wk7	wk8	wk9
2 Pac	Baby Don't Cry (Keep...)	2000-02-26	87	82	72	77	87	94	99		
2Ge+her	The Hardest Part Of ...	2000-09-02	91	87	92						
3 Doors Down	Kryptonite	2000-04-08	81	70	68	67	66	57	54	53	
3 Doors Down	Loser	2000-10-21	76	76	72	69	67	65	55	59	
504 Boyz	Wobble Wobble	2000-04-15	57	34	25	17	17	31	36	49	
98^0	Give Me Just One Nig...	2000-08-19	51	39	34	26	26	19	2	2	
A*Teens	Dancing Queen	2000-07-08	97	97	96	95	100				
Aaliyah	I Don't Wanna	2000-01-29	84	62	51	41	38	35	35	38	
Aaliyah	Try Again	2000-03-18	59	53	38	28	21	18	16	14	
Adams, Yolanda	Open My Heart	2000-08-26	76	76	74	69	68	67	61	58	
Adkins, Trace	More	2000-04-29	84	84	75	73	73	69	68	65	
Aguilera, Christina	Come On Over Baby (A...	2000-08-05	57	47	45	29	23	18	11	9	
Aguilera, Christina	I Turn To You	2000-04-15	50	39	30	28	21	19	20	17	
Aguilera, Christina	What A Girl Wants	1999-11-27	71	51	28	18	13	13	11	1	
Alice DeeJay	Better Off Alone	2000-04-08	79	65	53	48	45	36	34	29	
Allan, Gary	Smoke Rings In The D...	2000-01-22	80	78	76	77	92				
Amber	Sexual	1999-07-17	99	99	96	96	100	93	93	96	
Anastacia	I'm Outta Love	2000-04-01	92			95					
Anthony, Marc	My Baby You	2000-09-16	82	76	76	70	82	81	74	80	
Anthony, Marc	You Sang To Me	2000-02-26	77	54	50	43	30	27	21	18	
Avant	My First Love	2000-11-04	70	62	56	43	39	33	26	26	
Avant	Separated	2000-04-29	62	32	30	23	26	30	35	32	
BBMak	Back Here	2000-04-29	99	86	60	52	38	34	28	21	
Backstreet Boys, The	Shape Of My Heart	2000-10-14	39	25	24	15	12	12	10	9	

artist	track	date.entered	wk1	wk2	wk3	wk4	wk5	wk6	wk7	wk8	v
Backstreet Boys, The	Show Me The Meaning ...	2000-01-01	74	62	55	25	16	14	12	10	

```
(api/pivot->longer billboard #(clojure.string/starts-with? % "wk") {:target-columns :week
                                                                    :value-column-name :rank}))
```

data/billboard.csv.gz [5307 5]:

artist	track	date.entered	:week	:rank
3 Doors Down	Kryptonite	2000-04-08	wk35	4
Braxton, Toni	He Wasn't Man Enough	2000-03-18	wk35	34
Creed	Higher	1999-09-11	wk35	22
Creed	With Arms Wide Open	2000-05-13	wk35	5
Hill, Faith	Breathe	1999-11-06	wk35	8
Joe	I Wanna Know	2000-01-01	wk35	5
Lonestar	Amazed	1999-06-05	wk35	14
Vertical Horizon	Everything You Want	2000-01-22	wk35	27
matchbox twenty	Bent	2000-04-29	wk35	33
Creed	Higher	1999-09-11	wk55	21
Lonestar	Amazed	1999-06-05	wk55	22
3 Doors Down	Kryptonite	2000-04-08	wk19	18
3 Doors Down	Loser	2000-10-21	wk19	73
98^0	Give Me Just One Nig...	2000-08-19	wk19	93
Aaliyah	I Don't Wanna	2000-01-29	wk19	83
Aaliyah	Try Again	2000-03-18	wk19	3
Adams, Yolanda	Open My Heart	2000-08-26	wk19	79
Aguilera, Christina	Come On Over Baby (A...	2000-08-05	wk19	23
Aguilera, Christina	I Turn To You	2000-04-15	wk19	29
Aguilera, Christina	What A Girl Wants	1999-11-27	wk19	18
Alice DeeJay	Better Off Alone	2000-04-08	wk19	79
Amber	Sexual	1999-07-17	wk19	95
Anthony, Marc	My Baby You	2000-09-16	wk19	91
Anthony, Marc	You Sang To Me	2000-02-26	wk19	9
Avant	My First Love	2000-11-04	wk19	81

We can create numerical column out of column names

```
(api/pivot->longer billboard #(clojure.string/starts-with? % "wk") {:target-columns :week
                                                                    :value-column-name :rank
                                                                    :splitter #"wk(.*)"
                                                                    :datatypes {:week :int16}}))
```

data/billboard.csv.gz [5307 5]:

artist	track	date.entered	:week	:rank
3 Doors Down	Kryptonite	2000-04-08	46	21
Creed	Higher	1999-09-11	46	7
Creed	With Arms Wide Open	2000-05-13	46	37
Hill, Faith	Breathe	1999-11-06	46	31
Lonestar	Amazed	1999-06-05	46	5

artist	track	date.entered	:week	:rank
3 Doors Down	Kryptonite	2000-04-08	51	42
Creed	Higher	1999-09-11	51	14
Hill, Faith	Breathe	1999-11-06	51	49
Lonestar	Amazed	1999-06-05	51	12
2 Pac	Baby Don't Cry (Keep...	2000-02-26	6	94
3 Doors Down	Kryptonite	2000-04-08	6	57
3 Doors Down	Loser	2000-10-21	6	65
504 Boyz	Wobble Wobble	2000-04-15	6	31
98^0	Give Me Just One Nig...	2000-08-19	6	19
Aaliyah	I Don't Wanna	2000-01-29	6	35
Aaliyah	Try Again	2000-03-18	6	18
Adams, Yolanda	Open My Heart	2000-08-26	6	67
Adkins, Trace	More	2000-04-29	6	69
Aguilera, Christina	Come On Over Baby (A...	2000-08-05	6	18
Aguilera, Christina	I Turn To You	2000-04-15	6	19
Aguilera, Christina	What A Girl Wants	1999-11-27	6	13
Alice DeeJay	Better Off Alone	2000-04-08	6	36
Amber	Sexual	1999-07-17	6	93
Anthony, Marc	My Baby You	2000-09-16	6	81
Anthony, Marc	You Sang To Me	2000-02-26	6	27

When column names contain observation data, such column names can be splitted and data can be restored into separate columns.

```
(def who (api/dataset "data/who.csv.gz"))
```

```
(->> who
  (api/column-names)
  (take 10)
  (api/select-columns who))
```

data/who.csv.gz [7240 10]:

country	iso2	iso3	year	new_sp_m014w	sp_m1524w	sp_m2534w	sp_m3544w	sp_m4554w	sp_m5564
Afghanistan	AF	AFG	1980						
Afghanistan	AF	AFG	1981						
Afghanistan	AF	AFG	1982						
Afghanistan	AF	AFG	1983						
Afghanistan	AF	AFG	1984						
Afghanistan	AF	AFG	1985						
Afghanistan	AF	AFG	1986						
Afghanistan	AF	AFG	1987						
Afghanistan	AF	AFG	1988						
Afghanistan	AF	AFG	1989						
Afghanistan	AF	AFG	1990						
Afghanistan	AF	AFG	1991						
Afghanistan	AF	AFG	1992						
Afghanistan	AF	AFG	1993						
Afghanistan	AF	AFG	1994						
Afghanistan	AF	AFG	1995						
Afghanistan	AF	AFG	1996						



country	iso2	iso3	year	new_sp_m1524	new_sp_m1524	new_sp_m1524	new_sp_m1524	new_sp_m1524	new_sp_m1524
AfghanistanAF	AFG	1997	0	10	6	3	5	2	
AfghanistanAF	AFG	1998	30	129	128	90	89	64	
AfghanistanAF	AFG	1999	8	55	55	47	34	21	
AfghanistanAF	AFG	2000	52	228	183	149	129	94	
AfghanistanAF	AFG	2001	129	379	349	274	204	139	
AfghanistanAF	AFG	2002	90	476	481	368	246	241	
AfghanistanAF	AFG	2003	127	511	436	284	256	288	
AfghanistanAF	AFG	2004	139	537	568	360	358	386	

```
(api/pivot->longer who #(clojure.string/starts-with? % "new") {:target-columns [:diagnosis :gender :age]
                                                                :splitter #"new_?(.*)_(.)(.*)"
                                                                :value-column-name :count})
```

data/who.csv.gz [76046 8]:

country	iso2	iso3	year	:diagnosis	:gender	:age	:count
Albania	AL	ALB	2013	rel	m	1524	60
Algeria	DZ	DZA	2013	rel	m	1524	1021
Andorra	AD	AND	2013	rel	m	1524	0
Angola	AO	AGO	2013	rel	m	1524	2992
Anguilla	AI	AIA	2013	rel	m	1524	0
Antigua and Barbuda	AG	ATG	2013	rel	m	1524	1
Argentina	AR	ARG	2013	rel	m	1524	1124
Armenia	AM	ARM	2013	rel	m	1524	116
Australia	AU	AUS	2013	rel	m	1524	105
Austria	AT	AUT	2013	rel	m	1524	44
Azerbaijan	AZ	AZE	2013	rel	m	1524	958
Bahamas	BS	BHS	2013	rel	m	1524	2
Bahrain	BH	BHR	2013	rel	m	1524	13
Bangladesh	BD	BGD	2013	rel	m	1524	14705
Barbados	BB	BRB	2013	rel	m	1524	0
Belarus	BY	BLR	2013	rel	m	1524	162
Belgium	BE	BEL	2013	rel	m	1524	63
Belize	BZ	BLZ	2013	rel	m	1524	8
Benin	BJ	BEN	2013	rel	m	1524	301
Bermuda	BM	BMU	2013	rel	m	1524	0
Bhutan	BT	BTN	2013	rel	m	1524	180
Bolivia (Plurinational State of)	BO	BOL	2013	rel	m	1524	1470
Bonaire, Saint Eustatius and Saba	BQ	BES	2013	rel	m	1524	0
Bosnia and Herzegovina	BA	BIH	2013	rel	m	1524	57
Botswana	BW	BWA	2013	rel	m	1524	423

When data contains multiple observations per row, we can use splitter and pattern for target columns to create new columns and put values there. In following dataset we have two obseravations dob and gender for two childs. We want to put child infomation into the column and leave dob and gender for values.

```
(def family (api/dataset "data/family.csv"))
```

family

data/family.csv [5 5]:

family	dob_child1	dob_child2	gender_child1	gender_child2
1	1998-11-26	2000-01-29	1	2
2	1996-06-22		2	
3	2002-07-11	2004-04-05	2	2
4	2004-10-10	2009-08-27	1	1
5	2000-12-05	2005-02-28	2	1

```
(api/pivot->longer family (complement #{"family"}) {:target-columns [nil :child]
:splitter "_"
:datatypes {"gender" :int16}})
```

data/family.csv [9 4]:

family	:child	dob	gender
1	child1	1998-11-26	1
2	child1	1996-06-22	2
3	child1	2002-07-11	2
4	child1	2004-10-10	1
5	child1	2000-12-05	2
1	child2	2000-01-29	2
3	child2	2004-04-05	2
4	child2	2009-08-27	1
5	child2	2005-02-28	1

Similar here, we have two observations: **x** and **y** in four groups.

```
(def anscombe (api/dataset "data/anscombe.csv"))
```

anscombe

data/anscombe.csv [11 8]:

x1	x2	x3	x4	y1	y2	y3	y4
10	10	10	8	8.04	9.14	7.46	6.58
8	8	8	8	6.95	8.14	6.77	5.76
13	13	13	8	7.58	8.74	12.74	7.71
9	9	9	8	8.81	8.77	7.11	8.84
11	11	11	8	8.33	9.26	7.81	8.47
14	14	14	8	9.96	8.10	8.84	7.04
6	6	6	8	7.24	6.13	6.08	5.25
4	4	4	19	4.26	3.10	5.39	12.50
12	12	12	8	10.84	9.13	8.15	5.56
7	7	7	8	4.82	7.26	6.42	7.91
5	5	5	8	5.68	4.74	5.73	6.89

```
(api/pivot->longer anscombe :all {:splitter #"(.)"
:target-columns [nil :set]})
```

data/anscombe.csv [44 3]:

:set	x	y
1	10	8.04
1	8	6.95
1	13	7.58
1	9	8.81
1	11	8.33
1	14	9.96
1	6	7.24
1	4	4.26
1	12	10.84
1	7	4.82
1	5	5.68
2	10	9.14
2	8	8.14
2	13	8.74
2	9	8.77
2	11	9.26
2	14	8.10
2	6	6.13
2	4	3.10
2	12	9.13
2	7	7.26
2	5	4.74
3	10	7.46
3	8	6.77
3	13	12.74

```
(def pnl (api/dataset {:x [1 2 3 4]
                       :a [1 1 0 0]
                       :b [0 1 1 1]
                       :y1 (repeatedly 4 rand)
                       :y2 (repeatedly 4 rand)
                       :z1 [3 3 3 3]
                       :z2 [-2 -2 -2 -2]}))
```

pnl

\_\_unnamed [4 7]:

:x	:a	:b	:y1	:y2	:z1	:z2
1	1	0	0.65813737	0.54508201	3	-2
2	1	1	0.19029288	0.72242087	3	-2
3	0	1	0.39355996	0.16322046	3	-2
4	0	1	0.43179076	0.70814268	3	-2

```
(api/pivot->longer pnl [:y1 :y2 :z1 :z2] {:target-columns [nil :times]
                                           :splitter #":(.)(.)"})
```

\_\_unnamed [8 6]:

:x	:a	:b	:times	y	z
1	1	0	1	0.65813737	3
2	1	1	1	0.19029288	3
3	0	1	1	0.39355996	3
4	0	1	1	0.43179076	3
1	1	0	2	0.54508201	-2
2	1	1	2	0.72242087	-2
3	0	1	2	0.16322046	-2
4	0	1	2	0.70814268	-2

## Wider

`pivot->wider` converts rows to columns.

Arguments:

- `dataset`
- `columns-selector` - values from selected columns are converted to new columns
- `value-columns` - what are values

When multiple columns are used as columns selector, names are joined using `:concat-columns-with` option. `:concat-columns-with` can be a string or function (default: “\_”). Function accepts sequence of names.

When `columns-selector` creates non unique set of values, they are folded using `:fold-fn` (default: `vec`) option.

When `value-columns` is a sequence, multiple observations as columns are created appending value column names into new columns. Column names are joined using `:concat-value-with` option. `:concat-value-with` can be a string or function (default: “-”). Function accepts current column name and value.

---

Use `station` as a name source for columns and `seen` for values

```
(def fish (api/dataset "data/fish_encounters.csv"))
```

```
fish
```

data/fish\_encounters.csv [114 3]:

fish	station	seen
4842	Release	1
4842	I80_1	1
4842	Lisbon	1
4842	Rstr	1
4842	Base_TD	1
4842	BCE	1
4842	BCW	1
4842	BCE2	1
4842	BCW2	1
4842	MAE	1
4842	MAW	1
4843	Release	1
4843	I80_1	1
4843	Lisbon	1
4843	Rstr	1
4843	Base_TD	1

fish	station	seen
4843	BCE	1
4843	BCW	1
4843	BCE2	1
4843	BCW2	1
4843	MAE	1
4843	MAW	1
4844	Release	1
4844	I80_1	1
4844	Lisbon	1

```
(api/pivot->wider fish "station" "seen")
```

data/fish\_encounters.csv [5 12]:

fish	Rstr	Base_TD	I80_1	Release	MAE	BCE2	MAW	BCW2	BCE	Lisbon	BCW
4842	1	1	1	1	1	1	1	1	1	1	1
4843	1	1	1	1	1	1	1	1	1	1	1
4844	1	1	1	1	1	1	1	1	1	1	1
4858	1	1	1	1	1	1	1	1	1	1	1
4861	1	1	1	1	1	1	1	1	1	1	1

If selected columns contain multiple values, such values should be folded.

```
(def warpbreaks (api/dataset "data/warpbreaks.csv"))
```

warpbreaks

data/warpbreaks.csv [54 3]:

breaks	wool	tension
26	A	L
30	A	L
54	A	L
25	A	L
70	A	L
52	A	L
51	A	L
26	A	L
67	A	L
18	A	M
21	A	M
29	A	M
17	A	M
12	A	M
18	A	M
35	A	M
30	A	M
36	A	M
36	A	H
21	A	H

breaks	wool	tension
24	A	H
18	A	H
10	A	H
43	A	H
28	A	H

Let's see how many values are for each type of `wool` and `tension` groups

```
(-> warpbreaks
  (api/group-by ["wool" "tension"]))
  (api/aggregate { :n api/row-count}))
```

\_\_unnamed [6 3]:

wool	tension	:n
A	H	9
B	H	9
A	L	9
A	M	9
B	L	9
B	M	9

```
(-> warpbreaks
  (api/reorder-columns ["wool" "tension" "breaks"]))
  (api/pivot->wider "wool" "breaks" { :fold-fn vec}))
```

data/warpbreaks.csv [3 3]:

tension	B	A
M	[42 26 19 16 39 28 21 39 29]	[18 21 29 17 12 18 35 30 36]
H	[20 21 24 17 13 15 15 16 28]	[36 21 24 18 10 43 28 15 26]
L	[27 14 29 19 29 31 41 20 44]	[26 30 54 25 70 52 51 26 67]

We can also calculate mean (aggreate values)

```
(-> warpbreaks
  (api/reorder-columns ["wool" "tension" "breaks"]))
  (api/pivot->wider "wool" "breaks" { :fold-fn tech.v2.datatype.functional/mean}))
```

data/warpbreaks.csv [3 3]:

tension	B	A
H	18.78	24.55555556
M	28.78	24.00000000
L	28.22	44.55555556

Multiple source columns, joined with default separator.

```
(def production (api/dataset "data/production.csv"))
```

```
production
```

data/production.csv [45 4]:

product	country	year	production
A	AI	2000	1.63727150
A	AI	2001	0.15870784
A	AI	2002	-1.56797743
A	AI	2003	-0.44455510
A	AI	2004	-0.07133701
A	AI	2005	1.61183100
A	AI	2006	-0.70434684
A	AI	2007	-1.53550541
A	AI	2008	0.83907160
A	AI	2009	-0.37424111
A	AI	2010	-0.71158928
A	AI	2011	1.12805630
A	AI	2012	1.45718240
A	AI	2013	-1.55934095
A	AI	2014	-0.11695838
B	AI	2000	-0.02617661
B	AI	2001	-0.68863577
B	AI	2002	0.06248741
B	AI	2003	-0.72339684
B	AI	2004	0.47248950
B	AI	2005	-0.94173861
B	AI	2006	-0.34782109
B	AI	2007	0.52425283
B	AI	2008	1.83230940
B	AI	2009	0.10706490

```
(api/pivot->wider production ["product" "country"] "production")
```

data/production.csv [15 4]:

year	A_AI	B_EI	B_AI
2000	1.63727150	1.40470850	-0.02617661
2001	0.15870784	-0.59618372	-0.68863577
2002	-1.56797743	-0.26568580	0.06248741
2003	-0.44455510	0.65257806	-0.72339684
2004	-0.07133701	0.62565000	0.47248950
2005	1.61183100	-1.34530294	-0.94173861
2006	-0.70434684	-0.97184974	-0.34782109
2007	-1.53550541	-1.69715822	0.52425283
2008	0.83907160	0.04556128	1.83230940
2009	-0.37424111	1.19315040	0.10706490
2010	-0.71158928	-1.60557508	-0.32903662
2011	1.12805630	-0.77235496	-1.78319120
2012	1.45718240	-2.50262737	0.61125800
2013	-1.55934095	-1.62753773	-0.78526092

year	A_AI	B_EI	B_AI
2014	-0.11695838	0.03329644	0.97843635

Joined with custom function

```
(api/pivot->wider production ["product" "country"] "production" {::concat-columns-with vec})
```

data/production.csv [15 4]:

year	["A" "AI"]	["B" "EI"]	["B" "AI"]
2000	1.63727150	1.40470850	-0.02617661
2001	0.15870784	-0.59618372	-0.68863577
2002	-1.56797743	-0.26568580	0.06248741
2003	-0.44455510	0.65257806	-0.72339684
2004	-0.07133701	0.62565000	0.47248950
2005	1.61183100	-1.34530294	-0.94173861
2006	-0.70434684	-0.97184974	-0.34782109
2007	-1.53550541	-1.69715822	0.52425283
2008	0.83907160	0.04556128	1.83230940
2009	-0.37424111	1.19315040	0.10706490
2010	-0.71158928	-1.60557508	-0.32903662
2011	1.12805630	-0.77235496	-1.78319120
2012	1.45718240	-2.50262737	0.61125800
2013	-1.55934095	-1.62753773	-0.78526092
2014	-0.11695838	0.03329644	0.97843635

Multiple value columns

```
(def income (api/dataset "data/us_rent_income.csv"))
```

```
income
```

data/us\_rent\_income.csv [104 5]:

GEOID	NAME	variable	estimate	moe
1	Alabama	income	24476	136
1	Alabama	rent	747	3
2	Alaska	income	32940	508
2	Alaska	rent	1200	13
4	Arizona	income	27517	148
4	Arizona	rent	972	4
5	Arkansas	income	23789	165
5	Arkansas	rent	709	5
6	California	income	29454	109
6	California	rent	1358	3
8	Colorado	income	32401	109
8	Colorado	rent	1125	5
9	Connecticut	income	35326	195
9	Connecticut	rent	1123	5
10	Delaware	income	31560	247
10	Delaware	rent	1076	10



GEOID	NAME	variable	estimate	moe
11	District of Columbia	income	43198	681
11	District of Columbia	rent	1424	17
12	Florida	income	25952	70
12	Florida	rent	1077	3
13	Georgia	income	27024	106
13	Georgia	rent	927	3
15	Hawaii	income	32453	218
15	Hawaii	rent	1507	18
16	Idaho	income	25298	208

```
(api/pivot->wider income "variable" ["estimate" "moe"])
```

data/us\_rent\_income.csv [51 6]:

GEOID	NAME	rent-estimate	rent-moe	income-estimate	income-moe
1	Alabama	747	3	24476	136
2	Alaska	1200	13	32940	508
4	Arizona	972	4	27517	148
5	Arkansas	709	5	23789	165
6	California	1358	3	29454	109
8	Colorado	1125	5	32401	109
9	Connecticut	1123	5	35326	195
10	Delaware	1076	10	31560	247
11	District of Columbia	1424	17	43198	681
12	Florida	1077	3	25952	70
13	Georgia	927	3	27024	106
15	Hawaii	1507	18	32453	218
16	Idaho	792	7	25298	208
17	Illinois	952	3	30684	83
18	Indiana	782	3	27247	117
19	Iowa	740	4	30002	143
20	Kansas	801	5	29126	208
21	Kentucky	713	4	24702	159
22	Louisiana	825	4	25086	155
23	Maine	808	7	26841	187
24	Maryland	1311	5	37147	152
25	Massachusetts	1173	5	34498	199
26	Michigan	824	3	26987	82
27	Minnesota	906	4	32734	189
28	Mississippi	740	5	22766	194

Value concatenated by custom function

```
(api/pivot->wider income "variable" ["estimate" "moe"] { :concat-columns-with vec
                                                         :concat-value-with vector})
```

data/us\_rent\_income.csv [51 6]:

GEOID	NAME	["rent" "estimate"]	["rent" "moe"]	["income" "estimate"]	["income" "moe"]
1	Alabama	747	3	24476	136

GEOID	NAME	["rent" "estimate"]	["rent" "moe"]	["income" "estimate"]	["income" "moe"]
2	Alaska	1200	13	32940	508
4	Arizona	972	4	27517	148
5	Arkansas	709	5	23789	165
6	California	1358	3	29454	109
8	Colorado	1125	5	32401	109
9	Connecticut	1123	5	35326	195
10	Delaware	1076	10	31560	247
11	District of Columbia	1424	17	43198	681
12	Florida	1077	3	25952	70
13	Georgia	927	3	27024	106
15	Hawaii	1507	18	32453	218
16	Idaho	792	7	25298	208
17	Illinois	952	3	30684	83
18	Indiana	782	3	27247	117
19	Iowa	740	4	30002	143
20	Kansas	801	5	29126	208
21	Kentucky	713	4	24702	159
22	Louisiana	825	4	25086	155
23	Maine	808	7	26841	187
24	Maryland	1311	5	37147	152
25	Massachusetts	1173	5	34498	199
26	Michigan	824	3	26987	82
27	Minnesota	906	4	32734	189
28	Mississippi	740	5	22766	194

Reshape contact data

```
(def contacts (api/dataset "data/contacts.csv"))
```

contacts

data/contacts.csv [6 3]:

field	value	person_id
name	Jiena McLellan	1
company	Toyota	1
name	John Smith	2
company	google	2
email	john@google.com	2
name	Huxley Ratcliffe	3

```
(api/pivot->wider contacts "field" "value")
```

data/contacts.csv [1 4]:

person_id	email	name	company
2	john@google.com	John Smith	google

## Reshaping

A couple of `tidyr` examples of more complex reshaping.

World bank

```
(def world-bank-pop (api/dataset "data/world_bank_pop.csv.gz"))
```

```
(->> world-bank-pop
  (api/column-names)
  (take 8)
  (api/select-columns world-bank-pop))
```

data/world\_bank\_pop.csv.gz [1056 8]:

country	indicator	2000	2001	2002	2003	2004	2005
ABW	SP.URB.TOTL	0.124440000E+04	0.130480000E+04	0.136700000E+04	0.142460000E+04	0.146690000E+04	0.148890000E+04
ABW	SP.URB.GROW	0.18263230E+00	0.141302120E+00	0.143455960E+00	0.131036040E+00	0.151477700E-01	4.91302730E-01
ABW	SP.POP.TOTL	0.118530000E+04	0.128980000E+04	0.149920000E+04	0.170170000E+04	0.187370000E+04	0.1400031000E+05
ABW	SP.POP.GROW	0.1502680E+00	0.122593020E+00	0.122905610E+00	0.110935430E+00	0.1075735280E+00	0.1030203880E+00
AFG	SP.URB.TOTL	0.113629900E+06	0.164805500E+06	0.1689295100E+06	0.1615568600E+06	0.1642677000E+06	0.1669182300E+06
AFG	SP.URB.GROW	0.1222830E+00	0.166283850E+00	0.113467450E+00	0.1023045870E+00	0.112439300E+00	0.1076864700E+00
AFG	SP.POP.TOTL	0.1210937560E+07	0.1709664640E+07	0.1719799240E+07	0.1730648520E+07	0.1741189800E+07	0.1750707980E+07
AFG	SP.POP.GROW	0.1465870E+00	0.125150400E+00	0.1072052860E+00	0.1081804130E+00	0.1046891830E+00	0.1087047000E+00
AGO	SP.URB.TOTL	0.113476600E+06	0.1670800000E+06	0.1621878700E+06	0.1676519700E+06	0.1603435060E+06	0.1709494240E+06
AGO	SP.URB.GROW	0.13749430E+00	0.158771940E+00	0.1070013240E+00	0.1075812700E+00	0.1075341460E+00	0.1069279670E+00
AGO	SP.POP.TOTL	0.114409240E+07	0.1769832660E+07	0.1775726480E+07	0.1782033680E+07	0.1788657160E+07	0.1795525420E+07
AGO	SP.POP.GROW	0.1294350E+00	0.124549150E+00	0.1041151520E+00	0.1052630280E+00	0.1057396200E+00	0.1057589960E+00
ALB	SP.URB.TOTL	0.128939100E+06	0.1629858400E+06	0.1632722000E+06	0.1635484800E+06	0.1638182800E+06	0.1640729800E+06
ALB	SP.URB.GROW	0.121478600E-01	7.10442600E-01	2.18120880E+00	0.1206027410E+00	0.1097179890E+00	0.1082642940E+00
ALB	SP.POP.TOTL	0.1318902700E+06	0.1606017300E+06	0.1605101000E+06	0.1603961600E+06	0.1602693900E+06	0.1601148700E+06
ALB	SP.POP.GROW	-	-	-	-	-	-
		6.37356818E-01	9.38470423E-01	2.99876690E-01	3.74149173E-01	4.17931378E-01	5.11790097E-01
AND	SP.URB.TOTL	0.114170000E+06	0.119910000E+06	0.141940000E+06	0.167470000E+06	0.191920000E+06	0.112050000E+04
AND	SP.URB.GROW	0.127931380E+00	0.157186910E+00	0.149205350E+00	0.189996050E+00	0.159758970E+00	0.1086777930E+00
AND	SP.POP.TOTL	0.113900000E+06	0.173410000E+06	0.1400490000E+06	0.1431820000E+06	0.1462440000E+06	0.1488670000E+04
AND	SP.POP.GROW	0.1216560E+00	0.193999220E+00	0.1094257330E+00	0.1037544900E+00	0.1009892370E+00	0.1038241650E+00
ARB	SP.URB.TOTL	0.119981216E+08	0.1853924352E+08	0.1857985744E+08	0.1862267760E+08	0.1866820464E+08	0.1871813696E+08
ARB	SP.URB.GROW	0.15056300E+00	0.162908100E+00	0.163856050E+00	0.171038130E+00	0.180567460E+00	0.199318150E+00
ARB	SP.POP.TOTL	0.1213832000E+08	0.1889850368E+08	0.1896026560E+08	0.1802434528E+08	0.1809162016E+08	0.1816264736E+08
ARB	SP.POP.GROW	0.12148600E+00	0.112038830E+00	0.113082980E+00	0.116465160E+00	0.122445180E+00	0.129740330E+00
ARE	SP.URB.TOTL	0.12138600E+06	0.168261100E+06	0.184320800E+06	0.1604862700E+06	0.1634683000E+06	0.1676723900E+06

Step 1 - convert years column into values

```
(def pop2 (api/pivot->longer world-bank-pop (map str (range 2000 2018)) {:drop-missing? false
                                                                           :target-columns ["year"]
                                                                           :value-column-name "value"})))
```

pop2

data/world\_bank\_pop.csv.gz [19008 4]:

country	indicator	year	value
ABW	SP.URB.TOTL	2013	4.43600000E+04
ABW	SP.URB.GROW	2013	6.69504000E-01
ABW	SP.POP.TOTL	2013	1.03187000E+05
ABW	SP.POP.GROW	2013	5.92914000E-01
AFG	SP.URB.TOTL	2013	7.73396400E+06
AFG	SP.URB.GROW	2013	4.19298000E+00
AFG	SP.POP.TOTL	2013	3.17316880E+07
AFG	SP.POP.GROW	2013	3.31522420E+00
AGO	SP.URB.TOTL	2013	1.61194910E+07
AGO	SP.URB.GROW	2013	4.72272250E+00
AGO	SP.POP.TOTL	2013	2.59983400E+07
AGO	SP.POP.GROW	2013	3.53182400E+00
ALB	SP.URB.TOTL	2013	1.60350500E+06
ALB	SP.URB.GROW	2013	1.74363930E+00
ALB	SP.POP.TOTL	2013	2.89509200E+06
ALB	SP.POP.GROW	2013	-1.83211386E-01
AND	SP.URB.TOTL	2013	7.15270000E+04
AND	SP.URB.GROW	2013	-2.11923337E+00
AND	SP.POP.TOTL	2013	8.07880000E+04
AND	SP.POP.GROW	2013	-2.01331401E+00
ARB	SP.URB.TOTL	2013	2.18605120E+08
ARB	SP.URB.GROW	2013	2.78289400E+00
ARB	SP.POP.TOTL	2013	3.81702080E+08
ARB	SP.POP.GROW	2013	2.24884440E+00
ARE	SP.URB.TOTL	2013	7.66126800E+06

Step 2 - separate "indicator" column

```
(def pop3 (api/separate-column pop2
  "indicator" ["area" "variable"]
  #(rest (clojure.string/split % #"\\."))))
```

pop3

data/world\_bank\_pop.csv.gz [19008 5]:

country	area	variable	year	value
ABW	URB	TOTL	2013	4.43600000E+04
ABW	URB	GROW	2013	6.69504000E-01
ABW	POP	TOTL	2013	1.03187000E+05
ABW	POP	GROW	2013	5.92914000E-01
AFG	URB	TOTL	2013	7.73396400E+06
AFG	URB	GROW	2013	4.19298000E+00
AFG	POP	TOTL	2013	3.17316880E+07
AFG	POP	GROW	2013	3.31522420E+00
AGO	URB	TOTL	2013	1.61194910E+07
AGO	URB	GROW	2013	4.72272250E+00
AGO	POP	TOTL	2013	2.59983400E+07
AGO	POP	GROW	2013	3.53182400E+00
ALB	URB	TOTL	2013	1.60350500E+06

country	area	variable	year	value
ALB	URB	GROW	2013	1.74363930E+00
ALB	POP	TOTL	2013	2.89509200E+06
ALB	POP	GROW	2013	-1.83211386E-01
AND	URB	TOTL	2013	7.15270000E+04
AND	URB	GROW	2013	-2.11923337E+00
AND	POP	TOTL	2013	8.07880000E+04
AND	POP	GROW	2013	-2.01331401E+00
ARB	URB	TOTL	2013	2.18605120E+08
ARB	URB	GROW	2013	2.78289400E+00
ARB	POP	TOTL	2013	3.81702080E+08
ARB	POP	GROW	2013	2.24884440E+00
ARE	URB	TOTL	2013	7.66126800E+06

Step 3 - Make columns based on "variable" values.

```
(api/pivot->wider pop3 "variable" "value")
```

data/world\_bank\_pop.csv.gz [9419 5]:

country	area	year	GROW	TOTL
ABW	URB	2013	0.66950400	4.43600000E+04
ABW	POP	2013	0.59291400	1.03187000E+05
AFG	URB	2013	4.19298000	7.73396400E+06
AFG	POP	2013	3.31522420	3.17316880E+07
AGO	URB	2013	4.72272250	1.61194910E+07
AGO	POP	2013	3.53182400	2.59983400E+07
ALB	URB	2013	1.74363930	1.60350500E+06
ALB	POP	2013	-0.18321139	2.89509200E+06
AND	URB	2013	-2.11923337	7.15270000E+04
AND	POP	2013	-2.01331401	8.07880000E+04
ARB	URB	2013	2.78289400	2.18605120E+08
ARB	POP	2013	2.24884440	3.81702080E+08
ARE	URB	2013	1.55515590	7.66126800E+06
ARE	POP	2013	1.18180500	9.00626300E+06
ARG	URB	2013	1.18764910	3.88172560E+07
ARG	POP	2013	1.04727670	4.25399240E+07
ARM	URB	2013	0.28102720	1.82765600E+06
ARM	POP	2013	0.40125197	2.89350900E+06
ASM	URB	2013	0.05797582	4.83100000E+04
ASM	POP	2013	0.13931988	5.53070000E+04
ATG	URB	2013	0.38383110	2.47980000E+04
ATG	POP	2013	1.07605830	9.78240000E+04
AUS	URB	2013	1.87536410	1.97902080E+07
AUS	POP	2013	1.75833810	2.31459000E+07
AUT	URB	2013	0.91956020	4.86199100E+06

Multi-choice

```
(def multi (api/dataset {:id [1 2 3 4]
                        :choice1 ["A" "C" "D" "B"]
                        :choice2 ["B" "B" nil "D"]
                        :choice3 ["C" nil nil nil]}))
```

```
multi
```

```
__unnamed [4 4]:
```

:id	:choice1	:choice2	:choice3
1	A	B	C
2	C	B	
3	D		
4	B	D	

Step 1 - convert all choices into rows and add artificial column to all values which are not missing.

```
(def multi2 (-> multi
  (api/pivot->longer (complement #{:id}))
  (api/add-or-replace-column :checked true)))
```

```
multi2
```

```
__unnamed [8 4]:
```

:id	:\$column	:\$value	:checked
1	:choice1	A	true
2	:choice1	C	true
3	:choice1	D	true
4	:choice1	B	true
1	:choice2	B	true
2	:choice2	B	true
4	:choice2	D	true
1	:choice3	C	true

Step 2 - Convert back to wide form with actual choices as columns

```
(-> multi2
  (api/drop-columns :$column)
  (api/pivot->wider :$value :checked {:drop-missing? false})
  (api/order-by :id))
```

```
__unnamed [4 5]:
```

:id	A	B	C	D
1	true	true	true	
2		true	true	
3				true
4		true		true

## Construction

```
(def construction (api/dataset "data/construction.csv"))
(def construction-unit-map {"1 unit" "1"
                           "2 to 4 units" "2-4"
                           "5 units or more" "5+"})
```

construction

data/construction.csv [9 9]:

Year	Month	1 unit	2 to 4 units	5 units or more	Northeast	Midwest	South	West
2018	January	859		348	114	169	596	339
2018	February	882		400	138	160	655	336
2018	March	862		356	150	154	595	330
2018	April	797		447	144	196	613	304
2018	May	875		364	90	169	673	319
2018	June	867		342	76	170	610	360
2018	July	829		360	108	183	594	310
2018	August	939		286	90	205	649	286
2018	September	835		304	117	175	560	296

## Conversion 1 - Group two column types

```
(-> construction
  (api/pivot->longer #"^[125NWS].*|Midwest" {:target-columns [:units :region]
                                             :splitter (fn [col-name]
                                                         (if (re-matches #"^[125].*" col-name)
                                                             [(construction-unit-map col-name) nil]
                                                             [nil col-name]))
                                             :value-column-name :n
                                             :drop-missing? false}))
```

data/construction.csv [63 5]:

Year	Month	:units	:region	:n
2018	January	1		859
2018	February	1		882
2018	March	1		862
2018	April	1		797
2018	May	1		875
2018	June	1		867
2018	July	1		829
2018	August	1		939
2018	September	1		835
2018	January	2-4		
2018	February	2-4		
2018	March	2-4		
2018	April	2-4		
2018	May	2-4		
2018	June	2-4		
2018	July	2-4		
2018	August	2-4		
2018	September	2-4		

Year	Month	:units	:region	:n
2018	January	5+		348
2018	February	5+		400
2018	March	5+		356
2018	April	5+		447
2018	May	5+		364
2018	June	5+		342
2018	July	5+		360

Conversion 2 - Convert to longer form and back and rename columns

```
(-> construction
  (api/pivot->longer #"^[125NWS].*|Midwest" {:target-columns [:units :region]
                                             :splitter (fn [col-name]
                                                           (if (re-matches #"^[125].*" col-name)
                                                               [(construction-unit-map col-name) nil]
                                                               [nil col-name]))
                                             :value-column-name :n
                                             :drop-missing? false})

  (api/pivot->wider [:units :region] :n)
  (api/rename-columns (zipmap (vals construction-unit-map)
                              (keys construction-unit-map))))
```

data/construction.csv [0 9]:

Year	Month	Midwest	5 units or more	2 to 4 units	Northeast	South	1	West
------	-------	---------	-----------------	--------------	-----------	-------	---	------

Various operations on stocks, examples taken from gather and spread manuals.

```
(def stocks-tidyr (api/dataset "data/stockstidyr.csv"))
```

stocks-tidyr

data/stockstidyr.csv [10 4]:

time	X	Y	Z
2009-01-01	1.30989800	-1.89040196	-1.7794688
2009-01-02	-0.29993805	-1.82473087	2.3989250
2009-01-03	0.53647500	-1.03606856	-3.9869797
2009-01-04	-1.88390803	-0.52178389	-2.8306549
2009-01-05	-0.96052361	-2.21683359	1.4371517
2009-01-06	-1.18528962	-2.89350915	3.3978415
2009-01-07	-0.85207057	-2.16794825	-1.2010826
2009-01-08	0.25234172	-0.32854116	-1.5316048
2009-01-09	0.40257135	1.96407900	-6.8087883
2009-01-10	-0.64383501	2.68618400	-2.5590932

Convert to longer form



```
(def stocks-long (api/pivot->longer stocks-tidyr ["X" "Y" "Z"] {:value-column-name :price
                                                                :target-columns :stocks})))
```

```
stocks-long
```

data/stockstidyr.csv [30 3]:

time	:stocks	:price
2009-01-01	X	1.30989800
2009-01-02	X	-0.29993805
2009-01-03	X	0.53647500
2009-01-04	X	-1.88390803
2009-01-05	X	-0.96052361
2009-01-06	X	-1.18528962
2009-01-07	X	-0.85207057
2009-01-08	X	0.25234172
2009-01-09	X	0.40257135
2009-01-10	X	-0.64383501
2009-01-01	Y	-1.89040196
2009-01-02	Y	-1.82473087
2009-01-03	Y	-1.03606856
2009-01-04	Y	-0.52178389
2009-01-05	Y	-2.21683359
2009-01-06	Y	-2.89350915
2009-01-07	Y	-2.16794825
2009-01-08	Y	-0.32854116
2009-01-09	Y	1.96407900
2009-01-10	Y	2.68618400
2009-01-01	Z	-1.77946877
2009-01-02	Z	2.39892500
2009-01-03	Z	-3.98697972
2009-01-04	Z	-2.83065486
2009-01-05	Z	1.43715170

Convert back to wide form

```
(api/pivot->wider stocks-long :stocks :price)
```

data/stockstidyr.csv [10 4]:

time	Z	X	Y
2009-01-01	-1.7794688	1.30989800	-1.89040196
2009-01-02	2.3989250	-0.29993805	-1.82473087
2009-01-03	-3.9869797	0.53647500	-1.03606856
2009-01-04	-2.8306549	-1.88390803	-0.52178389
2009-01-05	1.4371517	-0.96052361	-2.21683359
2009-01-06	3.3978415	-1.18528962	-2.89350915
2009-01-07	-1.2010826	-0.85207057	-2.16794825
2009-01-08	-1.5316048	0.25234172	-0.32854116
2009-01-09	-6.8087883	0.40257135	1.96407900
2009-01-10	-2.5590932	-0.64383501	2.68618400

Convert to wide form on time column (let's limit values to a couple of rows)

```
(-> stocks-long
  (api/select-rows (range 0 30 4))
  (api/pivot->wider "time" :price))
```

data/stockstidyr.csv [0 6]:

	2009-01-05	2009-01-07	2009-01-01	2009-01-03	2009-01-09
:stocks					

## Join/Concat Datasets

Dataset join and concatenation functions.

Joins accept left-side and right-side datasets and columns selector. Options are the same as in `tech.ml.dataset` functions.

The difference between `tech.ml.dataset` join functions are: arguments order (first datasets) and possibility to join on multiple columns.

Additionally set operations are defined: `intersect` and `difference`.

To concat two datasets rowwise you can choose:

- `concat` - concats rows for matching columns, the number of columns should be equal.
- `union` - like concat but returns unique values
- `bind` - concats rows add missing, empty columns

To add two datasets columnwise use `bind`. The number of rows should be equal.

Datasets used in examples:

```
(def ds1 (api/dataset {:a [1 2 1 2 3 4 nil nil 4]
                      :b (range 101 110)
                      :c (map str "abs tract")}))
(def ds2 (api/dataset {:a [nil 1 2 5 4 3 2 1 nil]
                      :b (range 110 101 -1)
                      :c (map str "datatable")
                      :d (symbol "X")}))
```

ds1  
ds2

\_\_unnamed [9 3]:

	:a	:b	:c
1		101	a
2		102	b
1		103	s
2		104	
3		105	t
4		106	r
		107	a
		108	c
4		109	t

\_\_unnamed [9 4]:

:a	:b	:c	:d
	110	d	X
1	109	a	X
2	108	t	X
5	107	a	X
4	106	t	X
3	105	a	X
2	104	b	X
1	103	l	X
	102	e	X

### Left

```
(api/left-join ds1 ds2 :b)
```

left-outer-join [9 7]:

:b	:a	:c	:right.b	:right.a	:right.c	:d
109	4	t	109	1	a	X
108		c	108	2	t	X
107		a	107	5	a	X
106	4	r	106	4	t	X
105	3	t	105	3	a	X
104	2		104	2	b	X
103	1	s	103	1	l	X
102	2	b	102		e	X
101	1	a				

```
(api/left-join ds2 ds1 :b)
```

left-outer-join [9 7]:

:b	:a	:c	:d	:right.b	:right.a	:right.c
102		e	X	102	2	b
103	1	l	X	103	1	s
104	2	b	X	104	2	
105	3	a	X	105	3	t
106	4	t	X	106	4	r
107	5	a	X	107		a
108	2	t	X	108		c
109	1	a	X	109	4	t
110		d	X			

```
(api/left-join ds1 ds2 [:a :b])
```

left-outer-join [9 7]:

:a	:b	:c	:right.a	:right.b	:right.c	:d
4	106	r	4	106	t	X
3	105	t	3	105	a	X
2	104		2	104	b	X
1	103	s	1	103	l	X
2	102	b				
	108	c				
	107	a				
1	101	a				
4	109	t				

```
(api/left-join ds2 ds1 [:a :b])
```

left-outer-join [9 7]:

:a	:b	:c	:d	:right.a	:right.b	:right.c
1	103	l	X	1	103	s
2	104	b	X	2	104	
3	105	a	X	3	105	t
4	106	t	X	4	106	r
2	108	t	X			
1	109	a	X			
5	107	a	X			
	110	d	X			
	102	e	X			

## Right

```
(api/right-join ds1 ds2 :b)
```

right-outer-join [9 7]:

:b	:a	:c	:right.b	:right.a	:right.c	:d
109	4	t	109	1	a	X
108		c	108	2	t	X
107		a	107	5	a	X
106	4	r	106	4	t	X
105	3	t	105	3	a	X
104	2		104	2	b	X
103	1	s	103	1	l	X
102	2	b	102		e	X
			110		d	X

```
(api/right-join ds2 ds1 :b)
```

right-outer-join [9 7]:

:b	:a	:c	:d	:right.b	:right.a	:right.c
102		e	X	102	2	b
103	1	l	X	103	1	s
104	2	b	X	104	2	
105	3	a	X	105	3	t
106	4	t	X	106	4	r
107	5	a	X	107		a
108	2	t	X	108		c
109	1	a	X	109	4	t
				101	1	a

```
(api/right-join ds1 ds2 [:a :b])
```

right-outer-join [9 7]:

:a	:b	:c	:right.a	:right.b	:right.c	:d
4	106	r	4	106	t	X
3	105	t	3	105	a	X
2	104		2	104	b	X
1	103	s	1	103	l	X
				110	d	X
			1	109	a	X
			2	108	t	X
			5	107	a	X
				102	e	X

```
(api/right-join ds2 ds1 [:a :b])
```

right-outer-join [9 7]:

:a	:b	:c	:d	:right.a	:right.b	:right.c
1	103	l	X	1	103	s
2	104	b	X	2	104	
3	105	a	X	3	105	t
4	106	t	X	4	106	r
				1	101	a
				2	102	b
					107	a
					108	c
				4	109	t

## Inner

```
(api/inner-join ds1 ds2 :b)
```

inner-join [8 6]:

	:b	:a	:c	:right.a	:right.c	:d
109	4	t		1	a	X
108		c		2	t	X
107		a		5	a	X
106	4	r		4	t	X
105	3	t		3	a	X
104	2			2	b	X
103	1	s		1	l	X
102	2	b			e	X

---

```
(api/inner-join ds2 ds1 :b)
```

inner-join [8 6]:

	:b	:a	:c	:d	:right.a	:right.c
102		e	X		2	b
103	1	l	X		1	s
104	2	b	X		2	
105	3	a	X		3	t
106	4	t	X		4	r
107	5	a	X			a
108	2	t	X			c
109	1	a	X		4	t

---

```
(api/inner-join ds1 ds2 [:a :b])
```

inner-join [4 7]:

:a	:b	:c	:right.a	:right.b	:right.c	:d
4	106	r	4	106	t	X
3	105	t	3	105	a	X
2	104		2	104	b	X
1	103	s	1	103	l	X

---

```
(api/inner-join ds2 ds1 [:a :b])
```

inner-join [4 7]:

:a	:b	:c	:d	:right.a	:right.b	:right.c
1	103	l	X	1	103	s
2	104	b	X	2	104	
3	105	a	X	3	105	t
4	106	t	X	4	106	r

**Full**

Join keeping all rows

```
(api/full-join ds1 ds2 :b)
```

full-join [10 7]:

:b	:a	:c	:right.b	:right.a	:right.c	:d
109	4	t	109	1	a	X
108		c	108	2	t	X
107		a	107	5	a	X
106	4	r	106	4	t	X
105	3	t	105	3	a	X
104	2		104	2	b	X
103	1	s	103	1	l	X
102	2	b	102		e	X
101	1	a				
			110		d	X

```
(api/full-join ds2 ds1 :b)
```

full-join [10 7]:

:b	:a	:c	:d	:right.b	:right.a	:right.c
102		e	X	102	2	b
103	1	l	X	103	1	s
104	2	b	X	104	2	
105	3	a	X	105	3	t
106	4	t	X	106	4	r
107	5	a	X	107		a
108	2	t	X	108		c
109	1	a	X	109	4	t
110		d	X			
				101	1	a

```
(api/full-join ds1 ds2 [:a :b])
```

full-join [14 7]:

:a	:b	:c	:right.a	:right.b	:right.c	:d
4	106	r	4	106	t	X
3	105	t	3	105	a	X
2	104		2	104	b	X
1	103	s	1	103	l	X
2	102	b				
	108	c				
	107	a				
1	101	a				
4	109	t				
				110	d	X
			1	109	a	X

:a	:b	:c	:right.a	:right.b	:right.c	:d
			2	108	t	X
			5	107	a	X
				102	e	X

```
(api/full-join ds2 ds1 [:a :b])
```

full-join [14 7]:

:a	:b	:c	:d	:right.a	:right.b	:right.c
1	103	l	X	1	103	s
2	104	b	X	2	104	
3	105	a	X	3	105	t
4	106	t	X	4	106	r
2	108	t	X			
1	109	a	X			
5	107	a	X			
	110	d	X			
	102	e	X			
				1	101	a
				2	102	b
					107	a
					108	c
				4	109	t

## Semi

Return rows from ds1 matching ds2

```
(api/semi-join ds1 ds2 :b)
```

semi-join [5 3]:

	:b	:a	:c
109	4	t	
106	4	r	
105	3	t	
104	2		
103	1	s	

```
(api/semi-join ds2 ds1 :b)
```

semi-join [5 4]:

	:b	:a	:c	:d
103	1	l	X	
104	2	b	X	
105	3	a	X	



	:b	:a	:c	:d
106	4	t	X	
109	1	a	X	

---

```
(api/semi-join ds1 ds2 [:a :b])
```

semi-join [4 3]:

	:a	:b	:c
4	106	r	
3	105	t	
2	104		
1	103	s	

---

```
(api/semi-join ds2 ds1 [:a :b])
```

semi-join [4 4]:

	:a	:b	:c	:d
1	103	l	X	
2	104	b	X	
3	105	a	X	
4	106	t	X	

## Anti

Return rows from ds1 not matching ds2

```
(api/anti-join ds1 ds2 :b)
```

anti-join [4 3]:

	:b	:a	:c
108		c	
107		a	
102	2	b	
101	1	a	

---

```
(api/anti-join ds2 ds1 :b)
```

anti-join [4 4]:

	:b	:a	:c	:d
102		e	X	
107	5	a	X	
108	2	t	X	

:b	:a	:c	:d
110		d	X

---

```
(api/anti-join ds1 ds2 [:a :b])
```

anti-join [5 3]:

:a	:b	:c
2	102	b
	108	c
	107	a
1	101	a
4	109	t

---

```
(api/anti-join ds2 ds1 [:a :b])
```

anti-join [5 4]:

:a	:b	:c	:d
2	108	t	X
1	109	a	X
5	107	a	X
	110	d	X
	102	e	X

## Concat

`contact` joins rows from other datasets

```
(api/concat ds1)
```

null [9 3]:

:a	:b	:c
1	101	a
2	102	b
1	103	s
2	104	
3	105	t
4	106	r
	107	a
	108	c
4	109	t

---

```
(api/concat ds1 (api/drop-columns ds2 :d))
```

null [18 3]:

:a	:b	:c
1	101	a
2	102	b
1	103	s
2	104	
3	105	t
4	106	r
	107	a
	108	c
4	109	t
	110	d
1	109	a
2	108	t
5	107	a
4	106	t
3	105	a
2	104	b
1	103	l
	102	e

```
(apply api/concat (repeatedly 3 #(api/random DS)))
```

null [27 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
2	2	1.0	B
1	3	1.5	C
1	9	1.5	C
1	5	1.0	B
1	9	1.5	C
1	5	1.0	B
2	8	1.0	B
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	1	0.5	A
1	5	1.0	B
1	9	1.5	C
2	8	1.0	B
2	6	1.5	C
1	7	0.5	A
1	3	1.5	C
2	4	0.5	A
2	8	1.0	B
2	6	1.5	C
2	4	0.5	A
1	3	1.5	C

:V1	:V2	:V3	:V4
2	6	1.5	C

## Union

The same as `concat` but returns unique rows

```
(apply api/union (api/drop-columns ds2 :d) (repeat 10 ds1))
```

union [18 3]:

:a	:b	:c
	110	d
1	109	a
2	108	t
5	107	a
4	106	t
3	105	a
2	104	b
1	103	l
	102	e
1	101	a
2	102	b
1	103	s
2	104	
3	105	t
4	106	r
	107	a
	108	c
4	109	t

```
(apply api/union (repeatedly 10 #(api/random DS)))
```

union [9 4]:

:V1	:V2	:V3	:V4
1	5	1.0	B
1	1	0.5	A
2	2	1.0	B
2	6	1.5	C
2	4	0.5	A
1	9	1.5	C
1	7	0.5	A
1	3	1.5	C
2	8	1.0	B

## Bind

`bind` adds empty columns during concat

```
(api/bind ds1 ds2)
```

null [18 4]:

:a	:b	:c	:d
1	101	a	
2	102	b	
1	103	s	
2	104		
3	105	t	
4	106	r	
	107	a	
	108	c	
4	109	t	
	110	d	X
1	109	a	X
2	108	t	X
5	107	a	X
4	106	t	X
3	105	a	X
2	104	b	X
1	103	l	X
	102	e	X

```
(api/bind ds2 ds1)
```

null [18 4]:

:a	:b	:c	:d
	110	d	X
1	109	a	X
2	108	t	X
5	107	a	X
4	106	t	X
3	105	a	X
2	104	b	X
1	103	l	X
	102	e	X
1	101	a	
2	102	b	
1	103	s	
2	104		
3	105	t	
4	106	r	
	107	a	
	108	c	
4	109	t	

Append

append concatenates columns

```
(api/append ds1 ds2)
```

\_\_unnamed [9 7]:

:a	:b	:c	:a	:b	:c	:d
1	101	a		110	d	X
2	102	b	1	109	a	X
1	103	s	2	108	t	X
2	104		5	107	a	X
3	105	t	4	106	t	X
4	106	r	3	105	a	X
	107	a	2	104	b	X
	108	c	1	103	l	X
4	109	t		102	e	X

### Intersection

```
(api/intersect (api/select-columns ds1 :b)
               (api/select-columns ds2 :b))
```

intersection [8 1]:

:b
109
108
107
106
105
104
103
102

### Difference

```
(api/difference (api/select-columns ds1 :b)
                (api/select-columns ds2 :b))
```

difference [1 1]:

:b
101

```
(api/difference (api/select-columns ds2 :b)
                (api/select-columns ds1 :b))
```

difference [1 1]:

## Functions

This API doesn't provide any statistical, numerical or date/time functions. Use below namespaces:

Namespace	functions
tech.v2.datatype.functional	primitive operations, reducers, statistics
tech.v2.datatype.datetime	date/time converters
tech.v2.datatype.datetime.operations	date/time functions
tech.ml.dataset.pipeline	pipeline operations

## Other examples

### Stocks

```
(defonce stocks (api/dataset "https://raw.githubusercontent.com/techascent/tech.ml.dataset/master/test/data/stocks.csv"
stocks
```

<https://raw.githubusercontent.com/techascent/tech.ml.dataset/master/test/data/stocks.csv> [560 3]:

:symbol	:date	:price
MSFT	2000-01-01	39.81
MSFT	2000-02-01	36.35
MSFT	2000-03-01	43.22
MSFT	2000-04-01	28.37
MSFT	2000-05-01	25.45
MSFT	2000-06-01	32.54
MSFT	2000-07-01	28.40
MSFT	2000-08-01	28.40
MSFT	2000-09-01	24.53
MSFT	2000-10-01	28.02
MSFT	2000-11-01	23.34
MSFT	2000-12-01	17.65
MSFT	2001-01-01	24.84
MSFT	2001-02-01	24.00
MSFT	2001-03-01	22.25
MSFT	2001-04-01	27.56
MSFT	2001-05-01	28.14
MSFT	2001-06-01	29.70
MSFT	2001-07-01	26.93
MSFT	2001-08-01	23.21
MSFT	2001-09-01	20.82
MSFT	2001-10-01	23.65
MSFT	2001-11-01	26.12
MSFT	2001-12-01	26.95
MSFT	2002-01-01	25.92

```
(-> stocks
  (api/group-by (fn [row]
                  { :symbol (:symbol row)
                    :year (tech.v2.datatype.datetime.operations/get-years (:date row)) }))
  (api/aggregate #(tech.v2.datatype.functional/mean (% :price)))
  (api/order-by [:symbol :year]))
```

\_\_unnamed [51 3]:

:symbol	:year	:summary
AAPL	2000	21.74833341
AAPL	2001	10.17583323
AAPL	2002	9.40833330
AAPL	2003	9.34749989
AAPL	2004	18.72333336
AAPL	2005	48.17166678
AAPL	2006	72.04333369
AAPL	2007	133.35333379
AAPL	2008	138.48083242
AAPL	2009	150.39333344
AAPL	2010	206.56666565
AMZN	2000	43.93083342
AMZN	2001	11.73916642
AMZN	2002	16.72333336
AMZN	2003	39.01666673
AMZN	2004	43.26749992
AMZN	2005	40.18750032
AMZN	2006	36.25166623
AMZN	2007	69.95250066
AMZN	2008	69.01500003
AMZN	2009	90.73083433
AMZN	2010	124.21000417
GOOG	2004	159.47599945
GOOG	2005	286.47249858
GOOG	2006	415.25666809

```
(-> stocks
  (api/group-by (juxt :symbol #(tech.v2.datatype.datetime.operations/get-years (% :date))))
  (api/aggregate #(tech.v2.datatype.functional/mean (% :price)))
  (api/rename-columns {:$group-name-0 :symbol
                      :$group-name-1 :year}))
```

\_\_unnamed [51 3]:

:symbol	:year	:summary
AMZN	2007	69.95250066
AMZN	2008	69.01500003
AMZN	2009	90.73083433
AMZN	2010	124.21000417
AMZN	2000	43.93083342
AMZN	2001	11.73916642
AMZN	2002	16.72333336



:symbol	:year	:summary
AMZN	2003	39.01666673
AMZN	2004	43.26749992
AMZN	2005	40.18750032
AMZN	2006	36.25166623
IBM	2001	96.96833356
IBM	2002	75.12500032
IBM	2000	96.91416677
MSFT	2006	24.75833321
MSFT	2005	23.84583330
MSFT	2004	22.67416684
MSFT	2003	20.93416675
AAPL	2001	10.17583323
MSFT	2010	28.50666618
AAPL	2002	9.40833330
MSFT	2009	22.87250002
MSFT	2008	25.20833317
AAPL	2000	21.74833341
MSFT	2007	29.28416665

## data.table

Below you can find comparizon between functionality of `data.table` and Clojure dataset API. I leave it without comments, please refer original document explaining details:

Introduction to `data.table`

R

```
library(data.table)
library(knitr)

flights <- fread("https://raw.githubusercontent.com/Rdatatable/data.table/master/vignettes/flights14.csv")

kable(head(flights))
```

year	month	day	dep_delay	arr_delay	carrier	origin	dest	air_time	distance	hour
2014	1	1	14	13	AA	JFK	LAX	359	2475	9
2014	1	1	-3	13	AA	JFK	LAX	363	2475	11
2014	1	1	2	9	AA	JFK	LAX	351	2475	19
2014	1	1	-8	-26	AA	LGA	PBI	157	1035	7
2014	1	1	2	1	AA	JFK	LAX	350	2475	13
2014	1	1	4	0	AA	EWB	LAX	339	2454	18

Clojure

```
(require '[tech.v2.datatype.functional :as dfn]
         '[tech.v2.datatype :as dtype])

(defonce flights (api/dataset "https://raw.githubusercontent.com/Rdatatable/data.table/master/vignettes/"))
```

```
(api/head flights 6)
```

<https://raw.githubusercontent.com/Rdatatable/data.table/master/vignettes/flights14.csv> [6 11]:

year	month	day	dep_delay	arr_delay	carrier	origin	dest	air_time	distance	hour
2014	1	1	14	13	AA	JFK	LAX	359	2475	9
2014	1	1	-3	13	AA	JFK	LAX	363	2475	11
2014	1	1	2	9	AA	JFK	LAX	351	2475	19
2014	1	1	-8	-26	AA	LGA	PBI	157	1035	7
2014	1	1	2	1	AA	JFK	LAX	350	2475	13
2014	1	1	4	0	AA	EWR	LAX	339	2454	18

## Basics

### Shape of loaded data

R

```
dim(flights)
```

```
[1] 253316    11
```

Clojure

```
(api/shape flights)
```

```
[253316 11]
```

### What is data.table?

R

```
DT = data.table(  
  ID = c("b", "b", "b", "a", "a", "c"),  
  a = 1:6,  
  b = 7:12,  
  c = 13:18  
)
```

```
kable(DT)
```

ID	a	b	c
b	1	7	13
b	2	8	14
b	3	9	15
a	4	10	16
a	5	11	17
c	6	12	18

```
class(DT$ID)
```

```
[1] "character"
```

---

Clojure

```
(def DT (api/dataset {:ID ["b" "b" "b" "a" "a" "c"]
                      :a (range 1 7)
                      :b (range 7 13)
                      :c (range 13 19)}))
```

DT

\_\_unnamed [6 4]:

:ID	:a	:b	:c
b	1	7	13
b	2	8	14
b	3	9	15
a	4	10	16
a	5	11	17
c	6	12	18

```
(-> :ID DT meta :datatype)
```

:string

Get all the flights with “JFK” as the origin airport in the month of June.

R

```
ans <- flights[origin == "JFK" & month == 6L]
kable(head(ans))
```

year	month	day	dep_delay	arr_delay	carrier	origin	dest	air_time	distance	hour
2014	6	1	-9	-5	AA	JFK	LAX	324	2475	8
2014	6	1	-10	-13	AA	JFK	LAX	329	2475	12
2014	6	1	18	-1	AA	JFK	LAX	326	2475	7
2014	6	1	-6	-16	AA	JFK	LAX	320	2475	10
2014	6	1	-4	-45	AA	JFK	LAX	326	2475	18
2014	6	1	-6	-23	AA	JFK	LAX	329	2475	14

---

Clojure

```
(-> flights
  (api/select-rows (fn [row] (and (= (get row "origin") "JFK")
                                   (= (get row "month") 6))))
  (api/head 6))
```

<https://raw.githubusercontent.com/Rdatatable/data.table/master/vignettes/flights14.csv> [6 11]:

year	month	day	dep_delay	arr_delay	carrier	origin	dest	air_time	distance	hour
2014	6	1	-9	-5	AA	JFK	LAX	324	2475	8
2014	6	1	-10	-13	AA	JFK	LAX	329	2475	12

year	month	day	dep_delay	arr_delay	carrier	origin	dest	air_time	distance	hour
2014	6	1	18	-1	AA	JFK	LAX	326	2475	7
2014	6	1	-6	-16	AA	JFK	LAX	320	2475	10
2014	6	1	-4	-45	AA	JFK	LAX	326	2475	18
2014	6	1	-6	-23	AA	JFK	LAX	329	2475	14

Get the first two rows from `flights`.

R

```
ans <- flights[1:2]
kable(ans)
```

year	month	day	dep_delay	arr_delay	carrier	origin	dest	air_time	distance	hour
2014	1	1	14	13	AA	JFK	LAX	359	2475	9
2014	1	1	-3	13	AA	JFK	LAX	363	2475	11

Clojure

```
(api/select-rows flights (range 2))
```

<https://raw.githubusercontent.com/Rdatatable/data.table/master/vignettes/flights14.csv> [2 11]:

year	month	day	dep_delay	arr_delay	carrier	origin	dest	air_time	distance	hour
2014	1	1	14	13	AA	JFK	LAX	359	2475	9
2014	1	1	-3	13	AA	JFK	LAX	363	2475	11

Sort `flights` first by column `origin` in ascending order, and then by `dest` in descending order

R

```
ans <- flights[order(origin, -dest)]
kable(head(ans))
```

year	month	day	dep_delay	arr_delay	carrier	origin	dest	air_time	distance	hour
2014	1	5	6	49	EV	EWR	XNA	195	1131	8
2014	1	6	7	13	EV	EWR	XNA	190	1131	8
2014	1	7	-6	-13	EV	EWR	XNA	179	1131	8
2014	1	8	-7	-12	EV	EWR	XNA	184	1131	8
2014	1	9	16	7	EV	EWR	XNA	181	1131	8
2014	1	13	66	66	EV	EWR	XNA	188	1131	9

Clojure

```
(-> flights
  (api/order-by ["origin" "dest"] [:asc :desc])
  (api/head 6))
```

<https://raw.githubusercontent.com/Rdatatable/data.table/master/vignettes/flights14.csv> [6 11]:

year	month	day	dep_delay	arr_delay	carrier	origin	dest	air_time	distance	hour
2014	6	3	-6	-38	EV	EWR	XNA	154	1131	6
2014	1	20	-9	-17	EV	EWR	XNA	177	1131	8
2014	3	19	-6	10	EV	EWR	XNA	201	1131	6
2014	2	3	231	268	EV	EWR	XNA	184	1131	12
2014	4	25	-8	-32	EV	EWR	XNA	159	1131	6
2014	2	19	21	10	EV	EWR	XNA	176	1131	8

Select `arr_delay` column, but return it as a vector

R

```
ans <- flights[, arr_delay]
head(ans)
```

```
[1] 13 13 9 -26 1 0
```

Clojure

```
(take 6 (flights "arr_delay"))
```

```
(13 13 9 -26 1 0)
```

Select `arr_delay` column, but return as a `data.table` instead

R

```
ans <- flights[, list(arr_delay)]
kable(head(ans))
```

arr_delay
13
13
9
-26
1
0

Clojure

```
(-> flights
  (api/select-columns "arr_delay")
  (api/head 6))
```

<https://raw.githubusercontent.com/Rdatatable/data.table/master/vignettes/flights14.csv> [6 1]:

arr_delay
13
13

arr_delay
9
-26
1
0

Select both arr\_delay and dep\_delay columns

R

```
ans <- flights[, .(arr_delay, dep_delay)]
kable(head(ans))
```

arr_delay	dep_delay
13	14
13	-3
9	2
-26	-8
1	2
0	4

Clojure

```
(-> flights
  (api/select-columns ["arr_delay" "dep_delay"])
  (api/head 6))
```

<https://raw.githubusercontent.com/Rdatatable/data.table/master/vignettes/flights14.csv> [6 2]:

dep_delay	arr_delay
14	13
-3	13
2	9
-8	-26
2	1
4	0

Select both arr\_delay and dep\_delay columns and rename them to delay\_arr and delay\_dep

R

```
ans <- flights[, .(delay_arr = arr_delay, delay_dep = dep_delay)]
kable(head(ans))
```

delay_arr	delay_dep
13	14
13	-3
9	2
-26	-8
1	2

delay_arr	delay_dep
0	4

Clojure

```
(-> flights
  (api/select-columns {"arr_delay" "delay_arr"
                      "dep_delay" "delay_dep"}))
(api/head 6))
```

<https://raw.githubusercontent.com/Rdatatable/data.table/master/vignettes/flights14.csv> [6 2]:

delay_arr	delay_dep
14	13
-3	13
2	9
-8	-26
2	1
4	0

How many trips have had total delay < 0?

R

```
ans <- flights[, sum( (arr_delay + dep_delay) < 0 )]
ans

[1] 141814
```

Clojure

```
(->> (dfn/+ (flights "arr_delay") (flights "dep_delay"))
      (dfn/argfilter #(< % 0.0))
      (dtype/ecount))
```

141814

or pure Clojure functions (much, much slower)

```
(->> (map + (flights "arr_delay") (flights "dep_delay"))
      (filter neg?)
      (count))
```

141814

Calculate the average arrival and departure delay for all flights with “JFK” as the origin airport in the month of June

R

```
ans <- flights[origin == "JFK" & month == 6L,
               .(m_arr = mean(arr_delay), m_dep = mean(dep_delay))]
kable(ans)
```

m_arr	m_dep
5.839349	9.807884

Clojure

```
(-> flights
  (api/select-rows (fn [row] (and (= (get row "origin") "JFK")
                                   (= (get row "month") 6))))
  (api/aggregate {:m_arr #(dfn/mean (% "arr_delay"))
                  :m_dep #(dfn/mean (% "dep_delay"))}))
```

\_\_unnamed [1 2]:

:m_arr	:m_dep
5.83934932	9.80788411

How many trips have been made in 2014 from “JFK” airport in the month of June?

R

```
ans <- flights[origin == "JFK" & month == 6L, length(dest)]
ans
```

[1] 8422

or

```
ans <- flights[origin == "JFK" & month == 6L, .N]
ans
```

[1] 8422

Clojure

```
(-> flights
  (api/select-rows (fn [row] (and (= (get row "origin") "JFK")
                                   (= (get row "month") 6))))
  (api/row-count))
```

8422

deselect columns using - or !

R

```
ans <- flights[, !c("arr_delay", "dep_delay")]
kable(head(ans))
```

year	month	day	carrier	origin	dest	air_time	distance	hour
2014	1	1	AA	JFK	LAX	359	2475	9
2014	1	1	AA	JFK	LAX	363	2475	11
2014	1	1	AA	JFK	LAX	351	2475	19
2014	1	1	AA	LGA	PBI	157	1035	7



year	month	day	carrier	origin	dest	air_time	distance	hour
2014	1	1	AA	JFK	LAX	350	2475	13
2014	1	1	AA	EWR	LAX	339	2454	18

or

```
ans <- flights[, -c("arr_delay", "dep_delay")]
kable(head(ans))
```

year	month	day	carrier	origin	dest	air_time	distance	hour
2014	1	1	AA	JFK	LAX	359	2475	9
2014	1	1	AA	JFK	LAX	363	2475	11
2014	1	1	AA	JFK	LAX	351	2475	19
2014	1	1	AA	LGA	PBI	157	1035	7
2014	1	1	AA	JFK	LAX	350	2475	13
2014	1	1	AA	EWR	LAX	339	2454	18

Clojure

```
(-> flights
  (api/select-columns (complement #{"arr_delay" "dep_delay"}))
  (api/head 6))
```

<https://raw.githubusercontent.com/Rdatatable/data.table/master/vignettes/flights14.csv> [6 9]:

year	month	day	carrier	origin	dest	air_time	distance	hour
2014	1	1	AA	JFK	LAX	359	2475	9
2014	1	1	AA	JFK	LAX	363	2475	11
2014	1	1	AA	JFK	LAX	351	2475	19
2014	1	1	AA	LGA	PBI	157	1035	7
2014	1	1	AA	JFK	LAX	350	2475	13
2014	1	1	AA	EWR	LAX	339	2454	18

## Aggregations

How can we get the number of trips corresponding to each origin airport?

R

```
ans <- flights[, .(N), by = .(origin)]
kable(ans)
```

origin	N
JFK	81483
LGA	84433
EWR	87400

Clojure

```
(-> flights
  (api/group-by ["origin"])
  (api/aggregate {:N api/row-count}))
```

\_\_unnamed [3 2]:

origin	:N
LGA	84433
EWB	87400
JFK	81483

How can we calculate the number of trips for each origin airport for carrier code “AA”?

R

```
ans <- flights[carrier == "AA", .N, by = origin]
kable(ans)
```

origin	N
JFK	11923
LGA	11730
EWB	2649

Clojure

```
(-> flights
  (api/select-rows #(= (get % "carrier") "AA"))
  (api/group-by ["origin"])
  (api/aggregate {:N api/row-count}))
```

\_\_unnamed [3 2]:

origin	:N
LGA	11730
EWB	2649
JFK	11923

How can we get the total number of trips for each origin, dest pair for carrier code “AA”?

R

```
ans <- flights[carrier == "AA", .N, by = .(origin, dest)]
kable(head(ans))
```

origin	dest	N
JFK	LAX	3387
LGA	PBI	245
EWB	LAX	62
JFK	MIA	1876

origin	dest	N
JFK	SEA	298
EWR	MIA	848

Clojure

```
(-> flights
  (api/select-rows #(<= (get % "carrier") "AA"))
  (api/group-by ["origin" "dest"])
  (api/aggregate {:N api/row-count})
  (api/head 6))
```

\_\_unnamed [6 3]:

origin	dest	:N
JFK	MIA	1876
LGA	PBI	245
JFK	SEA	298
LGA	DFW	3785
JFK	AUS	297
JFK	STT	229

How can we get the average arrival and departure delay for each orig,dest pair for each month for carrier code “AA”?

R

```
ans <- flights[carrier == "AA",
  .(mean(arr_delay), mean(dep_delay)),
  by = .(origin, dest, month)]
kable(head(ans,10))
```

origin	dest	month	V1	V2
JFK	LAX	1	6.590361	14.2289157
LGA	PBI	1	-7.758621	0.3103448
EWR	LAX	1	1.366667	7.5000000
JFK	MIA	1	15.720670	18.7430168
JFK	SEA	1	14.357143	30.7500000
EWR	MIA	1	11.011236	12.1235955
JFK	SFO	1	19.252252	28.6396396
JFK	BOS	1	12.919643	15.2142857
JFK	ORD	1	31.586207	40.1724138
JFK	IAH	1	28.857143	14.2857143

Clojure

```
(-> flights
  (api/select-rows #(<= (get % "carrier") "AA"))
  (api/group-by ["origin" "dest" "month"]))
```

```
(api/aggregate [#(dfn/mean (% "arr_delay"))
               #(dfn/mean (% "dep_delay"))])
(api/head 10))
```

\_\_unnamed [10 5]:

month	origin	dest	:summary-0	:summary-1
9	LGA	DFW	-8.78772379	-0.25575448
10	LGA	DFW	3.50000000	4.55276382
1	JFK	AUS	25.20000000	27.60000000
4	JFK	AUS	4.36666667	-0.13333333
5	JFK	AUS	6.76666667	14.73333333
2	JFK	AUS	26.26923077	21.50000000
3	JFK	AUS	8.19354839	2.70967742
8	JFK	AUS	20.41935484	20.77419355
1	EWB	LAX	1.36666667	7.50000000
9	JFK	AUS	16.26666667	14.36666667

So how can we directly order by all the grouping variables?

R

```
ans <- flights[carrier == "AA",
               .(mean(arr_delay), mean(dep_delay)),
               keyby = .(origin, dest, month)]
kable(head(ans, 10))
```

origin	dest	month	V1	V2
EWB	DFW	1	6.427673	10.012579
EWB	DFW	2	10.536765	11.345588
EWB	DFW	3	12.865031	8.079755
EWB	DFW	4	17.792683	12.920732
EWB	DFW	5	18.487805	18.682927
EWB	DFW	6	37.005952	38.744048
EWB	DFW	7	20.250000	21.154762
EWB	DFW	8	16.936046	22.069767
EWB	DFW	9	5.865031	13.055215
EWB	DFW	10	18.813665	18.894410

Clojure

```
(-> flights
  (api/select-rows #(= (get % "carrier") "AA"))
  (api/group-by ["origin" "dest" "month"])
  (api/aggregate [#(dfn/mean (% "arr_delay"))
                  #(dfn/mean (% "dep_delay"))])
  (api/order-by ["origin" "dest" "month"])
  (api/head 10))
```

\_\_unnamed [10 5]:

month	origin	dest	:summary-0	:summary-1
1	EWR	DFW	6.42767296	10.01257862
2	EWR	DFW	10.53676471	11.34558824
3	EWR	DFW	12.86503067	8.07975460
4	EWR	DFW	17.79268293	12.92073171
5	EWR	DFW	18.48780488	18.68292683
6	EWR	DFW	37.00595238	38.74404762
7	EWR	DFW	20.25000000	21.15476190
8	EWR	DFW	16.93604651	22.06976744
9	EWR	DFW	5.86503067	13.05521472
10	EWR	DFW	18.81366460	18.89440994

Can by accept expressions as well or does it just take columns?

R

```
ans <- flights[, .N, .(dep_delay>0, arr_delay>0)]
kable(ans)
```

dep_delay	arr_delay	N
TRUE	TRUE	72836
FALSE	TRUE	34583
FALSE	FALSE	119304
TRUE	FALSE	26593

Clojure

```
(-> flights
  (api/group-by (fn [row]
                  { :dep_delay (pos? (get row "dep_delay"))
                    :arr_delay (pos? (get row "arr_delay")) }))
  (api/aggregate { :N api/row-count })))
```

\_\_unnamed [4 3]:

:dep_delay	:arr_delay	:N
true	false	26593
false	true	34583
false	false	119304
true	true	72836

Do we have to compute mean() for each column individually?

R

```
kable(DT)
```

ID	a	b	c
b	1	7	13
b	2	8	14

ID	a	b	c
b	3	9	15
a	4	10	16
a	5	11	17
c	6	12	18

```
DT[, print(.SD), by = ID]
```

```

  a b c
1: 1 7 13
2: 2 8 14
3: 3 9 15
  a b c
1: 4 10 16
2: 5 11 17
  a b c
1: 6 12 18
```

Empty data.table (0 rows and 1 cols): ID

```
kable(DT[, lapply(.SD, mean), by = ID])
```

ID	a	b	c
b	2.0	8.0	14.0
a	4.5	10.5	16.5
c	6.0	12.0	18.0

Clojure

DT

```
(api/group-by DT :ID {:result-type :as-map})
```

\_\_unnamed [6 4]:

:ID	:a	:b	:c
b	1	7	13
b	2	8	14
b	3	9	15
a	4	10	16
a	5	11	17
c	6	12	18

{“a” Group: a [2 4]:

:ID	:a	:b	:c
a	4	10	16
a	5	11	17

, “b” Group: b [3 4]:

:ID	:a	:b	:c
b	1	7	13
b	2	8	14
b	3	9	15

, “c” Group: c [1 4]:

:ID	:a	:b	:c
c	6	12	18

}

```
(-> DT
  (api/group-by [:ID])
  (api/aggregate-columns (complement #{:ID}) dfn/mean))
```

\_\_unnamed [3 4]:

:ID	:a	:b	:c
a	4.5	10.5	16.5
b	2.0	8.0	14.0
c	6.0	12.0	18.0

How can we specify just the columns we would like to compute the mean() on?

R

```
kable(head(flights[carrier == "AA",
  lapply(.SD, mean),
  by = .(origin, dest, month),
  .SDcols = c("arr_delay", "dep_delay")])) ## Only on trips with carrier "AA"
                                           ## compute the mean
                                           ## for every 'origin,dest,month'
                                           ## for just those specified in .SDcols
```

origin	dest	month	arr_delay	dep_delay
JFK	LAX	1	6.590361	14.2289157
LGA	PBI	1	-7.758621	0.3103448
EWB	LAX	1	1.366667	7.5000000
JFK	MIA	1	15.720670	18.7430168
JFK	SEA	1	14.357143	30.7500000
EWB	MIA	1	11.011236	12.1235955

Clojure

```
(-> flights
  (api/select-rows #(= (get % "carrier") "AA"))
  (api/group-by ["origin" "dest" "month"])
  (api/aggregate-columns ["arr_delay" "dep_delay"] dfn/mean)
  (api/head 6))
```

\_unnamed [6 5]:

month	origin	dest	dep_delay	arr_delay
9	LGA	DFW	-0.25575448	-8.78772379
10	LGA	DFW	4.55276382	3.50000000
1	JFK	AUS	27.60000000	25.20000000
4	JFK	AUS	-0.13333333	4.36666667
5	JFK	AUS	14.73333333	6.76666667
2	JFK	AUS	21.50000000	26.26923077

How can we return the first two rows for each month?

R

```
ans <- flights[, head(.SD, 2), by = month]
kable(head(ans))
```

month	year	day	dep_delay	arr_delay	carrier	origin	dest	air_time	distance	hour
1	2014	1	14	13	AA	JFK	LAX	359	2475	9
1	2014	1	-3	13	AA	JFK	LAX	363	2475	11
2	2014	1	-1	1	AA	JFK	LAX	358	2475	8
2	2014	1	-5	3	AA	JFK	LAX	358	2475	11
3	2014	1	-11	36	AA	JFK	LAX	375	2475	8
3	2014	1	-3	14	AA	JFK	LAX	368	2475	11

Clojure

```
(-> flights
  (api/group-by ["month"])
  (api/head 2) ;; head applied on each group
  (api/ungroup)
  (api/head 6))
```

\_unnamed [6 11]:

dep_delay	origin	air_time	hour	arr_delay	dest	distance	year	month	day	carrier
-8	LGA	113	18	-23	BNA	764	2014	4	1	MQ
-8	LGA	71	18	-11	RDU	431	2014	4	1	MQ
43	JFK	288	17	5	LAS	2248	2014	5	1	AA
-1	JFK	330	7	-38	SFO	2586	2014	5	1	AA
-9	JFK	324	8	-5	LAX	2475	2014	6	1	AA
-10	JFK	329	12	-13	LAX	2475	2014	6	1	AA

How can we concatenate columns a and b for each group in ID?

R

```
kable(DT[, .(val = c(a,b)), by = ID])
```



---

ID	val
b	1
b	2
b	3
b	7
b	8
b	9
a	4
a	5
a	10
a	11
c	6
c	12

---



---

Clojure

```
(-> DT
  (api/pivot->longer [ :a :b ] { :value-column-name :val })
  (api/drop-columns [ :$column :c ]))
```

\_\_unnamed [12 2]:

:ID	:val
b	1
b	2
b	3
a	4
a	5
c	6
b	7
b	8
b	9
a	10
a	11
c	12

What if we would like to have all the values of column a and b concatenated, but returned as a list column?

R

```
kable(DT[, .(val = list(c(a,b))), by = ID])
```

---

ID	val
b	c(1, 2, 3, 7, 8, 9)
a	c(4, 5, 10, 11)
c	c(6, 12)

---



---

Clojure

```
(-> DT
  (api/pivot->longer [ :a :b] { :value-column-name :val})
  (api/drop-columns [ :$column :c])
  (api/fold-by :ID))
```

\_\_unnamed [3 2]:

:ID	:val
a	[4 5 10 11]
b	[1 2 3 7 8 9]
c	[6 12]

## API tour

Below snippets are taken from A data.table and dplyr tour written by Atrebas (permission granted).

I keep structure and subtitles but I skip `data.table` and `dplyr` examples.

Example data

```
(def DS (api/dataset { :V1 (take 9 (cycle [1 2]))
                      :V2 (range 1 10)
                      :V3 (take 9 (cycle [0.5 1.0 1.5]))
                      :V4 (take 9 (cycle ["A" "B" "C"]))}))
```

```
(api/dataset? DS)
(class DS)
```

```
true
tech.ml.dataset.impl.dataset.Dataset
DS
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B
2	6	1.5	C
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

## Basic Operations

### Filter rows

Filter rows using indices

```
(api/select-rows DS [2 3])
```

\_\_unnamed [2 4]:

---

:V1	:V2	:V3	:V4
1	3	1.5	C
2	4	0.5	A

---

Discard rows using negative indices

In Clojure API we have separate function for that: **drop-rows**.

```
(api/drop-rows DS (range 2 7))
```

\_\_unnamed [4 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
2	8	1.0	B
1	9	1.5	C

---

Filter rows using a logical expression

```
(api/select-rows DS (comp #(> % 5) :V2))
```

\_\_unnamed [4 4]:

---

:V1	:V2	:V3	:V4
2	6	1.5	C
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

---

```
(api/select-rows DS (comp #{"A" "C"} :V4))
```

\_\_unnamed [6 4]:

---

:V1	:V2	:V3	:V4
1	1	0.5	A
1	3	1.5	C
2	4	0.5	A
2	6	1.5	C
1	7	0.5	A
1	9	1.5	C

---

Filter rows using multiple conditions

```
(api/select-rows DS #(and (= (:V1 %) 1)
                           (= (:V4 %) "A"))))
```

\_\_unnamed [2 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
1	7	0.5	A

Filter unique rows

```
(api/unique-by DS)
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B
2	6	1.5	C
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

```
(api/unique-by DS [ :V1 :V4])
```

\_\_unnamed [6 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B
2	6	1.5	C

Discard rows with missing values

```
(api/drop-missing DS)
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C

:V1	:V2	:V3	:V4
2	4	0.5	A
1	5	1.0	B
2	6	1.5	C
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

---

Other filters

```
(api/random DS 3) ;; 3 random rows
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
1	5	1.0	B
2	4	0.5	A
1	9	1.5	C

```
(api/random DS (/ (api/row-count DS) 2)) ;; fraction of random rows
```

\_\_unnamed [5 4]:

:V1	:V2	:V3	:V4
2	2	1.0	B
2	6	1.5	C
1	1	0.5	A
1	3	1.5	C
1	1	0.5	A

```
(api/by-rank DS :V1 zero?) ;; take top n entries
```

\_\_unnamed [4 4]:

:V1	:V2	:V3	:V4
2	2	1.0	B
2	4	0.5	A
2	6	1.5	C
2	8	1.0	B

---

Convenience functions

```
(api/select-rows DS (comp (partial re-matches #"^B") str :V4))
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
2	2	1.0	B
1	5	1.0	B
2	8	1.0	B

```
(api/select-rows DS (comp #(<= 3 % 5) :V2))
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B

```
(api/select-rows DS (comp #(< 3 % 5) :V2))
```

\_\_unnamed [1 4]:

:V1	:V2	:V3	:V4
2	4	0.5	A

```
(api/select-rows DS (comp #(<= 3 % 5) :V2))
```

\_\_unnamed [3 4]:

:V1	:V2	:V3	:V4
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B

Last example skipped.

## Sort rows

Sort rows by column

```
(api/order-by DS :V3)
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	4	0.5	A
1	7	0.5	A
2	2	1.0	B
1	5	1.0	B

:V1	:V2	:V3	:V4
2	8	1.0	B
1	3	1.5	C
2	6	1.5	C
1	9	1.5	C

Sort rows in decreasing order

```
(api/order-by DS :V3 :desc)
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	3	1.5	C
2	6	1.5	C
1	9	1.5	C
1	5	1.0	B
2	2	1.0	B
2	8	1.0	B
1	7	0.5	A
2	4	0.5	A
1	1	0.5	A

Sort rows based on several columns

```
(api/order-by DS [:V1 :V2] [:asc :desc])
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	9	1.5	C
1	7	0.5	A
1	5	1.0	B
1	3	1.5	C
1	1	0.5	A
2	8	1.0	B
2	6	1.5	C
2	4	0.5	A
2	2	1.0	B

## Select columns

Select one column using an index (not recommended)

```
(nth (api/columns DS :as-seq) 2) ;; as column (iterable)
```

```
#tech.ml.dataset.column<float64>[9]
```

```
:V3
```

```
[0.5000, 1.000, 1.500, 0.5000, 1.000, 1.500, 0.5000, 1.000, 1.500, ]
```

```
(api/dataset [(nth (api/columns DS :as-seq) 2)])
```

\_\_unnamed [9 1]:

<u>:V3</u>
0.5
1.0
1.5
0.5
1.0
1.5
0.5
1.0
1.5

---

Select one column using column name

```
(api/select-columns DS :V2) ;; as dataset
```

\_\_unnamed [9 1]:

<u>:V2</u>
1
2
3
4
5
6
7
8
9

```
(api/select-columns DS [:V2]) ;; as dataset
```

\_\_unnamed [9 1]:

<u>:V2</u>
1
2
3
4
5
6
7
8
9

```
(DS :V2) ;; as column (iterable)
```



```
#tech.ml.dataset.column<int64>[9]
:V2
[1, 2, 3, 4, 5, 6, 7, 8, 9, ]
```

Select several columns

```
(api/select-columns DS [ :V2 :V3 :V4])
```

\_\_unnamed [9 3]:

	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
3	3	1.5	C
4	4	0.5	A
5	5	1.0	B
6	6	1.5	C
7	7	0.5	A
8	8	1.0	B
9	9	1.5	C

Exclude columns

```
(api/select-columns DS (complement #{ :V2 :V3 :V4}))
```

\_\_unnamed [9 1]:

	:V1
1	1
2	2
1	1
2	2
1	1
2	2
1	1
2	2
1	1

```
(api/drop-columns DS [ :V2 :V3 :V4])
```

\_\_unnamed [9 1]:

	:V1
1	1
2	2
1	1
2	2
1	1
2	2
1	1

:V1
2
1

Other seletions

```
(->> (range 1 3)
      (map (comp keyword (partial format "V%d"))))
      (api/select-columns DS))
```

\_\_unnamed [9 2]:

:V1	:V2
1	1
2	2
1	3
2	4
1	5
2	6
1	7
2	8
1	9

```
(api/reorder-columns DS :V4)
```

\_\_unnamed [9 4]:

	:V4	:V1	:V2	:V3
A		1	1	0.5
B		2	2	1.0
C		1	3	1.5
A		2	4	0.5
B		1	5	1.0
C		2	6	1.5
A		1	7	0.5
B		2	8	1.0
C		1	9	1.5

```
(api/select-columns DS #(clojure.string/starts-with? (name %) "V"))
```

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1	1	0.5	A
2	2	1.0	B
1	3	1.5	C
2	4	0.5	A
1	5	1.0	B
2	6	1.5	C

:V1	:V2	:V3	:V4
1	7	0.5	A
2	8	1.0	B
1	9	1.5	C

```
(api/select-columns DS #(clojure.string/ends-with? (name %) "3"))
```

\_\_unnamed [9 1]:

:V3
0.5
1.0
1.5
0.5
1.0
1.5
0.5
1.0
1.5

```
(api/select-columns DS #"..2") ;; regex converts to string using `str` function
```

\_\_unnamed [9 1]:

:V2
1
2
3
4
5
6
7
8
9

```
(api/select-columns DS #{:V1 "X"})
```

\_\_unnamed [9 1]:

:V1
1
2
1
2
1
2
1
2
1

```
(api/select-columns DS #(not (clojure.string/starts-with? (name %) "V2")))
```

\_\_unnamed [9 3]:

:V1	:V3	:V4
1	0.5	A
2	1.0	B
1	1.5	C
2	0.5	A
1	1.0	B
2	1.5	C
1	0.5	A
2	1.0	B
1	1.5	C

## Summarise data

Summarise one column

```
(reduce + (DS :V1)) ;; using pure Clojure, as value
```

13

```
(api/aggregate-columns DS :V1 dfn/sum) ;; as dataset
```

\_\_unnamed [1 1]:

:V1
13.0

```
(api/aggregate DS {:sumV1 #(dfn/sum (% :V1))})
```

\_\_unnamed [1 1]:

:sumV1
13.0

Summarize several columns

```
(api/aggregate DS [#(dfn/sum (% :V1))
  #(dfn/standard-deviation (% :V3))])
```

\_\_unnamed [1 2]:

:summary-0	:summary-1
13.0	0.4330127

```
(api/aggregate-columns DS [:V1 :V3] [dfn/sum
  dfn/standard-deviation])
```

\_\_unnamed [1 2]:

:V1	:V3
13.0	0.4330127

Summarise several columns and assign column names

```
(api/aggregate DS {:sumv1 #(dfn/sum (% :V1))  
                  :sdv3 #(dfn/standard-deviation (% :V3))})
```

\_\_unnamed [1 2]:

:sumv1	:sdv3
13.0	0.4330127

Summarise a subset of rows

```
(-> DS  
  (api/select-rows (range 4))  
  (api/aggregate-columns :V1 dfn/sum))
```

\_\_unnamed [1 1]:

:V1
6.0

## Additional helpers

```
(-> DS  
  (api/first)  
  (api/select-columns :V3)) ;; select first row from `:V3` column
```

\_\_unnamed [1 1]:

:V3
0.5

```
(-> DS  
  (api/last)  
  (api/select-columns :V3)) ;; select last row from `:V3` column
```

\_\_unnamed [1 1]:

:V3
1.5

```
(-> DS
  (api/select-rows 4)
  (api/select-columns :V3)) ;; select forth row from `:V3` column
```

\_\_unnamed [1 1]:

<u>:V3</u>
1.0

```
(-> DS
  (api/select :V3 4)) ;; select forth row from `:V3` column
```

\_\_unnamed [1 1]:

<u>:V3</u>
1.0

```
(-> DS
  (api/unique-by :V4)
  (api/aggregate api/row-count)) ;; number of unique rows in `:V4` column, as dataset
```

\_\_unnamed [1 1]:

<u>:summary</u>
3

```
(-> DS
  (api/unique-by :V4)
  (api/row-count)) ;; number of unique rows in `:V4` column, as value
```

3

```
(-> DS
  (api/unique-by)
  (api/row-count)) ;; number of unique rows in dataset, as value
```

9

## Add/update/delete columns

Modify a column

```
(api/map-columns DS :V1 [:V1] #(dfn/pow % 2))
```

\_\_unnamed [9 4]:

<u>:V1</u>	<u>:V2</u>	<u>:V3</u>	<u>:V4</u>
1	1	0.5	A
4	2	1.0	B
1	3	1.5	C

:V1	:V2	:V3	:V4
4	4	0.5	A
1	5	1.0	B
4	6	1.5	C
1	7	0.5	A
4	8	1.0	B
1	9	1.5	C

```
(def DS (api/add-or-replace-column DS :V1 (dfn/pow (DS :V1) 2)))
```

DS

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1.0	1	0.5	A
4.0	2	1.0	B
1.0	3	1.5	C
4.0	4	0.5	A
1.0	5	1.0	B
4.0	6	1.5	C
1.0	7	0.5	A
4.0	8	1.0	B
1.0	9	1.5	C

---

Add one column

```
(api/map-columns DS :v5 [:V1] dfn/log)
```

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:v5
1.0	1	0.5	A	0.00000000
4.0	2	1.0	B	1.38629436
1.0	3	1.5	C	0.00000000
4.0	4	0.5	A	1.38629436
1.0	5	1.0	B	0.00000000
4.0	6	1.5	C	1.38629436
1.0	7	0.5	A	0.00000000
4.0	8	1.0	B	1.38629436
1.0	9	1.5	C	0.00000000

```
(def DS (api/add-or-replace-column DS :v5 (dfn/log (DS :V1))))
```

DS

\_\_unnamed [9 5]:

:V1	:V2	:V3	:V4	:v5
1.0	1	0.5	A	0.00000000

:V1	:V2	:V3	:V4	:v5
4.0	2	1.0	B	1.38629436
1.0	3	1.5	C	0.00000000
4.0	4	0.5	A	1.38629436
1.0	5	1.0	B	0.00000000
4.0	6	1.5	C	1.38629436
1.0	7	0.5	A	0.00000000
4.0	8	1.0	B	1.38629436
1.0	9	1.5	C	0.00000000

Add several columns

```
(def DS (api/add-or-replace-columns DS {:v6 (dfn/sqrt (DS :V1))
                                         :v7 "X"}))
```

DS

\_\_unnamed [9 7]:

:V1	:V2	:V3	:V4	:v5	:v6	:v7
1.0	1	0.5	A	0.00000000	1.0	X
4.0	2	1.0	B	1.38629436	2.0	X
1.0	3	1.5	C	0.00000000	1.0	X
4.0	4	0.5	A	1.38629436	2.0	X
1.0	5	1.0	B	0.00000000	1.0	X
4.0	6	1.5	C	1.38629436	2.0	X
1.0	7	0.5	A	0.00000000	1.0	X
4.0	8	1.0	B	1.38629436	2.0	X
1.0	9	1.5	C	0.00000000	1.0	X

Create one column and remove the others

```
(api/dataset {:v8 (dfn/+ (DS :V3) 1)})
```

\_\_unnamed [9 1]:

:v8
1.5
2.0
2.5
1.5
2.0
2.5
1.5
2.0
2.5

Remove one column



```
(def DS (api/drop-columns DS :v5))
```

DS

\_\_unnamed [9 6]:

:V1	:V2	:V3	:V4	:v6	:v7
1.0	1	0.5	A	1.0	X
4.0	2	1.0	B	2.0	X
1.0	3	1.5	C	1.0	X
4.0	4	0.5	A	2.0	X
1.0	5	1.0	B	1.0	X
4.0	6	1.5	C	2.0	X
1.0	7	0.5	A	1.0	X
4.0	8	1.0	B	2.0	X
1.0	9	1.5	C	1.0	X

---

Remove several columns

```
(def DS (api/drop-columns DS [:v6 :v7]))
```

DS

\_\_unnamed [9 4]:

:V1	:V2	:V3	:V4
1.0	1	0.5	A
4.0	2	1.0	B
1.0	3	1.5	C
4.0	4	0.5	A
1.0	5	1.0	B
4.0	6	1.5	C
1.0	7	0.5	A
4.0	8	1.0	B
1.0	9	1.5	C

---

Remove columns using a vector of colnames

We use set here.

```
(def DS (api/select-columns DS (complement #{:V3})))
```

DS

\_\_unnamed [9 3]:

:V1	:V2	:V4
1.0	1	A
4.0	2	B
1.0	3	C
4.0	4	A
1.0	5	B

:V1	:V2	:V4
4.0	6	C
1.0	7	A
4.0	8	B
1.0	9	C

---

Replace values for rows matching a condition

```
(def DS (api/map-columns DS :V2 [:V2] #(if (< % 4.0) 0.0 %)))
```

DS

\_\_unnamed [9 3]:

:V1	:V2	:V4
1.0	0	A
4.0	0	B
1.0	0	C
4.0	4	A
1.0	5	B
4.0	6	C
1.0	7	A
4.0	8	B
1.0	9	C

**by**

By group

```
(-> DS
  (api/group-by [:V4])
  (api/aggregate {:sumV2 #(dfn/sum (% :V2))}))
```

\_\_unnamed [3 2]:

:V4	:sumV2
B	13.0
C	15.0
A	11.0

---

By several groups

```
(-> DS
  (api/group-by [:V4 :V1])
  (api/aggregate {:sumV2 #(dfn/sum (% :V2))}))
```

\_\_unnamed [6 3]:

:V4	:V1	:sumV2
A	4.000	4.0

---

:V4	:V1	:sumV2
A	1.000	7.0
B	1.000	5.0
B	4.000	8.0
C	4.000	6.0
C	1.000	9.0

---

Calling function in by

```
(-> DS
  (api/group-by (fn [row]
                  (clojure.string/lower-case (:V4 row))))
  (api/aggregate {:sumV1 #(dfn/sum (% :V1))}))
```

\_\_unnamed [3 2]:

---

:\$group-name	:sumV1
a	6.0
b	9.0
c	6.0

---

Assigning column name in by

```
(-> DS
  (api/group-by (fn [row]
                  { :abc (clojure.string/lower-case (:V4 row)) }))
  (api/aggregate {:sumV1 #(dfn/sum (% :V1))}))
```

\_\_unnamed [3 2]:

---

:abc	:sumV1
a	6.0
b	9.0
c	6.0

---

```
(-> DS
  (api/group-by (fn [row]
                  (clojure.string/lower-case (:V4 row))))
  (api/aggregate {:sumV1 #(dfn/sum (% :V1))} {:add-group-as-column :abc}))
```

\_\_unnamed [3 2]:

---

:abc	:sumV1
a	6.0
b	9.0
c	6.0

---

Using a condition in by

```
(-> DS
  (api/group-by #(= (:V4 %) "A"))
  (api/aggregate #(dfn/sum (% :V1))))
```

\_\_unnamed [2 2]:

---

:\$group-name	:summary
false	15.0
true	6.0

---

By on a subset of rows

```
(-> DS
  (api/select-rows (range 5))
  (api/group-by :V4)
  (api/aggregate {:sumV1 #(dfn/sum (% :V1))}))
```

\_\_unnamed [3 2]:

---

:\$group-name	:sumV1
A	5.0
B	5.0
C	1.0

---

Count number of observations for each group

```
(-> DS
  (api/group-by :V4)
  (api/aggregate api/row-count))
```

\_\_unnamed [3 2]:

---

:\$group-name	:summary
A	3
B	3
C	3

---

Add a column with number of observations for each group

```
(-> DS
  (api/group-by [ :V1])
  (api/add-or-replace-column :n api/row-count)
  (api/ungroup))
```

\_\_unnamed [9 4]:

:V1	:V2	:V4	:n
4.0	0	B	4
4.0	4	A	4
4.0	6	C	4
4.0	8	B	4
1.0	0	A	5
1.0	0	C	5
1.0	5	B	5
1.0	7	A	5
1.0	9	C	5

---

Retrieve the first/last/nth observation for each group

```
(-> DS
  (api/group-by [ :V4 ])
  (api/aggregate-columns :V2 first))
```

\_\_unnamed [3 2]:

:V4	:V2
B	0
C	0
A	0

```
(-> DS
  (api/group-by [ :V4 ])
  (api/aggregate-columns :V2 last))
```

\_\_unnamed [3 2]:

:V4	:V2
B	8
C	9
A	7

```
(-> DS
  (api/group-by [ :V4 ])
  (api/aggregate-columns :V2 #(nth % 1)))
```

\_\_unnamed [3 2]:

:V4	:V2
B	5
C	6
A	4

Going further

## Advanced columns manipulation

Summarise all the columns

```
;; custom max function which works on every type  
(api/aggregate-columns DS :all (fn [col] (first (sort #(compare %2 %1) col))))
```

\_\_unnamed [1 3]:

---

:V1	:V2	:V4
4.0	9	C

---

Summarise several columns

```
(api/aggregate-columns DS [:V1 :V2] dfn/mean)
```

\_\_unnamed [1 2]:

---

:V1	:V2
2.33333333	4.33333333

---

Summarise several columns by group

```
(-> DS  
  (api/group-by [:V4])  
  (api/aggregate-columns [:V1 :V2] dfn/mean))
```

\_\_unnamed [3 3]:

---

	:V4	:V1	:V2
B		3.0	4.33333333
C		2.0	5.00000000
A		2.0	3.66666667

---

Summarise with more than one function by group

```
(-> DS  
  (api/group-by [:V4])  
  (api/aggregate-columns [:V1 :V2] (fn [col]  
                                     {:sum (dfn/sum col)  
                                      :mean (dfn/mean col)}})))
```

\_\_unnamed [3 5]:

---

	:V4	:V1-sum	:V1-mean	:V2-sum	:V2-mean
B		9.0	3.0	13.0	4.33333333
C		6.0	2.0	15.0	5.00000000
A		6.0	2.0	11.0	3.66666667

---

Summarise using a condition

```
(-> DS
  (api/select-columns :type/numerical)
  (api/aggregate-columns :all dfn/mean))
```

\_\_unnamed [1 2]:

:V1	:V2
2.33333333	4.33333333

Modify all the columns

```
(api/update-columns DS :all reverse)
```

\_\_unnamed [9 3]:

:V1	:V2	:V4
1.000	9	C
4.000	8	B
1.000	7	A
4.000	6	C
1.000	5	B
4.000	4	A
1.000	0	C
4.000	0	B
1.000	0	A

Modify several columns (dropping the others)

```
(-> DS
  (api/select-columns [ :V1 :V2 ])
  (api/update-columns :all dfn/sqrt))
```

\_\_unnamed [9 2]:

:V1	:V2
1.0	0.00000000
2.0	0.00000000
1.0	0.00000000
2.0	2.00000000
1.0	2.23606798
2.0	2.44948974
1.0	2.64575131
2.0	2.82842712
1.0	3.00000000

```
(-> DS
  (api/select-columns (complement #{ :V4 })))
```

```
(api/update-columns :all dfn/exp))
```

\_\_unnamed [9 2]:

:V1	:V2
2.71828183	1.00000000
54.59815003	1.00000000
2.71828183	1.00000000
54.59815003	54.59815003
2.71828183	148.41315910
54.59815003	403.42879349
2.71828183	1096.63315843
54.59815003	2980.95798704
2.71828183	8103.08392758

Modify several columns (keeping the others)

```
(def DS (api/update-columns DS [ :V1 :V2] dfn/sqrt))
```

DS

\_\_unnamed [9 3]:

:V1	:V2	:V4
1.0	0.00000000	A
2.0	0.00000000	B
1.0	0.00000000	C
2.0	2.00000000	A
1.0	2.23606798	B
2.0	2.44948974	C
1.0	2.64575131	A
2.0	2.82842712	B
1.0	3.00000000	C

```
(def DS (api/update-columns DS (complement #{:V4}) #(dfn/pow % 2)))
```

DS

\_\_unnamed [9 3]:

:V1	:V2	:V4
1.0	0.0	A
4.0	0.0	B
1.0	0.0	C
4.0	4.0	A
1.0	5.0	B
4.0	6.0	C
1.0	7.0	A
4.0	8.0	B
1.0	9.0	C



---

Modify columns using a condition (dropping the others)

```
(-> DS
  (api/select-columns :type/numerical)
  (api/update-columns :all #(dfn/- % 1)))
```

\_\_unnamed [9 2]:

:V1	:V2
0.0	-1.0
3.0	-1.0
0.0	-1.0
3.0	3.0
0.0	4.0
3.0	5.0
0.0	6.0
3.0	7.0
0.0	8.0

---

Modify columns using a condition (keeping the others)

```
(def DS (api/convert-types DS :type/numerical :int32))
```

DS

\_\_unnamed [9 3]:

:V1	:V2	:V4
1	0	A
4	0	B
1	0	C
4	4	A
1	5	B
4	5	C
1	7	A
4	8	B
1	9	C

---

Use a complex expression

```
(-> DS
  (api/group-by [:V4])
  (api/head 2)
  (api/add-or-replace-column :V2 "X")
  (api/ungroup))
```

\_\_unnamed [6 3]:

:V1	:V2	:V4
4	X	B

:V1	:V2	:V4
1	X	B
1	X	C
4	X	C
1	X	A
4	X	A

Use multiple expressions

```
(api/dataset (let [x (dfn/+ (DS :V1) (dfn/sum (DS :V2)))]
  (println (seq (DS :V1)))
  (println (api/info (api/select-columns DS :V1)))
  {:A (range 1 (inc (api/row-count DS)))
   :B x}))
```

(1 4 1 4 1 4 1 4 1) \_\_unnamed: descriptive-stats [1 9]:

:col-name	:datatype	:n-valid	:n-missing	:min	:mean	:max	:standard-deviation	:skew
:V1	:int32	9	0	1.0	2.33333333	4.0	1.58113883	0.27105237

\_\_unnamed [9 2]:

:A	:B
1	39.0
2	42.0
3	39.0
4	42.0
5	39.0
6	42.0
7	39.0
8	42.0
9	39.0

## Chain expressions

Expression chaining using >

```
(-> DS
  (api/group-by [:V4])
  (api/aggregate {:V1sum #(dfn/sum (% :V1))})
  (api/select-rows #(> (:V1sum %) 5) ))
```

\_\_unnamed [3 2]:

:V4	:V1sum
B	9.0
C	6.0
A	6.0

```
(-> DS
  (api/group-by [:V4])
  (api/aggregate {:V1sum #(dfn/sum (% :V1))})
  (api/order-by :V1sum :desc))
```

\_\_unnamed [3 2]:

:V4	:V1sum
B	9.0
C	6.0
A	6.0

## Indexing and Keys

Set the key/index (order)

```
(def DS (api/order-by DS :V4))
```

DS

\_\_unnamed [9 3]:

:V1	:V2	:V4
1	0	A
4	4	A
1	7	A
4	0	B
1	5	B
4	8	B
1	0	C
4	5	C
1	9	C

Select the matching rows

```
(api/select-rows DS #(= (:V4 %) "A"))
```

\_\_unnamed [3 3]:

:V1	:V2	:V4
1	0	A
4	4	A
1	7	A

```
(api/select-rows DS (comp #{"A" "C"} :V4))
```

\_\_unnamed [6 3]:

:V1	:V2	:V4
1	0	A
4	4	A

---

:V1	:V2	:V4
1	7	A
1	0	C
4	5	C
1	9	C

---

Select the first matching row

```
(-> DS
  (api/select-rows #(<= (:V4 %) "B"))
  (api/first))
```

\_\_unnamed [1 3]:

---

:V1	:V2	:V4
4	0	B

---

```
(-> DS
  (api/unique-by :V4)
  (api/select-rows (comp #{"B" "C"} :V4)))
```

\_\_unnamed [2 3]:

---

:V1	:V2	:V4
4	0	B
1	0	C

---

Select the last matching row

```
(-> DS
  (api/select-rows #(<= (:V4 %) "A"))
  (api/last))
```

\_\_unnamed [1 3]:

---

:V1	:V2	:V4
1	7	A

---

Nomatch argument

```
(api/select-rows DS (comp #{"A" "D"} :V4))
```

\_\_unnamed [3 3]:

---

:V1	:V2	:V4
1	0	A
4	4	A

---

:V1	:V2	:V4
1	7	A

Apply a function on the matching rows

```
(-> DS
  (api/select-rows (comp #{"A" "C"} :V4))
  (api/aggregate-columns :V1 (fn [col]
                                { :sum (dfn/sum col) }))))
```

\_\_unnamed [1 1]:

:V1-sum
12.0

Modify values for matching rows

```
(def DS (-> DS
  (api/map-columns :V1 [:V1 :V4] #(if (= %2 "A") 0 %1))
  (api/order-by :V4)))
```

DS

\_\_unnamed [9 3]:

:V1	:V2	:V4
0	0	A
0	4	A
0	7	A
4	0	B
1	5	B
4	8	B
1	0	C
4	5	C
1	9	C

Use keys in by

```
(-> DS
  (api/select-rows (comp (complement #{"B"}) :V4))
  (api/group-by [:V4])
  (api/aggregate-columns :V1 dfn/sum))
```

\_\_unnamed [2 2]:

:V4	:V1
C	6.0
A	0.0

---

Set keys/indices for multiple columns (ordered)

```
(api/order-by DS [ :V4 :V1])
```

\_\_unnamed [9 3]:

:V1	:V2	:V4
0	0	A
0	4	A
0	7	A
1	5	B
4	0	B
4	8	B
1	0	C
1	9	C
4	5	C

---

Subset using multiple keys/indices

```
(-> DS
  (api/select-rows #(and (= (:V1 %) 1)
                          (= (:V4 %) "C"))))
```

\_\_unnamed [2 3]:

:V1	:V2	:V4
1	0	C
1	9	C

```
(-> DS
  (api/select-rows #(and (= (:V1 %) 1)
                          (#{ "B" "C" } (:V4 %)))))
```

\_\_unnamed [3 3]:

:V1	:V2	:V4
1	5	B
1	0	C
1	9	C

```
(-> DS
  (api/select-rows #(and (= (:V1 %) 1)
                          (#{ "B" "C" } (:V4 %))) { :result-type :as-indexes}))
```

(4 6 8)

**set\*() modifications**

Replace values

There is no mutating operations `tech.ml.dataset` or easy way to set value.

```
(def DS (api/update-columns DS :V2 #(map-indexed (fn [idx v]
                                                    (if (zero? idx) 3 v)) %)))
```

DS

\_\_unnamed [9 3]:

---

:V1	:V2	:V4
0	3	A
0	4	A
0	7	A
4	0	B
1	5	B
4	8	B
1	0	C
4	5	C
1	9	C

---

Reorder rows

```
(def DS (api/order-by DS [:V4 :V1] [:asc :desc]))
```

DS

\_\_unnamed [9 3]:

---

:V1	:V2	:V4
0	3	A
0	4	A
0	7	A
4	0	B
4	8	B
1	5	B
4	5	C
1	0	C
1	9	C

---

Modify colnames

```
(def DS (api/rename-columns DS {:V2 "v2"}))
```

DS

\_\_unnamed [9 3]:

---

:V1	v2	:V4
0	3	A
0	4	A
0	7	A
4	0	B

:V1	v2	:V4
4	8	B
1	5	B
4	5	C
1	0	C
1	9	C

```
(def DS (api/rename-columns DS {"v2" :V2})) ;; revert back
```

Reorder columns

```
(def DS (api/reorder-columns DS :V4 :V1 :V2))
```

DS

\_\_unnamed [9 3]:

:V4	:V1	:V2
A	0	3
A	0	4
A	0	7
B	4	0
B	4	8
B	1	5
C	4	5
C	1	0
C	1	9

## Advanced use of by

Select first/last/... row by group

```
(-> DS
  (api/group-by :V4)
  (api/first)
  (api/ungroup))
```

\_\_unnamed [3 3]:

:V4	:V1	:V2
A	0	3
B	4	0
C	4	5

```
(-> DS
  (api/group-by :V4)
  (api/select-rows [0 2])
  (api/ungroup))
```

\_\_unnamed [6 3]:



:V4	:V1	:V2
A	0	3
A	0	7
B	4	0
B	1	5
C	4	5
C	1	9

```
(-> DS
  (api/group-by :V4)
  (api/tail 2)
  (api/ungroup))
```

\_\_unnamed [6 3]:

:V4	:V1	:V2
A	0	4
A	0	7
B	4	8
B	1	5
C	1	0
C	1	9

---

Select rows using a nested query

```
(-> DS
  (api/group-by :V4)
  (api/order-by :V2)
  (api/first)
  (api/ungroup))
```

\_\_unnamed [3 3]:

:V4	:V1	:V2
A	0	3
B	4	0
C	1	0

Add a group counter column

```
(-> DS
  (api/group-by [:V4 :V1])
  (api/ungroup {:add-group-id-as-column :Grp}))
```

\_\_unnamed [9 4]:

:Grp	:V4	:V1	:V2
0	A	0	3
0	A	0	4

:Grp	:V4	:V1	:V2
0	A	0	7
1	B	1	5
2	C	1	0
2	C	1	9
3	B	4	0
3	B	4	8
4	C	4	5

Get row number of first (and last) observation by group

```
(-> DS
  (api/add-or-replace-column :row-id (range))
  (api/select-columns [ :V4 :row-id])
  (api/group-by :V4)
  (api/ungroup))
```

\_\_unnamed [9 2]:

:V4	:row-id
A	0
A	1
A	2
B	3
B	4
B	5
C	6
C	7
C	8

```
(-> DS
  (api/add-or-replace-column :row-id (range))
  (api/select-columns [ :V4 :row-id])
  (api/group-by :V4)
  (api/first)
  (api/ungroup))
```

\_\_unnamed [3 2]:

:V4	:row-id
A	0
B	3
C	6

```
(-> DS
  (api/add-or-replace-column :row-id (range))
  (api/select-columns [ :V4 :row-id])
  (api/group-by :V4)
  (api/select-rows [0 2]))
```

```
(api/ungroup))
```

\_\_unnamed [6 2]:

:V4	:row-id
A	0
A	2
B	3
B	5
C	6
C	8

---

Handle list-columns by group

```
(-> DS  
  (api/select-columns [ :V1 :V4])  
  (api/fold-by :V4))
```

\_\_unnamed [3 2]:

:V4	:V1
B	[4 4 1]
C	[4 1 1]
A	[0 0 0]

```
(-> DS  
  (api/group-by :V4)  
  (api/unmark-group))
```

\_\_unnamed [3 3]:

:name	:group-id	:data
A	0	Group: A [3 3]:
B	1	Group: B [3 3]:
C	2	Group: C [3 3]:

---

Grouping sets (multiple by at once)

Not available.

## Miscellaneous

### Read / Write data

Write data to a csv file

```
(api/write-csv! DS "DF.csv")
```

nil

---

Write data to a tab-delimited file

```
(api/write-csv! DS "DF.txt" {:separator \tab})
```

nil

or

```
(api/write-csv! DS "DF.tsv")
```

nil

---

Read a csv / tab-delimited file

```
(api/dataset "DF.csv" {:key-fn keyword})
```

DF.csv [9 3]:

:V4	:V1	:V2
A	0	3
A	0	4
A	0	7
B	4	0
B	4	8
B	1	5
C	4	5
C	1	0
C	1	9

```
(api/dataset "DF.txt" {:key-fn keyword})
```

DF.txt [9 3]:

:V4	:V1	:V2
A	0	3
A	0	4
A	0	7
B	4	0
B	4	8
B	1	5
C	4	5
C	1	0
C	1	9

```
(api/dataset "DF.tsv" {:key-fn keyword})
```

DF.tsv [9 3]:

:V4	:V1	:V2
A	0	3

:V4	:V1	:V2
A	0	4
A	0	7
B	4	0
B	4	8
B	1	5
C	4	5
C	1	0
C	1	9

---

Read a csv file selecting / dropping columns

```
(api/dataset "DF.csv" {:key-fn keyword
                        :column-whitelist ["V1" "V4"]})
```

DF.csv [9 2]:

:V1	:V4
0	A
0	A
0	A
4	B
4	B
1	B
4	C
1	C
1	C

```
(api/dataset "DF.csv" {:key-fn keyword
                        :column-blacklist ["V4"]})
```

DF.csv [9 2]:

:V1	:V2
0	3
0	4
0	7
4	0
4	8
1	5
4	5
1	0
1	9

---

Read and rbind several files

```
(apply api/concat (map api/dataset ["DF.csv" "DF.csv"])))
```

null [18 3]:

V4	V1	V2
A	0	3
A	0	4
A	0	7
B	4	0
B	4	8
B	1	5
C	4	5
C	1	0
C	1	9
A	0	3
A	0	4
A	0	7
B	4	0
B	4	8
B	1	5
C	4	5
C	1	0
C	1	9

## Reshape data

Melt data (from wide to long)

```
(def mDS (api/pivot->longer DS [:V1 :V2] {:target-columns :variable
                                          :value-column-name :value}))
```

mDS

\_\_unnamed [18 3]:

:V4	:variable	:value
A	:V1	0
A	:V1	0
A	:V1	0
B	:V1	4
B	:V1	4
B	:V1	1
C	:V1	4
C	:V1	1
C	:V1	1
A	:V2	3
A	:V2	4
A	:V2	7
B	:V2	0
B	:V2	8
B	:V2	5
C	:V2	5
C	:V2	0
C	:V2	9

---

Cast data (from long to wide)

```
(-> mDS
  (api/pivot->wider :variable :value {:fold-fn vec})
  (api/update-columns [V1 V2] (partial map count)))
```

\_\_unnamed [3 3]:

	V4	V1	V2
C	3	3	
B	3	3	
A	3	3	

```
(-> mDS
  (api/pivot->wider :variable :value {:fold-fn vec})
  (api/update-columns [V1 V2] (partial map dfn/sum)))
```

\_\_unnamed [3 3]:

	V4	V1	V2
C	6.000	14.00	
B	9.000	13.00	
A	0.000	14.00	

```
(-> mDS
  (api/map-columns :value #(> % 5))
  (api/pivot->wider :value :variable {:fold-fn vec})
  (api/update-columns [true false] (partial map #(if (sequential? %) (count %) 1))))
```

\_\_unnamed [3 3]:

	V4	true	false
A	1	5	
B	1	5	
C	1	5	

Split

```
(api/group-by DS V4 {:result-type :as-map})
```

{“A” Group: A [3 3]:

	V4	V1	V2
A	0	3	
A	0	4	
A	0	7	

, “B” Group: B [3 3]:

:V4	:V1	:V2
B	4	0
B	4	8
B	1	5

, “C” Group: C [3 3]:

:V4	:V1	:V2
C	4	5
C	1	0
C	1	9

}

Split and transpose a vector/column

```
(-> { :a ["A:a" "B:b" "C:c"]}
  (api/dataset)
  (api/separate-column :a [:V1 :V2] ":"))
```

\_\_unnamed [3 2]:

:V1	:V2
A	a
B	b
C	c

## Other

Skipped

## Join/Bind data sets

```
(def x (api/dataset {"Id" ["A" "B" "C" "C"]
                     "X1" [1 3 5 7]
                     "XY" ["x2" "x4" "x6" "x8"]}))
(def y (api/dataset {"Id" ["A" "B" "B" "D"]
                     "Y1" [1 3 5 7]
                     "XY" ["y1" "y3" "y5" "y7"]}))
```

x y

\_\_unnamed [4 3]:

Id	X1	XY
A	1	x2
B	3	x4
C	5	x6
C	7	x8



\_\_unnamed [4 3]:

Id	Y1	XY
A	1	y1
B	3	y3
B	5	y5
D	7	y7

## Join

Join matching rows from y to x

```
(api/left-join x y "Id")
```

left-outer-join [5 6]:

Id	X1	XY	right.Id	Y1	right.XY
A	1	x2	A	1	y1
B	3	x4	B	3	y3
B	3	x4	B	5	y5
C	5	x6			
C	7	x8			

Join matching rows from x to y

```
(api/right-join x y "Id")
```

right-outer-join [4 6]:

Id	X1	XY	right.Id	Y1	right.XY
A	1	x2	A	1	y1
B	3	x4	B	3	y3
B	3	x4	B	5	y5
			D	7	y7

Join matching rows from both x and y

```
(api/inner-join x y "Id")
```

inner-join [3 5]:

Id	X1	XY	Y1	right.XY
A	1	x2	1	y1
B	3	x4	3	y3
B	3	x4	5	y5

Join keeping all the rows

```
(api/full-join x y "Id")
```

full-join [6 6]:

Id	X1	XY	right.Id	Y1	right.XY
A	1	x2	A	1	y1
B	3	x4	B	3	y3
B	3	x4	B	5	y5
C	5	x6			
C	7	x8			
			D	7	y7

Return rows from x matching y

```
(api/semi-join x y "Id")
```

semi-join [2 3]:

Id	X1	XY
A	1	x2
B	3	x4

Return rows from x not matching y

```
(api/anti-join x y "Id")
```

anti-join [2 3]:

Id	X1	XY
C	5	x6
C	7	x8

## More joins

Select columns while joining

```
(api/right-join (api/select-columns x ["Id" "X1"])  
  (api/select-columns y ["Id" "XY"])  
  "Id")
```

right-outer-join [4 4]:

Id	X1	right.Id	XY
A	1	A	y1
B	3	B	y3
B	3	B	y5
		D	y7

```
(api/right-join (api/select-columns x ["Id" "XY"])
  (api/select-columns y ["Id" "XY"])
  "Id")
```

right-outer-join [4 4]:

Id	XY	right.Id	right.XY
A	x2	A	y1
B	x4	B	y3
B	x4	B	y5
		D	y7

Aggregate columns while joining

```
(-> y
  (api/group-by ["Id"])
  (api/aggregate {"sumY1" #(dfn/sum (% "Y1"))})
  (api/right-join x "Id")
  (api/add-or-replace-column "X1Y1" (fn [ds] (dfn/* (ds "sumY1")
                                                    (ds "X1"))))
  (api/select-columns ["right.Id" "X1Y1"]))
```

right-outer-join [4 2]:

right.Id	X1Y1
A	1.0
B	24.0
C	NaN
C	NaN

Update columns while joining

```
(-> x
  (api/select-columns ["Id" "X1"])
  (api/map-columns "SqX1" "X1" (fn [x] (* x x)))
  (api/right-join y "Id")
  (api/drop-columns ["X1" "Id"]))
```

right-outer-join [4 4]:

SqX1	right.Id	Y1	XY
1	A	1	y1
9	B	3	y3
9	B	5	y5
	D	7	y7

Adds a list column with rows from y matching x (nest-join)

```
(-> (api/left-join x y "Id")
  (api/drop-columns ["right.Id"]))
```

```
(api/fold-by (api/column-names x)))
```

\_\_unnamed [4 5]:

XY	X1	Id	Y1	right.XY
x4	3	B	[3 5]	["y3" "y5"]
x6	5	C	[]	[]
x8	7	C	[]	[]
x2	1	A	[1]	["y1"]

Some joins are skipped

Cross join

```
(def cjds (api/dataset { :V1 [[2 1 1]]
                        :V2 [[3 2]]}))
```

cjds

\_\_unnamed [1 2]:

:V1	:V2
[2 1 1]	[3 2]

```
(reduce #(api/unroll %1 %2) cjds (api/column-names cjds))
```

\_\_unnamed [6 2]:

:V1	:V2
2	3
2	2
1	3
1	2
1	3
1	2

```
(-> (reduce #(api/unroll %1 %2) cjds (api/column-names cjds))
    (api/unique-by))
```

\_\_unnamed [4 2]:

:V1	:V2
2	3
2	2
1	3
1	2

## Bind

```
(def x (api/dataset {:V1 [1 2 3]}))  
(def y (api/dataset {:V1 [4 5 6]}))  
(def z (api/dataset {:V1 [7 8 9]  
                     :V2 [0 0 0]}))
```

x y z

\_\_unnamed [3 1]:

:V1
1
2
3

\_\_unnamed [3 1]:

:V1
4
5
6

\_\_unnamed [3 2]:

:V1	:V2
7	0
8	0
9	0

---

Bind rows

```
(api/bind x y)
```

null [6 1]:

:V1
1
2
3
4
5
6

```
(api/bind x z)
```

null [6 2]:

:V1	:V2
1	
2	
3	
7	0
8	0
9	0

Bind rows using a list

```
(->> [x y]
      (map-indexed #(api/add-or-replace-column %2 :id (repeat %1)))
      (apply api/bind))
```

null [6 2]:

:V1	:id
1	0
2	0
3	0
4	1
5	1
6	1

Bind columns

```
(api/append x y)
```

\_\_unnamed [3 2]:

:V1	:V1
1	4
2	5
3	6

## Set operations

```
(def x (api/dataset { :V1 [1 2 2 3 3]}))
(def y (api/dataset { :V1 [2 2 3 4 4]}))
```

x y

\_\_unnamed [5 1]:

:V1
1
2
2
3

$$\frac{:V1}{3}$$

\_\_unnamed [5 1]:

$$\frac{:V1}{2}$$

$$\frac{2}{3}$$

$$\frac{4}{4}$$

Intersection

(api/intersect x y)

intersection [2 1]:

$$\frac{:V1}{2}$$

$$\frac{3}{3}$$

Difference

(api/difference x y)

difference [1 1]:

$$\frac{:V1}{1}$$

Union

(api/union x y)

union [4 1]:

$$\frac{:V1}{1}$$

$$\frac{2}{3}$$

$$\frac{4}{4}$$

(api/concat x y)

null [10 1]:

<u>:V1</u>
1
2
2
3
3
2
2
3
4
4

---

Equality not implemented