

IFH Paris

PageSpeed Insights — Performance Action Plan

Source: pagespeed.web.dev · URL: <https://ifh-paris.com/fr> · Report: 17 Sep 2026 · Mobile + Desktop

Metric	Mobile	Desktop	Status
Performance (lab)	52	62	Needs improvement
Accessibility	86	86	Needs improvement
Best Practices	77	77	Needs improvement
SEO	92	92	Good
CWV field (this URL)	Failed — LCP 2.6s	Passed — LCP 1.8s	Mobile fail
Lab FCP / LCP	13.2s / 25.8s	0.7s / 6.0s	Images + blocking

Lab vs field: Real users on mobile are close to passing (LCP 2.6s vs 2.5s target). Lab looks much worse under Slow 4G because of huge image/JS payloads. Fix images, LCP discovery, and render-blocking assets first — that moves both scores.

1. Biggest bottlenecks (from PSI)

Issue	Impact	Priority
Improve image delivery	~1.3 MB mobile / ~2.8 MB desktop	P0 Critical
Render-blocking requests	~2.5 s mobile / ~0.4 s desktop	P0 Critical
Reduce unused JavaScript	~2.8 MB unused JS	P0 Critical
Enormous network payload	~17–19 MB total page weight	P0 Critical
Efficient cache lifetimes	~380–570 KiB	P1 High
LCP request discovery	Hero discovered late	P1 High
JS execution / main-thread	JS 1.6–2.5s · main 2.9–3.9s	P1 High
Alt text, contrast, landmarks	A11y 86 · SEO alt fail	P2 Medium

2. Actionable items (do in this order)

P0 — Critical (biggest LCP / weight wins)

P0

1. Compress & resize images (hero first)

Why: Image delivery is the #1 opportunity. The homepage hero is the LCP element.

How:

- Export hero at real display sizes (mobile ~800–1080px, desktop ~1600–1920px), not full camera resolution.
- Convert to WebP/AVIF via Webflow responsive images, or compress with TinyPNG/Tinify before upload.
- Replace oversized partner logos / CMS images; prefer SVG for logos when possible.
- Lazy-load below-the-fold images; keep the hero eager (first paint critical).
- Target: homepage mobile payload under ~3–4 MB (currently ~17–19 MB).

Owner: Design + Webflow

P0

2. Fix LCP request discovery for the hero

Why: PSI flags late discovery of the LCP image — the browser finds the hero too late.

How:

- Keep the LCP image in the initial HTML (not injected later by JS/slider).
- Add Head preload for the hero image (as=image, with imagesrcset/imagesizes when possible).
- Prefer a real img with srcset over CSS background-image for the hero.
- Do not hide/delay the hero behind Webflow interactions.
- Reduce preconnects (warning: more than 4). Keep only critical origins.

Owner: Webflow

P0

3. Cut render-blocking CSS/JS

Why: Render-blocking requests cost ~2.5s on mobile lab and delay FCP/LCP.

How:

- Keep Head lean: only critical CSS/preload; scripts in Footer.
- Defer third parties (Axeptio, GTM, widgets) until after first paint / consent.
- Avoid duplicate CDN CSS/JS (intl-tel-input already cleaned).
- Do not let analytics block the hero.

Owner: Dev / Custom code

P0

4. Reduce unused JavaScript (~2.8 MB)

Why: Unused JS dominates payload and main-thread work.

How:

- Audit GTM: remove unused tags; delay non-essential tags.
- Load Splide / intl-tel / Finsweet only on pages that need them (in progress).
- Consolidate language scripts; avoid redundant Weglot + custom overlaps.
- Remove unused homepage IX2 / libraries above the fold.
- Use Chrome Coverage + PSI unused-JS detail to kill top offenders.

Owner: Marketing ops + Dev

P1 — High (CWV & caching)

P1

5. Efficient cache lifetimes

Why: PSI estimates ~380–570 KiB from longer cache on static assets.

How:

- On ifh-code.pages.dev: longer Cache-Control for CSS/JS (or version with ?v= on updates).
- Prefer Webflow CDN assets (already cached); avoid needless re-uploads.
- Long-cache any self-hosted static files on custom domains.

Owner: Cloudflare / Dev

P1

6. Fonts: faster text paint

Why: Field FCP is still orange on mobile (2.1s). Easy win with font-display.

How:

- Ensure Jost uses font-display: swap.
- Preload only the primary above-the-fold weight.
- Drop unused font weights from the WebFont load list.

Owner: Webflow

P1

7. Explicit image width & height

Why: Missing dimensions add layout work (CLS risk even if CLS is currently good).

How:

- Set width/height on key images in Webflow, or aspect-ratio on wrappers.
- Prioritize logos, cards, and CMS thumbnails.

Owner: Webflow

P1

8. Homepage JS hygiene

Why: Minimize main-thread work (2.9–3.9s) and long tasks (9–18).

How:

- Defer non-critical UI scripts until DOMContentLoaded.
- Limit MutationObservers to form pages only.
- Do not init Splide on pages without those sliders.
- Use lite YouTube facades instead of full iframes on load.

Owner: Dev

P2 — Accessibility, SEO & best practices

P2

9. Add missing alt text & link names

Why: Missing alts and unnamed links hurt Accessibility (86) and SEO.

How:

- Audit homepage + templates; add descriptive FR/EN alts.
- Decorative images: empty alt.
- Icon-only links need aria-label or visible text.

Owner: Content + Webflow

P2

10. Fix contrast issues**Why:** Insufficient contrast flagged under Accessibility.**How:**

- Check gold (#B39059) on light backgrounds and light text on hero overlays.
- Increase overlay opacity or text weight where WCAG AA fails.
- Re-test with axe / Lighthouse Accessibility.

Owner: Design

P2

11. Main landmark + structure**Why:** Missing main landmark; agent accessibility tree not well-formed.**How:**

- Set primary content wrapper tag to main in Webflow.
- One h1 per page; fix heading order on templates.
- Use nav and footer landmarks correctly.

Owner: Webflow

P2

12. Best practices / privacy cleanup**Why:** Best Practices 77 — third-party cookies, console Issues.**How:**

- Load marketing tags only after Axeptio consent.
- Fix Chrome Issues panel errors (cookies, deprecated APIs).
- Security headers (CSP/HSTS) via Cloudflare later — after performance wins.

Owner: Dev / Analytics

3. Webflow homepage checklist

- Replace hero with compressed WebP at correct sizes; confirm it is LCP in PSI.
- Add hero image preload in Page Settings → Custom Code → Head.
- Disable unused homepage animations that delay first paint.
- Lazy-load all below-fold images and background videos.
- Keep Head critical-only; heavy scripts in Footer (Cloudflare assets).
- Publish staging → re-run PSI mobile → then production.

4. Success targets (2–4 weeks)

KPI	Current	Target
Mobile lab Performance	52	≥ 70
Desktop lab Performance	62	≥ 80
Field LCP (mobile URL)	2.6 s	≤ 2.5 s (pass CWV)
Field FCP (mobile URL)	2.1 s	≤ 1.8 s
Homepage weight (mobile)	~17–19 MB	< 4 MB
Accessibility	86	≥ 90

5. Suggested sprint plan

Sprint A (this week) — Images + LCP preload + cut homepage third-party/JS waste.

Sprint B — GTM audit, defer non-critical JS, fonts, Cloudflare cache headers.

Sprint C — Accessibility (alts, contrast, main landmark), re-test PSI, publish production.

Report: https://pagespeed.web.dev/analysis/https-ifh-paris-com-fr/wqzlo2tyzc?form_factor=mobile · IFH performance workstream · Sep 2026