

# Basic Operators in Oracle SQL

## 1. Arithmetic Operators

These operators perform mathematical operations on numerical values.

Operator	Description	Example
----------	-------------	---------

----- ----- -----		
-------------------	--	--

+	Addition	SELECT 10 + 5 FROM DUAL; -> 15
---	----------	--------------------------------

-	Subtraction	SELECT 10 - 5 FROM DUAL; -> 5
---	-------------	-------------------------------

*	Multiplication	SELECT 10 * 5 FROM DUAL; -> 50
---	----------------	--------------------------------

/	Division	SELECT 10 / 5 FROM DUAL; -> 2
---	----------	-------------------------------

MOD	Modulus (Remainder)	SELECT MOD(10, 3) FROM DUAL; -> 1
-----	---------------------	-----------------------------------

---

## 2. Comparison (Relational) Operators

These operators compare two values and return TRUE or FALSE.

Operator	Description	Example
----------	-------------	---------

----- ----- -----		
-------------------	--	--

=	Equal to	SELECT * FROM EMPLOYEES WHERE SALARY = 5000;
---	----------	--

!= or <>	Not equal to	SELECT * FROM EMPLOYEES WHERE DEPT_ID != 10;
----------	--------------	--

>	Greater than	SELECT * FROM EMPLOYEES WHERE SALARY > 5000;
---	--------------	--

<	Less than	SELECT * FROM EMPLOYEES WHERE SALARY < 5000;
---	-----------	--

>=	Greater than or equal to	SELECT * FROM EMPLOYEES WHERE SALARY >= 5000;
----	--------------------------	---

<=	Less than or equal to	SELECT * FROM EMPLOYEES WHERE SALARY <= 5000;
----	-----------------------	---

BETWEEN	Within a range	SELECT * FROM EMPLOYEES WHERE SALARY BETWEEN 3000 AND 7000;
---------	----------------	---

IN	Matches any value in a list	SELECT * FROM EMPLOYEES WHERE DEPT_ID IN (10, 20, 30);
----	-----------------------------	--

**LIKE | Pattern matching | SELECT \* FROM EMPLOYEES WHERE NAME LIKE 'J%';**  
**IS NULL | Check for NULL values | SELECT \* FROM EMPLOYEES WHERE MANAGER\_ID IS NULL;**

---

### **3. Logical Operators**

**Operator | Description | Example**

-----|-----|-----

**AND | Returns TRUE if both conditions are true | SELECT \* FROM EMPLOYEES WHERE DEPT\_ID = 10 AND SALARY > 3000;**

**OR | Returns TRUE if at least one condition is true | SELECT \* FROM EMPLOYEES WHERE DEPT\_ID = 10 OR SALARY > 5000;**

**NOT | Reverses the logical condition | SELECT \* FROM EMPLOYEES WHERE NOT DEPT\_ID = 10;**

---

### **4. Set Operators**

**Operator | Description | Example**

-----|-----|-----

**UNION | Combines result sets (removes duplicates) | SELECT NAME FROM EMPLOYEES UNION SELECT NAME FROM CUSTOMERS;**

**UNION ALL | Combines result sets (includes duplicates) | SELECT NAME FROM EMPLOYEES UNION ALL SELECT NAME FROM CUSTOMERS;**

**INTERSECT | Returns common records | SELECT NAME FROM EMPLOYEES INTERSECT SELECT NAME FROM CUSTOMERS;**

**MINUS | Returns records from first query that are not in second | SELECT NAME FROM EMPLOYEES MINUS SELECT NAME FROM CUSTOMERS;**

---

### **5. Concatenation Operator**

## **Operator | Description | Example**

-----|-----|-----

**|| | Concatenates two strings | SELECT 'Hello' || ' World' FROM DUAL;  
-> Hello World**

---

## **6. Miscellaneous Operators**

### **Operator | Description | Example**

-----|-----|-----

**EXISTS | Checks if subquery returns any rows | SELECT \* FROM  
EMPLOYEES WHERE EXISTS (SELECT 1 FROM DEPARTMENTS  
WHERE DEPARTMENTS.ID = EMPLOYEES.DEPT\_ID);**

**ANY | Compares value with any returned by subquery | SELECT \*  
FROM EMPLOYEES WHERE SALARY > ANY (SELECT SALARY FROM  
EMPLOYEES WHERE DEPT\_ID = 10);**

**ALL | Compares value with all returned by subquery | SELECT \*  
FROM EMPLOYEES WHERE SALARY > ALL (SELECT SALARY FROM  
EMPLOYEES WHERE DEPT\_ID = 10);**

---

### **Summary:**

- Arithmetic, Comparison, Logical, Set, and Concatenation operators provide powerful data manipulation.**
- Use EXISTS, ANY, and ALL for advanced subqueries.**
- UNION, INTERSECT, and MINUS allow result set combinations.**