UML DIAGRAM SUMMARY

```
class PropertiesAndMethods
{
    public int PublicAge { get; set; }
    public int PublicWithDefaultAge { get; set; } = 30;
    private int privateAge;
    readonly int privateReadonlyAge;
    protected int protectedAge;
    static int staticAge;

    public int Foo(int a, int b)
    {
        return a + b;
    }

    private int Foo2(int a, int b)
    {
        return a + b;
    }

    public virtual int Foo3(int a, int b)
    {
        return a + b;
    }

    private static int Foo4(int a, int b)
    {
        return a + b;
    }
}
```




```
abstract class AbstractClass
{
    public abstract int Foo(int a, int b);

    public virtual int Foo2(int a, int b)
    {
        return a + b;
    }
}
```



DEPENDENCY

'is dependent'
(dashed line with open arrow)

```
class A
{
    public void Foo() { }
}

class B
{
    void Bar(A a)
    {
        a.Foo();
    }
}
```



AGGREGATION

'has a'
(single line with hollow diamond)

```
class A
{
    public void Foo() { }
}

class B
{
    private A a;

    public B(A a)
    {
        this.a = a;
    }

    void Bar()
    {
        a.Foo();
    }
}
```



COMPOSITION

'owns a'
(single line with filled diamond)

```
class A
{
    public void Foo() { }
}

class B
{
    private A a = new A();
    void Bar()
    {
        a.Foo();
    }
}
```



INHERITANCE

'is a'

(single line with hollow triangle)

```
class A
{

}

class B : A
{

}
```



REALIZATION

'implements'

(dashed line with hollow triangle)

```
interface A
{
    void Foo();
}

class B : A
{
    public void Foo()
    {
        //...
    }
}
```