

Ursprungstabelle/csv

sales_order_item	
PK	<u>order_id + product_id</u>
- row_id - order_date - ship_date - ship_mode - customer_id - customer_name - segment - country - city - state - postal_code - region - category - sub_category - product_name - sales	

2NF

bruecken_tabelle	
PK	<u>order_id + product_id / [text]</u>
- sales / [numeric]	

order	
PK	<u>order_id / [text]</u>
- order_id / [text] - order_date / [date] - ship_date / [date] - ship_mode / [text] - customer_id / [text] - customer_name / [text] - segment / [text] - country / [text] - city / [text] - state / [text] - postal_code / [int] - region / [text]	

product	
PK	<u>product_id / [text]</u>
- product_name / [text] - category / [text] - sub_category / [text]	

3 NF

bruecken_tabelle	
PK	<u>order_id + product_id / [text]</u>
- sales / [numeric]	

order	
PK	<u>order_id / [text]</u>
- order_date / [date] - ship_date / [date] - ship_mode / [text] - customer_id / [text] - postal_code / [int]	

customer	
PK	<u>customer_id / [text]</u>
- customer_name / [text] - segment / [text]	

location	
PK	<u>postal_code / [int]</u>
- country / [text] - city / [text] - state / [text] - postal_code / [int] - region / [text]	

product	
PK	<u>product_id / [text]</u>
- product_name / [text] - category / [text] - sub_category / [text]	

category	
PK	<u>sub-category / [text]</u>
- category / [text]	