

DEEP LEARNING FOR COMPUTER VISION

Summer Seminar UPC TelecomBCN, 4 - 8 July 2016



Instructors



Xavier
Giró-i-Nieto



Elisa
Sayrol



Amaia
Salvador



Jordi
Torres



Eva
Moledano



Kevin
McGuinness

Organizers



UNIVERSITAT POLITÈCNICA
DE CATALUNYA
BARCELONATECH



Barcelona
Supercomputing
Center
Centro Nacional de Supercomputación



Dublin City University
Oifige Chathair Bhaile Átha Cliath



Centre for Data Analytics



CENTER OF
EXCELLENCE

Co-funded by the
Erasmus+ Programme
of the European Union




+ info: TelecomBCN.DeepLearning.Barcelona

[\[course site\]](#)

Day 4 Lecture 1

Generative models and adversarial training



Kevin McGuinness

kevin.mcguinness@dcu.ie

Research Fellow

[Insight Centre for Data Analytics](#)
[Dublin City University](#)



What is a generative model?

A model $P(X; \Theta)$ that we can draw samples from.

E.g. **A Gaussian Mixture Model**

- Fitting: EM algorithm
- Drawing samples:
 - Draw sample from categorical distribution to select Gaussian
 - Draw sample from Gaussian

GMMs are not generally complex enough to draw samples of images from.



$$P(X) = \lambda_1 \mathcal{N}(\mu_1, \sigma_1^2) + \lambda_2 \mathcal{N}(\mu_2, \sigma_2^2) + \dots$$

Why are generative models important?

- Model the probability density of images
- Understanding $P(X)$ may help us understand $P(Y | X)$
- Generate novel content
- Generate training data for discriminative networks
- Artistic applications
- Image completion
- Monte-carlo estimators

Generative adversarial networks

New method of training deep generative models

Idea: pit a generator and a discriminator against each other


Generator tries to draw samples from $P(X)$

Discriminator tries to tell if sample came from the generator or the real world

Both discriminator and generator are deep networks (differentiable functions)

Can train with backprop: train discriminator for a while, then train generator, then discriminator, ...

Generative adversarial networks (conceptual)




The generator

Deterministic mapping from a latent random vector to sample from $q(x) \sim p(x)$

Usually a deep neural network.


E.g. DCGAN:



The discriminator


Parameterised function that tries to distinguish between samples from real images $p(x)$ and generated ones $q(x)$.

Usually a deep convolutional neural network.




Training GANs


Alternate between training the discriminator and generator



1. Fix generator weights, draw samples from both real world and generated images
2. Train discriminator to distinguish between real world and generated images



1. Fix discriminator weights
2. Sample from generator
3. Backprop error through discriminator to update generator weights




Training GANs

Iterate these two steps until convergence (which may not happen)

- Updating the discriminator should make it better at discriminating between real images and generated ones (**discriminator improves**)
- Updating the generator makes it better at fooling the current discriminator (**generator improves**)

Eventually (we hope) that the generator gets so good that it is impossible for the discriminator to tell the difference between real and generated images. Discriminator accuracy = 0.5




Some examples...

ImageNet

Source:



<https://openai.com/blog/generative-models/>



CIFAR-10

Source

<https://openai.com/blog/generative-models/>





Credit:
[Alec Radford](#)

Code on [GitHub](#)



Credit: [Alec Radford](#) Code on [GitHub](#)

Issues

Known to be very difficult to train:

- Formulated as a “game” between two networks
- Unstable dynamics: hard to keep generator and discriminator in balance
- Optimization can **oscillate** between solutions
- Generator can collapse

Possible to use supervised labels to help prevent this:

<https://arxiv.org/abs/1606.03498>

Predicting the future with adversarial training

Want to train a classifier to predict the pixels in frame $(t+K)$ from pixels in frame t .

Many possible futures for same frame


Using supervised classification results in blurry solutions: loss is minimized if classifier averages over possibilities when predicting.

We really want a sample, not the mean

Adversarial training can solve this: easy for an adversary to detect blurry frames



Input frames



Ground truth



ℓ_2 result



ℓ_1 result



GDL ℓ_1 result



Adversarial result



Adversarial+GDL result




Input frames



Ground truth



ℓ_2 result



ℓ_1 result



GDL ℓ_1 result



Adversarial result



Adversarial+GDL result

Summary

Adversarial networks pit a generator network against a discriminator (adversary)

Can be trained to draw realistic sharp samples

Training can be difficult: can oscillate or generator can collapse