A practical Microcylinder Appearance Model for Cloth Rendering

Presented by Garoe Dorta Perez

University of Bath
Centre For Digital Entertainment

May 27, 2015

Overview

Introduction

Cloth rendering

Outline

Introduction

Cloth rendering

Introduction

$$L_o(\mathbf{p}, \boldsymbol{\omega_o}) = L_e(\mathbf{p}, \boldsymbol{\omega_o}) + \int_\Omega f(\mathbf{p}, \boldsymbol{\omega_o}, \boldsymbol{\omega_i}) L_i(\mathbf{p}, \boldsymbol{\omega_i}) |\cos\theta_i| d\boldsymbol{\omega_i}$$



Diagram of light emitted from **p**, image taken from [PH10].

where L_o is the outgoing radiance, L_i incoming radiance, L_e emitted radiance, f BRDF function, $\mathbf{p}$ surface point, $\boldsymbol{\omega_i}$ incident light, $\boldsymbol{\omega_o}$ outgoing light, Ω hemisphere above $\mathbf{p}$, θ_i angle of incidence.

The problem

- Render cloth fast and realistically
  - Small threads
  - Weaving patterns



Left shows a close up view of fabric, right shows a picture of cloth, images taken from [SBD*13].

Appearance model

- Two microcylinders [SBD*13]





Left shows model in a triangle mesh, right shows scattering cones in a patch, images taken from [SBD*13].

Appearance model

$$\text{BRDF: } f(t, \omega_i, \omega_r) = \frac{\text{Reflection term} + \text{Volume scattering term}}{\text{Normalization factor}},$$



Angle definitions for a single thread, image taken from [SBD*13].

where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction.

BRDF

$$\text{BRDF: } f(t,\omega_i,\omega_r) = \left(\overbrace{F_r(\eta,\omega_i)\cos(\phi_d/2)g(\gamma_s,\theta_h)}^{\text{Reflection term}} + F_t(\eta,\omega_i)F_t(\eta',\omega_r')\frac{(1-k_d)g(\gamma_v,\theta_h)+k_d}{\cos\theta_i+\cos\theta_r}A\right) / \cos^2(\theta_d),$$



where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction, F are Fresnel terms, η are Fresnel coefficients, g is a Gaussian lobe, k_d is a scattering constant, γ are Gaussian widths, $\theta_h = (\theta_i + \theta_r)/2$ and $\phi_d = \phi_i - \phi_r$.

$$\text{BRDF: } f(t,\omega_i,\omega_r) = \left(F_r(\eta,\omega_i) \overbrace{\cos(\phi_d/2)}^{\text{Cylinder reflection}} g(\gamma_s,\theta_h) + F_t(\eta,\omega_i) F_t(\eta',\omega_r') \frac{(1-k_d) g(\gamma_v,\theta_h) + k_d}{\cos\theta_i + \cos\theta_r} A \right) / \cos^2(\theta_d),$$



where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction, F are Fresnel terms, η are Fresnel coefficients, g is a Gaussian lobe, k_d is a scattering constant, γ are Gaussian widths, $\theta_h = (\theta_i + \theta_r)/2$ and $\phi_d = \phi_i - \phi_r$.

BRDF

$$\text{BRDF: } f(t,\omega_i,\omega_r) = \Bigg(F_r(\eta,\omega_i)\cos(\phi_d/2) \overbrace{g(\gamma_s,\theta_h)}^{\text{Cylinder roughness}} + F_t(\eta,\omega_i)F_t(\eta',\omega_r')\frac{(1-k_d)g(\gamma_v,\theta_h)+k_d}{\cos\theta_i+\cos\theta_r}A \Bigg) \Big/ \cos^2(\theta_d),$$



where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction, F are Fresnel terms, η are Fresnel coefficients, g is a Gaussian lobe, k_d is a scattering constant, γ are Gaussian widths, $\theta_h = (\theta_i + \theta_r)/2$ and $\phi_d = \phi_i - \phi_r$.

BRDF

$$\text{BRDF: } f(t,\omega_i,\omega_r) = \Bigg(\overbrace{F_r(\eta,\omega_i)}^{\text{Attenuation factor}} \cos(\phi_d/2) g(\gamma_s,\theta_h) + F_t(\eta,\omega_i) F_t(\eta',\omega_r') \frac{(1-k_d)g(\gamma_v,\theta_h)+k_d}{\cos\theta_i + \cos\theta_r} A \Bigg) \Big/ \cos^2(\theta_d),$$



where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction, F are Fresnel terms, η are Fresnel coefficients, g is a Gaussian lobe, k_d is a scattering constant, γ are Gaussian widths, $\theta_h = (\theta_i + \theta_r)/2$ and $\phi_d = \phi_i - \phi_r$.

$$\text{BRDF: } f(t,\omega_i,\omega_r) = \Bigg(F_r(\eta,\omega_i)\cos(\phi_d/2)g(\gamma_s,\theta_h) + \overbrace{F_t(\eta,\omega_i)F_t(\eta',\omega_r')\frac{(1-k_d)g(\gamma_v,\theta_h)+k_d}{\cos\theta_i+\cos\theta_r}A}^{\text{Volume scattering term}} \Bigg) / \cos^2(\theta_d),$$



where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction, F are Fresnel terms, η are Fresnel coefficients, g is a Gaussian lobe, k_d is a scattering constant, γ are Gaussian widths, $\theta_h = (\theta_i + \theta_r)/2$ and $\phi_d = \phi_i - \phi_r$.

BRDF

$$\text{BRDF: } f(t,\omega_i,\omega_r) = \Bigg(F_r(\eta,\omega_i)\cos(\phi_d/2)g(\gamma_s,\theta_h) +$$

$$\overbrace{F_t(\eta,\omega_i)F_t(\eta',\omega_r')}^{\text{Attenuation factor}} \frac{(1-k_d)g(\gamma_v,\theta_h)+k_d}{\cos\theta_i+\cos\theta_r} A \Bigg) \Big/ \cos^2(\theta_d),$$



where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction, F are Fresnel terms, η are Fresnel coefficients, g is a Gaussian lobe, k_d is a scattering constant, γ are Gaussian widths, $\theta_h = (\theta_i + \theta_r)/2$ and $\phi_d = \phi_i - \phi_r$.

$$\text{BRDF: } f(t,\omega_i,\omega_r) = \left(F_r(\eta,\omega_i)\cos(\phi_d/2) g(\gamma_s,\theta_h) + F_t(\eta,\omega_i)F_t(\eta',\omega_r') \frac{(1-k_d)\overbrace{g(\gamma_v,\theta_h)}^{\text{Scattering cone}} + k_d}{\cos\theta_i + \cos\theta_r} A \right) / \cos^2(\theta_d),$$



where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction, F are Fresnel terms, η are Fresnel coefficients, g is a Gaussian lobe, k_d is a scattering constant, γ are Gaussian widths, $\theta_h = (\theta_i + \theta_r)/2$ and $\phi_d = \phi_i - \phi_r$.

BRDF

$$\text{BRDF: } f(t,\omega_i,\omega_r) = \Big(F_r(\eta,\omega_i)\cos(\phi_d/2)g(\gamma_s,\theta_h) +$$

$$F_t(\eta,\omega_i)F_t(\eta',\omega_r')\frac{(1-k_d)g(\gamma_v,\theta_h)+k_d}{\underbrace{\cos\theta_i+\cos\theta_r}_{\text{Normalization factor}}}A\Big) / \cos^2(\theta_d),$$



where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction, F are Fresnel terms, η are Fresnel coefficients, g is a Gaussian lobe, k_d is a scattering constant, γ are Gaussian widths, $\theta_h = (\theta_i + \theta_r)/2$ and $\phi_d = \phi_i - \phi_r$.

BRDF

$$\text{BRDF: } f(t,\omega_i,\omega_r) = \Bigg(F_r(\eta,\omega_i)\cos(\phi_d/2)g(\gamma_s,\theta_h) + F_t(\eta,\omega_i)F_t(\eta',\omega_r')\frac{(1-k_d)g(\gamma_v,\theta_h)+k_d}{\cos\theta_i+\cos\theta_r}A\Bigg) \Big/ \overbrace{\cos^2(\theta_d)}^{\text{Normalization factor}},$$



where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction, F are Fresnel terms, η are Fresnel coefficients, g is a Gaussian lobe, k_d is a scattering constant, γ are Gaussian widths, $\theta_h = (\theta_i + \theta_r)/2$ and $\phi_d = \phi_i - \phi_r$.

Shading Model 1



Normal sampling, (top-left) cloth patch, (bottom-left) smallest cloth patch, (top-right) blue thread tangent curve, (bottom-right) red thread tangent curve, image taken from [SBD*13].

Shading Model 2



Masking examples, Green arrow points view from above, red arrow points view at grazing angle, image taken from [SBD*13].

Shading Model 3

$$L_r(\omega_r) = Q(t) \sum \int L_i(\omega_i) f(t, \omega_i, \omega_r) M(t) P(t) \cos\theta_i d\omega_i,$$

where f is the BRDF function, t is the thread direction, ω_i is the ray incoming direction, ω_r is the ray outgoing direction, θ_i is the incoming ray angle, $Q(t)$ is a normalization factor for samples and non watertight patches, $M(t)$ is the masking term and $P(t)$ is a view-projection normalization factor.

Results

- Results



Cloth render result from [SBD*13].



Cloth render with our code.

Conclusions and Future Work

- Limitations
  - Requires data capture
  - Difficult parametrization
- Future work
  - Implement full model
  - Importance sampling extensions by [MI] and [WXK]

Thank you

Questions?

References

[SBD*13] Sadeghi, I. et al. A practical microcylinder appearance model for cloth rendering. ACM 2013
[PH10] Pharr, M. et al. Physically based rendering: From theory to implementation, Morgan Kaufmann, 2010
[MI] Mizutani K. et al. Importance Sampling for Cloth Rendering under Environment Light, Mathematical Progress in Expressive Image Synthesis I, 2014
[WXK] Wang J. et al. Importance Sampling for a Microcylinder Based Cloth Bsdf, SIGGRAPH Talks, 2014